



JUN 28 2011

Donald Roberts
Naval Air Station Lemoore
750 Enterprise Ave.
Lemoore, CA 93246-5001

**Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # C-2106
Project # C-1073718**

Dear Mr. Roberts:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Naval Air Station Lemoore for its military base in Lemoore, California. In addition, you proposed to incorporate the recently issued C-2106-131-5 and '-170-0 into the Title V operating permit. These Authority to Construct permits provide for the installation of a mobile fire training device and establish a common fuel use limit for both fire training operations.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner
Director of Permit Services

Attachments

C: Frank DeMaris, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



JUN 28 2011

Gerardo C. Rios, Chief
Permits Office (AIR-3)
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

**Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # C-2106
Project # C-1073718**

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Naval Air Station Lemoore for its military base in Lemoore, California. In addition, the permittee is proposing to incorporate the recently issued C-2106-131-5 and '-170-0 into the Title V operating permit. These Authority to Construct permits provide for the installation of a mobile fire training device and establish a common fuel use limit for both fire training operations.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Attachments

C: Frank DeMaris, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061
www.valleyair.org

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



JUN 28 2011

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

**Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # C-2106
Project # C-1073718**

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Naval Air Station Lemoore for its military base in Lemoore, California. In addition, the permittee is proposing to incorporate the recently issued C-2106-131-5 and '-170-0 into the Title V operating permit. These Authority to Construct permits provide for the installation of a mobile fire training device and establish a common fuel use limit for both fire training operations.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner
Director of Permit Services

Attachments

C: Frank DeMaris, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Hanford Sentinel

**NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED RENEWAL OF
THE FEDERALLY MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed renewal of the Federally Mandated Operating Permit to Naval Air Station Lemoore for its military base in Lemoore, California.

The District's analysis of the legal and factual basis for this proposed action, project #C-1073718, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. There are no emission changes associated with this proposed action. This will be the public's only opportunity to comment on the specific conditions of the proposed renewal of the Federally Mandated Operating permit. If requested by the public, the District will hold a public hearing regarding issuance of this renewed permit. For additional information, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900. Written comments on the proposed renewed permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CALIFORNIA 93726-0244.

SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal and Minor Modification Evaluation Naval Air Station Lemoore C-2106

TABLE OF CONTENTS

I.	PROPOSAL.....	2
II.	FACILITY LOCATION	3
III.	EQUIPMENT LISTING	3
IV.	GENERAL PERMIT TEMPLATE USAGE	3
V.	SCOPE OF EPA AND PUBLIC REVIEW	3
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	4
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE.....	7
VIII.	PERMIT REQUIREMENTS	8
IX.	PERMIT SHIELD	19
X.	PERMIT CONDITIONS	20
XI.	ATTACHMENTS.....	20
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	AUTHORITIES TO CONSTRUCT	
D.	EMISSIONS INCREASES	
E.	DETAILED FACILITY LIST	

TITLE V PERMIT RENEWAL EVALUATION
Military Base

Engineer: Frank DeMaris
Date: June 23, 2011

Facility Number: C-2106
Facility Name: Naval Air Station Lemoore
Mailing Address: 750 Enterprise Ave.
Lemoore, CA 93246-5001

Contact Name: Simeon Bugay
Phone: (559) 998-2507

Responsible Official: Donald C. Roberts
Title: Environmental Site Manager

Project # : C-1073718
Deemed Complete: September 25, 2007

I. PROPOSAL

Naval Air Station Lemoore ("NASL") was issued a Title V permit on August 31, 2004. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

In addition, NASL has also applied to incorporate the recently issued Authority to Construct (ATC) permits C-2106-131-5 and '-170-0 into the Title V operating permit. These ATCs modify existing aircraft fire training facility (C-2106-131-2) to limit the annual fuel use, and to share the resulting fuel use limitation with the new mobile aircraft fire training device (C-2106-170-1).

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

NASL is located at Naval Air Station Lemoore, a military base located approximately six miles west of Lemoore, California.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment A. In addition, the equipment authorized by the following ATCs is being incorporated into the Title V permit:

C-2106-131-6: 54.3 MMBTU/HR LPG/PROPANE-FUELED FIRE TRAINING FACILITY

C-2106-170-1: TRANSPORTABLE LPG/PROPANE-FUELED MOBILE AIRCRAFT FIRE TRAINING DEVICE (MAFTD)

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Templates:

A. Template SJV-UM-0-3 Facility Wide Umbrella

The applicant has requested to utilize template number SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered

by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review:

Conditions 1 through 40 of the requirements for permit unit C-2016-0-2.

Incorporation of ATCs C-2106-131-2 and '-170-0 into the Title V permit is considered to be a minor modification and, as such, requires no public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 1020, Definitions
(amended January 15, 2009)
- District Rule 2020, Exemptions
(amended September 21, 2006 ⇒ amended December 20, 2007)
- District Rule 2201, New and Modified Stationary Source Review Rule
(amended April 20, 2005 ⇒ amended December 15, 2005 ⇒ amended September 21, 2006 ⇒ amended December 18, 2008)
- District Rule 4603, Surface Coating of Metal Parts and Products, Plastic Parts and Products, and Pleasure Crafts
(amended September 17, 2009)
- District Rule 4605, Aerospace Assembly and Component Coating Operations
(amended September 20, 2007 ⇒ amended June 16, 2011)
- District Rule 4606, Wood Products and Flat Wood Paneling Products Coating Operations
(amended September 20, 2007 ⇒ amended October 16, 2008)
- District Rule 4662, Organic Solvent Degreasing Operations
(amended September 20, 2007)

- District Rule 4702, Internal Combustion Engines – Phase 2
(amended June 16, 2005 ⇒ amended April 20, 2006 ⇒ amended January 18, 2007)
- District Rule 4703, Stationary Gas Turbines
(amended August 17, 2006 ⇒ amended September 20, 2007)

B. Rules Removed

- District Rule 4602, Motor Vehicle and Mobile Equipment Coating Operations
(retired January 1, 2009)

This rule was retired on January 1, 2009 when the provisions of the rule were superseded by the provisions of District Rule 4612. Rule 4602 was subsequently amended, on September 17, 2009, so that it applied to motor vehicle assembly coatings. Since NASL does not include a source operation subject to Rule 4602, this rule is listed as removed rather than updated.

C. Rules Added

- District Rule 4612, Motor Vehicle and Mobile Equipment Coating Operations
(adopted September 21, 2006 ⇒ amended September 20, 2007 ⇒ amended October 21, 2010)

D. Rules Not Updated

- District Rule 2520, Federally Mandated Operating Permits
(amended June 21, 2001)
- District Rule 4201, Particulate Matter Concentration
(amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate
(amended December 17, 1992)
- District Rule 4701, Internal Combustion Engines – Phase 1
(amended August 21, 2003)
- District Rule 4801, Sulfur Compounds
(amended December 17, 1992)
- 40 CFR 64, Compliance Assurance Monitoring (CAM)

E. Rules Covered by Template

The following rules are covered by the umbrella template and will not be further discussed in this evaluation:

- District Rule 1100, Equipment Breakdown
(amended December 17, 1992)
- District Rule 1160, Emission Statements
(adopted November 18, 1992)
- District Rule 2010, Permits Required
(amended December 17, 1992)
- District Rule 2031, Transfer of Permits
(amended December 17, 1992)
- District Rule 2040, Applications
(amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications
(amended December 17, 1992)
- District Rule 2080, Conditional Approval
(amended December 17, 1992)
- District Rule 4101, Visible Emissions
(amended February 17, 2005)
- District Rule 4601, Architectural Coatings
(amended December 17, 2009)
- District Rule 8011, General Requirements
(amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities
(amended August 19, 2004)
- District Rule 8031, Bulk Materials
(amended August 19, 2004)

- District Rule 8041, Carryout and Trackout
(amended August 19, 2004)
- District Rule 8051, Open Areas
(amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads
(amended September 16, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas
(amended September 16, 2004)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
- 40 CFR Part 82, Subpart F, Stratospheric Ozone

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Not Updated

District Rule 4102, Nuisance
(amended December 17, 1992)

Condition 42 of permit unit C-2106-0-2 is based on District Rule 4102 and will therefore not be discussed any further.

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit.

A. District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from the requirement to obtain a permit and specifies recordkeeping requirements to verify such exemptions where appropriate. The amendments to this rule do not have any affect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.26, defined as an action including at least one of the following items:

- 1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.
- 2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.
- 3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.
- 4) Addition of any new emissions unit which is subject to District permitting requirements.
- 5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Therefore, the updated requirements of this rule are not applicable at this time.

Permit units C-2106-131-5 and '-170-0 were subject to the District NSR Rule upon application for Authority to Construct (ATC). In accordance with the White Paper for Streamlined Development of Part 70 Permit Applications, dated July 10, 1995, conditions from the resulting PTO were addressed to define how NSR permit terms should be incorporated into the Title V permit.

a. C-2106-131-2 (Fire Training Facility):

- Conditions 1 through 3 from the Authority to Construct were deleted from the proposed Permit to Operate. These conditions addressed the requirement to apply for a Title V permit modification and coordinated the implementation of various ATCs.
- Conditions 4 and 5 are included in the facility-wide Permit to Operate.
- Conditions 6 through 13 from the Authority to Construct were renumbered as conditions 1 through 8 on the proposed Permit to Operate.

b. C-2106-170-1 (Mobile Aircraft Fire Training Device):

- Conditions 1 through 3 from the Authority to Construct were deleted from the proposed Permit to Operate. These conditions addressed the requirement to apply for a Title V permit modification and coordinated the implementation of various ATCs.
- Conditions 4 and 5 are included in the facility-wide Permit to Operate.
- Conditions 6 through 13 from the Authority to Construct were renumbered as conditions 1 through 8 on the proposed Permit to Operate.

In addition, certain source operations are subject to conditions under Rule 2201, or Kings County Air Pollution Control District (KCAPCD) Rule 210.1, which require update.

c. C-2106-39-2 (Ground Support Equipment Coating Operation)

- Condition 5 on the current Permit to Operate restricts emissions to 40 lb-VOC/day. This condition has been replaced by condition 5 on the proposed Permit to Operate, which replaced the VOC emission limit with a limit of 40.0 lb-VOC/day for consistency with District Policy SPR-1105, *Guidelines for the Use of Significant Figures in Engineering Calculations*.

C. District Rule 2520 - Federally Mandated Operating Permits

There are no federally applicable greenhouse gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR 98) is not included in the definition of an applicable requirement within Title V, as specified in 40 CFR 71.2. Therefore, no GHG requirements will be included in the proposed Permit to Operate. No further discussion is required.

D. District Rule 4603 - Surface Coating of Metal Parts and Products, Plastic Parts and Products, and Pleasure Crafts

The purpose of this rule is to limit VOC emissions from metal parts and products coating operations and similar affected facilities. The most recent amendment to the rule was adopted October 16, 2008 and approved into the SIP on January 19, 2010.

a. C-2106-39-3 (Ground Support Equipment Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 6 through 8, 14 through 16, 19 through 27, and 33 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- b. C-2106-117-6 (Squadron Coating Operation, Hanger 1, Modules 1-5)
- c. C-2106-118-6 (Squadron Coating Operation, Hanger 2, Module 1)
- d. C-2106-119-6 (Squadron Coating Operation, Hanger 2, Module 4)
- e. C-2106-120-6 (Squadron Coating Operation, Hanger 2, Module 2)
- f. C-2106-121-6 (Squadron Coating Operation, Hanger 2, Module 5)
- g. C-2106-122-6 (Squadron Coating Operation, Hanger 3, Module 2)
- h. C-2106-123-6 (Squadron Coating Operation, Hanger 3, Module 3)
- i. C-2106-124-6 (Squadron Coating Operation, Hanger 4, Module 5)
- j. C-2106-125-6 (Squadron Coating Operation, Hanger 2, Module 3)
- k. C-2106-126-6 (Squadron Coating Operation, Hanger 3, Module 4)
- l. C-2106-127-6 (Squadron Coating Operation, Hanger 3, Module 5):

Conditions on the current Permits to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permits to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 7 through 9, 14 through 16, 18 through 26, and 31 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

m. C-2106-149-2 (AIMD Paint Shop Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 7 through 9, 15 through 17, 20 through 28, and 34 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- n. C-2106-151-5 (Squadron Coating Operation, Hanger 5, Modules 1-3)
- o. C-2106-153-4 (Squadron Coating Operation, Hanger 4, Module 1)
- p. C-2106-154-4 (Squadron Coating Operation, Hanger 4, Module 2)
- q. C-2106-155-4 (Squadron Coating Operation, Hanger 4, Module 3)
- r. C-2106-156-4 (Squadron Coating Operation, Hanger 4, Module 4)
- s. C-2106-157-4 (Squadron Coating Operation, Hanger 3, Module 1):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 10 through 12, 18 through 20, 22 through 30, and 35 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

t. C-2106-168-2 (Metal Parts Coating With Electrostatic Spray Guns):

Conditions 15 and 16 on the current Permit to Operate ensure that coatings used in this operation are in compliance with this rule, and are retained on the proposed Permit to Operate. Condition 19 on the current Permit to Operate is a work practice standard that has been updated in the current version of the rule, so this condition has been replaced by conditions 19 and 20 on the proposed Permit to Operate.

E. District Rule 4605 - Aerospace Assembly and Component Coating Operations

The purpose of this rule is to limit VOC emissions from aerospace coating operations and similar affected facilities. The most recent amendment to the rule was adopted June 16, 2011 but has not been approved into the SIP yet. The previous version was approved into the SIP on January 26, 2010, but the approval was only partial because EPA determined that further review was required in order to ensure the reasonably available control technology requirements were satisfied. Since the rule amendment is exclusively intended to address the partial disapproval, it is evident that the amended rule is at least as stringent as the SIP-approved rule.

a. C-2106-39-3 (Ground Support Equipment Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 9, 14, 15, 17, 19, 21, 22, 28 through 30, 32, and 33 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- b. C-2106-117-6 (Squadron Coating Operation, Hanger 1, Modules 1-5)
- c. C-2106-118-6 (Squadron Coating Operation, Hanger 2, Module 1)
- d. C-2106-119-6 (Squadron Coating Operation, Hanger 2, Module 4)
- e. C-2106-120-6 (Squadron Coating Operation, Hanger 2, Module 2)
- f. C-2106-121-6 (Squadron Coating Operation, Hanger 2, Module 5)
- g. C-2106-122-6 (Squadron Coating Operation, Hanger 3, Module 2)
- h. C-2106-123-6 (Squadron Coating Operation, Hanger 3, Module 3)
- i. C-2106-124-6 (Squadron Coating Operation, Hanger 4, Module 5)
- j. C-2106-125-6 (Squadron Coating Operation, Hanger 2, Module 3)
- k. C-2106-126-6 (Squadron Coating Operation, Hanger 3, Module 4)
- l. C-2106-127-6 (Squadron Coating Operation, Hanger 3, Module 5):

Conditions on the current Permits to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permits to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 10, 14, 15, 17, 18, 20, 21, and 27 through 31 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

m. C-2106-149-2 (AIMD Paint Shop Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 10, 15, 16, 18, 20, 22, 23, 29 through 31, 33, and 34 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- n. C-2106-151-5 (Squadron Coating Operation, Hanger 5, Modules 1-3)
- o. C-2106-153-4 (Squadron Coating Operation, Hanger 4, Module 1)
- p. C-2106-154-4 (Squadron Coating Operation, Hanger 4, Module 2)
- q. C-2106-155-4 (Squadron Coating Operation, Hanger 4, Module 3)
- r. C-2106-156-4 (Squadron Coating Operation, Hanger 4, Module 4)
- s. C-2106-157-4 (Squadron Coating Operation, Hanger 3, Module 1):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 14, 18, 19, 21, 22, 24, 25, and 31 through 35 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

F. District Rule 4606 - Wood Products and Flat Wood Paneling Products Coating Operations

The purpose of this rule is to limit VOC emissions from wood products coating operations and similar affected facilities. The most recent amendment to the rule was adopted October 16, 2008 and approved into the SIP on October 15, 2009.

a. C-2106-39-3 (Ground Support Equipment Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 10 through 12, 14 through 16, 19, 21, 22, and 33 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- b. C-2106-117-6 (Squadron Coating Operation, Hanger 1, Modules 1-5)
- c. C-2106-118-6 (Squadron Coating Operation, Hanger 2, Module 1)
- d. C-2106-119-6 (Squadron Coating Operation, Hanger 2, Module 4)
- e. C-2106-120-6 (Squadron Coating Operation, Hanger 2, Module 2)
- f. C-2106-121-6 (Squadron Coating Operation, Hanger 2, Module 5)
- g. C-2106-122-6 (Squadron Coating Operation, Hanger 3, Module 2)
- h. C-2106-123-6 (Squadron Coating Operation, Hanger 3, Module 3)
- i. C-2106-124-6 (Squadron Coating Operation, Hanger 4, Module 5)
- j. C-2106-125-6 (Squadron Coating Operation, Hanger 2, Module 3)
- k. C-2106-126-6 (Squadron Coating Operation, Hanger 3, Module 4)
- l. C-2106-127-6 (Squadron Coating Operation, Hanger 3, Module 5):

Conditions on the current Permits to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permits to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 11 through 16, 18, 20, 21, and 31 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- m. C-2106-149-2 (AIMD Paint Shop Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 11 through 13, 15 through 17, 20, 22, 23, and 34 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- n. C-2106-151-5 (Squadron Coating Operation, Hanger 5, Modules 1-3)
- o. C-2106-153-4 (Squadron Coating Operation, Hanger 4, Module 1)
- p. C-2106-154-4 (Squadron Coating Operation, Hanger 4, Module 2)
- q. C-2106-155-4 (Squadron Coating Operation, Hanger 4, Module 3)
- r. C-2106-156-4 (Squadron Coating Operation, Hanger 4, Module 4)
- s. C-2106-157-4 (Squadron Coating Operation, Hanger 3, Module 1):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 15 through 20, 22, 24, 25, and 35 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

G. District Rule 4612 - Motor Vehicle and Mobile Equipment Coating Operations

The purpose of this rule is to limit VOC emissions from motor vehicle and mobile equipment coating operations and similar affected facilities. The most recent amendment to the rule was adopted October 21, 2010 but has not been approved into the SIP yet. The most recent SIP-approved amendment was adopted on September 20, 2007 and approved into the SIP on January 19, 2010. The non-SIP version of the rule was amended to remove redundant language and clarify the intent and requirements of the rule, but not to affect the meaning, scope, or prohibitions included in the rule. Therefore, the current version of Rule 4612 is at least as stringent as the SIP-approved version of the rule.

a. C-2106-39-3 (Ground Support Equipment Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 13 through 16, 18, 19, 21, 22, and 31 through 33 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

b. C-2106-149-2 (AIMD Paint Shop Coating Operation):

Conditions on the current Permit to Operate that limit the VOC content of coatings and solvents have been updated or replaced on the proposed Permit to Operate to ensure compliance with the VOC limits of the current rule. The testing and record keeping requirements have likewise been updated. The District has verified that conditions 14 through 17, 19, 20, 22, 23, and 32 through 34 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

H. District Rule 4662 - Organic Solvent Degreasing Operations

The purpose of this rule is to limit VOC emissions from solvent degreasing operations. The current version of the rule was adopted on September 20, 2007 and approved into the SIP on July 30, 2009.

a. C-2106-140-6 (Batch-Loaded Cold Cleaner Degreaser):

This unit is exempt from the requirements of Rule 4662. The District has verified that conditions 4 and 5 on the proposed Permit to Operate will ensure that this exemption remains valid.

b. C-2106-162-2 (Cold Solvent Degreaser #1)

c. C-2106-163-2 (Cold Solvent Degreaser #2)

d. C-2106-165-2 (Cold Solvent Degreaser #4)

e. C-2106-166-2 (Cold Solvent Degreaser #5):

These units are air-tight or airless degreasers subject to Rule 4662. The District has verified that conditions 2 through 10, 13, and 14 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

I. District Rule 4702 - Internal Combustion Engines – Phase 2

The purpose of this rule is to limit emissions of NO_x, CO, and VOC from stationary internal combustion (IC) engines. The most recent version of the rule was adopted on January 18, 2007 and approved into the SIP on January 10, 2008.

a. C-2106-1-3 (Control Tower Emergency IC Engine)

b. C-2106-2-3 (Field Lighting Vault Emergency IC Engine)

c. C-2106-6-3 (TACAN Site Emergency IC Engine)

d. C-2106-7-3 (Transmitter Facility Emergency IC Engine)

e. C-2106-8-3 (Receiver Facility Emergency IC Engine)

f. C-2106-9-4 (Approach Light Vault Emergency IC Engine):

These units are diesel-fueled emergency IC engines powering generators devoted to providing electricity for various airfield services in the event of a power outage. The District has verified that conditions 5 through 13 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- g. C-2106-25-7 (Runway 32R Arresting Gear IC Engines)
- h. C-2106-26-6 (Runway 32L Arresting Gear IC Engines)
- i. C-2106-27-6 (Runway 14R Arresting Gear IC Engines)
- j. C-2106-28-6 (Runway 14L Arresting Gear IC Engines):

These units are gasoline-fueled IC engines used to retract military aircraft arresting gear cables. Therefore, these engines are exempt from all but the record keeping requirements of Rule 4702. The District has verified that conditions 4, 7, and 8 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- k. C-2106-78-4 (Runway 32L Approach Radar Emergency IC Engine)
- l. C-2106-79-4 (Runway 32R Approach Radar Emergency IC Engine):

These engines are diesel-fueled emergency IC engines powering generators devoted to providing electricity for precision approach radars in the event of a power outage. The District has verified that conditions 5 through 13 on the proposed Permit to Operate will ensure compliance with the requirements of this rule.

- m. C-2106-158-3 (Radar Site Emergency IC Engine):

This engine is a diesel-fueled emergency IC engine powering a generator devoted to providing electricity to the radar site in the event of a power outage. The District has verified that conditions 7 through 15 will ensure compliance with the requirements of this rule.

J. District Rule 4703 - Stationary Gas Turbines

The purpose of this rule is to limit emissions of NO_x from stationary gas turbines. NASL operates two test cells, and one open engine test pad, where aircraft jet engines (gas turbines) are tested. However, Rule 4703 defines a stationary gas turbine as one attached to a foundation, or a portable unit operated at a facility for more than 90 days in any 12-month period. The gas turbines operated at these test cells are aircraft engines, which are not attached to a foundation and which will not be operated in either of the test cells more than 90 days in any 12-month period. Therefore, the requirements of Rule 4703 do not apply to any source operation at NASL.

K. 40 CFR Part 64 - CAM

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

The 13 total IC engines (both emergency and non-emergency), 6 total degreasers, 3 total jet engine test cells, 2 total fire training operations, and 18 total squadron maintenance coating operations are not subject to the CAM requirement because they do not have add-on controls for any pollutant. Note that the use of low-VOC coatings in the coating operations is a pollution prevention method rather than an add-on pollution control device.

The 3 coating operations with coating booths are not subject to the CAM requirement for VOC because the use of low-VOC coatings is not an add-on pollution control device. The use of a paint or powder coating booth is an add-on pollution control device for PM₁₀, but unit C-2106-39-3 does not have an emission limit for PM₁₀ and is therefore not subject to the CAM requirement for PM₁₀. Units C-2106-149-2 and '-168-2 do have emission limits for PM₁₀, so pre-control emissions must be calculated based on the typical control efficiency of 66% for dry paint booth filters:

C-2106-149-2:

$$PE = (6.5 \text{ lb-PM}_{10}/\text{day}) \times (365 \text{ day/yr}) \div (1 - 0.66) = 6,978 \text{ lb-PM}_{10}/\text{yr}$$

C-2106-168-2:

$$PE = (50 \text{ lb-PM}_{10}/\text{yr}) \div (1 - 0.66) = 147 \text{ lb-PM}_{10}/\text{yr}$$

Pre-control emissions from both C-2106-149-2 and '-168-2 are below the major source threshold of 140,000 lb-PM₁₀/yr. Therefore, the CAM requirement does not apply to these units for PM₁₀ either.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

1. Model General Permit Template SJV-UM-0-3

By submitting Model General Permit Template SJV-UM-0-2 (recently updated to '-0-3) qualification form, the applicant has requested that a permit shield be granted for all the applicable requirements identified by the template. Therefore, the permit shield, as granted in the Model General Permit Template, is included as conditions 39 and 40 of the facility-wide requirements (C-2106-0-2).

B. Requirements not Addressed by Model General Permit Templates

The applicant is requesting a permit shield for each of the requirements listed below:

1. District Rule 4801, Kings County APCD Rule 407

A requirement from the specification for California Reformulated Gasoline, contained in Title 13, California Code of Regulations, Section 2262 (13 CCR 2262), which will ensure compliance with the requirements of these rules, is presented in condition 2 of the proposed requirements for permit units C-2106-25-7 '-26-6, '-27-6, and '-28-6. KCAPCD Rule 407 was approved into the SIP on September 22, 1972, whereas District Rule 4801 was submitted to EPA for approval on September 28, 1994 but has not yet been approved into the SIP. Therefore, a permit shield is being granted for these requirements in condition 9 of the requirements for permit unit C-2106-25-7 '-26-6, '-27-6, and '-28-6.

A requirement from the airborne toxics control measure for diesel particulate matter, contained in 17 CCR 93115, which will ensure compliance with the requirements of these rules, is presented in condition 4 of the proposed requirements for permit units C-2106-78-4, '-79-4, and '-158-3. As noted previously, KCAPCD Rule 407 has been approved into the SIP while District Rule 4801 has not. Therefore, a permit shield is being granted for these requirements in condition 14 of the requirements

for permit units C-2106-78-4 and '-79-4, and condition 16 of the requirements for permit unit C-2106-158-3.

C. Obsolete Permit Shields From Existing Permit Requirements

1. Kings County APCD Rule 404

This rule specifies a maximum particulate matter concentration of 0.1 grains per cubic foot of gas at dry standard conditions. Conditions requiring compliance with this rule and providing a permit shield were included in Template SJV-IC-2-0, under which portions of the initial Title V permit application were processed. More recently, this template has been rescinded, while District Rule 4201 was approved into the SIP on April 4, 2002, superseding Rule 404. Condition 1 on the proposed Permit to Operate for permit units C-2106-25-7, '-26-6, '-27-6, and '-28-6 will ensure compliance with the requirements of these rules. No permit shield is required, so condition 11 on the current Permit to Operate for these units has been deleted.

X. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

XI. ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Authorities to Construct
- D. Emissions Increases
- E. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: C-2106-0-2

EXPIRATION DATE: 04/30/2008

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: NAS LEMOORE
Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001
C-2106-0-2 : Apr 1 2011 2:34PM -- DEMARISF

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On August 31, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-1-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

487 BHP CATERPILLAR MODEL #3406B-D1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 001, CONTROL TOWER)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-2-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 003, THE FIELD LIGHTING VAULT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-6-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

69 BHP CUMMINS MODEL #L634T-1710148L DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 461, TACAN SITE)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NO_x/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM₁₀ emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-7-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

375 BHP CUMMINS MODEL #NT855-G4 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 462, TRANSMITTER FACILITY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NO_x/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM₁₀ emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-7-3 : Apr 1 2011 2:34PM -- DEMARISF

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-8-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

135 BHP CUMMINS MODEL #6BT-5.9-G1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 464, RECEIVER FACILITY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-9-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 468, APPROACH LIGHT VAULT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-23-3

EQUIPMENT DESCRIPTION:
JET TEST CELL #3 (BLDG 175)

EXPIRATION DATE: 04/30/2008

DRAFT

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The average daily combined emissions from test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed any of the following limits, during any calendar month: 327 lb-NO_x/day, 166 lb-SO_x/day, 160 lb-PM₁₀/day, 1,454 lb-CO/day, or 613 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Emissions shall be calculated using the following emission factors: 0.106 lb-NO_x/gal, 0.054 lb-SO_x/gal, 0.052 lb-PM₁₀/gal, 0.472 lb-CO/gal, and 0.199 lb-VOC/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The average daily combined fuel usage for test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed 3,080 gallons/day, for any calendar month. [District NSR Rule] Federally Enforceable Through Title V Permit
6. A record shall be maintained of the date, type, and quantity of engines tested, and daily fuel usage based on based on a monthly average at this test cell. The record shall be retained on-site for at least five years and made available for District inspection upon request. [District Rule 1070 and 2520, and 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-25-7

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED EMERGENCY IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Unit shall be fired on gasoline with a sulfur content of less than 0.003% by weight. [13 CCR 2262] Federally Enforceable Through Title V Permit
3. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NO_x/bhp-hr, 0.30 g-PM₁₀/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the applicable requirements of SJVUAPCD Rule 4801 and Kings County APCD Rule 407. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-26-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL V-465D GASOLINE-FIRED EMERGENCY IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Unit shall be fired on gasoline with a sulfur content of less than 0.003% by weight. [13 CCR 2262] Federally Enforceable Through Title V Permit
3. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NOx/bhp-hr, 0.30 g-PM10/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the applicable requirements of SJVUAPCD Rule 4801 and Kings County APCD Rule 404. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-27-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL V-465D GASOLINE-FIRED EMERGENCY IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Unit shall be fired on gasoline with a sulfur content of less than 0.003% by weight. [13 CCR 2262] Federally Enforceable Through Title V Permit
3. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NOx/bhp-hr, 0.30 g-PM10/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the applicable requirements of SJVUAPCD Rule 4801 and Kings County APCD Rule 404. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-28-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL V-465D GASOLINE-FIRED EMERGENCY IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Unit shall be fired on gasoline with a sulfur content of less than 0.003% by weight. [13 CCR 2262] Federally Enforceable Through Title V Permit
3. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NOx/bhp-hr, 0.30 g-PM10/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the applicable requirements of SJVUAPCD Rule 4801 and Kings County APCD Rule 404. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-39-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

COATING OPERATION WITH HVLP SPRAY GUN(S) AND DEVILBISS MODEL DLFA (SERIAL # 501) PAINT SPRAY BOOTH WITH DISPOSABLE EXHAUST FILTERS (BLDG 179, GROUND SUPPORT EQUIPMENT MAINTENANCE)

PERMIT UNIT REQUIREMENTS

1. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), 4606 (Wood Products), or 4612 (Motor Vehicles and Mobile Equipment) depending on item being coated. [District Rules 4601, 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
2. All painting, including application of primer, shall be conducted inside the booth with filters in place, fan(s) operating, and doors closed. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed 40.0 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
7. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-39-3: Jun 23 2011 10:48AM - DEMARISF

9. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
10. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
13. The VOC Regulatory content of coatings used for motor vehicles and mobile equipment, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rule 4612] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603, 4606, and 4612] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. For bug and tar removal on motor vehicles and mobile equipment, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
19. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
21. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
23. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
26. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
28. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
30. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
31. The permittee shall maintain and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, and the VOC Actual for Coatings and VOC Regulatory for Coatings as applied; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

32. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rules 4605 and 4612] Federally Enforceable Through Title V Permit
33. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-69-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

261 HP AUXILIARY POWER UNIT (APU) TEST PAD (T-26) (ADJACENT TO BUILDING 175)

DRAFT

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Only GTC 36-200 engines shall be tested at this site. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Engine test rate shall not exceed 10 test/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep daily records of the number of engine tests, and fuel usage. Records shall be retained for at least five years and provided for District inspection upon request. [District Rule 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-70-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

T-14/T-17 OPEN ENGINE TEST PADS (BLDG 242)

DRAFT

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Only F-404-GE-400, F404-GE-402, and T-400-CP-400 engines shall be tested at this site. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Engine test rate shall not exceed five F-404-GE-400 or F404-GE-402 tests/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep daily records of the number of engine tests, engine types, and fuel usage. Records shall be retained for at least five years and provided for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-74-3

EQUIPMENT DESCRIPTION:
JET TEST CELL #4 (BLDG 176)

EXPIRATION DATE: 04/30/2008

DRAFT

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The average daily combined emissions from test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed any of the following limits, during any calendar month: 327 lb-NOx/day, 166 lb-SOx/day, 160 lb-PM10/day, 1,454 lb-CO/day, or 613 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Emissions shall be calculated using the following emission factors: 0.106 lb-NOx/gal, 0.054 lb-SOx/gal, 0.052 lb-PM10/gal, 0.472 lb-CO/gal, and 0.199 lb-VOC/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The average daily combined fuel usage for test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed 3,080 gallons/day, for any calendar month. [District NSR Rule] Federally Enforceable Through Title V Permit
6. A record shall be maintained of the date, type, and quantity of engines tested, and daily fuel usage based on based on a monthly average at this test cell. The record shall be retained on-site for at least five years and made available for District inspection upon request. [District Rule 1070 and 2520, and 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-78-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

95 BHP JOHN DEERE MODEL 1876F SERIAL #T06059T401715 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 467, RUNWAY 32L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 13.97 g-NOx/bhp-hr, 3.02 g-CO/bhp-hr, or 1.11 g-VOC/bhp-hr. [District Rule 2201 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. {2421} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-79-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

95 HP JOHN DEERE MODEL 1876F SERIAL #T06059T402783 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 466, RUNWAY 32R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Emissions from this IC engine shall not exceed any of the following limits: 13.97 g-NOx/bhp-hr, 3.02 g-CO/bhp-hr, or 1.11 g-VOC/bhp-hr. [District Rule 2201 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. {2421} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-117-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 1, MODULES 1 - 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-118-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 1)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-119-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 4)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-120-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-120-6 : Jun 23 2011 10:50AM - DEMARISF

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-121-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-121-6: Jun 23 2011 10:50AM - DEMARISF

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-122-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-123-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-124-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-125-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-126-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 4)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-127-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-127-6: Jun 23 2011 10:51AM - DEMARISF

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
15. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
18. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
23. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
25. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
28. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
30. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-131-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

54.3 MMBTU/HR PROPANE-FUELED FIRE TRAINING FACILITY

DRAFT

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. LPG gas consumption shall not exceed 1,800 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions shall not exceed any of the following limits: 21.45 lb NO_x/1000 gal, 0.094 lb-SO_x/1000 gal, 9.9 lb PM₁₀/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The fire training operation shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520] Federally Enforceable Through Title V Permit
7. Permittee shall maintain daily and annual records of the amount of LPG used in the fire training operation. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-140-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

BATCH LOADED COLD CLEANER DEGREASER, CONSISTING OF ONE CANISTER WITH 9.75 INCH OPEN DIAMETER AND CAPACITY LESS THAN 2.0 GALLONS (BLDG 188 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Degreaser shall be covered at all times except when parts are being added to, removed from, or handled in the solvent bath. [District Rule 4662] Federally Enforceable Through Title V Permit
3. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The capacity of the degreaser shall be less than 2.0 gallons. [District Rule 4662] Federally Enforceable Through Title V Permit
5. The degreaser shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
6. VOC emissions from this degreaser shall not exceed 2.0 lb VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.42 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The VOC content of the solvent shall not exceed 4.75 lb/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Operator records shall be retained on-site for at least five years and made available for District inspection upon request. [District Rules 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-149-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

COATING OPERATION WITH MODEL #SPF-24-8-10, HV FLOOR FILTER OPEN FRONT PAINT SPRAY BOOTH WITH 25'W X 8'6"H X 13'2"L OUTSIDE DIMENSIONS (BLDG 188 - AIMD PAINT SHOP)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), 4606 (Wood Products), or 4612 (Motor Vehicles and Mobile Equipment), depending on item being coated. [District Rules 4601, 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Emissions from paint booth shall not exceed either of the following limits: 46.2 lb VOC/day or 6.5 lb PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Total coating material usage shall not exceed 14.0 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. All painting, including application of primer, shall be conducted inside the booth with filters in place, fan(s) operating, and doors closed. [District NSR Rule] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

9. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
10. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
11. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
12. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
13. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
14. The VOC Regulatory content of coatings used for motor vehicles and mobile equipment, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rule 4612] Federally Enforceable Through Title V Permit
15. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
16. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
17. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603, 4606, and 4612] Federally Enforceable Through Title V Permit
18. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. For bug and tar removal on motor vehicles and mobile equipment, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
20. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
21. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit
24. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
25. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
28. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
30. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The permittee shall maintain and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, and the VOC Actual for Coatings and VOC Regulatory for Coatings as applied; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rules 4605 and 4612] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, 4606, and 4612] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-151-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 5, MODULES 1 - 3)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Permittee shall use no more than 68 gal/yr of cleanup solvents. [District Rule 4102]
9. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
11. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 øF or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 øF or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

12. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
14. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
17. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
18. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
20. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
21. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
23. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
24. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
26. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
29. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
31. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
33. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

34. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
35. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-153-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 1)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-154-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 øF or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 øF or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-155-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-155-4 : Jun 23 2011 10:53AM - DEMARISF

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT
PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-155-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 øF or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 øF or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-155-4: Jun 23 2011 10:54AM - DEMARISF

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-156-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 4)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-156-4 - Jun 23 2011 10:54AM - DEMARISF

DRAFT

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-157-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 1)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-157-4 : Jun 23 2011 10:54AM - DEMARISF

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605 (6/16/2011). [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT
PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-158-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

166 BHP PERKINS/CATERPILLAR ENGINE NUMBER YB50856, SN U8038, DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A 100 KW ELECTRICAL GENERATOR (BLDG 450, RADAR SITE)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap, roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. NOx emissions shall not exceed 5.30 g/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. The PM10 emissions rate shall not exceed 0.3 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
13. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the applicable requirements of SJVUAPCD Rule 4801 and Kings County APCD Rule 404. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-162-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #1 (BLDG 188, AIMD 500 TIRE SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-163-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #2 (BLDG 188, AIMD 500 TIRE SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: NAS LEMOORE

Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001

C-2106-163-2 : Apr 12 2011 2:37PM - DEMARISF

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-165-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #4 (BLDG 179, AIMD 900 DIVISION, GSE)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-166-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #5 (BLDG 170, AIMD 400 POWER PLANT SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-167-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR C, BLDG 180)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, -153 through -157, and -167 the Permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, -153 through -157, and -167 the Permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, -153 through -157, and -167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '127, '151, '153 through '157, and '167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal) [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
16. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
17. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
18. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits except as otherwise allowed by this permit: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT
PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
22. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
25. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
26. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603] Federally Enforceable Through Title V Permit
27. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97. [District Rule 4603] Federally Enforceable Through Title V Permit
28. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603] Federally Enforceable Through Title V Permit
29. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603] Federally Enforceable Through Title V Permit
30. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
31. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

DRAFT
PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4605] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-168-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

METAL PARTS AND PRODUCTS POWDER COATING OPERATION WITH ELECTROSTATIC SPRAY GUN(S), OPEN FACED POWDER COATING BOOTH WITH PULSE JET CARTRIDGE BAGHOUSE, 1.2 MMBTU/HR NATURAL GAS-FIRED CURING OVEN WITH A 1.2 MMBTU/HR ECLIPSE MODEL 160 AH BURNER, AND 1.9 MMBTU/HR NATURAL GAS-FIRED BURNOUT OVEN WITH A 1.9 MMBTU/HR ECLIPSE MODEL J121A-3 BURNER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The curing and burnout ovens shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A non-resettable hour meter to record the hours of operation for each of the curing and burnout oven shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Only electrostatic or equivalent coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4603] Federally Enforceable Through Title V Permit
8. All coating shall be conducted in booth with filters in place and fan(s) operating. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum hours of operation for the curing oven shall not exceed 8 hr/day or 260 days/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Maximum hours of operation for the burnout oven shall not exceed 8 hr/day or 260 days/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions from the natural gas-fired curing oven shall not exceed any of the following limits: 0.1 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the natural gas-fired burnout oven shall not exceed any of the following limits: 0.071 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Emissions from the spray booth shall not exceed 0.2 lb-PM10/day or 50 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. Powder coating use shall not exceed 320 lb/day or 83,200 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Powder coating operation shall be limited to polyester resin powder coating or other District-approved powder coating materials. [District Rules 2201 and 4603] Federally Enforceable Through Title V Permit
16. Powder coating material shall not contain VOC's. Manufacturer's Material Safety Data Sheets may be used to confirm the VOC content of the powder coating. [District Rules 2201 and 4603] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of daily and annual hours of operation of the curing and burnout oven. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall maintain daily records of quantity and type of powder coating used. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
20. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4603] Federally Enforceable Through Title V Permit
21. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-170-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TRANSPORTABLE LPG/PROPANE-FUELED MOBILE AIRCRAFT FIRE TRAINING DEVICE (MAFTD)

DRAFT

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. LPG gas consumption shall not exceed 600 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions shall not exceed any of the following limits: 21.45 lb NO_x/1000 gal, 0.094 lb-SO_x/1000 gal, 9.9 lb PM₁₀/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The MAFTD shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520] Federally Enforceable Through Title V Permit
7. Permittee shall maintain daily and annual records of the amount of LPG used in the MAFTD. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

ATTACHMENT B

Previous Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: C-2106-0-1

EXPIRATION DATE: 04/30/2008

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: NAS LEMOORE
Location: NAVAL AIR STATION LEMOORE, LEMOORE, CA 93246-5001
C-2106-0-1: Apr 1 2011 2:48PM - DEMARISF

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On August 31, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-1-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

487 BHP CATERPILLAR MODEL #3406B-D1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 001, CONTROL TOWER)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-2-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 003, THE FIELD LIGHTING VAULT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NO_x/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM₁₀ emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-6-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

69 BHP CUMMINS MODEL #L634T-1710148L DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 461, TACAN SITE)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NO_x/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM₁₀ emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-7-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

375 BHP CUMMINS MODEL #NT855-G4 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 462, TRANSMITTER FACILITY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-8-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

135 BHP CUMMINS MODEL #6BT-5.9-G1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 464, RECEIVER FACILITY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-9-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 468, APPROACH LIGHT VAULT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emissions control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District NSR Rule, District Rules 4701, and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel is to be used. [District NSR Rule, District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [District NSR Rule and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The PM10 emissions rate shall not exceed 1.0 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, District Rule 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-23-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:
JET TEST CELL #3 (BLDG 175)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The average daily combined emissions from test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed any of the following limits, during any calendar month: 327 lb-NOx/day, 166 lb-SOx/day, 160 lb-PM10/day, 1,454 lb-CO/day, or 613 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Emissions shall be calculated using the following emission factors: 0.106 lb-NOx/gal, 0.054 lb-SOx/gal, 0.052 lb-PM10/gal, 0.472 lb-CO/gal, and 0.199 lb-VOC/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The average daily combined fuel usage for test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed 3,080 gallons/day, for any calendar month. [District NSR Rule] Federally Enforceable Through Title V Permit
6. A record shall be maintained of the date, type, and quantity of engines tested, and daily fuel usage based on based on a monthly average at this test cell. The record shall be retained on-site for at least five years and made available for District inspection upon request. [District Rule 1070 and 2520, and 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-25-6

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Unit shall be fired on gasoline with a sulfur content of less than 0.008% by weight. [Rule 404 (Madera), 406 (Fresno) and 407 (6 remaining counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
4. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 6.2.3.1] Federally Enforceable Through Title V Permit
6. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NO_x/bhp-hr, 0.30 g-PM₁₀/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rules 406 (Fresno), 404 (Madera), 407 (Kern, Kings, San Joaquin, Stanislaus, Merced, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-26-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Unit shall be fired on gasoline with a sulfur content of less than 0.008% by weight. [Rule 404 (Madera), 406 (Fresno) and 407 (6 remaining counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
4. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 6.2.3.1] Federally Enforceable Through Title V Permit
6. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NO_x/bhp-hr, 0.30 g-PM₁₀/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rules 406 (Fresno), 404 (Madera), 407 (Kern, Kings, San Joaquin, Stanislaus, Merced, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-27-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Unit shall be fired on gasoline with a sulfur content of less than 0.008% by weight. [Rule 404 (Madera), 406 (Fresno) and 407 (6 remaining counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
4. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 6.2.3.1] Federally Enforceable Through Title V Permit
6. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NOx/bhp-hr, 0.30 g-PM10/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rules 406 (Fresno), 404 (Madera), 407 (Kern, Kings, San Joaquin, Stanislaus, Merced, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-28-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Unit shall be fired on gasoline with a sulfur content of less than 0.008% by weight. [Rule 404 (Madera), 406 (Fresno) and 407 (6 remaining counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
4. Operator shall maintain copies of fuel invoices and supplier certification of gasoline sulfur content. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 6.2.3.1] Federally Enforceable Through Title V Permit
6. Operation of each IC engine shall not exceed 4,680 hrs/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 5.96 g-NO_x/bhp-hr, 0.30 g-PM₁₀/bhp-hr, 234.4 g-CO/bhp-hr, or 2.49 g-VOC/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of total operation, the type of fuel used, and the purpose of the operation. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.3] Federally Enforceable Through Title V Permit
10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rules 406 (Fresno), 404 (Madera), 407 (Kern, Kings, San Joaquin, Stanislaus, Merced, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-39-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

COATING OPERATION WITH HVLP SPRAY GUN(S) AND DEVILBISS MODEL DLFA (SERIAL # 501) PAINT SPRAY BOOTH WITH DISPOSABLE EXHAUST FILTERS (BLDG 179, GROUND SUPPORT EQUIPMENT MAINTENANCE)

PERMIT UNIT REQUIREMENTS

1. The coating operation shall comply with Rule 4601 (Architectural), 4602 (Motor Vehicles and Mobile Equipment), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
2. All painting, including application of primer, shall be conducted inside the booth with filters in place, fan(s) operating, and doors closed. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed 40 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Amount of precoat used shall not exceed the amount of primer surfacer used. Precoat use shall be limited to one application per vehicle. Precoat shall not be used to fill in surface imperfections. [District Rule 4602] Federally Enforceable Through Title V Permit
7. VOC content of coatings as applied, excluding water and exempt compounds, used for Group I vehicles or Group II vehicles (when a color match is required) shall not exceed any of the following limits: pretreatment wash primer 780 g/l (6.5 lb/gal), precoat: 600 g/l (5.0 lb/gal) primer/primer surfacer: 250 g/l (2.1 lb/gal), primer sealer: 420 g/l (3.5 lb/gal), topcoat: 420 g/l (3.5 lb/gal), metallic/iridescent topcoat: 520 g/l (4.3 lb/gal), and multi-stage topcoat system: 540 g/l (4.5 lb/gal). [District Rule 4602] Federally Enforceable Through Title V Permit
8. VOC content of coatings as applied, excluding water and exempt compounds, used for Group II vehicles (when a color match is not required) shall not exceed any of the following limits: pretreatment wash primer 780 g/l (6.5 lb/gal), precoat: 600 g/l (5.0 lb/gal), primer/primer surfacer: 250 g/l (2.1 lb/gal), primer sealer: 340 g/l (2.8 lb/gal), topcoat: 420 g/l (3.5 lb/gal), metallic/iridescent topcoat: 420 g/l (3.5 lb/gal), and camouflage: 420 g/l (3.5 lb/gal). [District Rule 4602] Federally Enforceable Through Title V Permit
9. VOC content of specialty coatings (as defined in Rule 4602) as applied, excluding water and exempt compounds, shall not exceed 840 g/l (7.0 lb/gallon). If specialty coating usage, except anti-glare/safety coatings, exceeds 1 gallon per day, such coatings shall not exceed 5% (by volume) of total coatings applied in any month. [District Rule 4602] Federally Enforceable Through Title V Permit
10. VOC content of temporary protective coatings shall not exceed 60 g/l (0.5 lb/gal) of material. [District Rule 4602] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
14. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush or continuous coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4603] Federally Enforceable Through Title V Permit
15. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rule 4603] Federally Enforceable Through Title V Permit
16. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4603] Federally Enforceable Through Title V Permit
17. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4603] Federally Enforceable Through Title V Permit
18. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system, or equipment proven to be equally effective at controlling emissions, is used for cleaning. [District Rule 4603] Federally Enforceable Through Title V Permit
19. Effective 11/15/03, VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning (except, until June 30, 2005, cleaning of ultraviolet lamps used for the curing of ultraviolet coatings): 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application (except spot surface preparation solvent applied from hand held bottle for removal of road tar): 50 g/l (0.42 lb/gal); repair and maintenance cleaning: 50 g/l (0.42 lb/gal); and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). VOC content of solvents used for surface preparation of plastic substrates shall not exceed 100 g/l (0.83 lb/gallon). [District Rule 4602] Federally Enforceable Through Title V Permit
21. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605] Federally Enforceable Through Title V Permit
22. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
23. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
24. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
25. Until 6/30/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 550 g/l (4.6 lb/gallon), filler 500 g/l (4.2 lb/gallon), high-solids stains 700 g/l (5.8 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 550 g/l (4.6 lb/gallon), sanding sealer 550 g/l (4.6 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
26. Effective 7/1/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
27. Until 6/30/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 480 g/l (4.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
28. Effective 7/1/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
29. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
30. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
31. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

32. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
33. Permittee shall maintain daily records of the following: quantity and type (Group I, Group II vehicle with color match, or Group II vehicle without color match) of each vehicle coated; specific coatings used on each vehicle; mix ratios (by volume) of components added to each coating; volume of coatings applied; VOC content of each coating as applied; and purchase and usage of each specific solvent or reducer, showing the date, type and volume purchased or used. [District Rule 4602] Federally Enforceable Through Title V Permit
34. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-69-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

261 HP AUXILIARY POWER UNIT (APU) TEST PAD (T-26) (ADJACENT TO BUILDING 175)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Only GTC 36-200 engines shall be tested at this site. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Engine test rate shall not exceed 10 test/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep daily records of the number of engine tests, and fuel usage. Records shall be retained for at least five years and provided for District inspection upon request. [District Rule 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-70-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

T-14/T-17 OPEN ENGINE TEST PADS (BLDG 242)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Only F-404-GE-400, F404-GE-402, and T-400-CP-400 engines shall be tested at this site. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Engine test rate shall not exceed five F-404-GE-400 or F404-GE-402 tests/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep daily records of the number of engine tests, engine types, and fuel usage. Records shall be retained for at least five years and provided for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-74-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:
JET TEST CELL #4 (BLDG 176)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The average daily combined emissions from test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed any of the following limits, during any calendar month: 327 lb-NOx/day, 166 lb-SOx/day, 160 lb-PM10/day, 1,454 lb-CO/day, or 613 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Emissions shall be calculated using the following emission factors: 0.106 lb-NOx/gal, 0.054 lb-SOx/gal, 0.052 lb-PM10/gal, 0.472 lb-CO/gal, and 0.199 lb-VOC/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The average daily combined fuel usage for test cells #3 and #4, permit units C-2106-23 and -74, shall not exceed 3,080 gallons/day, for any calendar month. [District NSR Rule] Federally Enforceable Through Title V Permit
6. A record shall be maintained of the date, type, and quantity of engines tested, and daily fuel usage based on based on a monthly average at this test cell. The record shall be retained on-site for at least five years and made available for District inspection upon request. [District Rule 1070 and 2520, and 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-78-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

95 BHP JOHN DEERE MODEL 1876F SERIAL #T06059T401715 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 467, RUNWAY 32L)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 13.97 g-NOx/bhp-hr, 3.02 g-CO/bhp-hr, or 1.11 g-VOC/bhp-hr. [District Rule 2201 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-79-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

95 HP JOHN DEERE MODEL 1876F SERIAL #T06059T402783 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 466, RUNWAY 32R)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 13.97 g-NOx/bhp-hr, 3.02 g-CO/bhp-hr, or 1.11 g-VOC/bhp-hr. [District Rule 2201 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102 and 13 CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-117-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 1, MODULES 1 - 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-118-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 1)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-119-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 4)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-120-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-121-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-122-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-123-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-124-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-125-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-126-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 4)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-127-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 5)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
13. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
14. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
15. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
16. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
17. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit
18. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
20. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
21. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
22. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
24. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
26. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-131-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

54.3 MMBTU/HR LPG/PROPANE-FUELED FIRE TRAINING FACILITY

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
4. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201]
5. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201]
6. LPG gas consumption shall not exceed 1,800 gallons per day. [District Rule 2201]
7. Emissions shall not exceed any of the following limits: 21.45 lb NO_x/1000 gal, 0.094 lb-SO_x/1000 gal, 9.9 lb PM10/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201]
8. The fire training operation shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520, 9.3.2]
9. Permittee shall maintain daily and annual records of the amount of LPG used in the fire training operation. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520, 9.4.2]
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520, 9.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-140-5

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

BATCH LOADED COLD CLEANER DEGREASER, CONSISTING OF ONE CANISTER WITH 9.75 INCH OPEN DIAMETER AND CAPACITY LESS THAN 2.0 GALLONS (BLDG 188 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Degreaser shall be covered at all times except when parts are being added to, removed from, or handled in the solvent bath. [District Rule 4662] Federally Enforceable Through Title V Permit
3. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The capacity of the degreaser shall be less than 2.0 gallons. [District Rule 4662, 4.3] Federally Enforceable Through Title V Permit
5. The degreaser shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662, 4.3] Federally Enforceable Through Title V Permit
6. VOC emissions from this degreaser shall not exceed 2.0 lb VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.42 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The VOC content of the solvent shall not exceed 4.75 lb/gal. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Operator records shall be retained onsite for at least five years and provided for District inspection upon request. [District Rules 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-149-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

COATING OPERATION WITH MODEL #SPF-24-8-10, HV FLOOR FILTER OPEN FRONT PAINT SPRAY BOOTH WITH 25'W X 8'6"H X 13'2"L OUTSIDE DIMENSIONS (BLDG 188 - AIMD PAINT SHOP)

PERMIT UNIT REQUIREMENTS

1. The coating operation shall comply with Rule 4601 (Architectural), 4602 (Motor Vehicles and Mobile Equipment), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Emissions from paint booth shall not exceed either of the following limits: 46.2 lb VOC/day or 6.5 lb PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Total coating material usage shall not exceed 14.0 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. All painting, including application of primer, shall be conducted inside the booth with filters in place, fan(s) operating, and doors closed. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
8. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
9. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
10. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4602, 4603, and 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4602, 4603, and 4606] Federally Enforceable Through Title V Permit
12. Effective 11/15/03, VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning (except, until June 30, 2005, cleaning of ultraviolet lamps used for the curing of ultraviolet coatings): 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4602, 4603, and 4606] Federally Enforceable Through Title V Permit
13. Amount of precoat used shall not exceed the amount of primer surfacer used. Precoat use shall be limited to one application per vehicle. Precoat shall not be used to fill in surface imperfections. [District Rule 4602] Federally Enforceable Through Title V Permit
14. VOC content of coatings as applied, excluding water and exempt compounds, used for Group I vehicles or Group II vehicles (when a color match is required) shall not exceed any of the following limits: pretreatment wash primer 780 g/l (6.5 lb/gal), precoat: 600 g/l (5.0 lb/gal) primer/primer surfacer: 250 g/l (2.1 lb/gal), primer sealer: 420 g/l (3.5 lb/gal), topcoat: 420 g/l (3.5 lb/gal), metallic/iridescent topcoat: 520 g/l (4.3 lb/gal), and multi-stage topcoat system: 540 g/l (4.5 lb/gal). [District Rule 4602] Federally Enforceable Through Title V Permit
15. VOC content of coatings as applied, excluding water and exempt compounds, used for Group II vehicles (when a color match is not required) shall not exceed any of the following limits: pretreatment wash primer 780 g/l (6.5 lb/gal), precoat: 600 g/l (5.0 lb/gal), primer/primer surfacer: 250 g/l (2.1 lb/gal), primer sealer: 340 g/l (2.8 lb/gal), topcoat: 420 g/l (3.5 lb/gal), metallic/iridescent topcoat: 420 g/l (3.5 lb/gal), and camouflage: 420 g/l (3.5 lb/gal). [District Rule 4602] Federally Enforceable Through Title V Permit
16. VOC content of specialty coatings (as defined in Rule 4602) as applied, excluding water and exempt compounds, shall not exceed 840 g/l (7.0 lb/gallon). If specialty coating usage, except anti-glare/safety coatings, exceeds 1 gallon per day, such coatings shall not exceed 5% (by volume) of total coatings applied in any month. [District Rule 4602] Federally Enforceable Through Title V Permit
17. VOC content of temporary protective coatings shall not exceed 60 g/l (0.5 lb/gal) of material. [District Rule 4602] Federally Enforceable Through Title V Permit
18. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
19. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
20. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
21. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in Section 5.1, Table 1 of Rule 4605. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68 °F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit
23. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
24. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68°F. [District Rule 4605] Federally Enforceable Through Title V Permit
25. Effective 7/1/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
26. Until 6/30/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 480 g/l (4.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
27. Effective 7/1/2005, VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
28. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
29. The coating operation shall comply with, and all required records shall be maintained in accordance with, 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated as follows. [District NSR Rule, 4605, and 4606] Federally Enforceable Through Title V Permit
30. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
31. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
32. Permittee shall keep purchase and/or usage records showing the date, type and volume of each specific solvent or reducer used and the quantity and mix ratio of each specialty coating applied. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
33. Permittee shall maintain daily records of the following: quantity and type (Group I, Group II vehicle with color match, or Group II vehicle without color match) of each vehicle coated; specific coatings used on each vehicle; mix ratios (by volume) of components added to each coating; volume of coatings applied; VOC content of each coating as applied; and purchase and usage of each specific solvent or reducer, showing the date, type and volume purchased or used. [District Rule 4602] Federally Enforceable Through Title V Permit
34. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request.
[District Rules 4602, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-151-4

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 5, MODULES 1 - 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Permittee shall use no more than 68 gal/yr of cleanup solvents. [District Rule 4102]
9. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
12. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
14. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
15. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
16. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
17. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
18. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
20. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
21. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
23. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
26. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
27. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
30. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-153-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 1)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-154-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 2)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-155-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 3)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-156-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 4)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-157-3

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 1)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, '-153 through '-157, and '-167, the permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtalds Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, '-153 through '-157, and '-167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '-127, '-151, '-153 through '-157, and '-167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6; 4605, 5.5; and 4606, 5.4] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2; 4605, 5.5.3.2; and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 5.4 and 5.5.10; 4605, 5.4; and 4606, 5.5 and 5.6.10] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603, 5.5.7 and 4606, 5.6.6] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603, 5.5.9 and 4606, 5.6.8] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603, 5.5.2 and 4606, 5.6.3] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603, 5.1] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603, 5.2] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605, 5.1] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605, 5.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605, 5.2.3] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605, 5.3] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.5.6] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 6.2; 4605, 6.1.1; and 4606, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605, 6.1.2] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10; 4605, 6.1.5; and 4606, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-158-2

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

166 BHP PERKINS/CATERPILLAR ENGINE NUMBER YB50856, SN U8038, DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A 100 KW ELECTRICAL GENERATOR (BLDG 450, RADAR SITE)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115] Federally Enforceable Through Title V Permit
3. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [County Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus)] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap, roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
8. NOx emissions shall not exceed 5.30 g/bhp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The PM10 emissions rate shall not exceed 0.3 g/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule] Federally Enforceable Through Title V Permit
10. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 30 hours per calendar year. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the initial start-up hours, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-162-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #1 (BLDG 188, AIMD 500 TIRE SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-163-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #2 (BLDG 188, AIMD 500 TIRE SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-165-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #4 (BLDG 179, AIMD 900 DIVISION, GSE)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-166-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #5 (BLDG 170, AIMD 400 POWER PLANT SHOP)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. A permanent, conspicuous label shall be posted which lists operating requirements described in District Rule 4662. [District Rule 4662] Federally Enforceable Through Title V Permit
3. All fresh or spent solvent shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4662] Federally Enforceable Through Title V Permit
4. Solvent carryout shall be minimized by racking parts to allow complete drainage, tipping or rotating out any pool of solvent on the clean part before removal, and allowing parts to dry within the degreaser until visually dry. [District Rule 4662] Federally Enforceable Through Title V Permit
5. Permittee shall comply with the air-tight or airless cleaning system requirements. [District Rule 4662] Federally Enforceable Through Title V Permit
6. The equipment shall be operated in accordance with the manufacturer's specifications and operated with a door or other pressure sealing apparatus that is in place during all cleaning and drying cycles. [District Rule 4662] Federally Enforceable Through Title V Permit
7. All associated pressure relief devices shall not allow liquid solvents to drain out. Spills during solvent transfer shall be wiped up immediately and handled in accordance with Rule 4662, Section 5.1.1.7. [District Rule 4662] Federally Enforceable Through Title V Permit
8. A differential pressure gauge shall be installed to indicate the sealed chamber pressure. [District Rule 4662] Federally Enforceable Through Title V Permit
9. The degreaser and any solvent-holding pans shall be conspicuously marked to show the maximum allowable solvent level. [District Rule 4662] Federally Enforceable Through Title V Permit
10. Equipment shall be operated and maintained and records maintained in accordance with Rule 4662 (Organic Solvent Degreasing Operations). [District Rule 4662] Federally Enforceable Through Title V Permit
11. Solvent usage for this degreaser, excluding solvent that is recycled or disposed of properly, shall not exceed 0.14 gal/day. [District NSR Rule] Federally Enforceable Through Title V Permit
12. VOC emissions from this degreaser shall not exceed 1.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Operator shall maintain monthly records of solvent usage and type. The records shall be retained for at least five years and provided for District inspection upon request. [District Rules 1070 and 4662] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. The permittee shall maintain records on a monthly basis which show all of the following: the type of degreaser, the type of solvent and the VOC content of solvent as used, the solvent initial boiling point, the volume of solvent used, the volume of make-up solvent added, the volume of solvent removed for recycling or disposal purposes, and acceptable disposal methods. [District Rule 4662, 6.1.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-167-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR C, BLDG 180)

PERMIT UNIT REQUIREMENTS

1. Coating of aerospace parts not attached to the aircraft, metal parts, or wood products shall be done using brush, dip, roll coating application equipment. If spray coating equipment is used (except when coating aerospace parts attached to the aircraft), coating shall be done in paint spray booths (permit units C-2106-39 and -149). [District NSR Rule] Federally Enforceable Through Title V Permit
2. The permittee shall maintain monthly and annual summaries of total VOC emissions from all squadron corrosion control and maintenance coating operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The coating operation shall comply with Rule 4601 (Architectural), 4603 (Metal Parts and Products), 4605 (Aerospace Assembly or Components), or 4606 (Wood Products), depending on item being coated. [District Rules 4601, 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. In permit units C-2106-151, -153 through -157, and -167 the Permittee shall use no more than 34 gal/yr of each of the following aerospace coatings: PRF-85582 Polyamide Epoxy Primer, TT-P-2760 Low Infrared (IR) Primer, and C-83445 Rain Erosion Topcoat. [District Rule 4102]
6. In permit units C-2106-151, -153 through -157, and -167 the Permittee shall use no more than 17 gal/yr of each of the following aerospace coatings: Caap FP-070 Conformal Coating and Courtaldis Polyol PR-2414 Low Observability Coating. [District Rule 4102]
7. Permittee shall maintain monthly and annual summaries of the cumulative amounts of each type of aerospace coating and solvent applied in permit units C-2106-151, -153 through -157, and -167. [District Rule 4102]
8. Emissions from this unit shall not exceed either of the following limits: 63.2 lb-VOC/day or 27.0 lb-PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Emissions from all squadron coating operations (C-2106-117 through '127, '151, '153 through '157, and '167), shall not exceed either of the following limits: 254,334 lb-VOC/yr or 108,619 lb-PM10/yr based on a twelve month rolling average. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush coating, or continuous application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
11. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
13. Cleaning activities that use solvents with a VOC content greater than 50 g/l (0.42 lb/gallon) shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
14. Permittee shall not use materials with a VOC content greater than 50 g/l (0.42 lb/gallon) for spray equipment clean-up unless an enclosed system or equipment proven to be equally effective is used for cleaning. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
15. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 50 g/l (0.42 lb/gal), repair and maintenance cleaning: 50 g/l (0.42 lb/gal), and cleaning of coating application equipment: 550 g/l (4.6 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
16. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
17. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 360 g/l (3.0 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
18. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic topcoat: 420 g/l (3.5 lb/gal), pretreatment wash primer: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbant: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
19. VOC content of aerospace coatings as applied, excluding water and exempt compounds, used for aerospace components shall not exceed any of the limits listed in section 5.1, Table 1 of Rule 4605. [District Rule 4605] Federally Enforceable Through Title V Permit
20. Permittee shall not use materials with a VOC content greater than or equal to 200 g/l (1.67 lb/gal) as applied or with a VOC composite vapor pressure greater than 45 mmHg (0.87 psia) at 68°F, for aerospace surface cleaning, cleanup, or jet engine or rocket engine gas path cleaning or flushing, excluding stripping coatings or cleaning coating application equipment. [District Rule 4605] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall not use VOC-containing materials to clean spray equipment used for the application of aerospace coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use. [District Rule 4605] Federally Enforceable Through Title V Permit
22. Permittee shall not use or specify for use within the District an aerospace coating stripper with a VOC content greater than or equal to 300 g/l (2.5 lb/gal) as applied or with a VOC composite vapor pressure of greater than 9.5 mmHg (0.18 psia) at 68 °F. [District Rule 4605] Federally Enforceable Through Title V Permit
23. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
24. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
25. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606] Federally Enforceable Through Title V Permit
26. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
27. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records to support that the following aerospace coatings have been specified for their intended application: adhesion promoter, antichafe coating, electric/radiation effect, fuel tank adhesive, high temperature coating, impact resistant coating, optical anti-reflective coating, rain erosion resistant wing coating. [District Rule 4605] Federally Enforceable Through Title V Permit
29. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 4605, and 4606] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-168-1

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

METAL PARTS AND PRODUCTS POWDER COATING OPERATION WITH ELECTROSTATIC SPRAY GUN(S), OPEN FACED POWDER COATING BOOTH WITH PULSE JET CARTRIDGE BAGHOUSE, 1.2 MMBTU/HR NATURAL GAS-FIRED CURING OVEN WITH A 1.2 MMBTU/HR ECLIPSE MODEL 160 AH BURNER, AND 1.9 MMBTU/HR NATURAL GAS-FIRED BURNOUT OVEN WITH A 1.9 MMBTU/HR ECLIPSE MODEL J121A-3 BURNER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The curing and burnout ovens shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A non-resettable hour meter to record the hours of operation for each of the curing and burnout oven shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Only electrostatic or equivalent coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rule 4603] Federally Enforceable Through Title V Permit
8. All coating shall be conducted in booth with filters in place and fan(s) operating. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum hours of operation for the curing oven shall not exceed 8 hr/day or 260 days/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Maximum hours of operation for the burnout oven shall not exceed 8 hr/day or 260 days/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions from the natural gas-fired curing oven shall not exceed any of the following limits: 0.1 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the natural gas-fired burnout oven shall not exceed any of the following limits: 0.071 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Emissions from the spray booth shall not exceed 0.2 lb-PM10/day or 50 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Powder coating use shall not exceed 320 lb/day or 83,200 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Powder coating operation shall be limited to polyester resin powder coating or other District-approved powder coating materials. [District Rules 2201 and 4603] Federally Enforceable Through Title V Permit
16. Powder coating material shall not contain VOC's. Manufacturer's Material Safety Data Sheets may be used to confirm the VOC content of the powder coating. [District Rules 2201 and 4603] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of daily and annual hours of operation of the curing and burnout oven. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall maintain daily records of quantity and type of powder coating used. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. All fresh or spent coatings, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4603] Federally Enforceable Through Title V Permit
20. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-2106-170-0

EXPIRATION DATE: 04/30/2008

EQUIPMENT DESCRIPTION:

TRANSPORTABLE LPG/PROPANE-FUELED MOBILE AIRCRAFT FIRE TRAINING DEVICE (MAFTD)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
4. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201]
5. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201]
6. LPG gas consumption shall not exceed 600 gallons per day. [District Rule 2201]
7. Emissions shall not exceed any of the following limits: 21.45 lb NO_x/1000 gal, 0.094 lb-SO_x/1000 gal, 9.9 lb PM₁₀/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201]
8. The MAFTD shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520, 9.3.2]
9. Permittee shall maintain daily and annual records of the amount of LPG used in the MAFTD. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520, 9.4.2]
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520, 9.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Authorities to Construct



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



AUTHORITY TO CONSTRUCT

PERMIT NO: C-2106-131-5

ISSUANCE DATE: 06/24/2010

LEGAL OWNER OR OPERATOR: NAS LEMOORE
MAILING ADDRESS: BUILDING 750 CODE 50800
LEMOORE, CA 93246-5001

LOCATION: NAVAL AIR STATION LEMOORE
LEMOORE, CA 93246-5001

EQUIPMENT DESCRIPTION:
MODIFICATION OF 54.3 MMBTU/HR PROPANE-FUELED FIRE TRAINING FACILITY: COMBINED ANNUAL FUEL USAGE LIMIT WITH UNIT -170

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Authority to Construct (ATC) C-2106-131-3 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
3. This Authority to Construct (ATC) shall be implemented concurrently with ATC C-2106-170-0. [District Rule 2201]
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
7. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201]
8. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201]
9. LPG gas consumption shall not exceed 1,800 gallons per day. [District Rule 2201]
10. Emissions shall not exceed any of the following limits: 21.45 lb NOx/1000 gal, 0.094 lb-SOx/1000 gal, 9.9 lb PM10/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-2106-131-5 Jun 24 2010 4:42PM - REFUERZJ - Joint Inspection NOT Required

Conditions for C-2106-131-5 (continued)

11. The fire training operation shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520, 9.3.2]
12. Permittee shall maintain daily and annual records of the amount of LPG used in the fire training operation. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520, 9.4.2]
13. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520, 9.4.2]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-2106-170-0

ISSUANCE DATE: 06/24/2010

LEGAL OWNER OR OPERATOR: NAS LEMOORE
MAILING ADDRESS: BUILDING 750 CODE 50800
LEMOORE, CA 93246-5001

LOCATION: NAVAL AIR STATION LEMOORE
LEMOORE, CA 93246-5001

EQUIPMENT DESCRIPTION:
TRANSPORTABLE LPG/PROPANE FIRE MOBILE AIRCRAFT FIRE TRAINING DEVICE (MAFTD)


CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Authority to Construct (ATC) C-2106-131-3 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
3. This Authority to Construct (ATC) shall be implemented concurrently with ATC C-2106-131-5. [District Rule 2201]
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
7. The fire training operation shall be fired on LPG gas fuel (propane) only. [District Rule 2201]
8. The combined LPG gas consumption from units C-2106-131 and -170 shall not exceed 27,800 gallons per year. [District Rule 2201]
9. LPG gas consumption shall not exceed 600 gallons per day. [District Rule 2201]
10. Emissions shall not exceed any of the following limits: 21.45 lb NOx/1000 gal, 0.094 lb-SOx/1000 gal, 9.9 lb PM10/1000 gal, 36.43 lb CO/1000 gal, or 28.62 lb VOC/1000 gal. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO



DAVID WARNER, Director of Permit Services
C-2106-170-0 - Jun 24 2010 4:42PM - REFURZJ - Joint Inspection NOT Required

Conditions for C-2106-170-0 (continued)

11. The MAFTD shall be equipped with a non-resettable fuel flow metering device. [District NSR Rule and 2520, 9.3.2]
12. Permittee shall maintain daily and annual records of the amount of LPG used in the MAFTD. The amount of LPG used shall be taken from the non-resettable fuel flow meter. [District Rules 2201 and 2520, 9.4.2]
13. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520, 9.4.2]

ATTACHMENT D

Emissions Increases

	SSIPE (lb/yr)				
	NOx	VOC	CO	SOx	PM10
C-2106-131-5	0	0	0	0	0
C-2106-170-0	0	0	0	0	0
TOTAL	0	0	0	0	0

ATTACHMENT E

Detailed Facility List

Detailed Facility Report
For Facility=2106
Sorted by Facility Name and Permit Number

NAS LEMOORE NAVAL AIR STATION LEMOORE LEMOORE, CA 93246-5001	FAC # STATUS: TELEPHONE:	C 2106 A 5599984113	TYPE: TOXIC ID:	TitleV 40092	EXPIRE ON: AREA: INSP. DATE:	04/30/2008 9 / 05/11
---	---	--	----------------------------------	-------------------------------	---	---

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-1-2	487 hp IC engine	3020-10 D	1	479.00	479.00	A	487 BHP CATERPILLAR MODEL #3406B-D1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 001, CONTROL TOWER)
C-2106-2-2	749 hp IC engine	3020-10 D	1	479.00	479.00	A	749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 003, THE FIELD LIGHTING VAULT)
C-2106-3-0	113 HP EMERGENCY IC ENGINE	3020-10 B	1	117.00	117.00	D	113 HP PERKINS MODEL #T6-3544 6 CYLINDER DIESEL-FIRED EMERGENCY IC ENGINE. THE ENGINE IS LOCATED IN BUILDING 60 - THE OPERATIONS WASTEWATER TREATMENT PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-5-0)
C-2106-4-0	127 HP EMERGENCY IC ENGINE	3020-10 B	1	117.00	117.00	D	127 HP CATERPILLAR MODEL #3304 EMERGENCY IC ENGINE, DIESEL FIRED, 4 CYLINDER. THIS ENGINE IS LOCATED IN BUILDING 80 - THE TELEPHONE EXCHANGE. (TRANSFERRED TO C-2341, NEW PTO# C-2341-6-0)
C-2106-5-0	268 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	268 HP CATERPILLAR MODEL #3306 DIESEL-FIRED EMERGENCY IC ENGINE (BLDG 450, RADAR SITE)
C-2106-6-2	69 hp IC engine	3020-10 A	1	80.00	80.00	A	69 BHP CUMMINS MODEL #L634T-1710148L DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 461, TACAN SITE)
C-2106-7-2	375 hp IC engine	3020-10 C	1	240.00	240.00	A	375 BHP CUMMINS MODEL #NT855-G4 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 462, TRANSMITTER FACILITY)
C-2106-8-2	135 hp IC engine	3020-10 B	1	117.00	117.00	A	135 BHP CUMMINS MODEL #6BT-5.9-G1 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 464, RECEIVER FACILITY)
C-2106-9-3	749 hp IC engine	3020-10 D	1	479.00	479.00	A	749 BHP CATERPILLAR MODEL #3412 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE (BLDG 468, APPROACH LIGHT VAULT)
C-2106-12-0	586 HP EMERGENCY IC ENGINE	3020-10 D	1	479.00	479.00	D	586 HP DETROIT MODEL #81237300, 12 CYLINDER, DIESEL-FIRED EMERGENCY IC ENGINE. THIS ENGINE IS LOCATED IN BUILDING 928 - MOTOR GENERATOR BUILDING. (TRANSFERRED TO C-2341, NEW PTO# C-2341-7-0)
C-2106-13-0	293 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	293 HP DETROIT MODEL #80637405, 6 CYLINDER, DIESEL-FIRED EMERGENCY IC ENGINE. THIS ENGINE IS LOCATED IN BUILDING 928 - MOTOR GENERATOR BUILDING. (TRANSFERRED TO C-2341, NEW PTO# C-2341-8-0)
C-2106-14-0	42.5 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	42.5 HP ONAN DIESEL IC ENGINE, MODEL #P2297 4 CYLINDER, SERIAL #709669. THIS EMERGENCY GENERATOR IS LOCATED IN BUILDING 929 - MEDICAL STORES WAREHOUSE. *** EXEMPT FROM PERMITTING - LESS THAN 50 HP.
C-2106-15-0	268 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	268 HP CATERPILLAR MODEL #3306, 6 CYLINDER, DIESEL-FIRED EMERGENCY IC ENGINE. THIS ENGINE IS LOCATED IN BUILDING 930 - THE HOSPITAL. (TRANSFERRED TO C-2341, NEW PTO# C-2341-9-0)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-16-0	78 HP EMERGENCY IC ENGINE	3020-10 A	1	80.00	80.00	D	78 HP JOHN DEERE MODEL #R81841, 4 CYLINDER, DIESEL-FIRED EMERGENCY IC ENGINE. THIS EMERGENCY GENERATOR IS LOCATED IN BUILDING 960 - SURVIVAL SWIMMING POOL. (TRANSFERRED TO C-2341, NEW PTO# C-2341-47-0)
C-2106-17-0	175 HP EMERGENCY IC ENGINE	3020-10 B	1	117.00	117.00	D	175 HP JOHN DEERE MODEL #6076TF-00, 6 CYLINDER, DIESEL-FIRED EMERGENCY IC ENGINE. THIS ENGINE IS LOCATED IN BUILDING 980 - WASTE WATER TREATMENT AND ADMINISTRATION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-10-0)
C-2106-18-0	CLASSIFIED INCINERATOR	3020-06	1	105.00	105.00	D	CLASSIFIED WASTE INCINERATOR, COMTRO DISPOSAL SYSTEMS, MODEL A-24, SERIAL #C-318-82. LOCATED IN BLDG #4 - LIGHT ATTACK WEAPON SCHOOL. (TRANSFERRED TO C-2341, NEW PTO# C-2341-39-0)
C-2106-19-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER. LOCATED IN BLDG 824 - CAFETERIA AND NAVEX SHOPS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-24-0)
C-2106-21-0	JET TEST CELL #1	3020-02 H	1	1,030.00	1,030.00	D	JET TEST CELL #1 INCLUDING COANDA MODIFICATIONS. LOCATED IN BLDG 173. **SURRENDERED PER ATC CONDITION #5 (C-2106-74-0)**
C-2106-22-0	JET TEST CELL #2	3020-02 H	1	1,030.00	1,030.00	D	JET TEST CELL #2. LOCATED IN BLDG 174.
C-2106-23-2	>15,000 kBtu/hr gas turbine	3020-02 H	1	1,030.00	1,030.00	A	JET TEST CELL #3 (BLDG 175)
C-2106-24-0	2.1 MMBTU/HR BOILER	3020-02 E	1	412.00	412.00	D	2.1 MMBTU/HR PORTABLE CLEAVER-BROOKS MODEL CB100X-50 BOILER NO. 11, S/N L-69734. BOILER IS LOCATED IN BLDG 930, BASE HOSPITAL.
C-2106-25-6	132 bhp IC engines	3020-10 B	1	117.00	117.00	A	TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32R)
C-2106-26-5	132 bhp IC engines	3020-10 B	1	117.00	117.00	A	TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 32L)
C-2106-27-5	132 bhp IC engines	3020-10 B	1	117.00	117.00	A	TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14R)
C-2106-28-5	132 bhp IC engines	3020-10 B	1	117.00	117.00	A	TWO 66 HP TELEDYNE-WISCONSIN MODEL #V-465D GASOLINE-FIRED "MILITARY TACTICAL EQUIPMENT" IC ENGINES POWERING AN ARRESTING GEAR SYSTEM (RUNWAY 14L)
C-2106-29-2	50 HP PLASTIC-SHOT BLASTER	3020-01 C	1	197.00	197.00	D	50 HP PRAM 22-2 DRY STRIPPING SYSTEM WITH A 8'W X 12.5'L X 7'H BLAST ROOM SERVED BY A MECHANICAL SHAKER TYPE BAGHOUSE (SERIAL # 3897) (BLDG 170, AIMD CLEANING SHOP)
C-2106-30-0	10 HP GLASS BEAD BLASTING	3020-01 A	1	87.00	87.00	D	10 HP ZERO MANUFACTURING "BLAST-N-PEEN" (SERIAL # PFD-32832) GLASS BEAD BLASTING MACHINE EQUIPPED WITH CLEMCO INDUSTRIES MODEL 1648 COLLECTOR/SEPARATOR, HOODS AND DUCTS WITH A ROTOCONE MODEL 14 AIR FILTERING UNIT (BLDG 170)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-31-0	1475 GAL PAINT STRIPPING TANK	3020-06	1	105.00	105.00	D	1475 GALLON TURCO PRODUCTS MODEL 3504 TURBULATOR PAINT STRIPPING TANK. LOCATED IN BLDG 170--AIMD CLEANING SHOP.
C-2106-32-0	755 GALLON DESCALER TANK	3020-06	1	105.00	105.00	D	755 GALLON TURCO PRODUCTS MODEL 3502 TURBULATOR DESCALER TANK. LOCATED IN BLDG 170--AIMD CLEANING SHOP.
C-2106-33-0	755 GAL SCALE CONDITION'G TANK	3020-06	1	105.00	105.00	D	755 GALLON TURCO PRODUCTS MODEL 3502 TURBULATOR SCALE CONDITIONING TANK. LOCATED IN BLDG 170--AIMD CLEANING SHOP.
C-2106-34-0	STEAM CLEANING OPERATION	3020-06	1	105.00	105.00	D	STEAM / ALODYNE SOLVENT CLEANING OPERATION. LOCATED IN BLDG 170--AIMD CLEANING SHOP.
C-2106-35-0	60 GAL DEGREASER TANK	3020-06	1	105.00	105.00	D	60 GALLON PHILLIPS MFG. CO. MODEL T-60-S DEGREASER TANK, UTILIZING 1,1,1, TRICHLOROETHANE SOLVENT. LOCATED IN BLDG 170-- AIMD CLEANING SHOP.
C-2106-36-0	ULTRASONIC VAPOR DEGREASER	3020-06	1	105.00	105.00	D	ONE WESTINGHOUSE ELECTRIC CORP MODEL DG-3.5C5 ULTRASONIC VAPOR DEGREASER, UTILIZING 1,1,1, TRICHLOROETHANE SOLVENT. LOCATED IN BLDG 170--AIMD CLEANING SHOP.
C-2106-37-0	PAINT SPRAY BOOTH	3020-06	1	105.00	105.00	D	ONE WEST COAST SPRAY BOOTH MODEL WCB5-7 PAINT SPRAY BOOTH,S/N P95-60A-WCB 5X7-01. LOCATED IN BLDG 160, AIMD, AVIONICS. **EXEMPT FROM PERMITS. SPRAY CANS ONLY. EMISSIONS < 2.0 LB/DAY.
C-2106-38-2	10 HP ABRASIVE CLEANER	3020-06	1	105.00	105.00	D	10 HP ZERO CORP BLAST-N-PEEN (SERIAL # 40614) MULTIMEDIA ABRASIVE CLEANING MACHINE EQUIPPED WITH CLEMCO INDUSTRIES MODEL 1648 COLLECTOR/SEPARATOR SERVED BY A TORIT DUST COLLECTOR (BLDG 179, GROUND SUPPORT EQUIPMENT MAINTENANCE)
C-2106-39-2	10 hp electric motors	3020-01 A	1	87.00	87.00	A	COATING OPERATION WITH HVLP SPRAY GUN(S) AND DEVILBISS MODEL DLFA (SERIAL # 501) PAINT SPRAY BOOTH WITH DISPOSABLE EXHAUST FILTERS (BLDG 179, GROUND SUPPORT EQUIPMENT MAINTENANCE)
C-2106-40-0	WATER WALL PAINT SPRAY BOOTH	3020-06	1	105.00	105.00	D	DEVILBISS MODEL DW-6211 WATER WALL PAINT SPRAY BOOTH, 30' X 10' X 12'. LOCATED IN BLDG 180--AIRCRAFT MAINTENANCE. ***PERMIT SURRENDERED JUNE 10, 1993.
C-2106-41-0	7.5 DUST COLLECTOR W/CYCLONE	3020-01 A	1	87.00	87.00	D	WOODWORKING OPERATION SERVED BY DUSTVENT MODEL 22T7-1/2 DUST COLLECTOR, S/N 21789, WITH CYCLONE. LOCATED IN BLDG 745, PUBLIC WORKS DEPT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-37-0)
C-2106-42-0	10 HP DUST COLLECTOR W/CYCLONE	3020-01 A	1	87.00	87.00	D	10 HP SAWDUST COLLECTION SYSTEM DUCTED TO A NO. 16 TYPE D ROTO-CLONE WITH SKIMMER PRECLEANER AND HOPPER. LOCATED IN BLDG 750, PUBLIC WORKS DEPT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-38-0)
C-2106-43-1	1075 KBTU/HR BURNER	3020-02 D	1	314.00	314.00	D	SPRAY PAINT COATING OPERATION WITH HVLP SPRAY GUN, PAINT SPRAY BOOTH WITH EXHAUST FILTERS AND 1.075 MMBTU/HR BURNER. (TRANSFERRED TO C-2341, NEW PTO# C-2341-40-0)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-44-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 276. LOCATED IN BLDG 856 - BARRACKS.
C-2106-45-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 4229. LOCATED IN BLDG 930 - BASE HOSPITAL. (TRANSFERRED TO C-2341, NEW PTO# C-2341-25-0)
C-2106-46-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 4467. LOCATED IN BLDG 930 - BASE HOSPITAL. (TRANSFERRED TO C-2341, NEW PTO# C-2341-26-0)
C-2106-47-1	5,500 KBTU/HR	3020-02 G	1	815.00	815.00	D	5.5 MMBTU/HR RITE ENGINEERING MODEL 550 NATURAL GAS-FIRED BOILER, S/N 79-17488, WITH RAY PCPF BURNER, S/N 303298. LOCATED IN BLDG 730 - TRAINING BLDG A. (TRANSFERRED TO C-2341, NEW PTO# C-2341-27-0)
C-2106-48-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR RITE ENGINEERING MODEL A700WGO NATURAL GAS-FIRED BOILER, S/N 9022183. LOCATED IN BLDG 210 - AIR GROUP HANGAR 1. (TRANSFERRED TO C-2341, NEW PTO# C-2341-45-0)
C-2106-49-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR RITE ENGINEERING MODEL 700 NATURAL GAS-FIRED BOILER, S/N 11439Q7. LOCATED IN BLDG 240 - AIR GROUP HANGAR 2.
C-2106-50-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR RITE ENGINEERING MODEL A700WGO NATURAL GAS-FIRED BOILER, S/N 11440Q7. LOCATED IN BLDG 270 - AIR GROUP HANGAR 3.**SURRENDERED PER PROJECT 980310/C-2106-43**
C-2106-51-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR RITE ENGINEERING MODEL 700 NATURAL GAS-FIRED BOILER, S/N 9022308. LOCATED IN BLDG 300 - AIR GROUP HANGAR 4. (TRANSFERRED TO C-2341, NEW PTO# C-2341-46-0)
C-2106-52-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR SUPERIOR SCOTCH MODEL A-150 NATURAL GAS-FIRED BOILER, S/N 4469. LOCATED IN BLDG 10 - BRANCH SUBSISTANCE. ** PERMIT SURRENDERED FOR ERC PROJECT 990144 ***
C-2106-53-1	6,300 KBTU/HR	3020-02 G	1	815.00	815.00	D	6.3 MMBTU/HR SUPERIOR SCOTCH MODEL A-150 NATURAL GAS-FIRED BOILER, S/N 4486. LOCATED IN BLDG 10 - BRANCH SUBSISTANCE. (TRANSFERRED TO C-2341, NEW PTO# C-2341-28-0)
C-2106-54-0	8.4 MMBTU/HR BOILER	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR (250 BOHP) SUPERIOR SCOTCH MODEL A-200 BOILER, S/N 275, WITH A PEABODY-GORDON-PIATT S12.1-GO50 BURNER. LOCATED ON BLDG. 840 - BARRACKS. *** REMOVED PER 2/1/96 LETTER - MK ***
C-2106-55-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 272. LOCATED IN BLDG 843 - BARRACKS. *** PERMIT SURRENDERED FOR ERC PROJECT #990144 ***
C-2106-56-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 271, WITH PAWNEE MODEL S-12-6-50 BURNER. LOCATED IN BLDG 848 - BARRACKS. *** PERMIT SURRENDERED FOR ERC PROJECT 990144 ***

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-57-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 277. LOCATED IN BLDG 850 - BARRACKS.
C-2106-58-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 278. LOCATED IN BLDG 852 - BARRACKS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-29-0)
C-2106-59-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-200 NATURAL GAS-FIRED BOILER, S/N 273. LOCATED IN BLDG 855 - BARRACKS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-30-0)
C-2106-60-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-250 NATURAL GAS-FIRED BOILER, S/N 4485. LOCATED IN BLDG 860 - ENLISTED MESS AND COLD STORES. *** PERMIT SURRENDERED FOR ERC PROJECT 990144 ***
C-2106-61-1	8,400 KBTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR SUPERIOR SCOTCH MODEL A-250 NATURAL GAS-FIRED BOILER, S/N 4484. LOCATED IN BLDG 860 - ENLISTED MESS AND COLD STORES. *** PERMIT SURRENDERED FOR ERC PROJECT 990144 ***
C-2106-62-1	PAINT SPRAY BOOTH	3020-01 A	1	87.00	87.00	D	MODIFIED BINKS MODEL WE-8-T-LH PAINT SPRAY BOOTH. LOCATED IN BLDG 188, AIMD PAINT SHOP.
C-2106-63-1	CHEMCO PAINT SPRAY BOOTH	3020-01 A	1	87.00	87.00	D	MODIFIED BINKS MODEL WE-10-8-TLH PAINT SPRAY BOOTH. LOCATED IN BLDG 188, AIMD SHEETMETAL SHOP.
C-2106-64-0	PAINT SPRAY BOOTH	3020-06	1	105.00	105.00	D	DEVILBISS MODEL XVS 6080 PAINT SPRAY BOOTH WITH DISPOSABLE FILTERS. LOCATED IN BLDG 955--AUTO HOBBY SHOP. *** PERMIT SURRENDERED JULY, 1993.
C-2106-65-2	GASOLINE DISPENSING NOZZLES	3020-11 A	4	34.00	136.00	D	25,000 GALLON UNDERGROUND STORAGE TANK SERVED BY TWO POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-2-G) AND 4 FUELING POINTS WITH 4 GASOLINE DISPENSING NOZZLES SERVED BY BALANCE TYPE PHASE II VAPOR RECOVERY SYSTEM (G-70-52-AM). (TRANSFERRED TO C-2341, NEW PTO# C-2341-34-0)
C-2106-68-0	GASOLINE DISPENSING NOZZLES	3020-11 A	2	34.00	68.00	D	10,000 GALLON UNDERGROUND STORAGE TANK SERVED BY 2-POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-97) AND 2 GASOLINE DISPENSING NOZZLES SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-52-AM). EQUIPMENT IS LOCATED IN BUILDING 765 - PUBLIC WORKS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-35-0)
C-2106-69-1	261 hp engine	3020-10 C	1	240.00	240.00	A	261 HP AUXILIARY POWER UNIT (APU) TEST PAD (T-26) (ADJACENT TO BUILDING 175)
C-2106-70-3	T-14/T-17 open test cells	3020-02 H	1	1,030.00	1,030.00	A	T-14/T-17 OPEN ENGINE TEST PADS (BLDG 242)
C-2106-71-0	COLD CLEANER DEGREASER	3020-06	1	105.00	105.00	D	KLEER-FLO KLEENMASTER MODEL J-40 COLD CLEANER DEGREASER, SN 70-6751, LOCATED IN BLDG 188 - AIMD TIRE SHOP
C-2106-72-2	COLD CLEANER DEGREASER	3020-06	1	105.00	105.00	D	RAMCO MODEL MK-24 SERIAL #J9386-92-022 AGITATED PLATFORM DEGREASER (BLDG 188, AIMD TIRE SHOP)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-73-0	1 NOZZLE	3020-11 A	1	34.00	34.00	D	ONE 1000 GALLON CONVAULT ABOVEGROUND AVIATION FUEL TANK SERVED BY PHASE I RECOVERY SYSTEM (G-70-97A) WITH ONE GASOLINE DISPENSING NOZZLE EXEMPT FROM PHASE II REQUIREMENTS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-36-0)
C-2106-74-2	>15,000 kBtu/hr gas turbine	3020-02 H	1	1,030.00	1,030.00	A	JET TEST CELL #4 (BLDG 176)
C-2106-76-1	COLD CLEANER DEGREASER	3020-06	1	105.00	105.00	D	RAMCO MODEL MK-24 SERIAL # J9386-92-024 AGITATED PLATFORM DEGREASER
C-2106-77-1	COLD SOLVENT DEGREASER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY SOLVENT CLEANER, MODEL 1630, INSIDE TUB DIMENSION 32"L X 22"W X 10"H. LOCATED IN BUILDING 765. (TRANSFERRED TO C-2341, NEW PTO# C-2341-41-0)
C-2106-78-3	95 bhp IC engine	3020-10 A	1	80.00	80.00	A	95 BHP JOHN DEERE MODEL 1876F SERIAL #T06059T401715 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 467, RUNWAY 32L)
C-2106-79-3	95 bhp IC engine	3020-10 A	1	80.00	80.00	A	95 HP JOHN DEERE MODEL 1876F SERIAL #T06059T402783 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR (PRECISION APPROACH RADAR, STRUCTURE 466, RUNWAY 32R)
C-2106-80-0	275 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	275 HP CUMMINS MODEL NHS-6-1F EMERGENCY IC ENGINE, SN 226929, DIESEL FIRED, CENTRIFUGAL FIRE WATER PUMP #1, BLDG 50, WATER DISTRIBUTION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-11-0)
C-2106-81-1	270 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	270 HP CUMMINS MODEL #6CTA8.3F2 DIESEL-FIRED EMERGENCY IC ENGINE, EQUIPPED WITH TURBOCHARGER, AFTERCOOLER, AND PCV, DRIVING CENTRIFUGAL FIRE WATER PUMP #2, BLDG 50, WATER DISTRIBUTION PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-12-0)
C-2106-82-0	275 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	275 HP CUMMINS MODEL NHS-6-1F EMERGENCY IC ENGINE, DIESEL FIRED, DRIVING CENTRIFUGAL FIRE WATER PUMP #3, BLDG 50 WATER DISTRIBUTION PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-13-0)
C-2106-83-0	275 HP EMERGENCY IC ENGINE	3020-10 C	1	240.00	240.00	D	275 CUMMINS MODEL NHS-6-1F EMERGENCY IC ENGINE, DIESEL FIRED, DRIVING A CENTRIFUGAL FIRE WATER PUMP, BLDG 760, WATER TREATMENT PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-14-0)
C-2106-84-1	270 BHP	3020-10 C	1	240.00	240.00	D	270 BHP CUMMINS MODEL 6CTA8.3F2 DIESEL IC ENGINE WITH TURBOCHARGER AND AFTERCOOLER, POWERING AN EMERGENCY FIRE WATER PUMP. LOCATED AT BLDG 760 - WATER TREATMENT PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-15-0)
C-2106-85-1	550 BHP DIESEL EMERGENCY ICE	3020-10 D	1	479.00	479.00	D	550 HP CATERPILLAR MODEL 3408 B STANDBY IC ENGINE, SN 78Z05408, DRIVING A 365 KW EMERGENCY POWER GENERATOR. BLDG 722, WATER TREATMENT PLANT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-16-0)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-86-0	54 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 54 HP HERCULES MODEL D2300 DIESEL-FIRED IC ENGINE POWERING A 35 KW ELECTRICAL GENERATOR. USN# 007485. STORED IN BUILDING 765 - PUBLIC WORKS TRANSPORTATION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-48-0)
C-2106-87-0	64 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 64 HP PERKINS MODEL LD33473 DIESEL-FIRED IC ENGINE POWERING A 30 KW ELECTRICAL GENERATOR. USN# 007587. STORED IN BUILDING 258 - AIR OPERATIONS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-49-0)
C-2106-88-0	64 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 64 HP PERKINS MODEL LD33473 DIESEL-FIRED IC ENGINE POWERING A 30 KW ELECTRICAL GENERATOR. USN# 7588. STORED IN BUILDING 258 - AIR OPERATIONS. (TRANSFERRED TO C-2341, NEW PTO# C-2341-50-0)
C-2106-89-0	64 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 64 HP WHITE MODEL D298ER DIESEL-FIRED IC ENGINE POWERING A 30 KW ELECTRICAL GENERATOR. USN# 51-19451. STORED IN BUILDING 765 - PUBLIC WORKS TRANSPORTATION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-51-0)
C-2106-90-0	211 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	TRANSPORTABLE 211 HP JOHN DEERE MODEL 6076TF-00 DIESEL-FIRED IC ENGINE POWERING A 100 KW ELECTRICAL GENERATOR. STORED IN BUILDING 765 - PUBLIC WORKS TRANSPORTATION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-52-0)
C-2106-91-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 80 HP JOHN DEERE MODEL 4239DF IC ENGINE USN 31-07493, SERVING AN AIR COMPRESSOR. STORED IN BLDG 750, PUBLIC WORKS MAINT AND UTILITIES. (TRANSFERRED TO C-2341, NEW PTO# C-2341-17-0)
C-2106-92-0	66 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 66 HP 4 CYLINDER JOHN DEERE MODEL 4039DF DIESEL IC ENGINE SERVING AN AIR COMPRESSOR. USN# 31.07784. STORED IN BLDG 750, PUBLIC WORKS MAINT AND UTILITIES. (TRANSFERRED TO C-2341, NEW PTO# C-2341-18-0)
C-2106-93-0	58 HP DIESEL IC ENGINE	3020-10 A	1	80.00	80.00	D	TRANSPORTABLE 58 HP 4 CYLINDER FORD MODEL VSG-4131-6005-G GASOLINE IC ENGINE SERVING AN AIR COMPRESSOR. USN# 63042. STORED IN BLDG 750, PUBLIC WORKS MAINT AND UTILITIES. (TRANSFERRED TO C-2341, NEW PTO# C-2341-19-0)
C-2106-94-0	52 HP	3020-10 A	1	80.00	80.00	D	52 HP 4 CYLINDER TELEDYNE MODEL F163A-606 GASOLINE IC ENGINE, SN 4527-330004, SERVING A WELDING UNIT. USN# 51. 76795. LOCATED IN BLDG 750, PUBLIC WORKS MAINT AND UTILITIES.**EXEMPT PER 2020 SECTION 5.10.1.
C-2106-96-0	52 HP	3020-10 A	1	80.00	80.00	D	52 HP 4 CYLINDER TELEDYNE MODEL F163A-606 GASOLINE IC ENGINE, SN JA422525, SERVING A WELDING UNIT. USN# 43-5169. LOCATED IN BLDG 954, MWR AUTO SHOP.**EXEMPT PER 2020 SECTION 5.10.1.

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-97-0	71 HP	3020-10 A	1	80.00	80.00	D	71 HP 4 CYLINDER PERKINS MODEL DR-353P DIESEL IC ENGINE, SN 80W512831, SERVING A WELDING UNIT. USN# 44.1617. LOCATED IN BLDG 790, MWR RECYCLING CENTER.**EXEMPT PER 2020 SECTION 5.10.1.
C-2106-98-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINER DETROIT DIESEL MODEL 7063-3000 IC ENGINE, SN 06VA137091, SERVING AN AIR CONDITIONER UNIT. USN# 000036. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-99-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINER COMMENCEMENT OF EAT, DIESEL MODEL 7063-3000 IC ENGINE SN 06VA136306, SERVING AN AIR CONDITIONER UNIT. USN# 000039. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT. DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-100-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINDER DETROIT DIESEL MODEL 7063-3000 IC ENGINE, SN 06VA136882, SERVING AN AIR CONDITIONER UNIT. USN# S/N 000040. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT.
C-2106-101-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINDER DETROIT DIESEL MODEL 7063-3000 IC ENGINE, SN 06VA137089, SERVING AN AIR CONDITIONER UNIT. USN# S/N 000041. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-102-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINDER DETROIT DIESEL MODEL 7063-3000 IC ENGINE, SN 06VA113396, SERVING AN AIR CONDITIONER UNIT. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-103-0	232 HP DIESEL IC ENGINE	3020-10 C	1	240.00	240.00	D	232 HP 6 CYLINDER DETROIT DIESEL MODEL 7073-3000 IC ENGINE, SN 06VA134969, SERVING AN AIR CONDITIONER UNIT. USN# 00001. LOCATED IN BLDG 179, AIMD GROUND SUPPORT EQUIPMENT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-104-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-105-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP DETROIT IC ENGINE, MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-106-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-107-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-108-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-109-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-110-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY, AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-111-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-112-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-113-0	80 HP IC ENGINE	3020-10 A	1	80.00	80.00	D	80 HP IC ENGINE, DETROIT MODEL 5033-7000, OPERATING ON JET FUEL (JP-5), SERVING A MOBILE HYDRAULIC POWER SUPPLY AT BUILDING 179, AIMD GROUND SUPPORT EQUIPMENT MAINT. *DELETED, REGISTERED WITH CARB, 12/31/97 CGV*
C-2106-114-2	140 bhp IC engine	3020-10 B	1	117.00	117.00	D	140 HP DETROIT MODEL 5033-8301 DIESEL-FIRED TRANSPORTABLE IC ENGINE POWERING A RUNWAY SWEEPER (STORED IN BLDG 765)
C-2106-115-0	140 HP DIESEL IC ENGINE	3020-10 B	1	117.00	117.00	D	TRANSPORTABLE 140 HP DETROIT MODEL 5033-8300 IC ENGINE, SN 03D0211443, DIESEL FIRED, SERVING A RUNWAY SWEEPER, STORED IN BLDG 765.
C-2106-116-0	140 HP DIESEL IC ENGINE	3020-10 B	1	117.00	117.00	D	140 HP DETROIT MODEL 5033-8301 DIESEL-FIRED TRANSPORTABLE IC ENGINE POWERING A RUNWAY SWEEPER, STORED IN BLDG 765
C-2106-117-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 1, MODULES 1 - 5)
C-2106-118-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 1)
C-2106-119-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 4)
C-2106-120-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 2)

Detailed Facility Report

For Facility=2106

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-121-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 5)
C-2106-122-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 2)
C-2106-123-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 3)
C-2106-124-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 5)
C-2106-125-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 2, MODULE 3)
C-2106-126-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 4)
C-2106-127-5	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUNS AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 5)
C-2106-128-3	86 Gallon Degreasing Unit	3020-06	1	105.00	105.00	D	86 GALLON DEGREASING OPERATION USED TO CLEAN TURBINE FAN DRIVE SHAFTS, ROTOR AIR DUCTS, AND AIR DUCT DAMPERS (BLDG 170, AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-129-1	20 GALLON TANK	3020-05 A	1	75.00	75.00	D	ONE (1) 20 GALLON JUSTRITE SAFETY RINSE PAINT STRIPPING TANK AND A SELF CLOSING LID WITH TANK DIMENSIONS OF 35"L X 15"W X 20"D.
C-2106-130-0	JP-5 FUELED FIRE TRAINING		1	0.00	0.00	D	JP-5 FUELED FIRE TRAINING FACILITY. ***CANCELLED & REPLACED BY PTO #C-2106-131-0***
C-2106-131-5	54.3 MMBtu/hr burners	3020-02 H	1	1,030.00	1,030.00	A	54.3 MMBTU/HR LPG/PROPANE-FUELED FIRE TRAINING FACILITY
C-2106-132-0	150 BHP	3020-10 B	1	117.00	117.00	D	TRANSPORTABLE 150 HP JOHN DEERE MODEL 6059TF002 DIESEL-FIRED IC ENGINE WITH TURBOCHARGER, POWERING A 60 KW ELECTRICAL GENERATOR. STORED IN BUILDING 765 - PUBLIC WORKS TRANSPORTATION. (TRANSFERRED TO C-2341, NEW PTO# C-2341-53-0)
C-2106-133-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H (BLDG 170 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-134-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H (BLDG 165)

Detailed Facility Report
For Facility=2106
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-135-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H (BLDG 170 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-136-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H (BLDG 170 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-137-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H (BLDG 179 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-138-2	COLD SOLVENT CLEANER	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL 1630 SOLVENT CLEANER INSIDE TUB DIMENSIONS 32"L X 22"W X 10"H, (BLDG 188 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-139-1	140 bhp IC engine	3020-10 B	1	117.00	117.00	D	140 HP DETROIT MODEL 5033-8301 DIESEL-FIRED TRANSPORTABLE IC ENGINE POWERING A RUNWAY SWEEPER #4, STORED IN BLDG 765
C-2106-140-5	Cold cleaner degreaser	3020-06	1	105.00	105.00	A	BATCH LOADED COLD CLEANER DEGREASER, CONSISTING OF ONE CANISTER WITH 9.75 INCH OPEN DIAMETER AND CAPACITY LESS THAN 2.0 GALLONS (BLDG 188 - AIRCRAFT INTERMEDIATE MAINTENANCE DIVISION (AIMD))
C-2106-141-0	1 NOZZLE	3020-11 A	1	34.00	34.00	D	TEMPORARY 10,000 GALLON ABOVEGROUND TANK (G-70-167) SERVED BY TWO POINT PHASE I VAPOR RECOVERY SYS (G70-97-A), AND 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VRS. (TANK REMOVED 12-18-98, PER LETTER RECEIVED 1-4-99).
C-2106-142-0	134 HP STANDBY IC ENGINE	3020-10 B	1	117.00	117.00	D	134 HP CUMMINS MODEL 6BT-5.9 DIESEL IC ENGINE, SN 44225093, TURBOCHARGED WITH INTERCOOLER AND RETARDED TIMING, POWERING AN EMERGENCY GENERATOR FOR TELEPHONE EQUIPMENT. (TRANSFERRED TO C-2341, NEW PTO# C-2341-20-0)
C-2106-143-0	IC ENGINE 136 HP	3020-10 B	1	117.00	117.00	D	136 HP DETROIT DIESEL MODEL 50437001 DIESEL-FIRED TRANSPORTABLE INTERNAL COMBUSTION ENGINE POWERING AN EXCAVATION ARM AND BUCKET ON A MULTI-PURPOSE EXCAVATION VEHICLE. (TRANSFERRED TO C-2341, NEW PTO# C-2341-21-0)
C-2106-149-1	10 hp spray booth	3020-01 A	1	87.00	87.00	A	COATING OPERATION WITH MODEL #SPF-24-8-10, HV FLOOR FILTER OPEN FRONT PAINT SPRAY BOOTH WITH 25"W X 8'6"H X 13'2"L OUTSIDE DIMENSIONS (BLDG 188 - AIMD PAINT SHOP)
C-2106-151-4	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 5, MODULES 1 - 3)
C-2106-153-3	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 1)
C-2106-154-3	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 2)

Detailed Facility Report
For Facility=2106
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-2106-155-3	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 3)
C-2106-156-3	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 4, MODULE 4)
C-2106-157-3	Miscellaneous	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR 3, MODULE 1)
C-2106-158-2	166 bhp emergency IC engine	3020-10 B	1	117.00	117.00	A	166 BHP PERKINS/CATERPILLAR ENGINE NUMBER YB50856, SN U8038, DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A 100 KW ELECTRICAL GENERATOR (BLDG 450, RADAR SITE)
C-2106-159-1	8 hp electric motors	3020-01 A	1	87.00	87.00	D	5 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB ZERO MANUFACTURING MODEL #1648 BLASTING POT SERVED BY A BAGHOUSE (BLDG 170)
C-2106-162-1	Cold Solvent Degreaser	3020-06	1	105.00	105.00	A	INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #1 (BLDG 188, AIMD 500 TIRE SHOP)
C-2106-163-1	Cold Solvent Degreaser	3020-06	1	105.00	105.00	A	INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #2 (BLDG 188, AIMD 500 TIRE SHOP)
C-2106-164-1	Cold Solvent Degreaser	3020-06	1	105.00	105.00	D	INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #3 (BLDG 170, AIMD 400 POWER PLANT SHOP)
C-2106-165-1	Cold Solvent Degreaser	3020-06	1	105.00	105.00	A	INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #4 (BLDG 179, AIMD 900 DIVISION, GSE)
C-2106-166-1	Cold Solvent Degreaser	3020-06	1	105.00	105.00	A	INLAND TECHNOLOGY MODEL TEK JET 4500 COLD SOLVENT DEGREASER #5 (BLDG 170, AIMD 400 POWER PLANT SHOP)
C-2106-167-1	Squadron Coating Operation	3020-06	1	105.00	105.00	A	SQUADRON AIRCRAFT CORROSION CONTROL AND MAINTENANCE COATING OPERATION WITH HVLP SPRAY GUN(S) AND AN ENCLOSED GUN CLEANER (HANGAR C, BLDG 180)
C-2106-168-1	3.1 MMBtu/hr	3020-02 F	1	607.00	607.00	A	METAL PARTS AND PRODUCTS POWDER COATING OPERATION WITH ELECTROSTATIC SPRAY GUN(S), OPEN FACED POWDER COATING BOOTH WITH PULSE JET CARTRIDGE BAGHOUSE, 1.2 MMBTU/HR NATURAL GAS-FIRED CURING OVEN WITH A 1.2 MMBTU/HR ECLIPSE MODEL 160 AH BURNER, AND 1.9 MMBTU/HR NATURAL GAS-FIRED BURNOUT OVEN WITH A 1.9 MMBTU/HR ECLIPSE MODEL J121A-3 BURNER
C-2106-170-0	2.3 MMBtu/hr burners	3020-02 E	1	412.00	412.00	A	TRANSPORTABLE LPG/PROPANE-FUELED MOBILE AIRCRAFT FIRE TRAINING DEVICE (MAFTD)

Number of Facilities Reported: 1