



AUG 18 2011

Jeff Godfrey  
Plains Marketing LP  
3600 Bowman Court  
Bakersfield, CA 93308

**Re: Notice of Final Action - Title V Permit Renewal  
District Facility # S-1199  
Project # S-1091422**

Dear Mr. Godfrey:

The District has issued the Final Title V Permit for Plains Marketing LP. The preliminary decision for this project was made on June 23, 2011. No comments were received subsequent to the District preliminary decision. Enclosed are the Renewed Final Title V Permit and public notice to be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. Should you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



 David Warner  
Director of Permit Services

Attachments

cc: Sajjad Ahmad, Permit Services Engineer

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585



AUG 18 2011

Gerardo C. Rios, Chief  
Permits Office (AIR-3)  
U.S. EPA - Region IX  
75 Hawthorne St  
San Francisco, CA 94105


**Re: Notice of Final Action - Title V Permit Renewal  
District Facility # S-1199  
Project # S-1091422**

Dear Mr. Rios:

The District has issued the Final Title V Permit Renewal for Plains Marketing LP. The preliminary decision for this project was made on June 23, 2011. No comments were received subsequent to the District preliminary decision. Enclosed are the Renewed Final Title V Permit and public notice to be published approximately three days from the date of this letter.

I would like to thank you and your staff for working with us. We appreciate your concurrence with this action. Should you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner  
Director of Permit Services

Attachments

cc: Sajjad Ahmad, Permit Services Engineer

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585



AUG 18 2011

Mike Tollstrup, Chief  
Project Assessment Branch  
Air Resources Board  
P O Box 2815  
Sacramento, CA 95812-2815


**Re: Notice of Final Action - Title V Permit Renewal  
District Facility # S-1199  
Project # S-1091422**

Dear Mr. Tollstrup:

The District has issued the Final Title V Permit for Plains Marketing LP. The preliminary decision for this project was made on June 23, 2011. No comments were received subsequent to the District preliminary decision. Enclosed are the Renewed Final Title V Permit and public notice to be published approximately three days from the date of this letter.

I would like to thank you and your staff for working with us. Should you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner  
Director of Permit Services

Attachments

cc: Sajjad Ahmad, Permit Services Engineer

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585

Bakersfield Californian

**SAN JOAQUIN VALLEY  
AIR POLLUTION CONTROL DISTRICT  
NOTICE OF FINAL DECISION TO ISSUE  
RENEWED FEDERALLY MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District has made its final decision to issue the renewed Federally Mandated Operating Permit to Plains Marketing LP for its crude oil pumping facility located at Pentland Pumping Station near Maricopa, California.

The District's analysis of the legal and factual basis for this proposed action, project #S-1091422, is available for public inspection at [http://www.valleyair.org/notices/public\\_notices\\_idx.htm](http://www.valleyair.org/notices/public_notices_idx.htm) and the District office at the address below. For additional information regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900, or contact David Warner, Director of Permit Services, in writing at SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CA 93726-0244.



# Permit to Operate

**FACILITY:** S-1199

**EXPIRATION DATE:** 05/31/2016

**LEGAL OWNER OR OPERATOR:**

PLAINS MARKETING LP

**MAILING ADDRESS:**

BAK-00 ACCOUNTS PAYABLE

PO BOX 4648

HOUSTON, TX 77210-4648

**FACILITY LOCATION:**

PENTLAND PUMP STATION

MARICOPA, CA

**FACILITY DESCRIPTION:**

CRUDE PETROLEUM PIPELINE

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

**Seyed Sadredin**

Executive Director / APCO

**David Warner**

Director of Permit Services

# San Joaquin Valley Air Pollution Control District

FACILITY: S-1199-0-2

EXPIRATION DATE: 05/31/2016

## FACILITY-WIDE REQUIREMENTS

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: PLAINS MARKETING LP  
Location: PENTLAND PUMP STATION, MARICOPA, CA  
S-1199-0-2: Aug 8 2011 11:02AM -- AHMADS

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. On December 31, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
43. Facilities S-254 and S-1199 are included in the same stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-2-5

**EXPIRATION DATE:** 05/31/2016

**SECTION:** SE10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

50 BBL UNDERGROUND CRUDE OIL SUMP TANK WITH PRESSURE RELIEF VALVE, AND ASSOCIATED VALVES, FLANGES, PUMPS & PIPING.

## PERMIT UNIT REQUIREMENTS

---

1. All valves, flanges and pump seals shall be maintained leak-free as defined in Rule 4623. [District Rule NSR Rule] Federally Enforceable Through Title V Permit
2. True vapor pressure of any liquid introduced, placed, or stored in this permit unit shall not exceed 11.0 psia without prior District approval. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Average daily tank throughput (on annual basis) shall not exceed 50 bbl/day of fluid without prior District approval. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank shall be equipped with an operational stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank shall be equipped with a pressure/vacuum relief valve shall be set at 8.0 oz pressure and 0.5 oz vacuum. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.1.1, 5.6.3, and 6.4.8] Federally Enforceable Through Title V Permit
7. Permittee shall maintain accurate records of tank throughput, true vapor pressure and temperature of petroleum liquids in the tank, and such records shall be made readily available for District inspection upon request for a period of five years. [District NSR Rule and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-3-4

**EXPIRATION DATE:** 05/31/2016

**SECTION:** SE10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

30,000 BBL, 85 FT. DIA. X 42 FT. HIGH, DOUBLE-DECK, EXTERNAL FLOATING ROOF, WELDED CRUDE OIL STORAGE TANK #213 WITH MECHANICAL SHOE PRIMARY SEAL AND SINGLE WIPER SECONDARY SEAL.

## PERMIT UNIT REQUIREMENTS

---

1. Tank liquid throughput shall not exceed 40,034 bbl per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank liquid throughput shall not exceed 7,300,259 bbl per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
4. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1 and 40 CFR 60.112b(a)(2) & (i)] Federally Enforceable Through Title V Permit
6. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3 and 40CFR 60.112b(a)(2)(iii)] Federally Enforceable Through Title V Permit
7. Primary seal (lower seal) shall be either a mechanical shoe seal or a liquid-mounted seal. [40CFR 60.112b(a)(2)(i) and 60.112b(a)(2)(i)(A)] Federally Enforceable Through Title V Permit
8. Accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 cm<sup>2</sup> per meter of tank diameter, and the width of any gap shall not exceed 3.81 cm. [40CFR 60.113b(b)(4)(i)] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. Accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm<sup>2</sup> per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm (1/2 inch). [District Rule 4623, 5.3.2.1.2 and 40CFR 60.113b(b)(4)(ii)(B)] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5 and 40 CFR 60.112b(b)(4)(ii)(C)] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. Secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion. [40CFR 60.112b(a)(2)(i)(B)] Federally Enforceable Through Title V Permit
21. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
22. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
23. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
24. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
25. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit
26. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
28. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a gas-tight condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
29. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
30. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
32. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
33. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
34. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
35. Operator shall perform gap measurements on primary and secondary seals within 60 days of the initial fill and at least once every year thereafter to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1 and 40 CFR 60.113b(b)(1)(i) & (ii)] Federally Enforceable Through Title V Permit
36. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2 and 40CFR 60.113b(b)(6)] Federally Enforceable Through Title V Permit
37. Operator shall also perform gap measurements on primary seals during hydrostatic testing of the vessel. [40CFR 60.113b(b)(1)(i)] Federally Enforceable Through Title V Permit
38. If unit is out of service for a period of one year or more, subsequent refilling with volatile organic liquid shall be considered initial fill in accordance with the conditions of this permit. [40CFR60.113b(b)(1)(iii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

39. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
40. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the maximum true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7 and 40 CFR 60.116b(c)] Federally Enforceable Through Title V Permit
41. All covers, seals and lids covering openings in the roof used for sampling and gauging, except pressure-vacuum valves set to within 10 percent of the maximum allowable working pressure of the roof, shall be inspected annually by the facility operator to ensure compliance with the provisions of this permit. However, if one or more of the components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If none of the components of that type are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
42. Operator shall determine the presence of VOC leaks by EPA Method 21. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases; 1.) Zero air (less than 10 ppm of hydrocarbon in air); and 2.) A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
43. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
44. Operator shall notify the APCO 30 days in advance of any gap measurements required by this permit to afford the APCO opportunity to have an observer present. [40CFR 60.113b(b)(5)] Federally Enforceable Through Title V Permit
45. If the external floating roof has defects, or the primary seal or secondary seal has holes, tears, or other openings in the seal or seal fabric, the operator shall repair the items as necessary so that none of these conditions exist before filling or refilling the storage vessel with VOL. [40CFR 60.113b(b)(6)(i)] Federally Enforceable Through Title V Permit
46. For all visual inspections required by this permit, the operator shall notify the APCO in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the APCO the opportunity to inspect the storage vessel prior to refilling, except when notification is specifically allowed otherwise by this permit. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

47. If a visual inspection required by this permit is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall notify the APCO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so it is received by the APCO at least 7 days prior to the refilling. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit
48. Operator shall record the vessel on which the measurement was performed, date of the seal gap measurement, raw data obtained in the measurement process in accordance with the conditions of this permit. [40CFR 60.115b(b)(3)] Federally Enforceable Through Title V Permit
49. Within 60 days of performing the seal gap measurements required by this permit, the operator shall furnish the APCO with a report containing the date of measurement, raw data obtained in the measurement process, and all such gap calculations as required by this permit. [40CFR 60.115b(b)(2)] Federally Enforceable Through Title V Permit
50. After each seal gap measurement that detects gaps exceeding any limit of this permit, the operator shall submit a report to the APCO within 30 days of the inspection. The report will identify the vessel and contain the date of measurement, raw data obtained in the measurement process, all such gap calculations as required by this permit, and the date the vessel was emptied or the repairs made and the date of repair. [40CFR 60.115b(b)(4)] Federally Enforceable Through Title V Permit
51. If the seals do not meet the required specifications of this permit, operator shall repair or empty the storage vessel within 45 days of identification. [40CFR 60.113b(b)(4)] Federally Enforceable Through Title V Permit
52. Operator shall maintain a record showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The record shall be maintained for the life of the vessel. [40 CFR 60.116b(b)] Federally Enforceable Through Title V Permit
53. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 0.5 psia. [40 CFR 60.116b(e)(2)(ii)] Federally Enforceable Through Title V Permit
54. Operator shall determine the true vapor pressure of each VOL, other than crude oil or refined petroleum products, from standard reference texts, by ASTM Method D2879, or by using an appropriate method approved by EPA. [40 CFR 60.116b(e)(3)(iii)] Federally Enforceable Through Title V Permit
55. For storage vessels operated above or below ambient temperatures, the operator shall calculate the maximum true vapor pressure based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
56. Maximum true vapor pressure, for crude oil or refined petroleum products, may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). [40 CFR 60.116b(e)(2)(i)] Federally Enforceable Through Title V Permit
57. Operator of a tank storing a waste mixture of indeterminate or variable composition shall determine the highest maximum true vapor pressure for the range of liquid compositions to be stored prior to the initial filling, using methods specified for maximum true vapor pressure in this permit. [40CFR 60.116b(f)] Federally Enforceable Through Title V Permit
58. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
59. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



60. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
61. Operator of each storage vessel, either with a design capacity greater than or equal to 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure that is normally less than 0.75 psia or with a design capacity greater than or equal to 75 m<sup>3</sup> but less than 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure normally less than 4.0 psia, shall notify the APCO within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range. [40CFR 60.116b(d)] Federally Enforceable Through Title V Permit
62. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005) and 40CFR60, Subpart Kb (except 60.115b(b)(1)). A permit shield is granted from this requirement [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
63. This unit commenced construction, modification, or reconstruction after July 23, 1984. Therefore, the requirements of 40 CFR 60 Subpart K and Ka do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
64. The permittee shall keep accurate records of liquid throughput, Reid vapor pressure, storage temperature and types of liquids stored, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-6-9

**EXPIRATION DATE:** 05/31/2016

**SECTION:** SE10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

19.95 MMBTU/HR BROACH FORCED DRAFT NATURAL GAS-FIRED PIPELINE HEATER WITH A PRO-FIRE MODEL NTD210NGX-15S-6P ULTRA LOW NOX BURNER AND MANUAL FLUE GAS RECIRCULATION (FGR)

## PERMIT UNIT REQUIREMENTS

---

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown, emissions rates from the unit shall not exceed any of the following emission limits: 15 ppmv NOx @ 3% O2 or 0.018 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 80 ppmv CO @ 3% O2 or 0.059 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
7. During start-up and shutdown, emissions from the unit shall not exceed any of the following limits: 83 ppmv NOx @ 3% O2 or 0.1 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 115 ppmv CO @ 3% O2 or 0.84 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
9. The total duration of startup and shutdown time shall not exceed either of the following limits: 8.0 hours per day or 2,920 hours per year. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
10. The flue gas recirculation valve(s) setting shall be monitored at least on a weekly basis. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last week. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The acceptable settings for the flue gas recirculation valve(s) shall be established by source testing this unit or other representative units per Rule 4305 and as approved by the District. The normal range/level shall be that for which compliance with applicable NOx and CO emissions rates have been demonstrated through source testing at a similar firing rate. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
12. Normal range or level for the flue gas recirculation valve(s) settings shall be re-established during each source test required by this permit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
13. If the flue gas recirculation valve(s) setting is less than the normal range/level, the permittee shall return the flue gas recirculation valve(s) setting to the normal range/level as soon as possible, but no longer than 1 hour of operation after detection. If the flue gas recirculation valve(s) setting is not returned to the normal range/level within 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour, and conduct a source test within 60 days of the first exceedance, to demonstrate compliance with the applicable emission limits at the new flue gas recirculation valve(s) setting. A District-approved portable analyzer may be used in lieu of a source test to demonstrate compliance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
14. The permittee shall maintain records of the date and time of flue gas recirculation valve(s) settings, the observed setting, and the firing rate at the time of the flue gas recirculation valve(s) setting measurements. The records must also include a description of any corrective action taken to maintain the flue gas recirculation valve(s) setting within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. During the 36-month source testing interval, the owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit
18. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit
19. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
21. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

22. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
23. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
26. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
27. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit
28. On and after July 1, 2012, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
29. Daily records of start-up and shutdown durations shall be maintained. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit
30. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-7-6

**EXPIRATION DATE:** 05/31/2016

**SECTION:** 10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

50,000 BBL, 95 FT. DIA. X 48 FT. HIGH, DOUBLE-DECK, EXTERNAL FLOATING ROOF, WELDED CRUDE OIL STORAGE TANK #201 WITH MECHANICAL SHOE PRIMARY SEAL AND SINGLE WIPER SECONDARY SEAL.

## PERMIT UNIT REQUIREMENTS

---

1. Tank liquid throughput shall not exceed 49,919 bbl per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank liquid throughput shall not exceed 9,123,730 bbl per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
4. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1 and 40 CFR 60.112b(a)(2) & (i)] Federally Enforceable Through Title V Permit
6. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3 and 40CFR 60.112b(a)(2)(iii)] Federally Enforceable Through Title V Permit
7. Primary seal (lower seal) shall be either a mechanical shoe seal or a liquid-mounted seal. [40CFR 60.112b(a)(2)(i) and 60.112b(a)(2)(i)(A)] Federally Enforceable Through Title V Permit
8. Accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 cm<sup>2</sup> per meter of tank diameter, and the width of any gap shall not exceed 3.81 cm. [40CFR 60.113b(b)(4)(i)] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

12. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. Accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm<sup>2</sup> per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm (1/2 inch). [District Rule 4623, 5.3.2.1.2 and 40CFR 60.113b(b)(4)(ii)(B)] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5 and 40 CFR 60.112b(b)(4)(ii)(C)] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. Secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion. [40CFR 60.112b(a)(2)(i)(B)] Federally Enforceable Through Title V Permit
21. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
22. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
23. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
24. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
25. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit
26. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
28. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a gas-tight condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
29. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
30. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
32. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
33. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
34. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
35. Operator shall perform gap measurements on primary and secondary seals within 60 days of the initial fill and at least once every year thereafter to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1 and 40 CFR 60.113b(b)(1)(i) & (ii)] Federally Enforceable Through Title V Permit
36. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2 and 40CFR 60.113b(b)(6)] Federally Enforceable Through Title V Permit
37. Operator shall also perform gap measurements on primary seals during hydrostatic testing of the vessel. [40CFR 60.113b(b)(1)(i)] Federally Enforceable Through Title V Permit
38. If unit is out of service for a period of one year or more, subsequent refilling with volatile organic liquid shall be considered initial fill in accordance with the conditions of this permit. [40CFR60.113b(b)(1)(iii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



39. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
40. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the maximum true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7 and 40 CFR 60.116b(c)] Federally Enforceable Through Title V Permit
41. All covers, seals and lids covering openings in the roof used for sampling and gauging, except pressure-vacuum valves set to within 10 percent of the maximum allowable working pressure of the roof, shall be inspected annually by the facility operator to ensure compliance with the provisions of this permit. However, if one or more of the components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If none of the components of that type are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
42. Operator shall determine the presence of VOC leaks by EPA Method 21. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases; 1.) Zero air (less than 10 ppm of hydrocarbon in air); and 2.) A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
43. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
44. Operator shall notify the APCO 30 days in advance of any gap measurements required by this permit to afford the APCO opportunity to have an observer present. [40CFR 60.113b(b)(5)] Federally Enforceable Through Title V Permit
45. If the external floating roof has defects, or the primary seal or secondary seal has holes, tears, or other openings in the seal or seal fabric, the operator shall repair the items as necessary so that none of these conditions exist before filling or refilling the storage vessel with VOL. [40CFR 60.113b(b)(6)(i)] Federally Enforceable Through Title V Permit
46. For all visual inspections required by this permit, the operator shall notify the APCO in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the APCO the opportunity to inspect the storage vessel prior to refilling, except when notification is specifically allowed otherwise by this permit. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

47. If a visual inspection required by this permit is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall notify the APCO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so it is received by the APCO at least 7 days prior to the refilling. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit
48. Operator shall record the vessel on which the measurement was performed, date of the seal gap measurement, raw data obtained in the measurement process in accordance with the conditions of this permit. [40CFR 60.115b(b)(3)] Federally Enforceable Through Title V Permit
49. Within 60 days of performing the seal gap measurements required by this permit, the operator shall furnish the APCO with a report containing the date of measurement, raw data obtained in the measurement process, and all such gap calculations as required by this permit. [40CFR 60.115b(b)(2)] Federally Enforceable Through Title V Permit
50. After each seal gap measurement that detects gaps exceeding any limit of this permit, the operator shall submit a report to the APCO within 30 days of the inspection. The report will identify the vessel and contain the date of measurement, raw data obtained in the measurement process, all such gap calculations as required by this permit, and the date the vessel was emptied or the repairs made and the date of repair. [40CFR 60.115b(b)(4)] Federally Enforceable Through Title V Permit
51. If the seals do not meet the required specifications of this permit, operator shall repair or empty the storage vessel within 45 days of identification. [40CFR 60.113b(b)(4)] Federally Enforceable Through Title V Permit
52. Operator shall maintain a record showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The record shall be maintained for the life of the vessel. [40 CFR 60.116b(b)] Federally Enforceable Through Title V Permit
53. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 0.5 psia. [40 CFR 60.116b(e)(2)(ii)] Federally Enforceable Through Title V Permit
54. Operator shall determine the true vapor pressure of each VOL, other than crude oil or refined petroleum products, from standard reference texts, by ASTM Method D2879, or by using an appropriate method approved by EPA. [40 CFR 60.116b(e)(3)(iii)] Federally Enforceable Through Title V Permit
55. For storage vessels operated above or below ambient temperatures, the operator shall calculate the maximum true vapor pressure based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
56. Maximum true vapor pressure, for crude oil or refined petroleum products, may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). [40 CFR 60.116b(e)(2)(i)] Federally Enforceable Through Title V Permit
57. Operator of a tank storing a waste mixture of indeterminate or variable composition shall determine the highest maximum true vapor pressure for the range of liquid compositions to be stored prior to the initial filling, using methods specified for maximum true vapor pressure in this permit. [40CFR 60.116b(f)] Federally Enforceable Through Title V Permit
58. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
59. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



60. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
61. Operator of each storage vessel, either with a design capacity greater than or equal to 151 m3 storing a liquid with a maximum true vapor pressure that is normally less than 0.75 psia or with a design capacity greater than or equal to 75 m3 but less than 151 m3 storing a liquid with a maximum true vapor pressure normally less than 4.0 psia, shall notify the APCO within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range. [40CFR 60.116b(d)] Federally Enforceable Through Title V Permit
62. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005) and 40CFR60, Subpart Kb (except 60.115b(b)(1)). A permit shield is granted from this requirement [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
63. This unit commenced construction, modification, or reconstruction after July 23, 1984. Therefore, the requirements of 40 CFR 60 Subpart K and Ka do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
64. The permittee shall keep accurate records of liquid throughput, Reid vapor pressure, storage temperature and types of liquids stored, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-8-6

**EXPIRATION DATE:** 05/31/2016

**SECTION:** 10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

50,000 BBL, 95 FT. DIA. X 48 FT. HIGH, DOUBLE-DECK, EXTERNAL FLOATING ROOF, WELDED CRUDE OIL STORAGE TANK #202 WITH MECHANICAL SHOE PRIMARY SEAL AND SINGLE WIPER SECONDARY SEAL.

## PERMIT UNIT REQUIREMENTS

---

1. Tank liquid throughput shall not exceed 49,919 bbl per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank liquid throughput shall not exceed 9,123,730 bbl per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
4. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1 and 40 CFR 60.112b(a)(2) & (i)] Federally Enforceable Through Title V Permit
6. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3 and 40CFR 60.112b(a)(2)(iii)] Federally Enforceable Through Title V Permit
7. Primary seal (lower seal) shall be either a mechanical shoe seal or a liquid-mounted seal. [40CFR 60.112b(a)(2)(i) and 60.112b(a)(2)(i)(A)] Federally Enforceable Through Title V Permit
8. Accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 cm<sup>2</sup> per meter of tank diameter, and the width of any gap shall not exceed 3.81 cm. [40CFR 60.113b(b)(4)(i)] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

12. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. Accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm<sup>2</sup> per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm (1/2 inch). [District Rule 4623, 5.3.2.1.2 and 40CFR 60.113b(b)(4)(ii)(B)] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5 and 40 CFR 60.112b(b)(4)(ii)(C)] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. Secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion. [40CFR 60.112b(a)(2)(i)(B)] Federally Enforceable Through Title V Permit
21. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
22. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
23. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
24. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
25. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit
26. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
28. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a gas-tight condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
29. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
30. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
32. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
33. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
34. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
35. Operator shall perform gap measurements on primary and secondary seals within 60 days of the initial fill and at least once every year thereafter to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1 and 40 CFR 60.113b(b)(1)(i) & (ii)] Federally Enforceable Through Title V Permit
36. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2 and 40CFR 60.113b(b)(6)] Federally Enforceable Through Title V Permit
37. Operator shall also perform gap measurements on primary seals during hydrostatic testing of the vessel. [40CFR 60.113b(b)(1)(i)] Federally Enforceable Through Title V Permit
38. If unit is out of service for a period of one year or more, subsequent refilling with volatile organic liquid shall be considered initial fill in accordance with the conditions of this permit. [40CFR60.113b(b)(1)(iii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

39. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
40. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the maximum true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7 and 40 CFR 60.116b(c)] Federally Enforceable Through Title V Permit
41. All covers, seals and lids covering openings in the roof used for sampling and gauging, except pressure-vacuum valves set to within 10 percent of the maximum allowable working pressure of the roof, shall be inspected annually by the facility operator to ensure compliance with the provisions of this permit. However, if one or more of the components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If none of the components of that type are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
42. Operator shall determine the presence of VOC leaks by EPA Method 21. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases; 1.) Zero air (less than 10 ppm of hydrocarbon in air); and 2.) A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
43. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
44. Operator shall notify the APCO 30 days in advance of any gap measurements required by this permit to afford the APCO opportunity to have an observer present. [40CFR 60.113b(b)(5)] Federally Enforceable Through Title V Permit
45. If the external floating roof has defects, or the primary seal or secondary seal has holes, tears, or other openings in the seal or seal fabric, the operator shall repair the items as necessary so that none of these conditions exist before filling or refilling the storage vessel with VOL. [40CFR 60.113b(b)(6)(i)] Federally Enforceable Through Title V Permit
46. For all visual inspections required by this permit, the operator shall notify the APCO in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the APCO the opportunity to inspect the storage vessel prior to refilling, except when notification is specifically allowed otherwise by this permit. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

47. If a visual inspection required by this permit is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall notify the APCO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so it is received by the APCO at least 7 days prior to the refilling. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit
48. Operator shall record the vessel on which the measurement was performed, date of the seal gap measurement, raw data obtained in the measurement process in accordance with the conditions of this permit. [40CFR 60.115b(b)(3)] Federally Enforceable Through Title V Permit
49. Within 60 days of performing the seal gap measurements required by this permit, the operator shall furnish the APCO with a report containing the date of measurement, raw data obtained in the measurement process, and all such gap calculations as required by this permit. [40CFR 60.115b(b)(2)] Federally Enforceable Through Title V Permit
50. After each seal gap measurement that detects gaps exceeding any limit of this permit, the operator shall submit a report to the APCO within 30 days of the inspection. The report will identify the vessel and contain the date of measurement, raw data obtained in the measurement process, all such gap calculations as required by this permit, and the date the vessel was emptied or the repairs made and the date of repair. [40CFR 60.115b(b)(4)] Federally Enforceable Through Title V Permit
51. If the seals do not meet the required specifications of this permit, operator shall repair or empty the storage vessel within 45 days of identification. [40CFR 60.113b(b)(4)] Federally Enforceable Through Title V Permit
52. Operator shall maintain a record showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The record shall be maintained for the life of the vessel. [40 CFR 60.116b(b)] Federally Enforceable Through Title V Permit
53. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 0.5 psia. [40 CFR 60.116b(e)(2)(ii)] Federally Enforceable Through Title V Permit
54. Operator shall determine the true vapor pressure of each VOL, other than crude oil or refined petroleum products, from standard reference texts, by ASTM Method D2879, or by using an appropriate method approved by EPA. [40 CFR 60.116b(e)(3)(iii)] Federally Enforceable Through Title V Permit
55. For storage vessels operated above or below ambient temperatures, the operator shall calculate the maximum true vapor pressure based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
56. Maximum true vapor pressure, for crude oil or refined petroleum products, may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). [40 CFR 60.116b(e)(2)(i)] Federally Enforceable Through Title V Permit
57. Operator of a tank storing a waste mixture of indeterminate or variable composition shall determine the highest maximum true vapor pressure for the range of liquid compositions to be stored prior to the initial filling, using methods specified for maximum true vapor pressure in this permit. [40CFR 60.116b(f)] Federally Enforceable Through Title V Permit
58. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
59. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

60. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
61. Operator of each storage vessel, either with a design capacity greater than or equal to 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure that is normally less than 0.75 psia or with a design capacity greater than or equal to 75 m<sup>3</sup> but less than 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure normally less than 4.0 psia, shall notify the APCO within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range. [40CFR 60.116b(d)] Federally Enforceable Through Title V Permit
62. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005) and 40CFR60, Subpart Kb (except 60.115b(b)(1)). A permit shield is granted from this requirement [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
63. This unit commenced construction, modification, or reconstruction after July 23, 1984. Therefore, the requirements of 40 CFR 60 Subpart K and Ka do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
64. The permittee shall keep accurate records of liquid throughput, Reid vapor pressure, storage temperature and types of liquids stored, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-9-6

**EXPIRATION DATE:** 05/31/2016

**SECTION:** 10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

100,000, 125 FT. DIA. X 48 FT. HIGH, DOUBLE-DECK, FLOATING FLOATING ROOF, WELDED CRUDE OIL STORAGE TANK #203 WITH MECHANICAL SHOE PRIMARY SEAL AND SINGLE WIPER SECONDARY SEAL.

## PERMIT UNIT REQUIREMENTS

---

1. Tank liquid throughput shall not exceed 125,489 bbl per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank liquid throughput shall not exceed 22,862,352 bbl per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
4. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1 and 40 CFR 60.112b(a)(2) & (i)] Federally Enforceable Through Title V Permit
6. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3 and 40CFR 60.112b(a)(2)(iii)] Federally Enforceable Through Title V Permit
7. Primary seal (lower seal) shall be either a mechanical shoe seal or a liquid-mounted seal. [40CFR 60.112b(a)(2)(i) and 60.112b(a)(2)(i)(A)] Federally Enforceable Through Title V Permit
8. Accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 cm<sup>2</sup> per meter of tank diameter, and the width of any gap shall not exceed 3.81 cm. [40CFR 60.113b(b)(4)(i)] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



12. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. Accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm<sup>2</sup> per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm (1/2 inch). [District Rule 4623, 5.3.2.1.2 and 40CFR 60.113b(b)(4)(ii)(B)] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5 and 40 CFR 60.112b(b)(4)(ii)(C)] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. Secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion. [40CFR 60.112b(a)(2)(i)(B)] Federally Enforceable Through Title V Permit
21. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
22. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
23. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
24. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
25. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit
26. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
28. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a gas-tight condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
29. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
30. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
32. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
33. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
34. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
35. Operator shall perform gap measurements on primary and secondary seals within 60 days of the initial fill and at least once every year thereafter to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1 and 40 CFR 60.113b(b)(1)(i) & (ii)] Federally Enforceable Through Title V Permit
36. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2 and 40CFR 60.113b(b)(6)] Federally Enforceable Through Title V Permit
37. Operator shall also perform gap measurements on primary seals during hydrostatic testing of the vessel. [40CFR 60.113b(b)(1)(i)] Federally Enforceable Through Title V Permit
38. If unit is out of service for a period of one year or more, subsequent refilling with volatile organic liquid shall be considered initial fill in accordance with the conditions of this permit. [40CFR60.113b(b)(1)(iii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

39. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
40. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the maximum true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7 and 40 CFR 60.116b(c)] Federally Enforceable Through Title V Permit
41. All covers, seals and lids covering openings in the roof used for sampling and gauging, except pressure-vacuum valves set to within 10 percent of the maximum allowable working pressure of the roof, shall be inspected annually by the facility operator to ensure compliance with the provisions of this permit. However, if one or more of the components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If none of the components of that type are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
42. Operator shall determine the presence of VOC leaks by EPA Method 21. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases; 1.) Zero air (less than 10 ppm of hydrocarbon in air); and 2.) A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
43. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
44. Operator shall notify the APCO 30 days in advance of any gap measurements required by this permit to afford the APCO opportunity to have an observer present. [40CFR 60.113b(b)(5)] Federally Enforceable Through Title V Permit
45. If the external floating roof has defects, or the primary seal or secondary seal has holes, tears, or other openings in the seal or seal fabric, the operator shall repair the items as necessary so that none of these conditions exist before filling or refilling the storage vessel with VOL. [40CFR 60.113b(b)(6)(i)] Federally Enforceable Through Title V Permit
46. For all visual inspections required by this permit, the operator shall notify the APCO in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the APCO the opportunity to inspect the storage vessel prior to refilling, except when notification is specifically allowed otherwise by this permit. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

47. If a visual inspection required by this permit is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall notify the APCO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so it is received by the APCO at least 7 days prior to the refilling. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit
48. Operator shall record the vessel on which the measurement was performed, date of the seal gap measurement, raw data obtained in the measurement process in accordance with the conditions of this permit. [40CFR 60.115b(b)(3)] Federally Enforceable Through Title V Permit
49. Within 60 days of performing the seal gap measurements required by this permit, the operator shall furnish the APCO with a report containing the date of measurement, raw data obtained in the measurement process, and all such gap calculations as required by this permit. [40CFR 60.115b(b)(2)] Federally Enforceable Through Title V Permit
50. After each seal gap measurement that detects gaps exceeding any limit of this permit, the operator shall submit a report to the APCO within 30 days of the inspection. The report will identify the vessel and contain the date of measurement, raw data obtained in the measurement process, all such gap calculations as required by this permit, and the date the vessel was emptied or the repairs made and the date of repair. [40CFR 60.115b(b)(4)] Federally Enforceable Through Title V Permit
51. If the seals do not meet the required specifications of this permit, operator shall repair or empty the storage vessel within 45 days of identification. [40CFR 60.113b(b)(4)] Federally Enforceable Through Title V Permit
52. Operator shall maintain a record showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The record shall be maintained for the life of the vessel. [40 CFR 60.116b(b)] Federally Enforceable Through Title V Permit
53. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 0.5 psia. [40 CFR 60.116b(e)(2)(ii)] Federally Enforceable Through Title V Permit
54. Operator shall determine the true vapor pressure of each VOL, other than crude oil or refined petroleum products, from standard reference texts, by ASTM Method D2879, or by using an appropriate method approved by EPA. [40 CFR 60.116b(e)(3)(iii)] Federally Enforceable Through Title V Permit
55. For storage vessels operated above or below ambient temperatures, the operator shall calculate the maximum true vapor pressure based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
56. Maximum true vapor pressure, for crude oil or refined petroleum products, may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). [40 CFR 60.116b(e)(2)(i)] Federally Enforceable Through Title V Permit
57. Operator of a tank storing a waste mixture of indeterminate or variable composition shall determine the highest maximum true vapor pressure for the range of liquid compositions to be stored prior to the initial filling, using methods specified for maximum true vapor pressure in this permit. [40CFR 60.116b(f)] Federally Enforceable Through Title V Permit
58. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
59. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

60. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
61. Operator of each storage vessel, either with a design capacity greater than or equal to 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure that is normally less than 0.75 psia or with a design capacity greater than or equal to 75 m<sup>3</sup> but less than 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure normally less than 4.0 psia, shall notify the APCO within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range. [40CFR 60.116b(d)] Federally Enforceable Through Title V Permit
62. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005) and 40CFR60, Subpart Kb (except 60.115b(b)(1)). A permit shield is granted from this requirement [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
63. This unit commenced construction, modification, or reconstruction after July 23, 1984. Therefore, the requirements of 40 CFR 60 Subpart K and Ka do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
64. The permittee shall keep accurate records of liquid throughput, Reid vapor pressure, storage temperature and types of liquids stored, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-10-6

**EXPIRATION DATE:** 05/31/2016

**SECTION:** 10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

100,000 BBL, 125 FT. DIA. X 48 FT. HIGH, DOUBLE-DECK, EXTERNAL FLOATING ROOF, WELDED CRUDE OIL STORAGE TANK #204 WITH MECHANICAL SHOE PRIMARY SEAL AND SINGLE WIPE SECONDARY SEAL.

## PERMIT UNIT REQUIREMENTS

---

1. Tank liquid throughput shall not exceed 120,227 bbl per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank liquid throughput shall not exceed 21,903,701 bbl per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
4. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1 and 40 CFR 60.112b(a)(2) & (i)] Federally Enforceable Through Title V Permit
6. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3 and 40CFR 60.112b(a)(2)(iii)] Federally Enforceable Through Title V Permit
7. Primary seal (lower seal) shall be either a mechanical shoe seal or a liquid-mounted seal. [40CFR 60.112b(a)(2)(i) and 60.112b(a)(2)(i)(A)] Federally Enforceable Through Title V Permit
8. Accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 cm<sup>2</sup> per meter of tank diameter, and the width of any gap shall not exceed 3.81 cm. [40CFR 60.113b(b)(4)(i)] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



12. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. Accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm<sup>2</sup> per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm (1/2 inch). [District Rule 4623, 5.3.2.1.2 and 40CFR 60.113b(b)(4)(ii)(B)] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5 and 40 CFR 60.112b(b)(4)(ii)(C)] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. Secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion. [40CFR 60.112b(a)(2)(i)(B)] Federally Enforceable Through Title V Permit
21. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
22. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv as methane, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
23. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
24. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
25. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit
26. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4 and 40CFR 60.112b(a)(2)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
28. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a gas-tight condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
29. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
30. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
32. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
33. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
34. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
35. Operator shall perform gap measurements on primary and secondary seals within 60 days of the initial fill and at least once every year thereafter to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1 and 40 CFR 60.113b(b)(1)(i) & (ii)] Federally Enforceable Through Title V Permit
36. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2 and 40CFR 60.113b(b)(6)] Federally Enforceable Through Title V Permit
37. Operator shall also perform gap measurements on primary seals during hydrostatic testing of the vessel. [40CFR 60.113b(b)(1)(i)] Federally Enforceable Through Title V Permit
38. If unit is out of service for a period of one year or more, subsequent refilling with volatile organic liquid shall be considered initial fill in accordance with the conditions of this permit. [40CFR60.113b(b)(1)(iii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



39. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
40. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the maximum true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7 and 40 CFR 60.116b(c)] Federally Enforceable Through Title V Permit
41. All covers, seals and lids covering openings in the roof used for sampling and gauging, except pressure-vacuum valves set to within 10 percent of the maximum allowable working pressure of the roof, shall be inspected annually by the facility operator to ensure compliance with the provisions of this permit. However, if one or more of the components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If none of the components of that type are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
42. Operator shall determine the presence of VOC leaks by EPA Method 21. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases; 1.) Zero air (less than 10 ppm of hydrocarbon in air); and 2.) A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
43. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
44. Operator shall notify the APCO 30 days in advance of any gap measurements required by this permit to afford the APCO opportunity to have an observer present. [40CFR 60.113b(b)(5)] Federally Enforceable Through Title V Permit
45. If the external floating roof has defects, or the primary seal or secondary seal has holes, tears, or other openings in the seal or seal fabric, the operator shall repair the items as necessary so that none of these conditions exist before filling or refilling the storage vessel with VOL. [40CFR 60.113b(b)(6)(i)] Federally Enforceable Through Title V Permit
46. For all visual inspections required by this permit, the operator shall notify the APCO in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the APCO the opportunity to inspect the storage vessel prior to refilling, except when notification is specifically allowed otherwise by this permit. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

47. If a visual inspection required by this permit is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall notify the APCO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so it is received by the APCO at least 7 days prior to the refilling. [40CFR 60.113b(b)(6)(ii)] Federally Enforceable Through Title V Permit
48. Operator shall record the vessel on which the measurement was performed, date of the seal gap measurement, raw data obtained in the measurement process in accordance with the conditions of this permit. [40CFR 60.115b(b)(3)] Federally Enforceable Through Title V Permit
49. Within 60 days of performing the seal gap measurements required by this permit, the operator shall furnish the APCO with a report containing the date of measurement, raw data obtained in the measurement process, and all such gap calculations as required by this permit. [40CFR 60.115b(b)(2)] Federally Enforceable Through Title V Permit
50. After each seal gap measurement that detects gaps exceeding any limit of this permit, the operator shall submit a report to the APCO within 30 days of the inspection. The report will identify the vessel and contain the date of measurement, raw data obtained in the measurement process, all such gap calculations as required by this permit, and the date the vessel was emptied or the repairs made and the date of repair. [40CFR 60.115b(b)(4)] Federally Enforceable Through Title V Permit
51. If the seals do not meet the required specifications of this permit, operator shall repair or empty the storage vessel within 45 days of identification. [40CFR 60.113b(b)(4)] Federally Enforceable Through Title V Permit
52. Operator shall maintain a record showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The record shall be maintained for the life of the vessel. [40 CFR 60.116b(b)] Federally Enforceable Through Title V Permit
53. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 0.5 psia. [40 CFR 60.116b(e)(2)(ii)] Federally Enforceable Through Title V Permit
54. Operator shall determine the true vapor pressure of each VOL, other than crude oil or refined petroleum products, from standard reference texts, by ASTM Method D2879, or by using an appropriate method approved by EPA. [40 CFR 60.116b(e)(3)(iii)] Federally Enforceable Through Title V Permit
55. For storage vessels operated above or below ambient temperatures, the operator shall calculate the maximum true vapor pressure based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
56. Maximum true vapor pressure, for crude oil or refined petroleum products, may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). [40 CFR 60.116b(e)(2)(i)] Federally Enforceable Through Title V Permit
57. Operator of a tank storing a waste mixture of indeterminate or variable composition shall determine the highest maximum true vapor pressure for the range of liquid compositions to be stored prior to the initial filling, using methods specified for maximum true vapor pressure in this permit. [40CFR 60.116b(f)] Federally Enforceable Through Title V Permit
58. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
59. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

60. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
61. Operator of each storage vessel, either with a design capacity greater than or equal to 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure that is normally less than 0.75 psia or with a design capacity greater than or equal to 75 m<sup>3</sup> but less than 151 m<sup>3</sup> storing a liquid with a maximum true vapor pressure normally less than 4.0 psia, shall notify the APCO within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range. [40CFR 60.116b(d)] Federally Enforceable Through Title V Permit
62. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005) and 40CFR60, Subpart Kb (except 60.115b(b)(1)). A permit shield is granted from this requirement [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
63. This unit commenced construction, modification, or reconstruction after July 23, 1984. Therefore, the requirements of 40 CFR 60 Subpart K and Ka do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
64. The permittee shall keep accurate records of liquid throughput, Reid vapor pressure, storage temperature and types of liquids stored, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-12-3

**EXPIRATION DATE:** 05/31/2016

**SECTION:** 10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

166 BHP CUMMINS MODEL 359 5.9 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

## PERMIT UNIT REQUIREMENTS

---

1. The engine shall be operated with the timing retarded four degrees from the manufacturer's standard recommended timing. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The engine shall be equipped with a turbocharger and with an aftercooler or intercooler. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The engine shall be equipped with a positive crankcase ventilation (PCV) system or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rule 2520, 9.4.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 2520, 9.4.2 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-13-2

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

166 HP CUMMINS MODEL 6BT5.9-G2 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
3. The sulfur content of the diesel fuel used shall not exceed 0.05% by weight. [District Rule 2201]
4. Emissions from this engine shall not exceed any of the following limits: 4.9 g-NO<sub>x</sub>/hp-hr, 3.7 g-CO/hp-hr or 0.3 g-VOC/hp-hr. [District Rule 2201]
5. Emissions from this engine shall not exceed 0.22 g-PM<sub>10</sub>/hp-hr. [District Rules 2201 and 4102]
6. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201]
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. The engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per year. [District Rules 2201 and 4702, and 17 CCR 93115]
9. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
10. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
11. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), and the sulfur content of the diesel fuel used. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-14-1

**EXPIRATION DATE:** 05/31/2016

**SECTION:** SE10 **TOWNSHIP:** 11N **RANGE:** 23W

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK #217 WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-15-1

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK #218 WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-16-1

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK #219 WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-17-1

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK #225 WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-18-1

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK #226 WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1199-19-1

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

CRUDE OIL UNLOADING RACK "NORTH RACK" WITH TRANSFER PUMP AND ASSOCIATED HOSES, VALVES, FLANGES, AND THREADED CONNECTIONS

## PERMIT UNIT REQUIREMENTS

---

1. Only crude oil shall be unloaded through this equipment without prior approval by the District through Authority to Construct. [District Rule 2020] Federally Enforceable Through Title V Permit
2. VOC from the crude oil unloaded through this equipment shall only be routed to a fixed roof or floating roof storage tank which meets the control requirements of Rule 4623, "Storage of Organic Liquids". [District Rule 4624] Federally Enforceable Through Title V Permit
3. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
4. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or, for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane; or, for gasoline, a concentration of VOC greater than 10,000 ppmv, as methane, above background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624, 3.17] Federally Enforceable Through Title V Permit
5. Excess organic liquid drainage is defined as an average of more than ten (10) milliliters liquid drainage per disconnect from three consecutive disconnects. [District Rule 4624, 3.13] Federally Enforceable Through Title V Permit
6. Permittee shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
7. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
8. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and permittee shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections. [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
10. Permittee shall maintain all records of throughput, required monitoring data and support information for a minimum of five years and shall made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.