



OCT 27 2011

Mark A. Wolf
E & J Gallo Winery - Fresno
5610 E Olive Ave
Fresno, CA 93727

Re: Notice of Preliminary Decision - Authority to Construct
Project Number: C-1071622

Dear Mr. Wolf:

Enclosed for your review and comment is the District's analysis of E & J Gallo Winery - Fresno's application for an Authority to Construct for installation of a PV valve on 188 wine fermentation/storage tanks, at 5610 E Olive Avenue, Fresno, CA.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day public comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Stanley Tom of Permit Services at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

DW:st

Enclosures

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



HEALTHY AIR LIVING™

OCT 27 2011

Mike Tollstrup, Chief
Project Assessment Branch
Stationary Source Division
California Air Resources Board
PO Box 2815
Sacramento, CA 95812-2815

Re: Notice of Preliminary Decision - Authority to Construct
Project Number: C-1071622

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of E & J Gallo Winery - Fresno's application for an Authority to Construct for installation of a PV valve on 188 wine fermentation/storage tanks, at 5610 E Olive Avenue, Fresno, CA.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day public comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Stanley Tom of Permit Services at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

DW:st

Enclosure

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



HEALTHY AIR LIVING™

OCT 27 2011

Gerardo C. Rios (AIR 3)
Chief, Permits Office
Air Division
U.S. E.P.A. - Region IX
75 Hawthorne Street
San Francisco, CA 94105

**Re: Notice of Preliminary Decision - Authority to Construct
Project Number: C-1071622**

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of E & J Gallo Winery - Fresno's application for an Authority to Construct for installation of a PV valve on 188 wine fermentation/storage tanks, at 5610 E Olive Avenue, Fresno, CA.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day public comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Stanley Tom of Permit Services at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

DW:st

Enclosure

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 861-392-5500 FAX: 661-392-5585

Fresno Bee
Fresno Bee

**NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED ISSUANCE OF
AN AUTHORITY TO CONSTRUCT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Unified Air Pollution Control District solicits public comment on the proposed issuance of Authority to Construct to E & J Gallo Winery - Fresno for installation of a PV valve on 188 wine fermentation/storage tanks, at 5610 E Olive Avenue, Fresno, CA.

The analysis of the regulatory basis for this proposed action, Project #C-1071622, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. Written comments on this project must be submitted within 30 days of the publication date of this notice to **DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT, 1990 EAST GETTYSBURG AVENUE, FRESNO, CA 93726.**

San Joaquin Valley Air Pollution Control District
Authority to Construct
Application Review
188 Wine Fermentation/Storage Tanks

Facility Name:	E & J Gallo Winery - Fresno	Date:	October 22, 2011
Mailing Address:	5610 E Olive Ave Fresno, CA 93727	Engineer:	Stanley Tom
Contact Person:	Mark A. Wolf	Lead Engineer:	Joven Refuerzo
Telephone:	(559) 458-2417		
Application #(s):	C-447-27-1 through C-447-214-1		
Project #:	C-1071622		
Deemed Complete:	July 9, 2007		

I. PROPOSAL

E & J Gallo Winery - Fresno requests Authority to Construct (ATC) permits to install pressure/vacuum valves on tanks C-447-27 through '95 and '117 through '214.

The facility proposes to revise the equipment description for permits C-447-96 through '116 to include white wine fermentation. This change is to reflect the existing operation which was inadvertently omitted with the initial In-house Permits to Operate and does not require NSR calculations.

The facility proposes to revise the equipment description for permits C-447-159 through '162 to include fermentation. This change is to reflect the existing operation which was inadvertently omitted with the initial In-house Permits to Operate and does not require NSR calculations.

Tanks C-447-27 through '95 and C-447-117 through '214 are used as fermentation and storage tanks. Tanks C-447-96 through '116 are used for fermentation only.

The only permitting action in this project that is a NSR modification is the PV valve installation. The PV valve only affects the storage operation portion of the tanks. Therefore, NSR calculations will be performed for the storage operation only.

E & J Gallo Winery - Fresno has received their Title V Permit. This modification can be classified as a Title V minor modification pursuant to Rule 2520, Section 3.20, and can be processed with a Certificate of Conformity (COC). But the facility has not requested that this project be processed in that manner. The ATCs in this project will be implemented under the current Title V renewal project C-1060098.

II. Applicable Rules

Rule 2201	New and Modified Stationary Source Review Rule (9/21/06)
Rule 2520	Federally Mandated Operating Permits (6/21/01)
Rule 4001	New Source Performance Standards (4/14/99)
Rule 4002	National Emission Standards for Hazardous Air Pollutants (5/20/04)
Rule 4102	Nuisance (12/17/92)
Rule 4623	Storage of Organic Liquids (5/19/05)
Rule 4694	Wine Fermentation and Storage Tanks (12/15/05)
CH&SC 41700	Health Risk Assessment
CH&SC 42301.6	School Notice

III. Project Location

This facility is located at 5610 E Olive Avenue, Fresno. The District has verified that the facility is not located within 1,000 feet of the outer boundary of K-12 school. Therefore, the public notification requirement of California Health and Safety Code 42301.6 is not applicable to this project.

IV. Process Description

E&J Gallo Winery operates a wine fermentation and storage facility. During the "crush season", typically from late August to late November, both red and white grapes are received by truck and are delivered to a crusher-stemmer which serves to crush the grapes and remove the stems. In the case of red wines, the resultant juice (termed "must" and containing the grape skins, pulp and seeds) is pumped to red wine fermentation tanks for fermentation, a batch process. The red wine fermentation tanks are specifically designed to ferment the must in contact with the skins and to allow the separation of the skins and seeds from the wine after fermentation. In the case of white wines, the must is sent to screens and presses for separation of grape skins and seeds prior to fermentation. After separation of the skins and seeds, the white must is transferred to a fermentation tank. White wine fermentation can be carried out in a tank without design provisions for solids separation since the skins and seeds have already been separated.

After transfer of the must (red or white) to the fermentation tank, the must is inoculated with yeast which initiates the fermentation reactions. During fermentation, the yeast metabolizes the sugar in the grape juice, converting it to ethanol and carbon dioxide plus releasing heat. Temperature is typically controlled by refrigeration to maintain a temperature of 45-65° F for white wine fermentation and 70-95° F for red wine fermentation. The sugar content of the fermentation mass is measured in °Brix (weight %) and is typically 22-26° for unfermented grape juice, dropping to 4° or less for the end of fermentation. Finished ethanol concentration is approximately 12%. Batch fermentation requires 3-5 days/batch for red wine and 1-2 weeks for white wine. VOCs are emitted during the fermentation process along with the CO₂. The VOCs consist primarily of ethanol along with minor fermentation byproducts.

Following the completion of fermentation, the wine is transferred directly to storage tanks. The grape skins from the red wine fermentation are sent to a press for recovery of contained wine which is also transferred to the wine storage tanks. Wine is stored year-round for bottling, typically under refrigeration. Further VOC emissions occur as a result of the storage tank operation.

V. Equipment Listing

Pre-Project Equipment Description:

Permit #	Description
C-447-27-0	105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12
C-447-28-0	105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13
C-447-29-0	105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14
C-447-30-0	54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 509
C-447-31-0	54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 510
C-447-32-0	54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 511
C-447-33-0	54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 512
C-447-34-0	102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001
C-447-35-0	101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002
C-447-36-0	102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003
C-447-37-0	102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004
C-447-38-0	102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005
C-447-39-0	102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006
C-447-40-0	102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007
C-447-41-0	102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008
C-447-42-0	102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009
C-447-43-0	103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010
C-447-44-0	103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011
C-447-45-0	103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012
C-447-46-0	105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501

- C-447-47-0** 105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502
- C-447-48-0** 105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503
- C-447-49-0** 105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504
- C-447-50-0** 105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505
- C-447-51-0** 105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506
- C-447-52-0** 105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507
- C-447-53-0** 105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508
- C-447-54-0** 105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509
- C-447-55-0** 105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510
- C-447-56-0** 212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001
- C-447-57-0** 212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002
- C-447-58-0** 212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003
- C-447-59-0** 212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004
- C-447-60-0** 211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005
- C-447-61-0** 212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006
- C-447-62-0** 211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007
- C-447-63-0** 212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008
- C-447-64-0** 212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009
- C-447-65-0** 214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2010
- C-447-66-0** 213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2011
- C-447-67-0** 214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012
- C-447-68-0** 214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013
- C-447-69-0** 214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014
- C-447-70-0** 214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015

- C-447-71-0** 214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016
- C-447-72-0** 213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501
- C-447-73-0** 213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502
- C-447-74-0** 213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503
- C-447-75-0** 213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504
- C-447-76-0** 213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505
- C-447-77-0** 213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506
- C-447-78-0** 213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507
- C-447-79-0** 213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508
- C-447-80-0** 211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509
- C-447-81-0** 211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510
- C-447-82-0** 211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511
- C-447-83-0** 211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512
- C-447-84-0** 211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513
- C-447-85-0** 211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514
- C-447-86-0** 211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515
- C-447-87-0** 211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516
- C-447-88-0** 211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517
- C-447-89-0** 211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518
- C-447-90-0** 211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519
- C-447-91-0** 211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520
- C-447-92-0** 211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521
- C-447-93-0** 211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522
- C-447-94-0** 211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523

C-447-95-0	211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524
C-447-96-0	207,390 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2922
C-447-97-0	207,909 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2923
C-447-98-0	207,676 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2924
C-447-99-0	208,185 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2925
C-447-100-0	207,571 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2926
C-447-101-0	208,168 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2927
C-447-102-0	207,821 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2928
C-447-103-0	207,140 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2929
C-447-104-0	206,695 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2930
C-447-105-0	207,451 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2931
C-447-106-0	206,832 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2932
C-447-107-0	207,270 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2933
C-447-108-0	208,117 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2934
C-447-109-0	208,202 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2935
C-447-110-0	206,996 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2936
C-447-111-0	207,039 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2937
C-447-112-0	206,757 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2938
C-447-113-0	207,752 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2939
C-447-114-0	207,369 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2940
C-447-115-0	208,795 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2941
C-447-116-0	208,928 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2942
C-447-117-0	329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013
C-447-118-0	329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014

C-447-119-0 642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6013

C-447-120-0 642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6014

C-447-121-0 642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6015

C-447-122-0 643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6016

C-447-123-0 643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6017

C-447-124-0 642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6018

C-447-125-0 642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6019

C-447-126-0 643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6020

C-447-127-0 641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6021

C-447-128-0 641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6022

C-447-129-0 641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6023

C-447-130-0 641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6024

C-447-131-0 642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6025

C-447-132-0 640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6026

C-447-133-0 641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6027

C-447-134-0 641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6028

C-447-135-0 643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6029

C-447-136-0 643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6030

C-447-137-0 643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6031

C-447-138-0 642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6032

C-447-139-0 642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6033

C-447-140-0 644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6034

C-447-141-0 642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6035

C-447-142-0 642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6036

C-447-143-0 643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6037

C-447-144-0 641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6038

C-447-145-0 643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6039

C-447-146-0 643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6040

C-447-147-0 644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6041

C-447-148-0 642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6042

C-447-149-0 642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6043

C-447-150-0 642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6044

C-447-151-0 644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6045

C-447-152-0 643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6046

C-447-153-0 642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6047

C-447-154-0 643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6048

C-447-155-0 643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6049

C-447-156-0 642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6050

C-447-157-0 645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6051

C-447-158-0 643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6052

C-447-159-0 642,374 GALLON STEEL WINE STORAGE TANK 6053

C-447-160-0 641,400 GALLON STEEL WINE STORAGE TANK 6054

C-447-161-0 642,257 GALLON STEEL WINE STORAGE TANK 6055

C-447-162-0 643,277 GALLON STEEL WINE STORAGE TANK 6056

C-447-163-0 641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6501

C-447-164-0 642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6502

C-447-165-0 641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6503

C-447-166-0 641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6504

C-447-167-0 642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6505

C-447-168-0 642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6506

C-447-169-0 643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6507

C-447-170-0 642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6508

C-447-171-0 643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6509

C-447-172-0 642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6510

C-447-173-0 642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6511

C-447-174-0 642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6512

C-447-175-0 640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6513

C-447-176-0 643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6514

C-447-177-0 640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6515

C-447-178-0 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6516

C-447-179-0 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6517

C-447-180-0 643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6518

C-447-181-0 642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6519

C-447-182-0 642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6520

C-447-183-0 642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6521

C-447-184-0 642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6522

C-447-185-0 643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6523

C-447-186-0 641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6524

C-447-187-0 642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6526

C-447-188-0 639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6527

C-447-189-0 641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6528

C-447-190-0 642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6529

C-447-191-0 642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6601

C-447-192-0 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6602

C-447-193-0 640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6603

C-447-194-0 640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6604

C-447-195-0 642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6609

C-447-196-0 641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6610

C-447-197-0 641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6611

C-447-198-0 641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6612

C-447-199-0 640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6617

C-447-200-0 642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6618

C-447-201-0 641,719 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6619

C-447-202-0 642,050 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6620

C-447-203-0 640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6625

C-447-204-0 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6626

C-447-205-0 642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6627

C-447-206-0 642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6628

C-447-207-0 640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6633

C-447-208-0 641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6634

C-447-209-0 641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6635

C-447-210-0 639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6636

C-447-211-0 640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6637

C-447-212-0 640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6638

C-447-213-0 641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6639

C-447-214-0 641,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 6640

Proposed Modification:

Permit #	Description
C-447-27-1	MODIFICATION OF A 105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-28-1	MODIFICATION OF A 105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-29-1	MODIFICATION OF A 105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-30-1	MODIFICATION OF A 54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-31-1	MODIFICATION OF A 54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-32-1	MODIFICATION OF A 54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-33-1	MODIFICATION OF A 54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-34-1	MODIFICATION OF A 102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-35-1	MODIFICATION OF A 101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-36-1	MODIFICATION OF A 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-37-1	MODIFICATION OF A 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-38-1	MODIFICATION OF A 102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
C-447-39-1	MODIFICATION OF A 102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-40-1** MODIFICATION OF A 102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-41-1** MODIFICATION OF A 102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-42-1** MODIFICATION OF A 102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-43-1** MODIFICATION OF A 103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-44-1** MODIFICATION OF A 103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-45-1** MODIFICATION OF A 103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-46-1** MODIFICATION OF A 105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-47-1** MODIFICATION OF A 105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-48-1** MODIFICATION OF A 105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-49-1** MODIFICATION OF A 105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-50-1** MODIFICATION OF A 105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-51-1** MODIFICATION OF A 105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-52-1** MODIFICATION OF A 105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-53-1** MODIFICATION OF A 105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-54-1** MODIFICATION OF A 105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-55-1** MODIFICATION OF A 105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-56-1** MODIFICATION OF A 212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-57-1** MODIFICATION OF A 212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-58-1** MODIFICATION OF A 212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-59-1** MODIFICATION OF A 212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-60-1** MODIFICATION OF A 211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-61-1** MODIFICATION OF A 212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-62-1** MODIFICATION OF A 211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-63-1** MODIFICATION OF A 212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-64-1** MODIFICATION OF A 212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-65-1** MODIFICATION OF A 214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2010: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-66-1** MODIFICATION OF A 213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2011: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-67-1** MODIFICATION OF A 214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-68-1** MODIFICATION OF A 214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-69-1** MODIFICATION OF A 214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-70-1** MODIFICATION OF A 214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-71-1** MODIFICATION OF A 214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-72-1** MODIFICATION OF A 213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-73-1** MODIFICATION OF A 213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-74-1** MODIFICATION OF A 213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-75-1** MODIFICATION OF A 213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-76-1** MODIFICATION OF A 213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-77-1** MODIFICATION OF A 213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-78-1** MODIFICATION OF A 213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-79-1** MODIFICATION OF A 213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-80-1** MODIFICATION OF A 211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-81-1** MODIFICATION OF A 211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-82-1** MODIFICATION OF A 211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-83-1** MODIFICATION OF A 211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-84-1** MODIFICATION OF A 211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-85-1** MODIFICATION OF A 211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-86-1** MODIFICATION OF A 211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-87-1** MODIFICATION OF A 211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-88-1** MODIFICATION OF A 211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-89-1** MODIFICATION OF A 211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-90-1** MODIFICATION OF A 211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-91-1** MODIFICATION OF A 211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-92-1** MODIFICATION OF A 211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-93-1** MODIFICATION OF A 211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-94-1** MODIFICATION OF A 211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-95-1** MODIFICATION OF A 211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-96-1** MODIFICATION OF A 207,390 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2922: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-97-1** MODIFICATION OF A 207,909 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2923: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-98-1** MODIFICATION OF A 207,676 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2924: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-99-1** MODIFICATION OF A 208,185 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2925: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-100-1** MODIFICATION OF A 207,571 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2926: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-101-1** MODIFICATION OF A 208,168 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2927: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

- C-447-102-1** MODIFICATION OF A 207,821 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2928: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-103-1** MODIFICATION OF A 207,140 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2929: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-104-1** MODIFICATION OF A 206,695 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2930: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-105-1** MODIFICATION OF A 207,451 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2931: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-106-1** MODIFICATION OF A 206,832 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2932: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-107-1** MODIFICATION OF A 207,270 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2933: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-108-1** MODIFICATION OF A 208,117 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2934: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-109-1** MODIFICATION OF A 208,202 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2935: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-110-1** MODIFICATION OF A 206,996 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2936: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-111-1** MODIFICATION OF A 207,039 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2937: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-112-1** MODIFICATION OF A 206,757 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2938: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-113-1** MODIFICATION OF A 207,752 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2939: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

- C-447-114-1** MODIFICATION OF A 207,369 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2940: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-115-1** MODIFICATION OF A 208,795 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2941: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-116-1** MODIFICATION OF A 208,928 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2942: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK
- C-447-117-1** MODIFICATION OF A 329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-118-1** MODIFICATION OF A 329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-119-1** MODIFICATION OF A 642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-120-1** MODIFICATION OF A 642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-121-1** MODIFICATION OF A 642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-122-1** MODIFICATION OF A 643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-123-1** MODIFICATION OF A 643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-124-1** MODIFICATION OF A 642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-125-1** MODIFICATION OF A 642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-126-1** MODIFICATION OF A 643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-127-1** MODIFICATION OF A 641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-128-1** MODIFICATION OF A 641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-129-1** MODIFICATION OF A 641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-130-1** MODIFICATION OF A 641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-131-1** MODIFICATION OF A 642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-132-1** MODIFICATION OF A 640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-133-1** MODIFICATION OF A 641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-134-1** MODIFICATION OF A 641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-135-1** MODIFICATION OF A 643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-136-1** MODIFICATION OF A 643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-137-1** MODIFICATION OF A 643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-138-1** MODIFICATION OF A 642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-139-1** MODIFICATION OF A 642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-140-1** MODIFICATION OF A 644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-141-1** MODIFICATION OF A 642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-142-1** MODIFICATION OF A 642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-143-1** MODIFICATION OF A 643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-144-1** MODIFICATION OF A 641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-145-1** MODIFICATION OF A 643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-146-1** MODIFICATION OF A 643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-147-1** MODIFICATION OF A 644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-148-1** MODIFICATION OF A 642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-149-1** MODIFICATION OF A 642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-150-1** MODIFICATION OF A 642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-151-1** MODIFICATION OF A 644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-152-1** MODIFICATION OF A 643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-153-1** MODIFICATION OF A 642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-154-1** MODIFICATION OF A 643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-155-1** MODIFICATION OF A 643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-156-1** MODIFICATION OF A 642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-157-1** MODIFICATION OF A 645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-158-1** MODIFICATION OF A 643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-159-1** MODIFICATION OF A 642,374 GALLON STEEL WINE STORAGE TANK 6053: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK

- C-447-160-1** MODIFICATION OF A 641,400 GALLON STEEL WINE STORAGE TANK 6054: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK
- C-447-161-1** MODIFICATION OF A 642,257 GALLON STEEL WINE STORAGE TANK 6055: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK
- C-447-162-1** MODIFICATION OF A 643,277 GALLON STEEL WINE STORAGE TANK 6056: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK
- C-447-163-1** MODIFICATION OF A 641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-164-1** MODIFICATION OF A 642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-165-1** MODIFICATION OF A 641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-166-1** MODIFICATION OF A 641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-167-1** MODIFICATION OF A 642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-168-1** MODIFICATION OF A 642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-169-1** MODIFICATION OF A 643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-170-1** MODIFICATION OF A 642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-171-1** MODIFICATION OF A 643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-172-1** MODIFICATION OF A 642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-173-1** MODIFICATION OF A 642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-174-1** MODIFICATION OF A 642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-175-1** MODIFICATION OF A 640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-176-1** MODIFICATION OF A 643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-177-1** MODIFICATION OF A 640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-178-1** MODIFICATION OF A 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-179-1** MODIFICATION OF A 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-180-1** MODIFICATION OF A 643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-181-1** MODIFICATION OF A 642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-182-1** MODIFICATION OF A 642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-183-1** MODIFICATION OF A 642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-184-1** MODIFICATION OF A 642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-185-1** MODIFICATION OF A 643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-186-1** MODIFICATION OF A 641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-187-1** MODIFICATION OF A 642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-188-1** MODIFICATION OF A 639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-189-1** MODIFICATION OF A 641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-190-1** MODIFICATION OF A 642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-191-1** MODIFICATION OF A 642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-192-1** MODIFICATION OF A 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-193-1** MODIFICATION OF A 640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-194-1** MODIFICATION OF A 640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-195-1** MODIFICATION OF A 642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-196-1** MODIFICATION OF A 641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-197-1** MODIFICATION OF A 641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-198-1** MODIFICATION OF A 641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-199-1** MODIFICATION OF A 640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-200-1** MODIFICATION OF A 642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-201-1** MODIFICATION OF A 641,719 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-202-1** MODIFICATION OF A 642,050 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-203-1** MODIFICATION OF A 640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-204-1** MODIFICATION OF A 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

- C-447-205-1** MODIFICATION OF A 642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-206-1** MODIFICATION OF A 642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-207-1** MODIFICATION OF A 640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-208-1** MODIFICATION OF A 641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-209-1** MODIFICATION OF A 641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6635: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-210-1** MODIFICATION OF A 639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6636: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-211-1** MODIFICATION OF A 640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6637: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-212-1** MODIFICATION OF A 640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6638: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-213-1** MODIFICATION OF A 641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6639: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE
- C-447-214-1** MODIFICATION OF A 641,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6640: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

Post-Project Equipment Description:

Permit #	Description
C-447-27-1	105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12 WITH PV VALVE
C-447-28-1	105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13 WITH PV VALVE
C-447-29-1	105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14 WITH PV VALVE
C-447-30-1	54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 509 WITH PV VALVE
C-447-31-1	54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 510 WITH PV VALVE
C-447-32-1	54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 511 WITH PV VALVE

C-447-33-1 54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 512 WITH PV VALVE

C-447-34-1 102,087 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1001 WITH PV VALVE

C-447-35-1 101,870 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1002 WITH PV VALVE

C-447-36-1 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1003 WITH PV VALVE

C-447-37-1 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1004 WITH PV VALVE

C-447-38-1 102,175 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1005 WITH PV VALVE

C-447-39-1 102,235 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1006 WITH PV VALVE

C-447-40-1 102,211 GALLON STEEL ENCLOSED TOP WHITE WINE
FERMENTATION AND STORAGE TANK 1007 WITH PV VALVE

C-447-41-1 102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1008 WITH PV VALVE

C-447-42-1 102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1009 WITH PV VALVE

C-447-43-1 103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1010 WITH PV VALVE

C-447-44-1 103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1011 WITH PV VALVE

C-447-45-1 103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1012 WITH PV VALVE

C-447-46-1 105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1501 WITH PV VALVE

C-447-47-1 105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1502 WITH PV VALVE

C-447-48-1 105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1503 WITH PV VALVE

C-447-49-1 105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1504 WITH PV VALVE

C-447-50-1 105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1505 WITH PV VALVE

C-447-51-1 105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1506 WITH PV VALVE

C-447-52-1 105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1507 WITH PV VALVE

C-447-53-1 105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1508 WITH PV VALVE

C-447-54-1 105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1509 WITH PV VALVE

C-447-55-1 105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 1510 WITH PV VALVE

C-447-56-1 212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2001 WITH PV VALVE

C-447-57-1 212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2002 WITH PV VALVE

C-447-58-1 212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2003 WITH PV VALVE

C-447-59-1 212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2004 WITH PV VALVE

C-447-60-1 211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2005 WITH PV VALVE

C-447-61-1 212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2006 WITH PV VALVE

C-447-62-1 211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2007 WITH PV VALVE

C-447-63-1 212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2008 WITH PV VALVE

C-447-64-1 212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2009 WITH PV VALVE

C-447-65-1 214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2010 WITH PV VALVE

C-447-66-1 213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2011 WITH PV VALVE

C-447-67-1 214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2012 WITH PV VALVE

C-447-68-1 214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2013 WITH PV VALVE

C-447-69-1 214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2014 WITH PV VALVE

C-447-70-1 214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2015 WITH PV VALVE

C-447-71-1 214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2016 WITH PV VALVE

C-447-72-1 213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2501 WITH PV VALVE

C-447-73-1 213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2502 WITH PV VALVE

C-447-74-1 213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2503 WITH PV VALVE

C-447-75-1 213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2504 WITH PV VALVE

C-447-76-1 213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2505 WITH PV VALVE

C-447-77-1 213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2506 WITH PV VALVE

C-447-78-1 213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2507 WITH PV VALVE

C-447-79-1 213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2508 WITH PV VALVE

C-447-80-1 211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2509 WITH PV VALVE

C-447-81-1 211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2510 WITH PV VALVE

C-447-82-1 211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2511 WITH PV VALVE

C-447-83-1 211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2512 WITH PV VALVE

C-447-84-1 211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2513 WITH PV VALVE

C-447-85-1 211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2514 WITH PV VALVE

C-447-86-1 211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2515 WITH PV VALVE

C-447-87-1 211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2516 WITH PV VALVE

C-447-88-1 211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2517 WITH PV VALVE

C-447-89-1 211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2518 WITH PV VALVE

C-447-90-1 211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2519 WITH PV VALVE

C-447-91-1 211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2520 WITH PV VALVE

C-447-92-1 211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2521 WITH PV VALVE

C-447-93-1 211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2522 WITH PV VALVE

C-447-94-1 211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2523 WITH PV VALVE

C-447-95-1 211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION AND STORAGE TANK 2524 WITH PV VALVE

C-447-96-1 207,390 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2922

C-447-97-1 207,909 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2923

C-447-98-1 207,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2924

C-447-99-1 208,185 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2925

C-447-100-1 207,571 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2926

C-447-101-1 208,168 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2927

C-447-102-1 207,821 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2928

C-447-103-1 207,140 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2929

C-447-104-1 206,695 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE
FERMENTATION TANK 2930

C-447-105-1 207,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2931

C-447-106-1 206,832 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2932

C-447-107-1 207,270 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2933

C-447-108-1 208,117 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2934

C-447-109-1 208,202 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2935

C-447-110-1 206,996 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2936

C-447-111-1 207,039 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2937

C-447-112-1 206,757 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2938

C-447-113-1 207,752 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2939

C-447-114-1 207,369 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2940

C-447-115-1 208,795 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2941

C-447-116-1 208,928 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2942

C-447-117-1 329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013 WITH PV VALVE

C-447-118-1 329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014 WITH PV VALVE

C-447-119-1 642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013 WITH PV VALVE

C-447-120-1 642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014 WITH PV VALVE

C-447-121-1 642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015 WITH PV VALVE

C-447-122-1 643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016 WITH PV VALVE

C-447-123-1 643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017 WITH PV VALVE

C-447-124-1 642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018 WITH PV VALVE

C-447-125-1 642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019 WITH PV VALVE

C-447-126-1 643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020 WITH PV VALVE

C-447-127-1 641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021 WITH PV VALVE

C-447-128-1 641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022 WITH PV VALVE

C-447-129-1 641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023 WITH PV VALVE
C-447-130-1 641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024 WITH PV VALVE
C-447-131-1 642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025 WITH PV VALVE
C-447-132-1 640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026 WITH PV VALVE
C-447-133-1 641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027 WITH PV VALVE
C-447-134-1 641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028 WITH PV VALVE
C-447-135-1 643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029 WITH PV VALVE
C-447-136-1 643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030 WITH PV VALVE
C-447-137-1 643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031 WITH PV VALVE
C-447-138-1 642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032 WITH PV VALVE
C-447-139-1 642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033 WITH PV VALVE
C-447-140-1 644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034 WITH PV VALVE
C-447-141-1 642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035 WITH PV VALVE
C-447-142-1 642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036 WITH PV VALVE
C-447-143-1 643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037 WITH PV VALVE
C-447-144-1 641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038 WITH PV VALVE
C-447-145-1 643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039 WITH PV VALVE
C-447-146-1 643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040 WITH PV VALVE
C-447-147-1 644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041 WITH PV VALVE
C-447-148-1 642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042 WITH PV VALVE
C-447-149-1 642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043 WITH PV VALVE
C-447-150-1 642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044 WITH PV VALVE

C-447-151-1 644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045 WITH PV VALVE

C-447-152-1 643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046 WITH PV VALVE

C-447-153-1 642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047 WITH PV VALVE

C-447-154-1 643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048 WITH PV VALVE

C-447-155-1 643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049 WITH PV VALVE

C-447-156-1 642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050 WITH PV VALVE

C-447-157-1 645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051 WITH PV VALVE

C-447-158-1 643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052 WITH PV VALVE

C-447-159-1 642,374 GALLON STEEL WINE FERMENTATION AND STORAGE TANK 6053 WITH PV VALVE

C-447-160-1 641,400 GALLON STEEL WINE FERMENTATION AND STORAGE TANK 6054 WITH PV VALVE

C-447-161-1 642,257 GALLON STEEL WINE FERMENTATION AND STORAGE TANK 6055 WITH PV VALVE

C-447-162-1 643,277 GALLON STEEL WINE FERMENTATION AND STORAGE TANK 6056 WITH PV VALVE

C-447-163-1 641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501 WITH PV VALVE

C-447-164-1 642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502 WITH PV VALVE

C-447-165-1 641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503 WITH PV VALVE

C-447-166-1 641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504 WITH PV VALVE

C-447-167-1 642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505 WITH PV VALVE

C-447-168-1 642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506 WITH PV VALVE

C-447-169-1 643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507 WITH PV VALVE

C-447-170-1 642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508 WITH PV VALVE

C-447-171-1 643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509 WITH PV VALVE

C-447-172-1 642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510 WITH PV VALVE

C-447-173-1 642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511 WITH PV VALVE

C-447-174-1 642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512 WITH PV VALVE
C-447-175-1 640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513 WITH PV VALVE
C-447-176-1 643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514 WITH PV VALVE
C-447-177-1 640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515 WITH PV VALVE
C-447-178-1 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516 WITH PV VALVE
C-447-179-1 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517 WITH PV VALVE
C-447-180-1 643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518 WITH PV VALVE
C-447-181-1 642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519 WITH PV VALVE
C-447-182-1 642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520 WITH PV VALVE
C-447-183-1 642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521 WITH PV VALVE
C-447-184-1 642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522 WITH PV VALVE
C-447-185-1 643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523 WITH PV VALVE
C-447-186-1 641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524 WITH PV VALVE
C-447-187-1 642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526 WITH PV VALVE
C-447-188-1 639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527 WITH PV VALVE
C-447-189-1 641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528 WITH PV VALVE
C-447-190-1 642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529 WITH PV VALVE
C-447-191-1 642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601 WITH PV VALVE
C-447-192-1 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602 WITH PV VALVE
C-447-193-1 640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603 WITH PV VALVE
C-447-194-1 640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604 WITH PV VALVE
C-447-195-1 642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609 WITH PV VALVE
C-447-196-1 641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610 WITH PV VALVE

C-447-197-1	641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611 WITH PV VALVE
C-447-198-1	641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612 WITH PV VALVE
C-447-199-1	640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617 WITH PV VALVE
C-447-200-1	642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618 WITH PV VALVE
C-447-201-1	641,719 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619 WITH PV VALVE
C-447-202-1	642,050 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620 WITH PV VALVE
C-447-203-1	640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625 WITH PV VALVE
C-447-204-1	642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626 WITH PV VALVE
C-447-205-1	642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627 WITH PV VALVE
C-447-206-1	642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628 WITH PV VALVE
C-447-207-1	640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633 WITH PV VALVE
C-447-208-1	641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634 WITH PV VALVE
C-447-209-1	641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6635 WITH PV VALVE
C-447-210-1	639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6636 WITH PV VALVE
C-447-211-1	640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6637 WITH PV VALVE
C-447-212-1	640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6638 WITH PV VALVE
C-447-213-1	641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6639 WITH PV VALVE
C-447-214-1	641,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6640 WITH PV VALVE

VI. Emission Control Technology Evaluation

Emissions from wine storage tanks are controlled by maintaining storage temperature typically in the range of 40-70° F by refrigeration and by sealing the tank and installing a pressure/vacuum relief valve. Refrigerated storage serves to reduce the vapor pressure of the wine, minimizing volatilization of ethanol to the tank vapor space. The combination of refrigerated storage and pressure/vacuum valve serves to minimize VOC emissions which might result from tank breathing losses. The valve will not let vapor escape from the tank or air to enter the tank until the tank pressure is within 10% of the maximum allowable pressure or vacuum for the tank.

Wine fermentation tanks are open to the atmosphere during fermentation and are not equipped with any emission control equipment. Fermentation tanks may be also used for storage, in which case the pressure vacuum valve would be installed and the tank sealed prior to being put into storage service.

VII. General Calculations

For tanks C-447-96 through '116 to add white wine fermentation and for tanks C-447-159 through 162 to add red and white wine fermentation to the equipment description, this action is a revision to reflect the existing operation which was inadvertently omitted with the initial In-house Permits to Operate as these tanks have historically been in red and white wine fermentation service. Therefore, NSR calculations for the fermentation operation are not required for these tanks but will be shown for reference purposes.

A. Assumptions

- Installation of the PV-valve is a NSR modification only for the storage operation of the tanks. Therefore, fermentation emission calculations are not required.
- The maximum wine storage per tank is ten turnovers per day as worst case assumption (per applicant). Note, the applicant has stipulated this project will be a Major Modification.
- Only VOCs are emitted from the storage tanks.

B. Emission Factors

Storage (C-447-27 through '95 and C-447-117 through '214)

Operation	Emission Factor (lb-VOC/1000 gallons wine)
Red and White Wine Storage	0.338 ⁽¹⁾

(1) See FYI 114 based on a maximum red and white wine ethanol concentration of 23.9 volume percent.

Fermentation (C-447-96 through '116)

Uncontrolled emissions factors are taken from District FYI-114, *VOC Emission Factors for Wine Fermentation and Storage Tanks*.

Wine Type	EF (lb-VOC/1,000 gallon of wine)		Source
	Daily	Annual	
White	1.62	2.5	FYI-114
Red	3.46	6.2	FYI-114

Since these tanks can ferment either white or red wine, therefore, worst case emissions factors of red wine will be used to calculate the maximum potential emissions.

C. Calculations

1. Pre-Project Potential to Emit (PE1)

Storage (C-447-27 through '95 and C-447-117 through '214)

The PE1 is calculated with the following equation:

$$\text{Daily PE1} = \text{Capacity (gal)} \times \text{turnovers/day} \times \text{EF (lb/1000 gal)}$$

$$\text{Annual PE1} = \text{Daily PE1} \times 365 \text{ days/year}$$

Red and White Wine Storage Annual Potential to Emit (PE)					
Permit	Capacity (gal)	Turnovers/day	lb-VOC/10 ³ gal	lb-VOC/day	lb-VOC/year
C-447-27-0	105,179	10	0.338	355.5	129,759
C-447-28-0	105,043	10	0.338	355.0	129,592
C-447-29-0	105,306	10	0.338	355.9	129,916
C-447-30-0	54,680	10	0.338	184.8	67,459
C-447-31-0	54,668	10	0.338	184.8	67,444
C-447-32-0	54,672	10	0.338	184.8	67,449
C-447-33-0	54,668	10	0.338	184.8	67,444
C-447-34-0	102,087	10	0.338	345.1	125,945
C-447-35-0	101,870	10	0.338	344.3	125,677
C-447-36-0	102,253	10	0.338	345.6	126,150
C-447-37-0	102,253	10	0.338	345.6	126,150
C-447-38-0	102,175	10	0.338	345.4	126,053
C-447-39-0	102,235	10	0.338	345.6	126,127
C-447-40-0	102,211	10	0.338	345.5	126,098
C-447-41-0	102,968	10	0.338	348.0	127,032
C-447-42-0	102,262	10	0.338	345.6	126,161
C-447-43-0	103,122	10	0.338	348.6	127,222

C-447-44-0	103,146	10	0.338	348.6	127,251
C-447-45-0	103,080	10	0.338	348.4	127,170
C-447-46-0	105,264	10	0.338	355.8	129,864
C-447-47-0	105,259	10	0.338	355.8	129,858
C-447-48-0	105,284	10	0.338	355.9	129,889
C-447-49-0	105,100	10	0.338	355.2	129,662
C-447-50-0	105,215	10	0.338	355.6	129,804
C-447-51-0	105,011	10	0.338	354.9	129,552
C-447-52-0	105,287	10	0.338	355.9	129,893
C-447-53-0	105,054	10	0.338	355.1	129,605
C-447-54-0	105,194	10	0.338	355.6	129,778
C-447-55-0	105,021	10	0.338	355.0	129,564
C-447-56-0	212,026	10	0.338	716.6	261,576
C-447-57-0	212,468	10	0.338	718.1	262,122
C-447-58-0	212,151	10	0.338	717.1	261,731
C-447-59-0	212,120	10	0.338	717.0	261,692
C-447-60-0	211,917	10	0.338	716.3	261,442
C-447-61-0	212,275	10	0.338	717.5	261,884
C-447-62-0	211,691	10	0.338	715.5	261,163
C-447-63-0	212,254	10	0.338	717.4	261,858
C-447-64-0	212,766	10	0.338	719.1	262,489
C-447-65-0	214,253	10	0.338	724.2	264,324
C-447-66-0	213,963	10	0.338	723.2	263,966
C-447-67-0	214,245	10	0.338	724.1	264,314
C-447-68-0	214,528	10	0.338	725.1	264,663
C-447-69-0	214,325	10	0.338	724.4	264,413
C-447-70-0	214,301	10	0.338	724.3	264,383
C-447-71-0	214,236	10	0.338	724.1	264,303
C-447-72-0	213,126	10	0.338	720.4	262,934
C-447-73-0	213,596	10	0.338	722.0	263,513
C-447-74-0	213,687	10	0.338	722.3	263,626
C-447-75-0	213,298	10	0.338	720.9	263,146

C-447-76-0	213,018	10	0.338	720.0	262,800
C-447-77-0	213,471	10	0.338	721.5	263,359
C-447-78-0	213,296	10	0.338	720.9	263,143
C-447-79-0	213,411	10	0.338	721.3	263,285
C-447-80-0	211,766	10	0.338	715.8	261,256
C-447-81-0	211,311	10	0.338	714.2	260,694
C-447-82-0	211,316	10	0.338	714.2	260,701
C-447-83-0	211,260	10	0.338	714.1	260,631
C-447-84-0	211,748	10	0.338	715.7	261,234
C-447-85-0	211,712	10	0.338	715.6	261,189
C-447-86-0	211,422	10	0.338	714.6	260,831
C-447-87-0	211,573	10	0.338	715.1	261,018
C-447-88-0	211,633	10	0.338	715.3	261,092
C-447-89-0	211,487	10	0.338	714.8	260,912
C-447-90-0	211,378	10	0.338	714.5	260,777
C-447-91-0	211,658	10	0.338	715.4	261,122
C-447-92-0	211,732	10	0.338	715.7	261,214
C-447-93-0	211,788	10	0.338	715.8	261,283
C-447-94-0	211,189	10	0.338	713.8	260,544
C-447-95-0	211,962	10	0.338	716.4	261,498
C-447-117-0	329,824	10	0.338	1114.8	406,904
C-447-118-0	329,868	10	0.338	1115.0	406,958
C-447-119-0	642,674	10	0.338	2172.2	792,867
C-447-120-0	642,066	10	0.338	2170.2	792,117
C-447-121-0	642,494	10	0.338	2171.6	792,645
C-447-122-0	643,303	10	0.338	2174.4	793,643
C-447-123-0	643,934	10	0.338	2176.5	794,421
C-447-124-0	642,604	10	0.338	2172.0	792,781
C-447-125-0	642,738	10	0.338	2172.5	792,946
C-447-126-0	643,964	10	0.338	2176.6	794,458
C-447-127-0	641,070	10	0.338	2166.8	790,888
C-447-128-0	641,248	10	0.338	2167.4	791,108

C-447-129-0	641,965	10	0.338	2169.8	791,992
C-447-130-0	641,756	10	0.338	2169.1	791,734
C-447-131-0	642,656	10	0.338	2172.2	792,845
C-447-132-0	640,805	10	0.338	2165.9	790,561
C-447-133-0	641,489	10	0.338	2168.2	791,405
C-447-134-0	641,896	10	0.338	2169.6	791,907
C-447-135-0	643,208	10	0.338	2174.0	793,526
C-447-136-0	643,378	10	0.338	2174.6	793,735
C-447-137-0	643,676	10	0.338	2175.6	794,103
C-447-138-0	642,762	10	0.338	2172.5	792,975
C-447-139-0	642,796	10	0.338	2172.7	793,017
C-447-140-0	644,594	10	0.338	2178.7	795,236
C-447-141-0	642,126	10	0.338	2170.4	792,191
C-447-142-0	642,874	10	0.338	2172.9	793,114
C-447-143-0	643,803	10	0.338	2176.1	794,260
C-447-144-0	641,307	10	0.338	2167.6	791,180
C-447-145-0	643,509	10	0.338	2175.1	793,897
C-447-146-0	643,199	10	0.338	2174.0	793,515
C-447-147-0	644,851	10	0.338	2179.6	795,553
C-447-148-0	642,555	10	0.338	2171.8	792,720
C-447-149-0	642,690	10	0.338	2172.3	792,887
C-447-150-0	642,940	10	0.338	2173.1	793,195
C-447-151-0	644,141	10	0.338	2177.2	794,677
C-447-152-0	643,365	10	0.338	2174.6	793,719
C-447-153-0	642,506	10	0.338	2171.7	792,660
C-447-154-0	643,192	10	0.338	2174.0	793,506
C-447-155-0	643,544	10	0.338	2175.2	793,940
C-447-156-0	642,863	10	0.338	2172.9	793,100
C-447-157-0	645,153	10	0.338	2180.6	795,925
C-447-158-0	643,864	10	0.338	2176.3	794,335
C-447-159-0	642,374	10	0.338	2171.2	792,497
C-447-160-0	641,400	10	0.338	2167.9	791,295

C-447-161-0	642,257	10	0.338	2170.8	792,352
C-447-162-0	643,277	10	0.338	2174.3	793,611
C-447-163-0	641,867	10	0.338	2169.5	791,871
C-447-164-0	642,338	10	0.338	2171.1	792,452
C-447-165-0	641,222	10	0.338	2167.3	791,076
C-447-166-0	641,763	10	0.338	2169.2	791,743
C-447-167-0	642,501	10	0.338	2171.7	792,653
C-447-168-0	642,658	10	0.338	2172.2	792,847
C-447-169-0	643,620	10	0.338	2175.4	794,034
C-447-170-0	642,526	10	0.338	2171.7	792,684
C-447-171-0	643,178	10	0.338	2173.9	793,489
C-447-172-0	642,090	10	0.338	2170.3	792,146
C-447-173-0	642,542	10	0.338	2171.8	792,704
C-447-174-0	642,788	10	0.338	2172.6	793,008
C-447-175-0	640,725	10	0.338	2165.7	790,462
C-447-176-0	643,118	10	0.338	2173.7	793,415
C-447-177-0	640,772	10	0.338	2165.8	790,520
C-447-178-0	643,295	10	0.338	2174.3	793,633
C-447-179-0	642,491	10	0.338	2171.6	792,641
C-447-180-0	643,051	10	0.338	2173.5	793,332
C-447-181-0	642,451	10	0.338	2171.5	792,592
C-447-182-0	642,094	10	0.338	2170.3	792,151
C-447-183-0	642,344	10	0.338	2171.1	792,460
C-447-184-0	642,245	10	0.338	2170.8	792,338
C-447-185-0	643,156	10	0.338	2173.9	793,462
C-447-186-0	641,595	10	0.338	2168.6	791,536
C-447-187-0	642,871	10	0.338	2172.9	793,110
C-447-188-0	639,880	10	0.338	2162.8	789,420
C-447-189-0	641,428	10	0.338	2168.0	791,330
C-447-190-0	642,193	10	0.338	2170.6	792,274
C-447-191-0	642,592	10	0.338	2172.0	792,766
C-447-192-0	643,295	10	0.338	2174.3	793,633

C-447-193-0	640,961	10	0.338	2166.4	790,754
C-447-194-0	640,434	10	0.338	2164.7	790,103
C-447-195-0	642,594	10	0.338	2172.0	792,768
C-447-196-0	641,115	10	0.338	2167.0	790,944
C-447-197-0	641,345	10	0.338	2167.7	791,227
C-447-198-0	641,629	10	0.338	2168.7	791,578
C-447-199-0	640,936	10	0.338	2166.4	790,723
C-447-200-0	642,121	10	0.338	2170.4	792,185
C-447-201-0	641,719	10	0.338	2169.0	791,689
C-447-202-0	642,050	10	0.338	2170.1	792,097
C-447-203-0	640,612	10	0.338	2165.3	790,323
C-447-204-0	642,491	10	0.338	2171.6	792,641
C-447-205-0	642,974	10	0.338	2173.3	793,237
C-447-206-0	642,792	10	0.338	2172.6	793,012
C-447-207-0	640,729	10	0.338	2165.7	790,467
C-447-208-0	641,378	10	0.338	2167.9	791,268
C-447-209-0	641,008	10	0.338	2166.6	790,812
C-447-210-0	639,975	10	0.338	2163.1	789,537
C-447-211-0	640,530	10	0.338	2165.0	790,222
C-447-212-0	640,872	10	0.338	2166.1	790,644
C-447-213-0	641,462	10	0.338	2168.1	791,372
C-447-214-0	641,262	10	0.338	2167.5	791,125
Total					90,855,099

Fermentation (C-447-96 through '116)

Either red or white wine, the fermentation process takes longer than a day (3 to 5 days for red wine and 10 to 14 days for white wine). Therefore, maximum one turnover per day will be used to determine the potential daily emissions.

The potential daily and annual VOC emissions are determined using the red wine emissions factor, tank capacity, turnover rate, and the annual throughput as follows:

$$\begin{aligned} \text{Daily PE1} &= EF_{\text{red}} (\text{lb-VOC}/1,000 \text{ gal}) \times \text{tank capacity} (\text{gal}/\text{tank}) \times \text{turnover rate} (\text{tank}/\text{day}) \\ \text{Annual PE1} &= EF_{\text{red}} (\text{lb-VOC}/1,000 \text{ gal}) \times \text{tank capacity} (\text{gal}/\text{tank}) \times \\ &\quad \text{turnover rate} (\text{tank}/\text{day}) \times 365 \text{ days}/\text{year} \end{aligned}$$

Permit Unit	Daily EF	Annual EF	Tank Capacity	Turnover Rate	Daily	Annual
	(lb-VOC/1,000 gal)		(gallon)	(tank/day)	(lb/day)	(lb/yr)
C-447-96-1	3.46	6.2	207,390	10	7175.7	4,693,236
C-447-97-1			207,909		7193.7	4,704,981
C-447-98-1			207,676		7185.6	4,699,708
C-447-99-1			208,185		7203.2	4,711,227
C-447-100-1			207,571		7182.0	4,697,332
C-447-101-1			208,168		7202.6	4,710,842
C-447-102-1			207,821		7190.6	4,702,989
C-447-103-1			207,140		7167.0	4,687,578
C-447-104-1			206,695		7151.6	4,677,508
C-447-105-1			207,451		7177.8	4,694,616
C-447-106-1			206,832		7156.4	4,680,608
C-447-107-1			207,270		7171.5	4,690,520
C-447-108-1			208,117		7200.8	4,709,688
C-447-109-1			208,202		7203.8	4,711,611
C-447-110-1			206,996		7162.1	4,684,319
C-447-111-1			207,039		7163.5	4,685,293
C-447-112-1			206,757		7153.8	4,678,911
C-447-113-1			207,752		7188.2	4,701,428
C-447-114-1	207,369	7175.0	4,692,760			
C-447-115-1	208,795	7224.3	4,725,031			
C-447-116-1	208,928	7228.9	4,728,041			

2. Post Project Potential to Emit (PE2)

There is no change proposed in the throughput values. The installation of a PV valve would result in a decrease in emissions. However, this reduction does not need to be calculated and therefore, PE2 = PE1.

3. Pre-Project Stationary Source Potential to Emit (SSPE1)

Pursuant to Section 4.9 of District Rule 2201, the Pre-Project Stationary Source Potential to Emit (SSPE1) is the Potential to Emit (PE) from all units with valid Authorities to Construct (ATC) or Permits to Operate (PTO) at the Stationary Source and the quantity of emission reduction credits (ERC) which have been banked since September 19, 1991 for Actual Emissions Reductions that have occurred at the source, and which have not been used on-site.

This project only concerns VOC emissions. This facility acknowledges that its VOC emissions are already above the Offset and Major Source Thresholds for VOC emissions; therefore, SSPE1 calculations are not necessary.

4. Post Project Stationary Source Potential to Emit (SSPE2)

Pursuant to Section 4.10 of District Rule 2201, the Post Project Stationary Source Potential to Emit (SSPE2) is the Potential to Emit (PE) from all units with valid Authorities to Construct (ATC) or Permits to Operate (PTO) at the Stationary Source and the quantity of emission reduction credits (ERC) which have been banked since September 19, 1991 for Actual Emissions Reductions that have occurred at the source, and which have not been used on-site.

There is no proposed change in throughput or emissions in this project. Therefore, SSPE2 = SSPE1.

5. Major Source Determination

Pursuant to Section 3.24 of District Rule 2201, a Major Source is a stationary source with post-project emissions or a Post Project Stationary Source Potential to Emit (SSPE2), equal to or exceeding one or more of the following threshold values. However, Section 3.24.2 states, "for the purposes of determining major source status, the SSPE2 shall not include the quantity of emission reduction credits (ERC) which have been banked since September 19, 1991 for Actual Emissions Reductions that have occurred at the source, and which have not been used on-site."

This source is an existing Major Source for VOC emissions and will remain a Major Source for VOC. No change in other pollutants are proposed or expected as a result of this project.

6. Baseline Emissions (BE)

BE = Pre-project Potential to Emit for:

- Any unit located at a non-Major Source,
- Any Highly-Utilized Emissions Unit, located at a Major Source,
- Any Fully-Offset Emissions Unit, located at a Major Source, or
- Any Clean Emissions Unit, located at a Major Source.

otherwise,

BE = Historic Actual Emissions (HAE), calculated pursuant to Section 3.22

The BE calculation (in lb/year) is performed on a pollutant-by-pollutant basis to determine the amount of offsets required, where necessary, when the SSPE1 is greater than the offset threshold. This project is exempt from offsets pursuant to Rule 2201, Section 4.6.8. Therefore, BE calculations are not required.

7. Major Modification

Major Modification is defined in 40 CFR Part 51.165 as "*any physical change in or change in the method of operation of a major stationary source that would result in a significant net emissions increase of any pollutant subject to regulation under the Act.*"

As discussed in Section VII.C.5 above, the facility is an existing Major Source for VOC; however, the project by itself would need to be a significant increase in order to trigger a Major Modification. The emission units within this project do have a total potential to emit which is greater than Major Modification thresholds (see table below).

Major Modification Thresholds (Existing Major Source)			
Pollutant	Project PE (lb/year)	Threshold (lb/year)	Major Modification?
VOC	90,855,099	50,000	Yes

The applicant has stipulated this project is a Major Modification for VOC. Therefore, this project does constitute a Major Modification for VOC.

8. Federal Major Modification

District Rule 2201, Section 3.17 states that Federal Major Modifications are the same as "Major Modification" as defined in 40 CFR 51.165 and part D of Title I of the CAA.

The determination of Federal Major Modification is based on a two-step test. For the first step, only the emission *increases* are counted. Emission decreases may not cancel out the increases for this determination.

Step 1

For existing emissions units, the increase in emissions is calculated as follows.

$$\text{Emission Increase} = \text{PAE} - \text{BAE} - \text{UBC}$$

Where: PAE = Projected Actual Emissions, and
BAE = Baseline Actual Emissions
UBC = Unused baseline capacity

If there is no increase in design capacity or potential to emit, the PAE is equal to the annual emission rate at which the unit is projected to emit in any one year, selected by the operator, within 5 years after the unit resumes normal operation (10 years for existing units with an increase in design capacity or potential to emit). If detailed PAE are not provided, the PAE is equal to the PE2 for each permit unit.

The BAE is calculated based on historical emissions and operating records for any 24 month period, selected by the operator, within the previous 10 year period (5 years for

electric utility steam generating units). The BAE must be adjusted to exclude any non-compliant operation emissions and emissions that are no longer allowed due to lower applicable emission limits that were in effect when this application was deemed complete.

UBC: Since this project does not result in an increase in design capacity or potential to emit, and it does not impact the ability of the emission unit to operate at a higher utilization rate, the UBC is the portion of PAE that the emission units could have accommodated during the baseline period.

$$\text{Emission Increase} = \text{PAE} - \text{BAE} - \text{UBC} = 0$$

As demonstrated above, this project does not constitute a Federal Major Modification.

VIII. Compliance

Rule 2201 New and Modified Stationary Source Review Rule

A. Best Available Control Technology (BACT)

1. BACT Applicability

BACT requirements are triggered on a pollutant-by-pollutant basis and on an emissions unit-by-emissions unit basis for the following*:

- a. Any new emissions unit with a potential to emit exceeding two pounds per day,
- b. The relocation from one Stationary Source to another of an existing emissions unit with a potential to emit exceeding two pounds per day,
- c. Modifications to an existing emissions unit with a valid Permit to Operate resulting in an AIPE exceeding two pounds per day, and/or
- d. Any new or modified emissions unit, in a stationary source project, which results in a Major Modification.

*Except for CO emissions from a new or modified emissions unit at a Stationary Source with an SSPE2 of less than 200,000 pounds per year of CO.

However, BACT shall not be required for the following:

4.2.3 For existing facilities, the installation or modification of an emission control technique performed solely for the purpose of compliance with the requirements of District, State or Federal air pollution control laws, regulations, or orders, as approved by the APCO, shall be exempt from Best Available Control Technology for all air pollutants, provided all of the following conditions are met:

- 4.2.3.1 There shall be no increase in the physical or operational design of the existing facility, except for those changes to the design needed for the installation or modification of the emission control technique itself;
- 4.2.3.2 There shall be no increase in the permitted rating or permitted operating schedule of the permitted unit;

- 4.2.3.3 There shall be no increase in emissions from the stationary source that will cause or contribute to any violation of a National Ambient Air Quality Standard, Prevention of Significant Deterioration increment, or Air Quality Related Value in Class I areas; and
- 4.2.3.4 The project shall not result in an increase in permitted emissions or potential to emit of more than 25 tons per year of NO_x, or 25 tons per year of VOC, or 15 tons per year of SO_x, or 15 tons per year of PM₁₀, or 50 tons per year of CO.
- 4.2.3.5 The project shall not constitute a federal major modification.

Since each of the above-listed criteria are met, BACT is not triggered for any pollutant.

2. BACT Guideline

Since BACT is not triggered, the proposed operation is not subject to any BACT guideline. No further discussion is required.

3. Top-Down BACT Analysis

Since BACT is not triggered, the proposed operation is not subject to a top-down BACT analysis. No further discussion is required.

B. Offsets

1. Offset Applicability

The proposed modifications are solely for compliance with Rule 4306, and are exempt from offsets if the following criteria are satisfied. Rule 2201, Section 4.6.8 provides the following exemption from offsets.

Emission offsets shall not be required for the following:

- 4.6.8 For existing facilities, the installation or modification of an emission control technique performed solely for the purpose of compliance with the requirements of District, State or Federal air pollution control laws, regulations, or orders, as approved by the APCO, shall be exempt from offset requirements for all air pollutants provided all of the following conditions are met:
 - 4.6.8.1 There shall be no increase in the physical or operational design of the existing facility, except for those changes to the design needed for the installation or modification of the emission control technique itself;
 - 4.6.8.2 There shall be no increase in the permitted rating or permitted operating schedule of the permitted unit;
 - 4.6.8.3 There shall be no increase in emissions from the stationary source that will cause or contribute to any violation of a National Ambient Air Quality Standard, Prevention of Significant Deterioration increment, or Air Quality Related Value in Class I areas; and

4.6.8.4 The project shall not result in an increase in permitted emissions or potential to emit of more than 25 tons per year of NO_x, or 25 tons per year of VOC, or 15 tons per year of SO_x, or 15 tons per year of PM-10, or 50 tons per year of CO.

Since the above-listed criteria are met, offsets are not triggered for any pollutant.

2. Quantity of Offsets Required

As seen above, the project meets the exemption requirements of section 4.6.8 of District Rule 2201; therefore offset calculations are not necessary and offsets are not required for this project.

C. Public Notification

1. Applicability

Public noticing is required for:

- a. Any new Major Source, which is a new facility that is also a Major Source,
- b. Major Modifications,
- c. Any new emissions unit with a Potential to Emit greater than 100 pounds during any one day for any one pollutant,
- d. Any project which results in the offset thresholds being surpassed, and/or
- e. Any project with an SSPE of greater than 20,000 lb/year for any pollutant.

a. New Major Source

New Major Sources are new facilities, which are also Major Sources. Since this is not a new facility, public noticing is not required for this project for New Major Source purposes.

b. Major Modification

As demonstrated in VII.C.7, this project does constitute a Major Modification; therefore, public noticing for Major Modification purposes is required.

c. PE > 100 lb/day

Applications which include a new emissions unit with a Potential to Emit greater than 100 pounds during any one day for any pollutant will trigger public noticing requirements. As seen in Section VII.C.2 above, this project does not include a new emissions unit which has daily emissions greater than 100 lb/day for any pollutant, therefore public noticing for PE > 100 lb/day purposes is not required.

d. Offset Threshold

The following table compares the SSPE1 with the SSPE2 in order to determine if any offset thresholds have been surpassed with this project.

Offset Threshold				
Pollutant	SSPE1 (lb/year)	SSPE2 (lb/year)	Offset Threshold	Public Notice Required?
VOC	> 20,000	> 20,000	20,000 lb/year	No

As detailed above, there were no thresholds surpassed with this project; therefore public noticing is not required for offset purposes.

e. SSIPE > 20,000 lb/year

Public notification is required for any permitting action that results in a Stationary Source Increase in Permitted Emissions (SSIPE) of more than 20,000 lb/year of any affected pollutant. According to District policy, the SSIPE is calculated as the Post Project Stationary Source Potential to Emit (SSPE2) minus the Pre-Project Stationary Source Potential to Emit (SSPE1), i.e. $SSIPE = SSPE2 - SSPE1$. The values for SSPE2 and SSPE1 are calculated according to Rule 2201, Sections 4.9 and 4.10, respectively. The SSIPE is compared to the SSIPE Public Notice thresholds in the following table:

Stationary Source Increase in Permitted Emissions [SSIPE] – Public Notice					
Pollutant	Σ PE2 (lb/year)	Σ PE1 (lb/year)	SSIPE (lb/year)	SSIPE Public Notice Threshold	Public Notice Required?
VOC	90,855,099	90,855,099	0	20,000 lb/year	No

As demonstrated above, the SSIPEs for all pollutants were less than 20,000 lb/year; therefore public noticing for SSIPE purposes is not required.

2. Public Notice Action

As discussed above, public noticing is required for this project for Major Modification for VOC. Therefore, public notice documents will be submitted to the California Air Resources Board (CARB) and a public notice will be published in a local newspaper of general circulation prior to the issuance of the ATCs for this equipment.

D. Daily Emission Limits (DELs)

Daily Emissions Limitations (DELs) and other enforceable conditions are required by Section 3.15 to restrict a unit's maximum daily emissions, to a level at or below the emissions associated with the maximum design capacity. Per Sections 3.15.1 and 3.15.2, the DEL must be contained in the latest ATC and contained in or enforced by the latest PTO and enforceable, in a practicable manner, on a daily basis. DELs are also required to enforce the applicability of BACT.

For these wine storage tanks, the tank capacity inherently establishes the daily emission limit for each tank.

E. Compliance Assurance

1. Source Testing

Pursuant to District Policy APR 1705, source testing is not required to demonstrate compliance with Rule 2201.

2. Monitoring

No monitoring is required to demonstrate compliance with Rule 2201.

3. Recordkeeping

Recordkeeping is required to demonstrate compliance with the offset, public notification and daily emission limit requirements of Rule 2201. The following condition(s) will appear on the permits to operate:

- All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]

4. Reporting

No reporting is required to demonstrate compliance with Rule 2201.

F. Ambient Air Quality Analysis

Section 4.14.1 of this Rule requires that an ambient air quality analysis (AAQA) be conducted for the purpose of determining whether a new or modified Stationary Source will cause or make worse a violation of an air quality standard. However, since this project involves only VOC and no ambient air quality standard exists for VOC, an AAQA is not required for this project.

Rule 2520 Federally Mandated Operating Permits

This facility is subject to this Rule, and has received their Title V Operating Permit. The proposed modification is a Minor Modification to the Title V Permit pursuant to Section 3.20 of this rule:

In accordance with Rule 2520, 3.20, these modifications:

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;

4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include:
 - a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
 - b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

As discussed above, the facility has not applied for a Certificate of Conformity (COC); therefore, the facility must apply to modify their Title V permit with a minor modification, prior to operating with the proposed modifications. The ATCs in this project will be implemented under the current Title V renewal project C-1060098. Continued compliance with this rule is expected.

Rule 4001 New Source Performance Standards (4/14/99)

40 CFR 60, Subpart KB, Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) For Which Construction Commenced After July 23, 1984, applies to each storage vessel with a capacity greater than or equal to 75 cubic meters that is used to store volatile organic liquids for which construction, reconstruction, or modification is commenced after July 23, 1984. However, Section 60.110b(7) of Subpart KB states that vessels used to store beverage alcohol are exempt from the requirements of Subpart Kb. There are no other applicable requirements of Rule 4001.

Rule 4002 National Emission Standards for Hazardous Air Pollutants

This rule incorporates NESHAPs from Part 61, Chapter I, Subchapter C, Title 40, CFR and the NESHAPs from Part 63, Chapter I, Subchapter C, Title 40, CFR; and applies to all sources of hazardous air pollution listed in 40 CFR Part 61 or 40 CFR Part 63. However, no subparts of 40 CFR Part 61 or 40 CFR Part 63 apply to wine fermentation and storage operations.

Rule 4102 Nuisance

Rule 4102 states that no air contaminant shall be released into the atmosphere which causes a public nuisance. Public nuisance conditions are not expected as a result of these operations, provided the equipment is well maintained. Therefore, the following condition will be listed on each ATC to ensure compliance:

- {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

California Health & Safety Code 41700 (Health Risk Assessment)

District Policy APR 1905 – Risk Management Policy for Permitting New and Modified Sources specifies that for an increase in emissions associated with a proposed new source or modification, the District perform an analysis to determine the possible impact to the nearest resident or worksite.

As demonstrated above, there are no increases in emissions associated with this project, therefore a health risk assessment is not necessary and no further risk analysis is required.

Rule 4623 Storage of Organic Liquids

The purpose of this rule is to limit volatile organic compound (VOC) emissions from the storage of organic liquids and the rule applies to any tank with a capacity of 1,100 gallons or greater in which any organic liquid is placed, held, or stored. However, pursuant to Section 4.1.4, the rule specifically exempts tanks used in wine fermentation and for storage of resulting products, byproducts, and spirits. Therefore, the provisions of this rule do not apply to this project.

Rule 4694 Fermentation and Wine Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. This rule is applicable to all facilities with fermentation emissions in excess of 10 tons-VOC/year. The storage tank provisions of this rule apply to all tanks with capacity in excess of 5,000 gallons.

Section 5.1 requires the winery operator achieve Required Annual Emissions Reductions (RAER) equal to at least 35% of the winery's Baseline Fermentation Emissions (BFE). Per the definition of RAER in Section 3.25 of the Rule, the RAER may be achieved by any combination of Fermentation Emission Reductions (FER), Certified Emission Reductions (CER) or District Obtained Emission Reductions (DOER) as established in the facility's District-approved Rule 4694 Compliance Plan, due every three years on December 1st beginning in 2006. The facility has submitted the required plan to the District and is currently satisfying the required emission reductions in the form of Certified Emission Reductions.

The following condition on the facility-wide permit ensures compliance:

- This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]

Section 5.2 places specific restrictions on wine storage tanks with 5,000 gallons or more in capacity when such tanks are not constructed of wood or concrete. Section 5.2.1 requires these tanks to be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:

- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
- The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and
- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.

The following conditions will be placed on the permits for stainless steel tanks \geq 5,000 gallons in capacity to ensure compliance with the requirements of Section 5.2.1:

- This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694]
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]

Section 5.2.2 requires that the temperature of the stored wine be maintained at or below 75° F.

The following condition will be placed on the permits for stainless steel tanks \geq 5,000 gallons in capacity to ensure compliance with the requirements of Section 5.2.2:

- The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]

Every three years, Section 6.1 and 6.2 require the facility to submit a Three-Year Compliance Plan and a Three-Year Compliance Plan Verification respectively. Section 6.3 requires that an Annual Compliance Plan Demonstration be submitted to the District no later than February 1 of each year to show compliance with the applicable requirements of the Rule. Section 6.4.3 requires that all monitoring be performed for any Certified Emission Reductions as identified in the facility's Three-Year Compliance Plan and that the records of all monitoring be maintained.

The following conditions on the facility-wide permit ensure compliance:

- By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]
- By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]
- By February 1, 2008, and every year thereafter, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]
- Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

Section 6.4.1 requires that records be kept for each fermentation batch. The following condition will be placed on the ATC for each fermentation tank to ensure compliance:

- For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]

Section 6.4.2 requires that weekly records be kept of wine volume and temperature in each storage tank. The following conditions will be placed on the permit for each storage tank to ensure compliance with the requirements of Section 6.4.2:

- The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

Section 6.4.3 requires that all monitoring be performed for any Certified Emission Reductions as identified in the facility's Three-Year Compliance Plan and that the records of all monitoring be maintained. The following condition on the facility-wide permit ensures compliance:

- Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

Section 6.4 requires that records required by this rule be maintained, retained on-site for a minimum of five years, and made available to the APCO upon request. The following conditions will be placed on all permits to ensure compliance:

- All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694]

California Health & Safety Code 42301.6 (School Notice)

The District has verified that this site is located within 1,000 feet of a school. However, pursuant to California Health and Safety Code 42301.6, since this project will not result in an increase in emissions, a school notice is not required.

California Environmental Quality Act (CEQA)

The California Environmental Quality Act (CEQA) requires each public agency to adopt objectives, criteria, and specific procedures consistent with CEQA Statutes and the CEQA Guidelines for administering its responsibilities under CEQA, including the orderly evaluation of projects and preparation of environmental documents. The San Joaquin Valley Unified Air Pollution Control District (District) adopted its *Environmental Review Guidelines* (ERG) in 2001. The basic purposes of CEQA are to:

- Inform governmental decision-makers and the public about the potential, significant environmental effects of proposed activities;
- Identify the ways that environmental damage can be avoided or significantly reduced;
- Prevent significant, avoidable damage to the environment by requiring changes in projects through the use of alternatives or mitigation measures when the governmental agency finds the changes to be feasible; and
- Disclose to the public the reasons why a governmental agency approved the project in the manner the agency chose if significant environmental effects are involved.

The District performed an Engineering Evaluation (this document) for the proposed project and determined that all project specific emission unit(s) are exempt from Best Available Control Technology (BACT) requirements.

Issuance of permits for emissions units not subject to BACT requirements and with health impact less than significant is a matter of ensuring conformity with applicable District rules and regulations and does not require discretionary judgment or deliberation. Thus, the District concludes that this permitting action constitutes a ministerial approval. Section 21080 of the Public Resources Code exempts from the application of CEQA those projects over which a public agency exercises only ministerial approval. Therefore, the District finds that this project is exempt from the provisions of CEQA.

IX. Recommendation

Compliance with all applicable rules and regulations is expected. Pending a successful NSR Public Noticing period, issue Authorities to Construct C-447-27-1 through 214-1 subject to the permit conditions on the attached draft Authorities to Construct in Attachment A.

X. Billing Information

Annual Permit Fees			
Permit Number	Fee Description	Fee Schedule	Annual Fee
C-447-27-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-28-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-29-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-30-1	50,000 or Greater but Less Than 100,000	3020-05-D	\$185.00
C-447-31-1	50,000 or Greater but Less Than 100,000	3020-05-D	\$185.00
C-447-32-1	50,000 or Greater but Less Than 100,000	3020-05-D	\$185.00
C-447-33-1	50,000 or Greater but Less Than 100,000	3020-05-D	\$185.00
C-447-34-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-35-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-36-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-37-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-38-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-39-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-40-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-41-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-42-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-43-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-44-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-45-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-46-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-47-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-48-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-49-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-50-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-51-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-52-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-53-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-54-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-55-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-56-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-57-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-58-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-59-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-60-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-61-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00
C-447-62-1	100,000 or Greater but Less Than 500,000	3020-05-E	\$246.00

C-447-204-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-205-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-206-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-207-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-208-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-209-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-210-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-211-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-212-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-213-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00
C-447-214-1	500,000 or Greater but Less Than 1,000,000	3020-05-F	\$301.00

Attachments

A: Draft ATCs

Attachment A
Draft ATCs

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-27-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-27-1 : Oct 25 2011 11:46AM - TOMS : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-28-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-28-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-29-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-29-1 : Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-30-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 509. INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-30-1 : Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-31-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-31-1 : Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-32-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-32-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-33-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-33-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-34-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-34-1: Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-35-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-35-1: Oct 27 2011 1:44PM - BROWN - Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-36-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-36-1: Oct 27 2011 1:44PM - BROWNND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-37-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-37-1: Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-38-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-38-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-39-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-39-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-40-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-40-1: Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-41-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-41-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-42-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT
DAVID WARNER, Director of Permit Services

C-447-42-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-43-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-43-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-44-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-44-1 : Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-45-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-45-1; Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-46-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-46-1: Oct 27 2011 1:44PM - BROWN - Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-47-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director YAPCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-47-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-48-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT
DAVID WARNER, Director of Permit Services

C-447-48-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-49-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-49-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-50-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-50-1 - Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-51-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-51-1: Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-52-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-52-1 : Oct 27 2011 1:44PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-53-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-53-1 : Oct 27 2011 1:44PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-54-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-54-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-55-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-447-55-1: Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-56-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-56-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-57-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-57-1: Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-58-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-58-1 : Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-59-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-59-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-60-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-60-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-61-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-61-1 - Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-62-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-62-1: Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-63-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-63-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-64-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-64-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-65-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2010: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-65-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-66-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2011: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-66-1 : Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-67-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-67-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-68-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-68-1 - Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: G-447-69-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-69-1 : Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-70-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-70-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-71-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-71-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-72-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-72-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-73-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-73-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-74-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-74-1 : Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-75-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-75-1; Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-76-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-76-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-77-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-77-1; Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-78-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-78-1: Oct 27 2011 1:45PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-79-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-79-1: Oct 27 2011 1:45PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-80-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-80-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-81-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-81-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-82-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-82-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-83-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-83-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-84-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-84-1 : Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-85-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-85-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-86-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-86-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-87-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-87-1; Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-88-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-88-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-89-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-89-1 : Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-90-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-90-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-91-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-91-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-92-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-92-1 : Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-93-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-93-1: Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-94-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-94-1: Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-95-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-95-1 - Oct 27 2011 1:46PM - BROWND - Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-96-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,390 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2922: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-96-1: Oct 27 2011 1:46PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-97-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,909 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2923: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-97-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-98-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,676 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2924: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-98-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-99-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,185 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2925: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-99-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-100-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,571 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2926: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-100-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-101-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,168 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2927: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-101-1 : Oct 27 2011 1:46PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-102-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,821 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2928: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-102-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-103-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,140 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2929: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-103-1: Oct 27 2011 1:46PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-104-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 206,695 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2930: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-104-1; Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-105-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,451 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2931: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-105-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-106-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 206,832 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2932: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-106-1 : Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-107-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,270 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2933: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-107-1 : Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-108-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE

FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,117 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2934: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-108-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-109-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,202 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2935: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-109-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-110-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 206,996 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2936: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-110-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-111-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,039 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2937: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-111-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-112-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 206,757 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2938: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-112-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-113-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,752 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2939: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-113-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-114-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 207,369 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2940: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-114-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-115-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,795 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2941: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-115-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-116-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 208,928 GALLON STEEL ENCLOSED TOP RED WINE FERMENTATION TANK 2942: REVISE EQUIPMENT DESCRIPTION AS A RED AND WHITE WINE FERMENTATION TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-116-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-117-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-117-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-118-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-118-1 : Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-119-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-119-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-120-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-120-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-121-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-121-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-122-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-122-1 : Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-123-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-123-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-124-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-124-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-125-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-125-1 : Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-126-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-126-1, Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-127-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-127-1 : Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-128-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-128-1: Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-129-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-129-1 : Oct 27 2011 1:47PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-130-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-130-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-131-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE

FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-131-1: Oct 27 2011 1:47PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-132-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-132-1; Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-133-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-133-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-134-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-134-1, Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-135-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-135-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-136-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-136-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-137-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-137-1: Oct 27, 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-138-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-138-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-139-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-139-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-140-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-140-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-141-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-141-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-142-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-142-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-143-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-143-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-144-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-144-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-145-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-145-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-146-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-146-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-147-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE

FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-147-1 : Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-148-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-148-1; Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-149-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-149-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-150-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-150-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-151-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-151-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-152-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-152-1 : Oct 27 2011 1:48PM -- BROWN0 : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-153-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-153-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-154-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-154-1; Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-155-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-155-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-156-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-156-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-157-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-157-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-158-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-158-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-159-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE

FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,374 GALLON STEEL WINE STORAGE TANK 6053: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-159-1: Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-160-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,400 GALLON STEEL WINE STORAGE TANK 6054: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-160-1 - Oct 27 2011 1:49PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-161-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,257 GALLON STEEL WINE STORAGE TANK 6055: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-161-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-162-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,277 GALLON STEEL WINE STORAGE TANK 6056: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE AND REVISE EQUIPMENT DESCRIPTION AS A FERMENTATION AND STORAGE TANK

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-162-1 : Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-163-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE

FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-163-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-164-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-164-1 : Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-165-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-165-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-166-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-166-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-167-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-167-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-168-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-168-1 : Oct 27 2011 1:49PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-169-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-169-1 : Oct 27 2011 1:49PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-170-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-170-1: Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-171-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-171-1, Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-172-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-172-1 : Oct 27 2011 1:49PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-173-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-173-1: Oct 27 2011 1:49PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-174-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-174-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-175-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-175-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-176-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-176-1: Oct 27 2011 1:48PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-177-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-177-1 : Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-178-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-178-1: Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-179-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-179-1: Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-180-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-180-1 : Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-181-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694; 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-181-1 : Oct 27 2011 1:49PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-182-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-182-1 - Oct 27 2011 1:49PM - BROWN - Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-183-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-183-1: Oct 27 2011 1:48PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-184-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-184-1: Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-185-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-185-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-186-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-186-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-187-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-187-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-188-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-447-188-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-189-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-189-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-190-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-190-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-191-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-191-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-192-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-192-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-193-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-193-1; Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-194-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-194-1: Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-195-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-195-1; Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-196-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-196-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-197-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-197-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-198-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-198-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-199-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-199-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-200-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-200-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-201-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 641,719 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-201-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-202-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,050 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-202-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-203-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-203-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-204-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-204-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-205-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:
MODIFICATION OF A 642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-205-1 : Oct 27 2011 1:50PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-206-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-206-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

**San Joaquin Valley
Air Pollution Control District**

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-207-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-207-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-208-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6850 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-208-1 : Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-209-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6635: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-447-209-1: Oct 27 2011 1:50PM -- BROWND : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-447-210-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6636: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-447-210-1 : Oct 27 2011 1:51PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-211-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6637: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-211-1: Oct 27 2011 1:51PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-212-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6638: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-212-1: Oct 27 2011 1:51PM -- BROWND : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: C-447-213-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6639: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-447-213-1: Oct 27 2011 1:51PM -- BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-447-214-1

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY

MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

EQUIPMENT DESCRIPTION:

MODIFICATION OF A 641,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6640: INSTALL A PV VALVE FOR RULE 4694 COMPLIANCE

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-447-214-1 : Oct 27 2011 1:51PM - BROWND : Joint Inspection NOT Required

6. When used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
7. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
8. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT