



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

SEP 20 2012-

Charlie Comfort
TRC Operating Company, Inc
P O Box 227
Taft, CA 93268

Re: Notice of Final Action - Title V Permit
District Facility # S-3088
Project # 1110983

Dear Mr. Comfort:

The District has issued the Final Title V Permit for TRC Operating Company, Inc. The preliminary decision for this project was made on 7/11/12. No comments were received subsequent to the District preliminary decision. Enclosed are the Final Title V Permit and public notice to be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. Should you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

A handwritten signature in black ink, appearing to read "D. Warner", with a long horizontal flourish extending to the right.

David Warner
Director of Permit Services

Attachments

cc: David Torii, Permit Services Engineer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061
www.valleyair.org

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

SEP 20 2012

Gerardo C. Rios, Chief
Permits Office (AIR-3)
U.S. EPA - Region IX
75 Hawthorne St
San Francisco, CA 94105

Re: Notice of Final Action - Title V Permit
District Facility # S-3088
Project # 1110983

Dear Mr. Rios:

The District has issued the Final Title V Permit for TRC Operating Company, Inc. The preliminary decision for this project was made on 7/11/12. No comments were received subsequent to the District preliminary decision. Enclosed are the Final Title V Permit and public notice to be published approximately three days from the date of this letter.

I would like to thank you and your staff for working with us. We appreciate your concurrence with this action. Should you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

A handwritten signature in black ink, appearing to read "D. Warner", with a long horizontal flourish extending to the right.

David Warner
Director of Permit Services

Attachments

cc: David Torii, Permit Services Engineer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061
www.valleyair.org

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

SEP 20 2012

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

**Re: Notice of Final Action - Title V Permit
District Facility # S-3088
Project # 1110983**

Dear Mr. Tollstrup:

The District has issued the Final Title V Permit for TRC Operating Company, Inc. The preliminary decision for this project was made on 7/11/12. No comments were received subsequent to the District preliminary decision. Enclosed are the Final Title V Permit and public notice to be published approximately three days from the date of this letter.

I would like to thank you and your staff for working with us. Should you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

A handwritten signature in black ink, appearing to read "D. Warner", with a long horizontal flourish extending to the right.

David Warner
Director of Permit Services

Attachments

cc: David Torii, Permit Services Engineer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061
www.valleyair.org

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

**SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT
NOTICE OF FINAL DECISION TO ISSUE
FEDERALLY MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District has made its final decision to issue the initial Federally Mandated Operating Permit to TRC Operating Company, Inc for its crude oil and natural gas production operation at its western Kern County fields Heavy Oil stationary source, California.

The District's analysis of the legal and factual basis for this proposed action, project #1110983, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. For additional information regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500, or contact David Warner, Director of Permit Services, in writing at SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 34946 FLYOVER COURT, BAKERSFIELD, CA 93308.



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



HEALTHY AIR LIVING™

Permit to Operate

FACILITY: S-3088

EXPIRATION DATE: 05/31/2017

LEGAL OWNER OR OPERATOR:

TRC CYPRESS GROUP LLC

MAILING ADDRESS:

P O BOX 227
TAFT, CA 93268

FACILITY LOCATION:

HEAVY OIL WESTERN STATIONARY SOURCE
CA

FACILITY DESCRIPTION:

CRUDE OIL AND NATURAL GAS PRODUCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin

Executive Director / APCO

David Warner

Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: S-3088-0-2

EXPIRATION DATE: 05/31/2017

FACILITY-WIDE REQUIREMENTS

1. Facilities S-3088 and S-2622 are included in the same stationary source. [District Rule 2201] Federally Enforceable Through Title V Permit
2. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rule 2080] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
5. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
6. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160] Federally Enforceable Through Title V Permit
7. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, and 2020] Federally Enforceable Through Title V Permit
8. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 2080; and 2520] Federally Enforceable Through Title V Permit
9. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
10. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: TRC CYPRESS GROUP LLC
Location: HEAVY OIL WESTERN STATIONARY SOURCE, CA
S-3088-0-2: Sep 14 2012 8:24AM - TORID

11. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520] Federally Enforceable Through Title V Permit
12. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520] Federally Enforceable Through Title V Permit
13. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520] Federally Enforceable Through Title V Permit
14. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 1100] Federally Enforceable Through Title V Permit
15. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520] Federally Enforceable Through Title V Permit
16. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
17. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520] Federally Enforceable Through Title V Permit
18. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520] Federally Enforceable Through Title V Permit
19. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520] Federally Enforceable Through Title V Permit
20. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
22. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
23. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

24. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
25. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
26. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601] Federally Enforceable Through Title V Permit
27. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601] Federally Enforceable Through Title V Permit
28. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
29. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520] Federally Enforceable Through Title V Permit
30. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
31. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
32. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
33. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
34. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
35. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
36. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

37. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
38. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
39. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520] Federally Enforceable Through Title V Permit
40. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520] Federally Enforceable Through Title V Permit
41. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
43. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
44. On September 30, 2012, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-4-2

EXPIRATION DATE: 05/31/2017

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

250 BBL FIXED ROOF PETROLEUM STORAGE TANK (#T-250)

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure (TVP) of liquids placed, stored, or held in the tank shall not exceed 1.5 psia at storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623] Federally Enforceable Through Title V Permit
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-7-7

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR NATURAL GAS/WASTE GAS FIRED STEAM GENERATOR WITH NORTH AMERICAN MAGNA-FLAME G-LE ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION (CYPRESS LEASE)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Emissions rates from the unit shall not exceed any of the following limits: 15 ppmv NOx @ 3% O2 or 0.018 lb-NOx/MMBtu, 0.037 lb-PM10/MMBtu, 104 ppmv CO @ 3% O2 or 0.0757 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
5. SOx emissions from this steam generator shall not exceed 328.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. An ATC application to modify this permit to comply with section 5.4 of Rule 4320 shall be submitted by 4/30/2012. [District Rule 4320] Federally Enforceable Through Title V Permit
7. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
8. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
9. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
10. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
11. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. Permittee shall monitor H₂S content of the gas prior to incineration in this steam generator on a daily basis utilizing Draeger tubes calibrated for H₂S or other District-approved fuel sulfur detection method(s) or device(s). If compliance with fuel sulfur content limit(s) for the affected steam generators is demonstrated for 5 consecutive days, then the monitoring frequency shall be weekly. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The following calculation shall be used to show compliance with the SO_x daily emissions limit: $\text{lb SO}_x \text{ emitted/day} = (\text{volume of gas incinerated per day, in scf}) \times (\text{ppm H}_2\text{S prior to incineration}) \times (0.32)$. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Records of daily and weekly Draeger tube results for sulfur content as required by this permit, and daily natural gas and waste gas consumption volume in scf shall be maintained, retained on-site for a period of at least five years and made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
24. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO_x emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO_x emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-8-11

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION WITH 150 STEAM ENHANCED CRUDE OIL PRODUCTION WELLS AND 665 SCFM AIR ASSIST STANDBY FLARE, WITH VAPOR PIPING FROM TANKS S-3088-9 THROUGH -16, -21 AND -22, GAS/LIQUID SEPARATORS, COMPRESSORS, HEAT EXCHANGERS, CONDENSATE PUMPS, FOUR SULFATREAT HP PACKED VESSELS, AND INCINERATION IN STEAM GENERATORS S-3088-7 OR -20, OR STANDBY FLARE

PERMIT UNIT REQUIREMENTS

1. VOC content of the vapor control system gas shall not exceed 10% by weight as determined in accordance with the latest revision of ASTM Methods D1945 for gases and South Coast AQMD Method 304-91 or the latest revision of ASTM Method E-168, E-169 or E-260 for liquids. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
2. Thermally enhanced oil recovery operation shall include no more than 150 cyclically steam enhanced wells. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Liquid from separators, heat exchangers, condensate collection vessels, compressor knockouts, and flare shall be piped only in closed piping to tanks with vapor control. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Vapor control system gas shall be incinerated in steam generator S-3088-7 and S-3088-20 or standby John Zink model STF-LH-336-6/15 air assisted flare when steam generators are not operational. Flare shall be equipped with automatic re-ignition system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Flare shall operate smokelessly (i.e. visible emissions shall be less than 1/4 Ringelmann). [District Rule 4101] Federally Enforceable Through Title V Permit
6. No more than 0.958 MM scf/day of TEOR and/or TVR gas shall be incinerated in standby flare. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Standby flare emissions shall not exceed any of the following limits: NOx: 0.068 lb/MMBtu, PM10: 0.008 lb/MMBtu, CO: 0.370 lb/MMBtu or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. SOx emissions from flare shall not exceed 207.6 lb/day based on mass balance calculation with H2S content and daily volume of the TEOR and/or TVR gas combusted. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When the standby flare is being used, daily records shall be maintained of scrubbed vapor control system gas volume flow rate and sulfur content. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The operator shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
11. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, component identification, record keeping, and notification requirements of Rule 4401 for all steam enhanced crude oil production wells at this facility except for those wells and components specifically exempted in Section 4.0 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
13. The inspection and re-inspection requirements set forth in Sections 5.8.1 through 5.8.5 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of 10% by weight or less [District Rule 4401] Federally Enforceable Through Title V Permit
14. The operator shall be in violation of Rule 4401 if any District inspection, or any operator inspection that is required by this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401] Federally Enforceable Through Title V Permit
15. Operator shall conduct quarterly sampling of vapor recovery system gas. If vapor recovery system gas is shown to be less than 10% VOC by weight for 8 consecutive quarterly sampling, sampling shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The sulfur content of the scrubbed vapor control system gas shall be tested at least monthly. [District Rule 1081] Federally Enforceable Through Title V Permit
17. The sulfur content of the vapor control system gas being combusted in the flare shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The flare flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311] Federally Enforceable Through Title V Permit
19. The flare outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
20. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated. [District Rule 4311] Federally Enforceable Through Title V Permit
21. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311] Federally Enforceable Through Title V Permit
22. Permittee shall maintain a record of all vapor control system gas sample analysis conducted for VOC and sulfur content, the volume flow rate to the flare, and a current listing of the steam enhanced wells with casing vents connected to the well vent collection and control system. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-9-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1500 BBL FIXED ROOF CONSTANT LEVEL CRUDE OIL WASH TANK (1000-01) SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-10-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL SHIPPING/REJECT TANK (T-1000-2) SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '-16 and '-21 upstream of TVR compressor # 1(prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-11-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL SHIPPING/REJECT TANK (T-1000-03) SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '-16 and '-21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-12-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL SHIPPING/REJECT TANK (T-1000-04) SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-13-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL SHIPPING/REJECT TANK (T-1000-05) SERVED BY VAPOR CONTROL LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption from the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-14-4

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

200 BBL FIXED ROOF CRUDE OIL SLOP TANK (T-3000-01) SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption from the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-15-4

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

250 BBL FIXED ROOF CRUDE OIL SLOP TANK (T-3000-02) SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1(prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-16-4

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL SLOP TANK (T-3000-03) SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption form the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-20-5

EXPIRATION DATE: 05/31/2017

SECTION: SW22 TOWNSHIP: 32S RANGE: 23E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR C.E. NATCO NATURAL GAS/WASTE GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE, ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION - CYPRESS LEASE

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Testing for vapor recovery gas sulfur content shall be conducted no less than monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas sulfur content shall not exceed 5 gr S/100 scf. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Permittee shall determine sulfur content of combusted gas annually. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
7. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 15 ppmvd NO_x @ 3% O₂ or 0.018 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.0076 lb-PM₁₀/MMBtu, 47.5 ppmvd CO @ 3% O₂ or 0.035 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
8. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
9. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The permittee shall keep daily records of the amount of natural gas and waste gas combusted, the sulfur content and higher heating value of each fuel, and the resulting calculated emissions of SO_x (as SO₂)/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
22. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO_x emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO_x emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-21-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

1500 BBL CONSTANT LEVEL FIXED ROOF CRUDE OIL WASH TANK SERVED BY VAPOR CONTROL SYSTEM
SHARED WITH S-3088-8

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed system that collects VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in section 6.4 of District Rule 4623. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC's collected from tank shall vent only to vapor control system S-3088-8. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Maximum VOC content of vapor in the tank vapor control system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) and API gravity testing of fluid stored by tanks S-3088-8 through '-16 and '-21 at least once every 24 months during summer (July- September), and/or whenever there is a change in the source or type of organic liquid stored in tanks S-3088-8 through '-16 and '-21 in order to maintain exemption from the rule. Sample for TVP analysis shall be taken from tank with highest storage temperature. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the Compliance Section of the Southern Region of the SJVAPCD within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Operator shall conduct quarterly gas sampling of gas from vapor recovery system serving tanks S-3088-8 through '16 and '21 upstream of TVR compressor # 1 (prior to connection to any other vapor control system). If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
14. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
16. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of this permit. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
17. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
18. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain records of the VOC content of vapor in the tank vapor control system, including date and test results. [District Rule 2201] Federally Enforceable Through Title V Permit
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-3088-24-3

EXPIRATION DATE: 05/31/2017

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR C.E. NATCO NATURAL GAS/WASTE GAS FIRED STEAM GENERATOR (#92 DIS# 27572-80) WITH NORTH AMERICAN MAGNA FLAME GLE ULTRA LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Emission rates from the unit shall not exceed any of the following limits: 0.028 lb-SO_x/MMBtu, 0.058 lb-PM₁₀/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
5. An ATC application to modify this permit to comply with section 5.4 of Rule 4320 shall be submitted by 4/30/2012. [District Rule 4320] Federally Enforceable Through Title V Permit
6. Except during startup and shutdown, emission rates from the unit shall not exceed any of the following limits: 15 ppmv NO_x @ 3% O₂. or 47 ppmv CO @ 3% O₂. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
7. Emission rates during startup and shutdown shall not exceed: NO₂ - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4301 and 4405] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed any of the following: NO_x (as NO₂): 54.0 lb/day or 9855 lb/year, CO: 52.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Each fuel source shall be tested weekly for sulfur content and higher heating value using ASTM D 1072, D 4468, D 4084, D3246 or grab sample analysis by double GC for H₂S and mercaptans performed in the laboratory. If compliance with the sulfur emission limits has been demonstrated for 8 consecutive weeks, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. If the source of fuel is changed, weekly testing shall again be required as outlined in this permit condition. When source or type of fuel gas changes, sampling for sulfur content and heating value shall be conducted within one week. A change in fuel type is defined as changing between any of the following: crude oil, refined petroleum product, PUC-quality gas, unprocessed field gas or any field gas with any specific level of pretreatment. For certified fuel sources, permittee may use sulfur content analysis provided by the fuel supplier to meet testing requirements. [District Rule 2201] Federally Enforceable Through Title V Permit
21. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
23. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall keep daily records of the amount of natural gas and waste gas combusted, the sulfur content and higher heating value of each fuel, and the resulting calculated emissions of SO_x (as SO₂)/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
27. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO_x emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO_x emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



PERMIT-EXEMPT EQUIPMENT REGISTRATION (PEER)

PEER NO: S-3088-1-0

EXPIRATION DATE: 06/12/2013

LEGAL OWNER OR OPERATOR: TRC CYPRESS GROUP LLC
MAILING ADDRESS: P O BOX 227
TAFT, CA 93268

FACILITY LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
CA

EQUIPMENT DESCRIPTION:

4.92 MMBTU/HR SUPERIOR MODEL X-4461 NATURAL GAS-FIRED NATURAL DRAFT PROCESS HEATER WITH TWO
2.46 MMBTU/HR NATIONAL TANK MODEL 34 NS-160 BURNERS

CONDITIONS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. The owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4307]
5. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4307]
6. The owner/operator shall maintain records to verify that the required tune-ups have been performed. [District Rule 4307]
7. Tune-up records shall include: 1) date of tune-up, 2) name of technician performing tune-up, and 3) reason that they are qualified. [District Rule 4307]
8. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 4307]

CONDITIONS CONTINUE ON NEXT PAGE

This PEER remains valid through the expiration date listed above, subject to payment of the annual registration fees and compliance with the PEER conditions and all applicable local, state, and federal regulations. This PEER is valid only within the San Joaquin Valley Air Pollution Control District. Any equipment or operation change may require a PEER application be filed with the District.

Sayed Sadredin
Executive Director / APCO

David Warner
Director of Permit Services

S-3088-1-0: 9/14/2012 - TORID . Joint Inspection NOT Required

9. This unit shall be in full compliance with District Rule 4307 by the applicable compliance plan. The full compliance date for Group 1 units is July 1, 2008. The full compliance date for Group 2 units is July 1, 2009. If this facility has only one unit subject to Rule 4307, the unit falls under Group 2. [District Rule 4307]