



OCT 03 2012

Mr. Christopher Savage
Gallo Glass Company
600 Yosemite Boulevard
Modesto, CA 95354

**Re: Final - Authority to Construct / COC (Significant Mod)
District Facility # N-1662
Project # N-1120773**

Dear Mr. Savage:

The Air Pollution Control Officer has issued an Authority to Construct (N-1662-4-15) with a Certificate of Conformity to Gallo Glass Company 605 South Santa Cruz Avenue in Modesto. The modifications are to re-brick glass melting furnace number four and to increase its footprint.

Enclosed is the Authority to Construct. The application and proposal were sent to US EPA Region IX on August 3, 2012. No comments were received following the District's preliminary decision on this project.

The notice of final decision for this project will be published approximately three days from the date of this letter.

Prior to operating with modifications authorized by the Authority to Construct, you must submit an application to modify the Title V permit as an administrative amendment in accordance with District Rule 2520, Section 11.5.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Rupi Gill, Permit Services Manager, at (209) 557-6400.

Sincerely,

David Warner
Director of Permit Services

Enclosures
DW/MJS:bw

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



OCT 03 2012

Gerardo C. Rios, Chief
Permits Office
Air Division
U.S. EPA - Region IX
75 Hawthorne St
San Francisco, CA 94105

**Re: Final - Authority to Construct / COC (Significant Mod)
District Facility # N-1662
Project # N-1120773**

Dear Mr. Rios:

The Air Pollution Control Officer has issued an Authority to Construct (N-1662-4-15) with a Certificate of Conformity to Gallo Glass Company 605 South Santa Cruz Avenue in Modesto. The modifications are to re-brick glass melting furnace number four and to increase its footprint.

Enclosed is a copy of the Authority to Construct. The application and proposal were sent to US EPA Region IX on August 3, 2012. No comments were received following the District's preliminary decision on this project.

The notice of final decision for this project will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Rupi Gill, Permit Services Manager, at (209) 557-6400.

Sincerely,



David Warner
Director of Permit Services

Enclosures
DW/MJS:bw

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT



HEALTHY AIR LIVING™

OCT 03 2012

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

**Re: Final - Authority to Construct / COC (Significant Mod)
District Facility # N-1662
Project # N-1120773**

Dear Mr. Tollstrup:

The Air Pollution Control Officer has issued an Authority to Construct (N-1662-4-15) with a Certificate of Conformity to Gallo Glass Company 605 South Santa Cruz Avenue in Modesto. The modifications are to re-brick glass melting furnace number four and to increase its footprint.

Enclosed is a copy of the Authority to Construct. The application and proposal were sent to US EPA Region IX on August 3, 2012. No comments were received following the District's preliminary decision on this project.

The notice of final decision for this project will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Rupi Gill, Permit Services Manager, at (209) 557-6400.

Sincerely,

David Warner
Director of Permit Services

Enclosures
DW/MJS:bw

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Modesto Bee

**NOTICE OF FINAL DECISION
FOR THE ISSUANCE OF AUTHORITY TO CONSTRUCT AND
THE PROPOSED SIGNIFICANT MODIFICATION OF FEDERALLY
MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District has made its final decision to issue an Authority to Construct to Gallo Glass Company for the glass container manufacturing operation located 605 South Santa Cruz Avenue in Modesto, California. The modifications are to re-brick glass melting furnace number four and to increase its footprint.

The District's analysis of the legal and factual basis for this proposed action, project #N-1120773, is available for public inspection at the District office at the address below. For additional information regarding this matter, please contact Mr. Rupi Gill, Permit Services Manager, at (209) 557-6400, or contact David Warner, Director of Permit Services, in writing at SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 4800 ENTERPRISE WAY, MODESTO, CA 95356.



AUTHORITY TO CONSTRUCT

PERMIT NO: N-1662-4-15

ISSUANCE DATE: 09/28/2012

LEGAL OWNER OR OPERATOR: GALLO GLASS COMPANY

MAILING ADDRESS: P.O. BOX 3044
MODESTO, CA 95353

LOCATION: 605 S SANTA CRUZ AVE
MODESTO, CA 95354

EQUIPMENT DESCRIPTION:

GLASS FURNACE #4 WITH 12 MAXON GAS/OXYGEN BURNERS AND ASSOCIATED FORMING EQUIPMENT (90 MMBTU/HR MAX HEAT CAPACITY). THIS FURNACE IS DUCTED THROUGH A STACK COMMON TO PERMIT UNITS N-1662-1, N-1662-2, N-1662-3 AND N-1662-4. THE FURNACES ARE SERVED BY A SHARED SOX SCRUBBER AND AN ELECTROSTATIC PRECIPITATOR AND/OR A TRI-MER UTF460 CERAMIC FILTER TYPE DUST COLLECTOR. MODIFICATION TO REBRICK THE FURNACE AND TO INCREASE ITS FOOTPRINT WITHOUT A THROUGHPUT INCREASE.

CONDITIONS

1. In the event that Authorities to Construct N-1662-1-14, N-1662-2-15, N-1662-3-15 and N-1662-4-16 are not previously implemented, the equipment description of this Authority to Construct Permit shall be modified to remove reference to the ceramic filter dust collector and all conditions related to the ceramic dust collector shall be modified or removed as appropriate. [District Rule 2201]
2. This Authority to Construct serves as a written Certificate of Conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2520] Federally Enforceable Through Title V Permit
3. Prior to operating with the modifications authorized by this Authority to Construct, the facility shall submit an application for an administrative amendment to its Title V permit, in accordance with District Rule 2520, Section 11.4.2. [District Rule 2520] Federally Enforceable Through Title V Permit
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications, and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Saadedin, Executive Director / APCD

DAVID WARNER, Director of Permit Services

N-1662-4-15, Sep 28 2012 10:02AM, 6CHONHOM, Joint Inspection NOT Required

5. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
6. The unit is exempt from the NO_x, CO and VOC emission limits of District Rule 4354 (Glass Melting Furnaces) during the furnace rebuild start-up period. The start-up period shall not exceed 18 days and shall start upon activation of the primary combustion system. [District Rule 4354] Federally Enforceable Through Title V Permit
7. During the furnace rebuild start-up period, the stoichiometric ratio of the primary furnace combustion system shall not exceed 5% excess oxygen, as calculated from the actual fuel and oxidant flow measurements for combustion in the glass melting furnace. [District Rule 4354] Federally Enforceable Through Title V Permit
8. The emission control system shall be in operation as soon as technologically feasible following the commencement of the furnace rebuild start-up to minimize emissions. [District Rule 4354] Federally Enforceable Through Title V Permit
9. A record of the post-rebuild start-up duration and of the dates of the start-up period activities shall be kept. The records shall be maintained for a period of at least five years and shall be made available to the District upon request. [District Rule 4354] Federally Enforceable Through Title V Permit
10. Particulate matter emissions shall not exceed 0.1 grain/dscf in concentration. [District Rule 4201 and Stanislaus County Rule 404] Federally Enforceable Through Title V Permit
11. The furnace shall be fired on natural gas and LPG only. [District NSR Rule] Federally Enforceable Through Title V Permit
12. The furnace shall have continuous monitoring systems for NO_x and SO_x. The monitoring devices shall have continuous recording devices, and all records shall be kept on site. [District Rules 1080 and 4354, §5.9] Federally Enforceable Through Title V Permit
13. One continuous emissions monitoring (CEM) system may be used for monitoring oxy-fuel fired furnaces #1, #2, #3, and #4 provided all of the exhaust gases of each of these furnaces are ducted to a common stack, and monitored down stream of the common stack. The CEMS shall comply with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13, 40 CFR Part 60 Appendix B (Performance Specifications) and Appendix F (Quality Assurance Procedures) and the applicable sections of Rule 1080 (Stack Monitoring). [District Rule 4354, 5.9 and 6.6.1] Federally Enforceable Through Title V Permit
14. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEM data polling software system and shall make CEM data available to the District's automated polling system on a daily basis. [District Rule 1080] Federally Enforceable Through Title V Permit
15. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NO_x, CO, and O₂ analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Source Emission Monitoring and Testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. During startups, the permittee shall comply with the requirements of section 5.5 of District Rule 4354. [District Rule 4354, §5.5] Federally Enforceable Through Title V Permit
17. The NO_x control system shall be in operation as soon as technologically feasible during the startup period to minimize emissions. [District Rule 4354, §5.5.6] Federally Enforceable Through Title V Permit
18. The NO_x control system shall be in operation whenever technologically feasible during shutdown to minimize emissions. [District Rule 4354, §5.6.2] Federally Enforceable Through Title V Permit
19. The NO_x control system shall be in operation whenever technologically feasible during furnace idling to minimize emissions. [District Rule 4354, §5.7.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The duration of shutdown, as measured from the time the furnace operations drop below the idle threshold specified in section 3.17 of District Rule 4354 to when all emissions from the furnace cease, shall not exceed 20 days. [District Rule 4354, §5.6.1] Federally Enforceable Through Title V Permit
21. The oxygen to fuel ratio shall be maintained within the range shown by the most recent source test to result in compliance with the CO and VOC limits of this permit. The acceptable range of the oxygen to fuel ratio shall be established during the initial source test and during each subsequent annual source test. [District Rule 4354] Federally Enforceable Through Title V Permit
22. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E=3.59P^{0.62}$ ($P < 30$ tph) or $E=17.31P^{0.16}$ ($P > 30$ tph). [District Rule 4202] Federally Enforceable Through Title V Permit
23. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [Stanislaus County Rule 407 and District Rule 4801] Federally Enforceable Through Title V Permit
24. Source testing to demonstrate compliance with the NO_x, CO, VOC, SO_x and PM₁₀ emission limits of this permit shall be conducted within 60 days after initial startup. [District Rules 2201 and 4354]
25. Source testing to demonstrate compliance with permit conditions and all rules and regulations for both natural gas and LPG shall be conducted at least once every calendar year. NO_x and CO testing shall be performed using CARB Method 100. VOC testing shall be performed using EPA method 25A. PM₁₀ testing shall be performed using EPA methods 201 and 202, EPA methods 201a and 202, or CARB methods 501 and 5. SO_x testing shall be performed using EPA Method 8 and CARB Method 1-100. [District Rules 1081; 2520, §9.3.2; and 4354, 6.4 and 6.5] Federally Enforceable Through Title V Permit
26. Source testing when firing on LPG fuel need not be performed if the LPG fuel usage for this furnace does not exceed 100 hours during any one calendar year. A source test shall be performed within 90 days after this furnace exceeds 100 hours of operation, on LPG, on an annual basis. [District Rule 1081] Federally Enforceable Through Title V Permit
27. Source testing shall be conducted by a CARB-certified source testing contractor. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to source testing. The results of each source test shall be submitted to the District within 60 days after the source test date. [District Rule 1081] Federally Enforceable Through Title V Permit
28. Source test conditions shall be representative of operations equal to or greater than 60 percent of the fuel use capacity for each furnace as stated in the Permit to Operate. [District Rule 4354, §6.4.2] Federally Enforceable Through Title V Permit
29. PM and PM₁₀ source testing shall be conducted down stream of the particulate matter control equipment in the common stack. Furnaces #1, #2, #3, and #4 must operate simultaneously during source testing unless prior approval is obtained from the District. [District Rule 1081] Federally Enforceable Through Title V Permit
30. An annual Relative Accuracy Test Audit (RATA) shall be performed on the continuous monitoring system as outlined in 40 CFR Part 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit
31. The owner/operator shall perform a relative accuracy test audit (RATA) as specified by 40 CFR Part 60, Appendix F (CGAs and RATAs) and if applicable 40 CFR Part 75, Appendix B (linearity and RATAs) at least once every four calendar quarters and annually within 30 days of the anniversary date of the initial test. The permittee shall comply with the applicable requirements for quality assurance testing and maintenance of the continuous emission monitor equipment in accordance with the procedures and guidance specified in 40 CFR Part 60, Appendix F. [District Rule 1080] Federally Enforceable Through Title V Permit
32. An exceedance of a NO_x or SO_x emission limit as indicated by the CEMS shall be reported by the operator to the APCO within 24 hours. The notification shall include 1) name and location of the facility, 2) identification of furnace(s) causing the exceedances, 3) calculation of actual NO_x, CO and VOC emissions, and 4) corrective actions and schedules to complete the work. [District Rule 1080 and Stanislaus County Rule 108] Federally Enforceable Through Title V Permit

33. The operator shall notify the APCO no later than one hour after the detection of a breakdown of the CEMS. The operator shall inform the APCO of the intent to shut down the CEMS at least 24 hours prior to the event. [District Rule 1100] Federally Enforceable Through Title V Permit
34. The permittee shall submit a written report including copies of any Equipment Breakdown reports and/or pertinent variance decisions to the APCO for each calendar quarter, within 30 days of the end of the quarter, including: time intervals, data and magnitude of excess emissions, nature and cause of excess emissions (if known), corrective actions taken and preventive measures adopted; averaging period used for data reporting shall correspond to the averaging period for each respective emission standard; applicable time and date of each period during which the CEM was inoperative (except for zero and span checks) and the nature of system repairs and adjustments; and a negative declaration when no excess emissions occurred. [District Rule 1080] Federally Enforceable Through Title V Permit
35. Upon notice by the District that the facility's CEM system is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEM data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit
36. Results of continuous emissions monitoring shall be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the ARB, and the EPA. [District Rule 1080] Federally Enforceable Through Title V Permit
37. Cylinder gas audits (GGAs) of continuous emission monitors shall be conducted quarterly, except during quarters in which relative accuracy and total accuracy testing is performed, in accordance with EPA guidelines. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080] Federally Enforceable Through Title V Permit
38. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Stanislaus County Rule 404, District Rule 4202 and Stanislaus County Rule 405. A permit shield is granted from these requirements. [District Rule 2520, §13.2] Federally Enforceable Through Title V Permit
39. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4801 and Stanislaus County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, §13.2] Federally Enforceable Through Title V Permit
40. The requirements of District Rule 4301 and Stanislaus County Rule 408 were determined to not apply to this unit because the unit does not utilize indirect heat transfer. A permit shield is granted from these requirements. [District Rule 2520, §13.2] Federally Enforceable Through Title V Permit
41. The requirements of 40 CFR Part 60, Subpart CC were determined to not apply to this unit because the unit was constructed prior to the effective date in the regulation and has not been modified (according to the definition of "modified" in the regulation). A permit shield is granted from these requirements. [District Rule 2520, §13.2] Federally Enforceable Through Title V Permit
42. The requirements of 40 CFR Part 61, Subpart N were determined to not apply to this unit because the unit does not use commercial arsenic. A permit shield is granted from these requirements. [District Rule 2520, §13.2] Federally Enforceable Through Title V Permit
43. Any glass melting furnace located at an Area Source of hazardous air pollutants shall comply with 40 CFR Part 63 Subpart SSSSSS (National Emission Standards for Hazardous Air Pollutants for Glass Manufacturing Area Sources). [40 CFR Part 63 Subpart SSSSSS] Federally Enforceable Through Title V Permit
44. The amount of glass produced shall not exceed 637.9 tons during any one day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
45. NOx emissions shall not exceed 1.3 pounds per ton of glass produced. This performance based limit is to enforce the NOx emission reductions granted by certificate number N-107-2. [District NSR Rule] Federally Enforceable Through Title V Permit
46. Except during furnace idling, shutdown, and startup, the aggregated NOx emissions shall not exceed 3.6 lb-NOx per ton of glass produced (based on a block 24-hour average). Aggregated NOx emission are the NOx emissions as measured at the common stack divided by the sum of the daily amount of glass produced by permit units N-1662-1, N-1662-2, N-1662-3 and N-1662-4. [District Rule 4354, 9.0 and 9.6] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

47. CO emissions shall not exceed 0.20 pounds per ton of glass produced. [District NSR Rule] Federally Enforceable Through Title V Permit
48. The VOC emissions shall not exceed 0.2 pounds per ton of glass produced. [District Rule 2201] Federally Enforceable Through Title V Permit
49. The combined SOx emissions from permit units N-1662-1, N-1662-2, N-1662-3 and N-1662-4, while producing glass with equal to or greater than 25% by weight mixed color cullet, shall not exceed 0.99 lb/ton of glass produced (over a rolling 30 day average). [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
50. The combined SOx emissions from permit units N-1662-1, N-1662-2, N-1662-3 and N-1662-4, while producing glass with less than 25% by weight mixed color cullet, shall not exceed 0.81 lb/ton of glass produced (over a rolling 30 day average). [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
51. The PM10 emissions, except for during full or partial emission control system bypass episodes, shall not exceed 0.45 lb/ton of glass produced. [District NSR Rules 2201 and 4354] Federally Enforceable Through Title V Permit
52. The PM10 emissions, during full or partial emission control system bypass episodes, shall not exceed 0.71 lb/ton of glass produced. [District Rule 2201] Federally Enforceable Through Title V Permit
53. The number of hours that the furnace exhaust is not fully treated by a control device shall not exceed 144 hours per calendar year. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
54. The PM10 emissions shall not exceed 28,132 pounds during the first calendar quarter, 28,445 pounds during the second calendar quarter, 28,757 pounds during the third calendar quarter and 28,758 pounds during the fourth calendar quarter. These limits are to enforce the PM10 emission reductions granted by certificate number N-161-4. [District NSR Rule] Federally Enforceable Through Title V Permit
55. During furnace idling, NOx emissions shall not exceed 1,888.0 pounds in any one day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
56. During furnace idling, CO emissions shall not exceed 637.9 pounds in any one day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
57. During furnace idling, VOC emissions shall not exceed 159.5 pounds in any one day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
58. During furnace idling, SOx emissions shall not exceed 701.7 pounds in any one day when producing glass with equal to or greater than 25% by weight mixed color cullet. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
59. During furnace idling, SOx emissions shall not exceed 574.1 pounds in any one day when producing glass with less than 25% by weight mixed color cullet. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
60. During furnace idling, PM10 emissions shall not exceed 319.0 pounds in any one day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
61. The facility shall not use commercial arsenic as a raw material in the production process. [40 CFR Part 61 Subpart N] Federally Enforceable Through Title V Permit
62. The ceramic filter dust collector shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
63. The ceramic filter dust collector cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
64. Material removed from the ceramic filter dust collector shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
65. Replacement filters numbering at least 10% of the total number of filters in the ceramic filter dust collector shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
66. Devices to measure the primary and secondary voltage and current of the electrostatic precipitator shall be maintained in accordance with the manufacturer's specifications. [District Rule 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

67. The specific power of the electrostatic precipitator shall be at least 70 milliwatts/acfm except during the bypass episodes allowed by this permit. [District Rules 2520, §9.3.2 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
68. The ceramic filter dust collector shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rules 2201 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
69. During operation of the ceramic filter dust collector, the pressure differential gauge reading shall be 5 to 10 inches of water column. [District Rules 2201 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
70. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR Part 64.7. [40 CFR Part 64] Federally Enforceable Through Title V Permit
71. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR Part 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64] Federally Enforceable Through Title V Permit
72. The permittee shall comply with the record keeping and reporting requirements of 40 CFR Part 64.9. [40 CFR Part 64] Federally Enforceable Through Title V Permit
73. The specific power of the electrostatic precipitator shall be continuously monitored and recorded. [District Rules 2201 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
74. Dust collector filters shall be inspected annually while in operation for evidence of particulate matter breakthrough and replaced as needed. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
75. Dust Collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or hole that might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
76. A daily record of the hours of operation, the amount of glass pulled from the furnace (in tons), the NO_x emissions (in lb/ton of glass pulled), the SO_x emissions (in lb/ton of glass pulled), the weight of mixed color mix cullet used, the total amount of cullet used (by weight) and the ratio of the mixed color cullet weight to the total cullet weight (in percent) shall be kept. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
77. The oxygen to fuel ratio shall be continuously monitored and recorded. [District Rule 4354] Federally Enforceable Through Title V Permit
78. The permittee shall maintain daily records of the aggregated NO_x emissions. [District Rules 2520, 9.3.2 and 4354, 9.6.1 and 9.7] Federally Enforceable Through Title V Permit
79. The permittee shall maintain the burner oxygen to fuel ratio records required by this permit. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
80. A record of the PM₁₀ emissions from this unit, in pounds per calendar quarter, shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit
81. A record of the cumulative annual number of hours that the emission control system is either fully or partially bypassed shall be kept. The record shall be updated at least weekly. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
82. The permittee shall maintain daily records of the specific power of the electrostatic precipitator (in milliwatts/acfm). [District Rules 2201, 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
83. The operator shall monitor and record the pressure differential gauge reading of the ceramic filter dust collector at least once during each day that the unit operates. [District Rules 2201 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
84. Records of dust collector maintenance, inspections and repairs shall be maintained. The records shall include, date of inspection, change outs of filter media, corrective action taken ,and identification of the individual performing the inspection. [District Rules 2201 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

85. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 2201 and 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit