

Appendix B: Detailed Air Monitoring Site Information

Sites organized by County, alphabetical therein:

County	MSA	Site Name	Page Number
Fresno	Fresno	Clovis–Villa	B-2
		Fresno–Drummond	B-6
		Fresno–Garland	B-10
		Fresno–Pacific	B-16
		Fresno–Sky Park	B-18
		Huron	B-21
		Parlier	B-23
		Tranquillity	B-27
Kern	Bakersfield	Arvin–Di Giorgio	B-29
		Bakersfield–Planz	B-31
		Bakersfield–California	B-33
		Bakersfield–Muni	B-37
		Edison	B-42
		Lebec	B-44
		Maricopa	B-46
		Oildale	B-48
		Shafter	B-50
Kings	Hanford – Corcoran	Corcoran–Patterson	B-53
		Hanford–Irwin	B-56
Madera	Madera	Madera--City	B-59
		Madera--Pump Yard	B-62
Merced	Merced	Merced–Coffee Road	B-65
		Merced M Street	B-68
San Joaquin	Stockton	Manteca	B-70
		Stockton–Hazelton	B-73
		Stockton–Wagner/Holt	B-77
		Tracy–Airport	B-79
Stanislaus	Modesto	Modesto–14 th Street	B-83
		Turlock	B-87
Tulare	Visalia – Porterville	Porterville	B-91
		Sequoia–Ash Mountain	B-93
		Sequoia–Lower Kaweah	B-95
		Visalia–Airport	B-97
		Visalia–Church	B-99

Site name	Clovis–Villa	
AIRS #	060195001	
County	Fresno	
Collecting (Operating) Agency	All equipment operated by SJVAPCD	
Reporting Agency	Data reported by SJVAPCD: PM2.5 FEM, CO, NO ₂ , NMHC, Speciated VOC, Meteorology	Data reported by CARB: PM10 FRM
Site Start Date	9/1/90	
Pollutant Parameters	Ozone, PM10 FRM, PM2.5 FEM, CO, NO ₂ , NMHC, Speciated VOC	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation	
Address	908 N. Villa Ave., Clovis CA 93612	
Latitude	N 36.81944	
Longitude	W -119.716	
Elevation (m)	86	
Location	Portable building in lot	
Distance to road	500 m + (east)	
Traffic Count	4876	
Ground Cover	Paved	

Clovis–Villa (1 of 3)			
Pollutant	Ozone	PM10 FRM	PM2.5 FEM
Parameter Code	44201	81102	88101
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research support	Timely/public
Monitor type	SLAMS	SLAMS	SLAMS
POC (or primary monitor for PM2.5 and PM10)	1	1	3
Method code	087	063	170
Sampling method (List Instrument)	400 E	Sierra Andersen	Met One 1020
Analysis method	UV	Gravimetric	Beta attenuation
Start date	1/1/1990	1/1/1990	11/25/2008
Operation schedule (e.g. 1:1, 1:3)	1:1	1:6	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	7.5 m	7.0 m	7.0 m
Distance from supporting structure (meters)	4.5 m	0.25 m	4.0 m
Distance from obstructions on roof	_____	_____	_____
Distance from obstructions not on roof (meters)	32.0 m	31.5 m	31.0 m
Distance from trees (meters)	24.5 m	27.5 m	25.0 m
Distance to furnace or incinerator flue (meters)	16.0 m	15.5 m	17.0 m
Distance between collocated monitors (meters)	_____	3.7 m	2.5 m
Unrestricted airflow (degrees)	355	355	355
Probe material (Teflon, etc.)	TEFLON	_____	ALUMINUM
Residence time (seconds)	12.6	_____	_____
Frequency of flow rate verification for manual PM samplers audit	_____	Quarterly	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	Bi-weekly
Frequency of one-point QC check (gaseous)	1:1	_____	_____
Last Annual Performance Evaluation (gaseous)	10/20/2009, 11/2/2010	_____	_____
Last two semi-annual flow rate audits for PM monitors	_____	5/27/2010, 11/2/2010	5/27/2010, 11/2/2010
Changes planned within the next 18 months (Y/N))	N	N	N

Clovis–Villa (2 of 3)				
Pollutant	CO	NO₂	Speciated VOC (PAMS)	NMHC (PAMS)
Parameter code	42101	42602	Many	43102
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	High concentration	Population	Population
Monitor objective	Standards/strategy	Standards/strategy, research	Research	Research
Monitor type	SLAMS	PAMS	PAMS	PAMS
POC	1	1	1	1
Sampling method (List Instrument)	48i-TLE	42C	910A, 925	55
Method code	054	074	164	177
Analysis method	IR	CL	GC	GC
Start date	1/1/1990	1/1/1990	1/1/1990	1/1/1990
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:3	1:1
Sampling season	ALL YEAR	ALL YEAR	JUN-JUL-AUG	ALL YEAR
Probe height (meters)	7.5 m	7.5 m	6.5 m	7.5 m
Distance from supporting structure (meters)	4.5 m	4.5 m	0.25 m	4.5 m
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	32.0 m	32.0 m	33.5 m	32.0 m
Distance from trees (meters)	24.5 m	24.5 m	28.0 m	24.5 m
Distance to furnace or incinerator flue (meters)	16.0 m	16.0 m	13.5 m	16.0 m
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	355	355	350	355
Probe material (Teflon, etc.)	TEFLON	TEFLON	S. STEEL	TEFLON
Residence time (seconds)	11.6	11.6	_____	_____
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	1:1	_____	1:1
Last Annual Performance Evaluation (gaseous)	11/2/2010	11/2/2010	5/10/2010	_____
Last two semi-annual flow rate audits for PM monitors	_____	_____	_____	_____
Changes planned within the next 18 months (Y/N))	N	N	N	N

Clovis–Villa (3 of 3)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	PAMS
POC	1
Method code	Many
Sampling method (List Instrument)	ITP-125-125 HV, OT-06A-2, BP-092, RH-HMP45D, SRD-Mod.8-48, WD-020C, WS-010C
Analysis method	_____
Start date	1/1/1990
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	9.6 m
Distance from supporting structure (meters)	2.7 m
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	29.5 m
Distance from trees (meters)	25.5 m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Fresno–Drummond	
AIRS #	060190007	
County	Fresno	
Collecting (Operating) Agency	All equipment operated by SJVAPCD	
Reporting Agency	Data reported by SJVAPCD: Ozone, CO, NO ₂	Data reported by CARB: PM10 FRM
Site Start Date	7/1/84	
Pollutant Parameters	Ozone, PM10 FRM, CO, NO ₂	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure	
Address	4706 E. Drummond Street, Fresno CA 93725	
Latitude	N 36.70556	
Longitude	W -119.741	
Elevation (m)	89	
Location	Portable building in parking lot	
Distance to road	42.5 m (north), 121 m (east)	
Traffic Count	600	
Ground Cover	Paved	

Fresno–Drummond (1 of 2)					
Pollutant	Ozone	PM10 FRM		CO	NO₂
Parameter code	44201	81102		42101	42602
Spatial scale	Neighborhood	Neighborhood		Neighborhood	Neighborhood
Site type	Population, regional transport	Population		Population	High concentration
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research support		Standards/strategy	Standards/strategy
Monitor type	SLAMS	SLAMS	Other	SLAMS	SLAMS
POC	1	1 (Primary)	3 (Collocated)	1	1
Method code	087	063		054	074
Sampling method (List Instrument)	400 E	Sierra Andersen		48	42C
Analysis method	UV	Gravimetric		IR	CL
Start date	7/1/1984	7/1989	Collocated Scheduled to start 10/2012	7/1/1984	7/1/1984
Operation schedule (e.g. 1:1, 1:3)	1:1	1:6		1:1	1:1
Sampling season	ALL YEAR	ALL YEAR		ALL YEAR	ALL YEAR
Probe height (meters)	8.5 m	6 m		8.5 m	8.5 m
Distance from supporting structure (meters)	_____	10.5 m		_____	_____
Distance from obstructions on roof	_____	0.5 m		_____	_____
Distance from obstructions not on roof (meters)	_____	5 m		_____	_____
Distance from trees (meters)	25 m	24 m		25 m	25 m
Distance to furnace or incinerator flue (meters)	23.5 m	23 m		23.5 m	23.5 m
Distance between collocated monitors (meters)	_____	_____		_____	_____
Unrestricted airflow (degrees)	360	260		360	360
Probe material (Teflon, etc.)	TEFLON	_____		TEFLON	TEFLON

Fresno–Drummond (1 of 2) continued				
Residence time (seconds)	12.8	_____	12.6	12.9
Frequency of flow rate verification for manual PM samplers audit	_____	Quarterly	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	_____	1:1	1:1
Last Annual Performance Evaluation (gaseous)	3/1/2011	_____	3/1/2011	3/1/2011
Last two semi-annual flow rate audits for PM monitors	_____	2/10/2010, 8/1/2010, 3/1/2011	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Fresno–Drummond (2 of 2)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	SLAMS
POC	1
Method code	Many
Sampling method (List Instrument)	ITP-125-125 HV, OT-060A-2, BP-092, WD-020C, WS-010C
Analysis method	_____
Start date	10/7/2004
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	10 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	25 m
Distance to furnace or incinerator flue (meters)	23 m
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Fresno–Garland	
AIRS #	060190011	
County	Fresno	
Collecting (Operating) Agency	All equipment operated by CARB	
Reporting Agency	Data reported by CARB: PM10 FRM, PM10 FEM, PM2.5 FRM, PM2.5 Non-FEM, CO, NO ₂ , Toxics	Data reported by NPS: SO ₂
Site Start Date	12/31/2011	
Pollutant Parameters	Ozone, PM10 FRM, PM10 FEM, PM2.5 FRM, PM2.5 Non-FEM, CO, NO ₂ , SO ₂ , Toxics	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure	
Address	3727 N. First St., Ste.104, Fresno CA 93726	
Latitude	N 36.78538	
Longitude	W -119.77321	
Elevation (m)	97	
Location		
Distance to road		
Traffic Count		
Ground Cover	Roof	

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Fresno–Garland (1 of 3)					
Pollutant	Ozone	PM10 FRM	PM10 FEM	PM2.5 FRM	PM2.5 FRM
Parameter code	44201	81102	85101	88101	88101
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	High concentration	High concentration	High concentration	High concentration
Monitor objective	Max Precursor Emissions Impact	Max Precursor Emissions Impact	Max Precursor Emissions Impact	Population Exposure	
Monitor type	SLAMS	SLAMS	SPM	SLAMS	
POC	1	1	1	1 (Primary)	2 (Collocated)
Method code	087	063	063	118	118
Sampling method (List Instrument)	API/Teledyne 400	Andersen SA1200	Met One 1020	R&P 2025	R&P 2025
Analysis method	UV	Gravimetric	Beta Attenuation	Sequential	Sequential
Start date					
Operation schedule (e.g. 1:1, 1:3)	1:1	1:6	1-Hour	Daily	1:6
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)					
Distance from supporting structure (meters)					
Distance from obstructions on roof					
Distance from obstructions not on roof (meters)	None	None	None	None	None
Distance from trees (meters)	None	None	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None	None	None
Distance between collocated monitors (meters)	--	--	--	--	
Unrestricted airflow (degrees)	360	360	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	Teflon	Teflon
Residence time (seconds)	4.2	--	--	--	
Frequency of flow rate verification for manual PM samplers audit	--	Once a Month	--	Once a Month	Once a Month

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Fresno–Garland (1 of 3) continued					
Pollutant	Ozone	PM10 FRM	PM10 FEM	PM2.5 FRM	PM2.5 FRM
Frequency of flow rate verification for automated PM analyzers audit	--	--	Twice a Month	--	
Frequency of one-point QC check (gaseous)	Twice a month	--	--	--	
Last Annual Performance Evaluation (gaseous)	09/22/2010	--	--	--	
Last two semi-annual flow rate audits for PM monitors	--	09/20/2010	09/20/2010	06/08/2010	
Changes planned within the next 18 months (Y/N))	Y	Y	Y	Y	Y

Fresno–Garland (2 of 3)						
Pollutant	PM2.5 FEM	PM2.5 Non-FEM	PM2.5		CO	NO₂
Parameter code	88101	88501	88502		42101	42602
Spatial scale	Neighborhood	Neighborhood	Neighborhood		Neighborhood	Neighborhood
Site type	High concentration	High concentration	High concentration		Population	Population
Monitor objective		Population Exposure	Population Exposure		Max Precursor Emissions Impact	Max Precursor Emissions Impact
Monitor type	SLAMS	SPM (Non-regulatory)	Trend	Improve	SPM	SLAMS
POC	3	3	5	1	3	1
Method code	170	731	810	707	731	074
Sampling method (List Instrument)	MetOne 1020	MetOne 1020	R&P 2025		Dasibi 3008	API 200E
Analysis method		Beta Attenuation	Gravimetric			
Start date						
Operation schedule (e.g. 1:3, 1-Hour, etc.)	1-Hour	1-Hour	Daily		1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR		ALL YEAR	ALL YEAR

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Fresno–Garland (2 of 3) continued					
Pollutant	PM2.5 FEM	PM2.5 Non-FEM	PM2.5	CO	NO₂
Probe height (meters)					
Distance from supporting structure (meters)					
Distance from obstructions on roof					
Distance from obstructions not on roof (meters)	None	None	None	None	None
Distance from trees (meters)	None	None	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None	None	None
Distance between collocated monitors (meters)		1.5	--	--	--
Unrestricted airflow (degrees)		360	360	360	360
Probe material (Teflon, etc.)		Teflon	Teflon	Teflon	Teflon
Residence time (seconds)		--	--		6.2
Frequency of flow rate verification for manual PM samplers audit		--	Once a Month	--	--
Frequency of flow rate verification for automated PM analyzers audit		Twice a month	--	--	--
Frequency of one-point QC check (gaseous)		--	--	Twice a month	Twice a month
Last Annual Performance Evaluation (gaseous)		--	--	09/22/2010	09/22/2010
Last two semi-annual flow rate audits for PM monitors		09/22/2010	09/22/2010	--	--
Changes planned within the next 18 months (Y/N)	Y	Y	Y	Y	Y

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Fresno–Garland (3 of 3)			
Pollutant	SO₂	Toxics	Met Parameters
Parameter code	42401	Many	Many
Spatial scale	Neighborhood	Neighborhood	Regional
Site type	Population	Population	General
Monitor objective	Other	Unknown	Research, timely/public
Monitor type	SLAMS	Many	Many
POC	1	Many	Many
Method code	009	Many	Many
Sampling method (List Instrument)	-	Xontech 924	
Analysis method	TECO 43	--	
Start date			
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)			
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)		None	None
Distance from trees (meters)	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None
Distance between collocated monitors (meters)	None	--	--
Unrestricted airflow (degrees)	--	360	360
Probe material (Teflon, etc.)	360	Teflon	Teflon
Residence time (seconds)	Teflon		
Frequency of flow rate verification for manual PM samplers audit	5.9	--	--
Frequency of flow rate verification for automated PM analyzers audit	--	--	--
Frequency of one-point QC check (gaseous)	--	Twice a month	--

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Fresno–Garland (3 of 3) continued			
Pollutant	SO₂	Toxics	Met Parameters
Last Annual Performance Evaluation (gaseous)	Twice a month	09/23/2010	--
Last two semi-annual flow rate audits for PM monitors	09/22/2010	--	--
Changes planned within the next 18 months (Y/N)	N	N	N

In December 2011, CARB moved the Fresno-First air monitoring station to Garland Avenue which is two blocks north of the Fresno-First site.

Site name	Fresno–Pacific
AIRS #	060195025
County	Fresno
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by Ventura County APCD
Site Start Date	1/1/00
Pollutant Parameters	PM2.5 FRM
Meteorological Parameters	None
Address	1716 Winery, Fresno CA 93726
Latitude	N 36.72639
Longitude	W -119.733
Elevation (m)	100
Location	On school roof
Distance to road	62.0 m (north), 52.0 m (east)
Traffic Count	2539
Ground Cover	Roof material

Fresno–Pacific	
Pollutant	PM2.5 FRM
Parameter code	88101
Spatial scale	Neighborhood
Site type	Population
Monitor objective	Standards/strategy, research support
Monitor type	SLAMS
POC	1
Method code	120
Sampling method (List Instrument)	Partisol 2025 installed on 9/15/2010
Analysis method	GRAVI-METRIC
Start date	1/1/2000
Operation schedule (e.g. 1:1, 1:3)	1:3, 1:6
Sampling season	ALL YEAR
Probe height (meters)	8.0 m
Distance from supporting structure (meters)	6.0 m
Distance from obstructions on roof	54.5 m
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	76.0 m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	MONTHLY
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	9/15/2010, 3/3/2011
Changes planned within the next 18 months (Y/N)	N

Site name	Fresno–Sky Park
AIRS #	060190242
County	Fresno
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	7/1/86
Pollutant Parameters	Ozone, CO, NO ₂
Meteorological Parameters	Wind speed, wind direction, outdoor temperature
Address	4508 Chennault Ave, Fresno CA 93722
Latitude	N 36.84056
Longitude	W -119.874
Elevation (m)	65
Location	Portable building
Distance to road	11.5 m (west)
Traffic Count	100
Ground Cover	Gravel

Fresno–Sky Park				
Pollutant	Ozone	CO	NO₂	Met Parameters
Parameter code	44201	42101	42602	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Regional
Site type	Population, regional transport	Population	Population	General
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy	Standards/strategy	Research, timely/public
Monitor type	SLAMS	SLAMS	SLAMS	SLAMS
POC	1	1	1	1
Method code	087	054	074	Many
Sampling method (List Instrument)	400E	48	42C	ITP-125-125 HV, OT-06A-2, WD-020C, WS-010B
Analysis method	UV	IR	CL	_____
Start date	7/1/1986	7/1/1986	7/1/1986	7/1/1986
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	4 m	4 m	4 m	5 m
Distance from supporting structure (meters)	_____	_____	_____	_____
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	5 m / 16 m	5 m / 16 m	5 m / 16 m	5 m / 16 m
Distance from trees (meters)	27 m / 20 m	27 m / 20 m	27 m / 20 m	27 m / 20 m
Distance to furnace or incinerator flue (meters)	_____	_____	_____	_____
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	280	280	280	280
Probe material (Teflon, etc.)	TEFLON	TEFLON	TEFLON	_____
Residence time (seconds)	10.0	9.4	10.1	_____
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	1:1	1:1	_____
Last Annual Performance Evaluation (gaseous)	3/2/2011	3/2/2011	3/2/2011	3/2/2011

Fresno–Sky Park (continued)				
Pollutant	Ozone	CO	NO₂	Met Parameters
Last two semi-annual flow rate audits for PM monitors	_____	_____	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Site name	Huron
AIRS #	060192008
County	Fresno
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	10/12/09
Pollutant Parameters	PM2.5 Non-FEM
Meteorological Parameters	Barometric pressure
Address	16875 4 th St., Huron, CA 93234
Latitude	N 36.2363
Longitude	W -119.765689
Elevation (m)	112
Location	In school room
Distance to road	202 m (west), 99.5 m (north)
Traffic Count	1205
Ground Cover	Paved/vegetated

Huron		
Pollutant	PM2.5 Non-FEM	Met Parameters
Parameter code	88502	64101
Spatial scale	Neighborhood	Neighborhood
Site type	Population	Population
Monitor objective	Timely/public	Timely/public
Monitor type	SPM	-
POC	3	1
Method code	731	
Sampling method (List Instrument)	Anderson	ITP-125-50-HV, BP-092
Analysis method	BETA-ATTENUATION	
Start date	Q3-2009	2/1/2010
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)	4.5 m	
Distance from supporting structure (meters)	1.5 m	
Distance from obstructions on roof	_____	
Distance from obstructions not on roof (meters)	_____	
Distance from trees (meters)	41.5 m	
Distance to furnace or incinerator flue (meters)	_____	
Distance between collocated monitors (meters)	_____	
Unrestricted airflow (degrees)	270	
Probe material (Teflon, etc.)	ALUMINUM	
Residence time (seconds)	_____	
Frequency of flow rate verification for manual PM samplers audit	_____	
Frequency of flow rate verification for automated PM analyzers audit	BI-WEEKLY	
Frequency of one-point QC check (gaseous)	_____	
Last Annual Performance Evaluation (gaseous)	_____	
Last two semi-annual flow rate audits for PM monitors	7/21/2010, 11/2/2010	
Changes planned within the next 18 months (Y/N)	N	N

Site name	Parlier
AIRS #	060194001
County	Fresno
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	1/1/06
Pollutant Parameters	Ozone, NO ₂ , Speciated VOC, NMHC
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation
Address	9240 S. Riverbend Ave., Parlier CA 93648
Latitude	N 36.59722
Longitude	W -119.504
Elevation (m)	78
Location	Portable building in university field
Distance to road	500 m+ (north)
Traffic Count	8700
Ground Cover	Dirt/vegetated

Parlier (1 of 2)				
Pollutant	Ozone	NO₂	Total Speciated VOC	NMHC
Parameter code	44201	42602	43102	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	High concentration, regional transport	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research	Research	Research
Monitor type	PAMS	PAMS	PAMS	PAMS
POC	1	1	1	1
Method code	087	074	164	177
Sampling method (List Instrument)	400 E	42C / 200E installed on 1/10/2011	910A	55C
Analysis method	UV	CL	GC	GC
Start date	3/1/1983	3/1/1983	3/1/1983	3/1/83
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:3	1:1
Sampling season	ALL YEAR	ALL YEAR	JUN-JUL-AUG	ALL YEAR
Probe height (meters)	9.0 m	9.0 m	7.0 m	9.0 m
Distance from supporting structure (meters)	_____	_____	_____	_____
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	_____	_____	_____	_____
Distance from trees (meters)	_____	_____	12.5 m	_____
Distance to furnace or incinerator flue (meters)	_____	_____	_____	_____
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	360	360	270	360
Probe material (Teflon, etc.)	TEFLON	TEFLON	S. STEEL	TEFLON
Residence time (seconds)	13.6	13.3	_____	12.9
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	1:1	_____	1:1
Last Annual Performance Evaluation (gaseous)	1/27/2011	1/27/2011	5/10/2010	_____

Parlier (1 of 2) continued				
Pollutant	Ozone	NO₂	Speciated VOC	NMHC
Last 2 semi-annual flow rate audits, PM monitors	_____	_____	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	Y

Parlier (2 of 2)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	PAMS
POC	1
Method code	Many
Sampling method (List Instrument)	ITP-125-125 HV, OT-06A-2, BP-092, RH-HMP45D, SRD-Mod.8-48, WD-020C, WS-010C
Analysis method	_____
Start date	3/1/83
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	9.5 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	_____
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____

Parlier (2 of 2) continued

Pollutant	Met Parameters
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Tranquillity
AIRS #	060192009
County	Fresno
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	11/9/2009
Pollutant Parameters	Ozone, PM2.5 FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	32650 W. Adams, Tranquillity CA 93668
Latitude	N 36.600833
Longitude	-120.382222
Elevation (m)	59
Location	Portable shed
Distance to road	186 m (south)
Traffic Count	
Ground Cover	Gravel/vegetation

Tranquillity			
Pollutant	Ozone	PM2.5 FEM	Met Parameters
Parameter code	44201		Many
Spatial scale	Urban	Urban	Urban
Site type	Population	Population	Population
Monitor objective	Timely/public	Timely/public	Timely/public
Monitor type	SPM	SPM	
POC	1	3	1
Method code	087	170	Many
Sampling method (List Instrument)	400 E	1020	ITP-020B, OT-060, BP-092C, WD-020C, WS-010C
Analysis method	UV	BETA-ATTENUATION	
Start date	10/30/2009	10/30/2009	10/30/2009
Operation schedule (e.g. 1:1, 1:3)	1:1	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	4 m	4 m	10 m
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)			
Distance from trees (meters)	102 m	102 m	102 m
Distance to furnace or incinerator flue (meters)	97.5 m	97.5 m	97.5 m
Distance between collocated monitors (meters)			
Unrestricted airflow (degrees)	360	360	360
Probe material (Teflon, etc.)	TEFLON	ALUMINUM	
Residence time (seconds)	6.0		
Frequency of flow rate verification for manual PM samplers audit			
Frequency of flow rate verification for automated PM analyzers audit		BI-WEEKLY	
Frequency of one-point QC check (gaseous)	1:1		
Last Annual Performance Evaluation (gaseous)	7/21/2010		
Last 2 semi-annual flow rate audits, PM monitors	10/21/2010, 4/12/2011		
Changes planned within the next 18 months (Y/N)	N		

Site name	Arvin-Di Giorgio
AIRS #	060295002
County	Kern
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	11/16/2009
Pollutant Parameters	
	Ozone
Meteorological Parameters	
	Outdoor temperature
Address	
	19405 Buena Vista Blvd, Arvin CA 93203
Latitude	N 35° 14' 21"
Longitude	W -118° 47' 18.6"
Elevation (m)	107
Location	
Distance to road	
	10 m
Traffic Count	500
Ground Cover	Dirt

Arvin-Di Giorgio		
Pollutant	Ozone	Met Parameters
Parameter code	44201	62101
Spatial scale	Neighborhood	Regional
Site type		
Monitor objective	Population Exposure	Research, timely/public
Monitor type	PAMS	PAMS
POC	1	1
Method code	087	040
Sampling method (List Instrument)	400 E	
Analysis method	UV	
Start date	11/16/2009	
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)		
Distance from supporting structure (meters)	_____	_____
Distance from obstructions on roof	_____	_____
Distance from obstructions not on roof (meters)	_____	_____
Distance from trees (meters)		
Distance to furnace or incinerator flue (meters)	_____	_____
Distance between collocated monitors (meters)	_____	_____
Unrestricted airflow (degrees)	350	
Probe material (Teflon, etc.)	TEFLON	_____
Residence time (seconds)	10.7	_____
Frequency of flow rate verification for manual PM samplers audit	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____
Frequency of one-point QC check (gaseous)	1:1	_____
Last Annual Performance Evaluation (gaseous)	07/27/2010	_____
Last two semi-annual flow rate audits for PM monitors	_____	
Changes planned within the next 18 months (Y/N)	Y	Y

Site name	Bakersfield–Planz
AIRS #	060290016
County	Kern
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by Ventura County APCD
Site Start Date	9/19/00
Pollutant Parameters	
	PM2.5 FRM
Meteorological Parameters	
	None
Address	
	401 E. Planz Rd., Bakersfield CA 93307
Latitude	
	N 36° 19' 52"
Longitude	
	W 118° 59' 59"
Elevation (m)	
	145
Location	
Distance to road	
	500 m
Traffic Count	
	1000
Ground Cover	
	Asphalt

Bakersfield–Planz	
Pollutant	PM2.5 FRM
Parameter code	88101
Spatial scale	Neighborhood
Site type	Population
Monitor objective	Population Exposure
Monitor type	SLAMS
POC	1
Method code	120
Sampling method (List Instrument)	R&P 2025
Analysis method	Gravimetric
Start date	
Operation schedule (e.g. 1:1, 1:3)	1:3
Sampling season	ALL YEAR
Probe height (meters)	
Distance from supporting structure (meters)	
Distance from obstructions on roof	
Distance from obstructions not on roof (meters)	None
Distance from trees (meters)	None
Distance to furnace or incinerator flue (meters)	None
Distance between collocated monitors (meters)	None
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	Teflon
Residence time (seconds)	NA
Frequency of flow rate verification for manual PM samplers audit	Once a month
Frequency of flow rate verification for automated PM analyzers audit	--
Frequency of one-point QC check (gaseous)	--
Last Annual Performance Evaluation (gaseous)	--
Last two semi-annual flow rate audits for PM monitors	01/29/2010
Changes planned within the next 18 months (Y/N)	Y

Site name	Bakersfield–California	
AIRS #	060290014	
County	Kern	
Collecting (Operating) Agency	Equipment operated by CARB: PM10 FRM, PM2.5 FRM, PM2.5 Non-FEM, NO ₂ , Toxics, Meteorology	Equipment operated by SJVAPCD: Temporary PM10 FEM
Reporting Agency	Data reported by CARB: PM10 FRM, PM2.5 FRM, NO ₂ , Toxics, Meteorology	Data reported by Ventura County APCD: PM2.5 Non-FEM
Site Start Date	3/1/94	
Pollutant Parameters	Ozone, PM10 FRM, PM2.5 FRM, PM2.5 Non-FEM, NO ₂ , Toxics	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure	
Address	5558 California Ave., Bakersfield CA 93309	
Latitude	N 35° 21' 24"	
Longitude	N 119° 3' 46"	
Elevation (m)	117	
Location		
Distance to road	300 m	
Traffic Count	10000	
Ground Cover	Roof	

Bakersfield–California (1 of 2)					
Pollutant	Ozone	PM10 FRM	PM10 FRM	PM2.5 FRM	PM2.5 FRM
Parameter code	44201	81102	81102	88101	88101
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population		Population	Population
Monitor objective	Unknown	Unknown	Unknown	Population Exposure	Other
Monitor type	SLAMS	SLAMS	Other (Collocated)	SLAMS (Primary)	SLAMS (Collocated)
POC	1	1	2	1	2
Method code	087	063	063	118	118
Sampling method (List Instrument)	API/Teledyne 400	SA/GMW 1200	SA/GMW 1200	R&P 2025	R&P 2025
Analysis method	UV	Gravimetric	Gravimetric	Sequential	Sequential
Start date		4/1/1994	1/3/2003	1/1/1999	1/1/1999
Operation schedule (e.g. 1:6, Daily, etc.)	1:1	1:6	1:6	Daily	1:6
Sampling season					
Probe height (meters)				7.3	
Distance from supporting structure (meters)					
Distance from obstructions on roof					
Distance from obstructions not on roof (meters)	None	None		None	None
Distance from trees (meters)	None	None		None	None
Distance to furnace or incinerator flue (meters)	None	None		None	None
Distance between collocated monitors (meters)	--	3.0		3.0	3.0
Unrestricted airflow (degrees)	360	360		360	360
Probe material (Teflon, etc.)	Teflon	Teflon		Teflon	Teflon
Residence time (seconds)	10.0	--		--	--
Frequency of flow rate verification for manual PM samplers audit	--	Once per month		Once per month	Once per month

Bakersfield–California (1 of 2) continued

Pollutant	Ozone	PM10 FRM	PM10 FRM	PM2.5 FRM	PM2.5 FRM
Frequency of flow rate verification for automated PM analyzers audit	--	--		--	--
Frequency of one-point QC check (gaseous)	Twice per month	--		--	--
Last Annual Performance Evaluation (gaseous)	10/28/2009	--		--	--
Last two semi-annual flow rate audits for PM monitors	--	01/29/2010		01/29/2010	01/29/2010
Changes planned within the next 18 months (Y/N)	N	N		N	N

Bakersfield–California (2 of 2)

Pollutant	PM2.5 Non-FEM	PM2.5 Non-FEM	NO₂	Toxics	Met Parameters
Parameter code	88501	88501	42602	Many	Many
Spatial scale	Neighborhood		Neighborhood	Neighborhood	Regional
Site type	Population		Population	Population	General
Monitor objective	Other	Other	Unknown	Unknown	Research, Timely/public
Monitor type	SPM Non-Regulatory (Primary)	SPM Non-Regulatory (Collocated)	SLAMS	Many	Many
POC	3	4	1	Many	Many
Method code	731	731	074	Many	Many
Sampling method (List Instrument)	Met One 1020	Met One 1020	API 200A	Xontech 924	
Analysis method	PM2.5 SCC Beta	PM2.5 SCC Beta	CL		
Start date	12/1/2001	12/1/2001			
Operation schedule (e.g. 1:1, 1-Hour)	1-Hour	1-Hour	1:1	1:1	1:1
Sampling season					
Probe height (meters)	2.0	2.0			
Distance from supporting structure (meters)					

Bakersfield–California (2 of 2) continued					
Pollutant	PM2.5 Non-FEM	PM2.5 Non-FEM	NO₂	Toxics	Met Parameters
Distance from obstructions not on roof (meters)	None	None	None	None	None
Distance from trees (meters)	None	None	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None	None	None
Distance between collocated monitors (meters)	3.0		--		--
Unrestricted airflow (degrees)	360	360	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	Teflon	Teflon
Residence time (seconds)	--	--	14.7	--	--
Frequency of flow rate verification for manual PM samplers audit	--	--	--	--	--
Frequency of flow rate verification for automated PM analyzers audit	Twice per month	Twice per month	--	--	--
Frequency of one-point QC check (gaseous)	--	--	Twice per month	Twice per month	--
Last Annual Performance Evaluation (gaseous)	--	--	11/04/2009	12/13/2009	--
Last two semi-annual flow rate audits for PM monitors	01/29/2010		--	--	--
Changes planned within the next 18 months (Y/N)	N	N	N	N	N

Site name	Bakersfield-Muni
AIRS #	060292012
County	Kern
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	Speciated VOC PAMS equipment 6/2012; Met Parameters (PAMS), PM2.5 and PM10 equipment 7/2012; NMHC equipment scheduled start date 10/2012
Pollutant Parameters	Ozone, PM10 FEM, PM2.5 FRM, PM2.5 BAM/non-FEM, CO, NO ₂ , Speciated-VOC for PAMS program, NMHC (PAMS)
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation
Address	2000 South Union Ave., Bakersfield, CA 93307
Latitude	N 35.33132
Longitude	W -119.000044
Elevation (m)	116 m
Location	Portable building in lot
Distance to road	305 m + (west)
Traffic Count	71000
Ground Cover	Paved

Bakersfield-Muni (1 of 3)					
Pollutant	Ozone	PM10 STP FEM	PM10 LC FEM	PM2.5 FRM	PM2.5 Non-FEM (Non-regulatory)
Parameter Code	44201	81102	85101	88101	88502
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	High Concentration	High Concentration	High Concentration	High Concentration	High Concentration
Monitor objective	Standards/Strategy, Research Support, Timely/Public	Standards/Strategy, Research support	Research support	Standards/Strategy, Research Support, Timely/Public	Population Exposure
Monitor type	SLAMS	SLAMS	SLAMS	SLAMS	SPM
POC (or primary monitor for PM2.5 and PM10)	1	1	1	1	3
Method code	087	079	079	145	170
Sampling method (List Instrument)		BAM 1020	BAM 1020	Partisol	BAM 1020
Analysis method		BETA ATTENUATION	BETA ATTENUATION	Gravimetric	BETA ATTENUATION
Start date	6/2012	7/2012	7/2012	7/2012	7/2012
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:1	1:3 and 1:6	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	Seasonal	ALL YEAR
Probe height (meters)					
Distance from supporting structure (meters)					
Distance from obstructions on roof					
Distance from obstructions not on roof (meters)					
Distance from trees (meters)					
Distance to furnace or incinerator flue (meters)					

Site information is still being compiled for Bakersfield-Muni.

Bakersfield-Muni (1 of 3) continued					
Pollutant	Ozone	PM10 STP FEM	PM10 LC FEM	PM2.5 FRM	PM2.5 BAM/Non-FEM
Unrestricted airflow (degrees)					
Probe material (Teflon, etc.)					
Residence time (seconds)					
Frequency of flow rate verification for manual PM samplers audit	_____				_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____			
Last Annual Performance Evaluation (gaseous)		_____			_____
Last two semi-annual flow rate audits for PM monitors	_____				
Changes planned within the next 18 months (Y/N))	N	N	N	N	N

Bakersfield-Muni (2 of 3)				
Pollutant	CO	NO₂	Speciated-VOC (PAMS)	NMHC (PAMS)
Parameter code	42101	42602	Many	43102
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	High concentration	High Concentration	Population
Monitor objective	Standards/strategy	Standards/strategy, research	Research	Research
Monitor type	SLAMS	PAMS	PAMS	PAMS
POC	1	1	1	1
Sampling method (List Instrument)				
Method code	054	074	011	164
Analysis method				

Site information is still being compiled for Bakersfield-Muni.

Bakersfield-Muni (2 of 3) continued				
Pollutant	CO	NO₂	Speciated-VOC (PAMS)	NMHC (PAMS)
Start date	7/2012	7/2012	6/2012	Scheduled for 10/2012
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:3	1:1
Sampling season	ALL YEAR	ALL YEAR	JUN-JUL-AUG	ALL YEAR
Probe height (meters)				
Distance from supporting structure (meters)				
Distance from obstructions on roof				
Distance from obstructions not on roof (meters)				
Distance from trees (meters)				
Distance to furnace or incinerator flue (meters)				
Unrestricted airflow (degrees)				
Probe material (Teflon, etc.)				
Residence time (seconds)				
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)				
Last Annual Performance Evaluation (gaseous)				
Last two semi-annual flow rate audits for PM monitors				
Changes planned within the next 18 months (Y/N)	N	N	N	N

Site information is still being compiled for Bakersfield-Muni.

Bakersfield-Muni (3 of 3)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, Timely/Public
Monitor type	PAMS
POC	1
Method code	Many
Sampling method (List Instrument)	
Analysis method	
Start date	7/2012
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	
Distance from supporting structure (meters)	
Distance from obstructions on roof	
Distance from obstructions not on roof (meters)	
Distance from trees (meters)	
Distance to furnace or incinerator flue (meters)	
Distance between collocated monitors (meters)	
Unrestricted airflow (degrees)	
Probe material (Teflon, etc.)	
Residence time (seconds)	
Frequency of flow rate verification for manual PM samplers audit	
Frequency of flow rate verification for automated PM analyzers audit	
Frequency of one-point QC check (gaseous)	
Last Annual Performance Evaluation (gaseous)	
Last two semi-annual flow rate audits for PM monitors	
Changes planned within the next 18 months (Y/N)	N

Site information is still being compiled for Bakersfield-Muni.

Site name	Edison
AIRS #	060290007
County	Kern
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	1/1/80
Pollutant Parameters	Ozone, NO ₂
Meteorological Parameters	Wind speed, wind direction, outdoor temperature
Address	Johnson Farm-Shed Rd, Edison CA 93320
Latitude	N 35° 20' 45"
Longitude	N 119° 51' 6"
Elevation (m)	172
Location	
Distance to road	450
Traffic Count	50000
Ground Cover	Dirt

Edison			
Pollutant	Ozone	NO₂	Met Parameters
Parameter code	44201	42602	Many
Spatial scale	Neighborhood	Neighborhood	Regional
Site type	High concentration, regional transport	Population	General
Monitor objective	Unknown	Unknown	Research, timely/public
Monitor type	SLAMS	SLAMS	Other
POC	1	1	1
Method code	087	074	Many
Sampling method (List Instrument)	API/Teledyne 400	API 200 A	
Analysis method	UV	CL	
Start date			
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)			
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)	None	None	None
Distance from trees (meters)	18.5	18.5	18.5
Distance to furnace or incinerator flue (meters)	None	None	None
Distance between collocated monitors (meters)	--	--	--
Unrestricted airflow (degrees)	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon
Residence time (seconds)	15	13.6	--
Frequency of flow rate verification for manual PM samplers audit	--	--	--
Frequency of flow rate verification for automated PM analyzers audit	--	--	--
Frequency of one-point QC check (gaseous)	Twice a month	Twice a month	--
Last Annual Performance Evaluation (gaseous)	02/02/2010	02/08/2010	--
Last two semi-annual flow rate audits for PM monitors	--	--	--
Changes planned within the next 18 months (Y/N)	N	N	N

Site name	Lebec
AIRS #	060292009
County	Kern
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	1/20/2009
Pollutant Parameters	PM2.5 Non-FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	1277 Beartrap Road, Lebec, CA 93243
Latitude	34.8415
Longitude	-118.861
Elevation (m)	1063
Location	
Distance to road	
Traffic Count	67000
Ground Cover	Dirt, vegetated

Lebec			
Pollutant	PM2.5 Non-FEM	Met Parameters	
Parameter code	88502	Many	
Spatial scale	Neighborhood	Regional	
Site type	Population	General	
Monitor objective	Timely/public	Research, timely/public	
Monitor type	SPM	SPM	
POC	3	1	
Method code	731	Many	
Sampling method (List Instrument)	BAM 1020		
Analysis method	BETA- ATTENUATION	ITP-125-50 HV, OT-060A-2, BP-092, WD-020C, WS-010C	
Start date	1/27/2009	Outdoor temperature, wind speed, wind direction 12/9/2009	Barometric pressure 1/28/2010
Operation schedule (e.g. 1:1, 1-Hour)	1-Hour	1:1	
Sampling season	ALL YEAR	ALL YEAR	
Probe height (meters)	5.5 m	9.6 m	
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)			
Distance from trees (meters)			
Distance to furnace or incinerator flue (meters)			
Distance between collocated monitors (meters)			
Unrestricted airflow (degrees)	360	360	
Probe material (Teflon, etc.)	ALUMINUM		
Residence time (seconds)			
Frequency of flow rate verification for manual PM samplers audit			
Frequency of flow rate verification for automated PM analyzers audit	BI-WEEKLY		
Frequency of one-point QC check (gaseous)			
Last Annual Performance Evaluation (gaseous)	7/20/2010, 12/14/2010		
Last two semi-annual flow rate audits for PM monitors			
Changes planned within the next 18 months (Y/N)	N		

Site name	Maricopa
AIRS #	060290008
County	Kern
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	7/1/87
Pollutant Parameters	Ozone
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	755 Stanislaus St., Maricopa CA 93352
Latitude	35.05139
Longitude	W -119.403
Elevation (m)	289
Location	In old school building
Distance to road	500 m + (north)
Traffic Count	0
Ground Cover	Gravel

Maricopa		
Pollutant	Ozone	Met Parameters
Parameter code	44201	Many
Spatial scale	Neighborhood	Regional
Site type	Regional transport	General
Monitor objective	Timely/public, standards/strategy, research support	Research, timely/public
Monitor type	SLAMS	SLAMS
POC	1	1
Method code	087	Many
Sampling method (List Instrument)	400 E	ITP-125-50 HV, OT-06A-2, BP-092, WD-020C, WS-010C
Analysis method	UV	
Start date	7/1/1987	7/1/1987
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)	5 m	5 m
Distance from supporting structure (meters)		2.7 m (OT)
Distance from obstructions on roof		5 m (BP) 1.5 m (OT)
Distance from obstructions not on roof (meters)		
Distance from trees (meters)		
Distance to furnace or incinerator flue (meters)		
Distance between collocated monitors (meters)		
Unrestricted airflow (degrees)	360	360 (WD,WS, BP), 270 (OT)
Probe material (Teflon, etc.)	TEFLON	
Residence time (seconds)	5.9	
Frequency of flow rate verification for manual PM samplers audit		
Frequency of flow rate verification for automated PM analyzers audit		
Frequency of one-point QC check (gaseous)	1:1	
Last Annual Performance Evaluation (gaseous)	10/11/2010	
Last two semi-annual flow rate audits for PM monitors		
Changes planned within the next 18 months (Y/N)	N	N

Site name	Oildale
AIRS #	060290232
County	Kern
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	1/1/80
Pollutant Parameters	
	Ozone, PM10 FRM
Meteorological Parameters	
	None
Address	
	3311 Manor St, Oildale CA 93308
Latitude	
	N 35° 28'17"
Longitude	
	N 119° 1' 0"
Elevation (m)	
	183
Location	
Distance to road	
	150 m
Traffic Count	
	10000
Ground Cover	
	Dirt

Oildale		
Pollutant	Ozone	PM10 FRM
Parameter code	44201	81102
Spatial scale	Neighborhood	Neighborhood
Site type	Regional transport	Population
Monitor objective	Highest Concentration	Unknown
Monitor type	SLAMS	SLAMS
POC	1	2
Method code	087	063
Sampling method (List Instrument)	API/Teledyne 400	Sierra Anderson 1200
Analysis method	UV	Gravimetric
Start date		
Operation schedule (e.g. 1:1, 1:3)	1:1	1:6
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)		
Distance from supporting structure (meters)		
Distance from obstructions on roof		
Distance from obstructions not on roof (meters)	None	None
Distance from trees (meters)	None	None
Distance to furnace or incinerator flue (meters)	None	None
Distance between collocated monitors (meters)	--	--
Unrestricted airflow (degrees)	360	360
Probe material (Teflon, etc.)	Teflon	Teflon
Residence time (seconds)	9.0	--
Frequency of flow rate verification for manual PM samplers audit	--	Once a month
Frequency of flow rate verification for automated PM analyzers audit	--	--
Frequency of one-point QC check (gaseous)	Twice a month	--
Last Annual Performance Evaluation (gaseous)	01/06/2009	
Last two semi-annual flow rate audits for PM monitors	--	10/19/2009
Changes planned within the next 18 months (Y/N)	N	N

Site name	Shafter	
AIRS #	060296001	
County	Kern	
Collecting (Operating) Agency	Equipment operated by CARB: Ozone, NO ₂	Equipment operated by SJVAPCD: Meteorology, Speciated VOC, NMHC
Reporting Agency	Data reported by CARB: Ozone, NO ₂	Data reported by SJVAPCD: Speciated VOC, NMHC, Meteorology
Site Start Date	1/1/89	
Pollutant Parameters	Ozone, NO ₂ , Speciated VOC, NMHC	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, solar radiation	
Address	578 Walker St, Shafter CA 93263	
Latitude	N 35° 30' 13"	
Longitude	N 119° 16' 21"	
Elevation (m)	126	
Location	DMV building	
Distance to road	10 m	
Traffic Count		
Ground Cover	Asphalt	

Shafter (1 of 2)				
Pollutant	Ozone	NO₂	Total Speciated VOC	NMHC
Parameter code	44201	42602	43102	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	General/background	Population	Population	Population
Monitor objective	Population Exposure	Population Exposure	Research	Research
Monitor type	PAMS	PAMS	PAMS	PAMS
POC	1	1	1	1
Method code	087	074	164	177
Sampling method (List Instrument)	400E (ARB)	TECO 42, 42C, 42i	910A	55 sampler
Analysis method	UV	CL	GC	GC
Start date	1/1/1989	1/1/1989	7/1/1994	7/1/1994
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:3	1:1
Sampling season	ALL YEAR	ALL YEAR	JUN-JUL-AUG	ALL YEAR
Probe height (meters)	10.0 m	10.0 m	7.0 m	7.0 m
Distance from supporting structure (meters)	_____	_____	_____	_____
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	_____	_____	_____	_____
Distance from trees (meters)	_____	_____	_____	_____
Distance to furnace or incinerator flue (meters)	_____	_____	10.5 m	11.0 m
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	TEFLON	TEFLON	S. STEEL	TEFLON
Residence time (seconds)	10.1	8.9	_____	9.6
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	1:1	_____	1:1
Last Annual Performance Evaluation (gaseous)	05/26/2010 10/13/2010	05/26/2010 10/13/2010	5/10/2010	_____
Last two semi-annual flow rate audits for PM monitors	_____	_____	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Shafter (2 of 2)

Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	Other
POC	1
Method code	Many
Sampling method (List Instrument)	ITP-BA512AABB, OT-06A-2, SRD-Mod. 8-48, WD-020B, WS-010C, BP-092
Analysis method	_____
Start date	1/1/1989
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	10.0 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	_____
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Corcoran–Patterson		
AIRS #	060310004		
County	Kings		
Collecting (Operating) Agency	All equipment operated by SJVAPCD		
Reporting Agency	Data reported by SJVAPCD: PM2.5 FEM, PM10 FEM, Meteorology	Data reported by Ventura County APCD: PM2.5 FRM	
Site Start Date	10/1/96		
Pollutant Parameters	PM10 FEM, PM2.5 FRM, PM2.5 FEM		
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure		
Address	1520 Patterson Ave, Corcoran CA 93212		
Latitude	N 36.10222		
Longitude	W -119.566		
Elevation (m)	62		
Location	Portable building		
Distance to road	35.0 (east), 38.5 (south)		
Traffic Count	1035		
Ground Cover	Gravel		

Corcoran–Patterson (1 of 2)		
Pollutant	PM10 FEM	PM2.5 FRM
Parameter code	81102	88101
Spatial scale	Neighborhood	Neighborhood
Site type	High concentration	High concentration
Monitor objective	Timely/public	Standards/strategy, research support
Monitor type	SLAMS	SLAMS
POC	7	1
Method code	079	120
Sampling method (List Instrument)	TEOM	Partisol
Analysis method	TAPERED ELEMENT	Gravimetric
Start date	8/8/2005	9/6/2012
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1-Hour	1:3, 1:6
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)		
Distance from supporting structure (meters)		
Distance from obstructions on roof		
Distance from obstructions not on roof (meters)		
Distance from trees (meters)	48.0 m	50.0 m
Distance to furnace or incinerator flue (meters)		
Distance between collocated monitors (meters)		
Unrestricted airflow (degrees)	360	360
Probe material (Teflon, etc.)	TEFLON	
Residence time (seconds)		
Frequency of flow rate verification for manual PM samplers audit		
Frequency of flow rate verification for automated PM analyzers audit	BI-WEEKLY	
Frequency of one-point QC check (gaseous)		
Last Annual Performance Evaluation (gaseous)		
Last two semi-annual flow rate audits for PM monitors	8/4/10, 1/26/2011	3/23/2010, 9/30/2010
Changes planned within the next 18 months (Y/N)	N	N

Corcoran–Patterson (2 of 2)		
Pollutant	PM2.5 FEM (For evaluation)	Met Parameters
Parameter code	88101	Many
Spatial scale	Neighborhood	Regional
Site type	High concentration	General
Monitor objective	Timely/public	Research, timely/public
Monitor type	SPM	Many
POC	3	Many
Method code	195	Many
Sampling method (List Instrument)	Grimm 180	ITP - 110-50HV, OT-06A-2, BP-090D, WD-020C, WS-010B
Analysis method	Laser light scattering	
Start date	9/2012	10/1/1996
Operation schedule (e.g. 1:1, 1-Hour)	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)		9.6 m
Distance from supporting structure (meters)		
Distance from obstructions on roof		
Distance from obstructions not on roof (meters)		
Distance from trees (meters)	50.0 m	51.5 m
Distance to furnace or incinerator flue (meters)		
Distance between collocated monitors (meters)	1.2 m	
Unrestricted airflow (degrees)	360	360
Probe material (Teflon, etc.)		
Residence time (seconds)		
Frequency of flow rate verification for manual PM samplers audit		
Frequency of flow rate verification for automated PM analyzers audit		
Frequency of one-point QC check (gaseous)		
Last Annual Performance Evaluation (gaseous)		
Last two semi-annual flow rate audits for PM monitors		
Changes planned within the next 18 months (Y/N)	Y	N

Site name	Hanford-Irwin	
AIRS #	060311004	
County	Kings	
Collecting (Operating) Agency	All equipment operated by SJVAPCD	
Reporting Agency	Data reported by SJVAPCD: Ozone, PM10 FEM, PM2.5 FEM, NO ₂ , Meteorology	Data reported by CARB: PM10 FRM
Site Start Date	10/11/93	
Pollutant Parameters	Ozone, PM10 FRM, PM10 FEM, PM2.5 FEM, NO ₂	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure	
Address	807 S Irwin St, Hanford CA 93230	
Latitude	N 36.31472	
Longitude	W -119.644	
Elevation (m)	82	
Location	School roof	
Distance to road	158 m (south)	
Traffic Count	3383	
Ground Cover	Vegetation/roof material	

Hanford–Irwin (1 of 2)			
Pollutant	Ozone	PM10 FRM	PM10 FEM
Parameter code	44201	81102	81102
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research support	Standards/strategy, research support
Monitor type	SLAMS	SLAMS	SLAMS
POC	1	1	3
Method code	087	063	079
Sampling method (List Instrument)	400 E	Sierra Andersen	TEOM
Analysis method	UV	Gravimetric	
Start date	2/25/2010	10/11/1993	7/14/2010
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1:1	1:6	1-Hour
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	5.5 m	5.5 m	5.5 m
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)			
Distance from trees (meters)			
Distance to furnace or incinerator flue (meters)			
Distance between collocated monitors (meters)			
Unrestricted airflow (degrees)	360	360	
Probe material (Teflon, etc.)	TEFLON		
Residence time (seconds)	12.7		
Frequency of flow rate verification for manual PM samplers audit		QUARTERLY	
Frequency of flow rate verification for automated PM analyzers audit			
Frequency of one-point QC check (gaseous)	1:1		
Last Annual Performance Evaluation (gaseous)	1/24/2011		
Last two semi-annual flow rate audits for PM monitors		9/21/2010, 1/24/2011	
Changes planned within the next 18 months (Y/N)	N	N	N

Hanford–Irwin (2 of 2)

Pollutant	PM2.5 FEM (Regulatory)	NO₂	Met Parameters
Parameter code	88101	42602	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Research Support Timely/Public	Timely/public, standards/strategy, research support	Timely/public, standards/strategy, research support
Monitor type	SPM	SLAMS	Many
POC	3	1	Many
Method code	170	074	Many
Sampling method (List Instrument)	BAM 1020	API 200 E	ITP-110-50HV, OT-06A-2, BP-092, WD-020C, WS- 010C
Analysis method	BETA	CL	
Start date	2/25/2010	2/25/2010	2/25/2010
Operation schedule (e.g. 1:1, 1-Hour)	1-Hour	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	5.5 m	5.5 m	9.6 m
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)			
Distance from trees (meters)			
Distance to furnace or incinerator flue (meters)			
Distance between collocated monitors (meters)			
Unrestricted airflow (degrees)	360	360	360
Probe material (Teflon, etc.)	ALUMINUM	TEFLON	
Residence time (seconds)		14.8	
Frequency of flow rate verification for manual PM samplers audit			
Frequency of flow rate verification for automated PM analyzers audit	BI-WEEKLY		
Frequency of one-point QC check (gaseous)		1:1	
Last Annual Performance Evaluation (gaseous)		1/24/2011	
Last two semi-annual flow rate audits for PM monitors	6/9/2010, 1/24/2011		
Changes planned within the next 18 months (Y/N)	N	N	N

Site name	Madera–City
AIRS #	060392010
County	Madera
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	6/1/2010
Pollutant Parameters	Ozone, PM10 FEM, PM2.5 FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation
Address	28261 Avenue 14, Madera CA 93638
Latitude	N 36.953282
Longitude	-120.03421
Elevation (m)	84
Location	Portable building
Distance to road	686 m
Traffic Count	
Ground Cover	Asphalt

Madera—City				
Pollutant	Ozone	PM10 FEM	PM2.5 FEM	Met Parameters
Parameter code	44201	85101	88101	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	General/background	Population	Population	General/background
Monitor objective	Timely/public, standards/strategy, research support	Timely/public	Timely/public	Timely/public, standards/strategy, research support
Monitor type	SLAMS	SLAMS	SPM	SLAMS
POC	1	3	3	1
Method code	087	079	170	Many
Sampling method (List Instrument)	400 E	TEOM	BAM	ITP-110-50HV, OT-06A-2, BP-092, WD-020C, WS-010C
Analysis method	UV	TAPERED ELEMENT	BETA	
Start date	6/1/2010	6/1/2010	6/1/2010	
Operation schedule (e.g. 1:1, 1-Hour)	1:1	1-Hour	1-Hour	
Sampling season	ALL YEAR	ALL YEAR		
Probe height (meters)	5.5 m	5.5 m	5.5 m	
Distance from supporting structure (meters)	0.1 m	0.5 m	0.5 m	
Distance from obstructions on roof				
Distance from obstructions not on roof (meters)	39 m	35 m	37.5 m	
Distance from trees (meters)	13 m	15.5 m	14.5 m	
Distance to furnace or incinerator flue (meters)	48 m	43.5 m	45 m	
Distance between collocated monitors (meters)				
Unrestricted airflow (degrees)	360	360	360	
Probe material (Teflon, etc.)	TEFLON	STAINLESS STEEL	ALUMINUM	
Residence time (seconds)	13.5			
Frequency of flow rate verification for manual PM samplers audit				
Frequency of flow rate verification for automated PM analyzers audit		BI-WEEKLY	BI-WEEKLY	
Frequency of one-point QC check (gaseous)	1:1			

Madera—City (continued)

Pollutant	Ozone	PM10 FEM	PM2.5 FEM	Met Parameters
Last Annual Performance Evaluation (gaseous)	7/22/2010			
Last two semi-annual flow rate audits for PM monitors	7/22/2010, 12/7/2010			
Changes planned within the next 18 months (Y/N)	N	N	N	N

Site name	Madera–Pump Yard
AIRS #	060390004
County	Madera
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	10/1/99
Pollutant Parameters	Ozone, NO ₂ , Speciated VOC, NMHC, Carbonyls
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation
Address	Av 8 and Road 29 1/2, Madera CA 93637
Latitude	N 36.86722
Longitude	W -120.01
Elevation (m)	85
Location	Portable building, outside school
Distance to road	16.0 m (west)
Traffic Count	0
Ground Cover	Dirt, paved

Madera–Pump Yard (1 of 2)				
Pollutant	Ozone	NO₂	Speciated VOC	NMHC
Parameter code	44201	42602	43102	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	General/background	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research	Research	Research
Monitor type	PAMS	PAMS	PAMS	PAMS
POC	1	1	1	1
Method code	087	074	164	177
Sampling method (List Instrument)	400E	42	910A	55C
Analysis method	UV	CL	GC	GC
Start date	10/1/1999	10/1/1999	10/1/1999	10/1/1999
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:3	1:1
Sampling season	ALL YEAR	ALL YEAR	JUN-JUL-AUG	ALL YEAR
Probe height (meters)	9.0 m	9.0 m	6.0 m	6.0 m
Distance from supporting structure (meters)	_____	_____	_____	_____
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	_____	_____	_____	_____
Distance from trees (meters)	41.0 m	41.0 m	41.5 m	41.5 m
Distance to furnace or incinerator flue (meters)	_____	_____	_____	_____
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	TEFLON	TEFLON	S. STEEL	TEFLON
Residence time (seconds)	16.9	15.0		16.9
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	_____	_____
Frequency of one-point QC check (gaseous)	1:1	1:1	_____	1:1
Last Annual Performance Evaluation (gaseous)	11/4/2010	11/4/2010	5/10/2010	_____
Last two semi-annual flow rate audits for PM monitors	_____	_____	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Madera–Pump Yard (2 of 2)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	Many
POC	Many
Method code	Many
Sampling method (List Instrument)	ITP-125-125-HV, OT-060A-2, BP-092, RH-HMP45D, SRD-Mod. 8-48, WD-020C, WS-010C
Analysis method	_____
Start date	10/1/1999
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	9.0 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	41.0 m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Merced–Coffee
AIRS #	060470003
County	Merced
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	10/1/91
Pollutant Parameters	Ozone, PM2.5 FEM, NO ₂
Meteorological Parameters	Wind speed, wind direction, outdoor temperature
Address	385 S. Coffee St., Merced CA 95340
Latitude	37.28167
Longitude	-120.434
Elevation (m)	86
Location	Portable building, residential area
Distance to road	20 m (east)
Traffic Count	0
Ground Cover	Dirt, vegetated

Merced-Coffee				
Pollutant	Ozone	PM2.5 FEM	NO₂	Met Parameters
Parameter code	44201	88101	42602	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Regional
Site type	Population	Population	Population	General
Monitor objective	Timely/public, standards/strategy, research support	Timely/public	Standards/strategy	Research, timely/public
Monitor type	SLAMS	SPM	SLAMS	Other
POC	1	3	1	Many
Method code	087	170	074	Many
Sampling method (List Instrument)	400E	BAM 1020	42 C	ITP - 110-50HV, OT-06A-2, WD-020C, WS-010C
Analysis method	UV	BETA	CL	_____
Start date	10/1/1991		10/1/1991	10/1/1991
Operation schedule (e.g. 1:1, 1-Hour)	1:1	1-Hour	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	5.0 m	5.5 m	5.0 m	8.0 m
Distance from supporting structure (meters)	_____		_____	_____
Distance from obstructions on roof	_____		_____	_____
Distance from obstructions not on roof (meters)	_____		_____	_____
Distance from trees (meters)	13.5 m	13.5 m	13.5 m	13.5 m
Distance to furnace or incinerator flue (meters)	_____		_____	_____
Distance between collocated monitors (meters)	_____		_____	_____
Unrestricted airflow (degrees)	345	345	345	345
Probe material (Teflon, etc.)	TEFLON	ALUMINUM	TEFLON	_____
Residence time (seconds)	11.9		13.7	_____
Frequency of flow rate verification for manual PM samplers audit	_____		_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	BI-WEEKLY	_____	_____
Frequency of one-point QC check (gaseous)	1:1		1:1	_____
Last Annual Performance Evaluation (gaseous)	10/5/2010		10/5/2011	_____

Merced–Coffee (continued)				
Pollutant	Ozone	PM2.5 FEM	NO₂	Met Parameters
Last two semi-annual flow rate audits for PM monitors	_____	10/5/2010, 4/25/2011	_____	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Site name	Merced—M Street	
AIRS #	060472510	
County	Merced	
Collecting (Operating) Agency	All equipment operated by SJVAPCD	
Reporting Agency	Data reported by CARB: PM10 FRM	Data reported by Ventura County APCD: PM2.5 FRM
Site Start Date	4/1/99	
Pollutant Parameters	PM10 FRM, PM2.5 FRM	
Meteorological Parameters	None	
Address	2334 M Street, Merced CA 95340	
Latitude	37.30861	
Longitude	-120.48	
Elevation (m)	35	
Location	Roof, post office	
Distance to road	100 m (railroad, east); PM10: 66 m (north) & 72.5 m (south); PM2.5: 52.5 m (north), 87 m (south)	
Traffic Count	22400	
Ground Cover	Gravel	

Merced—M Street		
Pollutant	PM10 FRM	PM2.5 FRM
Parameter code	81102	88101
Spatial scale	Neighborhood	Neighborhood
Site type	Representative concentration	Representative concentration
Monitor objective	Standards/strategy, research support	Standards/strategy, research support
Monitor type	SLAMS	SLAMS
POC	1	1
Method code	063	120
Sampling method (List Instrument)	Sierra Andersen	Partisol in service on 9/14/2010
Analysis method	GRAVI-METRIC	GRAVI-METRIC
Start date	4/1/1999	4/1/1999
Operation schedule (e.g. 1:1, 1:3)	1:6	1:3, 1:6
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)	8.7 m	8.7 m
Distance from supporting structure (meters)	_____	_____
Distance from obstructions on roof	_____	_____
Distance from obstructions not on roof (meters)	_____	_____
Distance from trees (meters)	_____	_____
Distance to furnace or incinerator flue (meters)	38.5 m	45.0 m
Distance between collocated monitors (meters)	_____	_____
Unrestricted airflow (degrees)	360	360
Probe material (Teflon, etc.)	_____	_____
Residence time (seconds)	_____	_____
Frequency of flow rate verification for manual PM samplers audit	QUARTERLY	MONTHLY
Frequency of flow rate verification for automated PM analyzers audit	_____	_____
Frequency of one-point QC check (gaseous)	_____	_____
Last Annual Performance Evaluation (gaseous)	_____	_____
Last two semi-annual flow rate audits for PM monitors	10/4/2010, 3/1/2011	10/4/2010, 4/5/2011
Changes planned within the next 18 months (Y/N)	N	N

Site name	Manteca
AIRS #	060772010
County	San Joaquin
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	11/16/10
Pollutant Parameters	PM2.5 FEM; PM10 FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	530 Fishback Rd., Manteca CA 95337
Latitude	37.7933804512
Longitude	-121.24778867
Elevation (m)	11
Location	Portable building, cement pad, dirt, corner near school
Distance to road	12 M to Fishback Rd
Traffic Count	
Ground Cover	Sidewalk, dirt, grass

Manteca			
Pollutant	PM2.5 FEM	PM10 FEM	Met Parameters
Parameter code	88101	85101	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Standards/Strategy Research Support	Standards/Strategy Research Support	Standards/Strategy Research Support
Monitor type	SLAMS	SPM	Non-regulatory
POC	3	3	1
Method code	170	079	Many
Sampling method (List Instrument)	BAM 1020	TEOM 1405	ITP-125-125,OT-06A-2;BP-092; WD-020C;WS-010C
Analysis method			
Start date	11/16/10	5/2/11	11/16/10
Operation schedule (e.g. 1:1, 1-Hour)	1-Hour	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	6M	6M	10M
Distance from supporting structure (meters)	1.5 M	1.5 M	
Distance from obstructions on roof	0	0	
Distance from obstructions not on roof (meters)	87.5 M	87.5 M	87.5 M
Distance from trees (meters)	53.5 M	53.5 M	53.5 M
Distance to furnace or incinerator flue (meters)	n/a	n/a	n/a
Distance between collocated monitors (meters)	n/a	n/a	n/a
Unrestricted airflow (degrees)	360	360	360
Probe material (Teflon, etc.)	Aluminum	Teflon	
Residence time (seconds)			
Frequency of flow rate verification for manual PM samplers audit			
Frequency of flow rate verification for automated PM analyzers audit	Bi-weekly	Bi-Weekly	
Frequency of one-point QC check (gaseous)	n/a	n/a	n/a

Manteca (continued)			
Pollutant	PM2.5 FEM	PM10 FEM	Met Parameters
Last Annual Performance Evaluation (gaseous)	n/a	n/a	n/a
Last two semi-annual flow rate audits for PM monitors	11/10/10	4/15/11	
Changes planned within the next 18 months (Y/N)	N	N	N

Site name	Stockton–Hazelton
AIRS #	060771002
County	San Joaquin
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	
Pollutant Parameters	Ozone, PM10 FRM, PM2.5FRM, PM2.5 FEM, CO, NO ₂ , Toxics
Meteorological Parameters	Outdoor temperature
Address	1593 E. Hazelton St., Stockton CA 95205
Latitude	N 37° 57' 6"
Longitude	N 121° 16' 8"
Elevation (m)	4
Location	
Distance to road	62 m
Traffic Count	1000
Ground Cover	Roof

Stockton–Hazelton (1 of 2)			
Pollutant	Ozone	PM10 FRM	PM2.5 FEM
Parameter code	44201	81102	88101
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Unknown	Highest Concentration	Population Exposure
Monitor type	SLAMS	SLAMS	SLAMS
POC	1	2	3
Method code	087	063	170
Sampling method (List Instrument)	API/Teledyne 400	Sierra Anderson 1200	Met One 1020
Analysis method	UV	Gravimetric	Beta Attenuation
Start date			
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1:1	1:6	1-Hour
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)			
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)	None	None	None
Distance from trees (meters)	0.0	0.0	0.0
Distance to furnace or incinerator flue (meters)	None	None	None
Distance between collocated monitors (meters)	--	--	--
Unrestricted airflow (degrees)	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon
Residence time (seconds)	8.5	--	--
Frequency of flow rate verification for manual PM samplers audit	--	Once a month	--
Frequency of flow rate verification for automated PM analyzers audit	--	--	Twice a month
Frequency of one-point QC check (gaseous)	Twice a month	--	--
Last Annual Performance Evaluation (gaseous)	10/25/2010	--	--
Last two semi-annual flow rate audits for PM monitors	--	08/23/2010	10/26/2010
Changes planned within the next 18 months (Y/N)	N	N	N

Stockton–Hazelton (2 of 2)					
Pollutant	CO	NO₂	Toxics SN20021014	Toxics SN20021016	Met Parameters
Parameter code	42101	42602	Many	Many	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood	Regional
Site type	Population	Population	Population	Population	General
Monitor objective	Population Exposure	Unknown	Unknown	Unknown	Research, timely/public
Monitor type	SLAMS	SLAMS	Many	Many	Many
POC	1	2	Many	Many	Many
Method code	054	074	Many	Many	Many
Sampling method (List Instrument)	Dasibi 3008	Teco 42, 42C, 42i	Xontech 924	Xontech 924	
Analysis method	IR	CL			
Start date					
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	1:1	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)					
Distance from supporting structure (meters)					
Distance from obstructions on roof					
Distance from obstructions not on roof (meters)	None	None	None	None	None
Distance from trees (meters)	0.0	0.0	0.0.	0.0.	0.0.
Distance to furnace or incinerator flue (meters)	None	None	None	None	None
Distance between collocated monitors (meters)	--	--	2	2	--
Unrestricted airflow (degrees)	360	360	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	Teflon	Teflon
Residence time (seconds)	7.9	8.7	--	--	--
Frequency of flow rate verification for manual PM samplers audit					
Frequency of flow rate verification for automated PM analyzers audit					
Frequency of one-point QC check (gaseous)					
Last Annual Performance Evaluation (gaseous)	10/25/2010	10/25/2010	10/26/2010	10/26/2010	

Stockton–Hazelton (2 of 2) continued					
Pollutant	CO	NO₂	Toxics SN20021014	Toxics SN20021016	Met Parameters
Last two semi-annual flow rate audits for PM monitors					
Changes planned within the next 18 months (Y/N)	N	N	N	N	N

Site name	Stockton–Wagner/Holt
AIRS #	060773010
County	San Joaquin
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by CARB
Site Start Date	10/1/96
Pollutant Parameters	PM10 FRM
Meteorological Parameters	None
Address	8778 Brattle Pl., Stockton CA 95209
Latitude	38.02972
Longitude	-121.353
Elevation (m)	7
Location	On school roof
Distance to road	30 m (north), 60 m (west)
Traffic Count	0
Ground Cover	Felt/rubber

Stockton–Wagner/Holt	
Pollutant	PM10 FRM
Parameter code	81102
Spatial scale	Neighborhood
Site type	Population
Monitor objective	Standards/strategy, research support
Monitor type	SLAMS
POC	1
Method code	063
Sampling method (List Instrument)	Anderson
Analysis method	GRAVI-METRIC
Start date	10/1/1996
Operation schedule (e.g. 1:1, 1:3)	1:6
Sampling season	ALL YEAR
Probe height (meters)	10 m
Distance from supporting structure (meters)	1.5 m
Distance from obstructions on roof	11.8 m
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	12.5 m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	280
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	QUARTERLY
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	11/10/2010, 3/10/2011
Changes planned within the next 18 months (Y/N)	Y

Site name	Tracy–Airport
AIRS #	060773005
County	San Joaquin
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	1/11/05
Pollutant Parameters	Ozone, PM10 FEM, PM2.5 Non-FEM, NO ₂
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure, radio acoustic sounding system (RASS)
Address	5749 S. Tracy Blvd., Tracy CA 95376
Latitude	37.682682
Longitude	-121.442393
Elevation (m)	30
Location	Municipal airport yard
Distance to road	685.7 m
Traffic Count	868
Ground Cover	Gravel

Tracy–Airport (1 of 2)				
Pollutant	Ozone	PM10 FEM	PM2.5 Non-FEM	NO₂
Parameter code	44201	81102	88502	42602
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Regional transport	Regional transport	Regional transport	Population
Monitor objective	Timely/public, standards/strategy, research support	Timely/public	Timely/public	Standards/strategy
Monitor type	SLAMS	SPM	SPM	SLAMS
POC	1	3	3	1
Method code	087	079	731	074
Sampling method (List Instrument)	400E	TEOM	BAM 1020	42C
Analysis method	UV	TAPERED ELEMENT	BETA-ATTENUATION	CL
Start date	1/11/2005	10/25/2005	1/11/2005	1/11/2005
Operation schedule (e.g. 1:1, 1-Hour)	1:1	1-Hour	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	7.0 m	6.5 m	6.5 m	7.0 m
Distance from supporting structure (meters)	_____	_____	_____	
Distance from obstructions on roof	_____	_____	_____	
Distance from obstructions not on roof (meters)	42.7 m	42.7 m	42.7 m	42.7 m
Distance from trees (meters)	41.5 m	41.5 m	41.5 m	41.5 m
Distance to furnace or incinerator flue (meters)	_____	_____	_____	
Distance between collocated monitors (meters)	_____	3.5m	3.5m	
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	TEFLON	TEFLON	ALUMINUM	TEFLON
Residence time (seconds)	10.6	_____	_____	13.8
Frequency of flow rate verification for manual PM samplers audit	_____	_____	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	BI-WEEKLY	BI-WEEKLY	_____
Frequency of one-point QC check (gaseous)	1:1	_____	_____	1:1
Last Annual Performance Evaluation (gaseous)	4/6/2011	_____	_____	4/6/2011

Tracy–Airport (1 of 2) continued				
Pollutant	Ozone	PM10 FEM	PM2.5 Non-FEM	NO₂
Last two semi-annual flow rate audits for PM monitors	_____	7/1/2010, 4/6/2011	7/26/2010, 4/6/2011	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Tracy–Airport (2 of 2)	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	SLAMS
POC	Many
Method code	Many
Sampling method (List Instrument)	ITP-125-125 HV, OT-06A-2, BP-092, WD-020C, WS-010C
Analysis method	_____
Start date	1/11/2005
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	10 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	48.7m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	360
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____

Tracy–Airport (2 of 2) continued	
Pollutant	Met Parameters
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Modesto–14th Street
AIRS #	060990005
County	Stanislaus
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	1/1/81
Pollutant Parameters	Ozone, PM10 FRM, PM2.5 FRM, PM2.5 FEM, CO
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	814 14th Street, Modesto CA 95354
Latitude	N 37° 38' 31"
Longitude	W 120° 59' 39"
Elevation (m)	27
Location	
Distance to road	13 m
Traffic Count	10000
Ground Cover	Roof

Modesto–14th Street (1 of 2)				
Pollutant	Ozone	PM10 FRM	PM2.5 FRM	PM2.5 FEM
Parameter code	44201	81102	88101	88101
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population	Population
Monitor objective	Unknown	Unknown	Population Exposure	Population Exposure
Monitor type	SLAMS	SLAMS	SLAMS	SLAMS
POC	1	3	1	3
Method code	087	063	118	170
Sampling method (List Instrument)	API/Teledyne 400	Sierra Anderson 1200	R&P 2025	Met One 1020
Analysis method	UV	Gravimetric	Gravimetric	Beta Attenuation
Start date				
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1:1	1:6	1:3	1-Hour
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)				
Distance from supporting structure (meters)				
Distance from obstructions on roof				
Distance from obstructions not on roof (meters)	None	None	None	None
Distance from trees (meters)	None	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None	None
Distance between collocated monitors (meters)	--	--	--	--
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	Teflon
Residence time (seconds)	5.9	--	--	--
Frequency of flow rate verification for manual PM samplers audit	--	Once a month	Once a month	--
Frequency of flow rate verification for automated PM analyzers audit	--	--	--	Twice a month
Frequency of one-point QC check (gaseous)	Twice a month	--	--	--
Last Annual Performance Evaluation (gaseous)	09/28/2010	--	--	--
Last two semi-annual flow rate audits for PM monitors	--	10/26/2010	10/12/2010	09/28/2010
Changes planned within the next 18 months (Y/N)	N	N	N	N

Modesto–14th Street (2 of 2)			
Pollutant	CO	PM2.5 Speciation	Met Parameters
Parameter code	42101	Many	Many
Spatial scale	Neighborhood	Neighborhood	Regional
Site type	Population		General
Monitor objective	Unknown		
Monitor type	SLAMS	Supplemental speciation	SLAMS
POC	1	5	Many
Method code	067	811/812	Many
Sampling method (List Instrument)	Dasibi 3008		
Analysis method	IR	Gravimetric	
Start date			
Operation schedule (e.g. 1:1, 1:3)	1:1		1:1
Sampling season	ALL YEAR		ALL YEAR
Probe height (meters)			
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)	None		None
Distance from trees (meters)	None		None
Distance to furnace or incinerator flue (meters)	None		None
Distance between collocated monitors (meters)	--		--
Unrestricted airflow (degrees)	360		360
Probe material (Teflon, etc.)	Teflon		Teflon
Residence time (seconds)	5.4		--
Frequency of flow rate verification for manual PM samplers audit	--		--
Frequency of flow rate verification for automated PM analyzers audit	--		--

Modesto–14th Street (2 of 2) continued			
Pollutant	CO	PM2.5 Speciation	Met Parameters
Frequency of one-point QC check (gaseous)	Twice a month		--
Last Annual Performance Evaluation (gaseous)	09/28/2010		--
Last two semi-annual flow rate audits for PM monitors	--		--
Changes planned within the next 18 months (Y/N)	N	N	N

Site name	Turlock	
AIRS #	060990006	
County	Stanislaus	
Collecting (Operating) Agency	All equipment operated by SJVAPCD	
Reporting Agency	Data reported by SJVAPCD: Ozone, PM2.5 FEM, CO, NO ₂ , Meteorology	Data reported by CARB: PM10 FRM
Site Start Date	1994	
Pollutant Parameters	Ozone, PM10 FRM, PM2.5 FEM, CO, NO ₂	
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure	
Address	1034 S. Minaret St., Turlock CA 95380	
Latitude	37.48806	
Longitude	-120.836	
Elevation (m)	30	
Location	Portable building – neighborhood	
Distance to road	32 m (east), 4 m (north)	
Traffic Count	670	
Ground Cover	Gravel	

Turlock (1 of 2)				
Pollutant	Ozone	PM10 FRM	PM2.5 FEM	CO
Parameter code	44201	81102	88101	42101
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Standards/strategy, research support	Timely/public	Standards/strategy
Monitor type	SLAMS	SLAMS	SLAMS	SLAMS
POC	1	1	3	1
Method code	087	063	170	054
Sampling method (List Instrument)	400E	Sierra Andersen	1020	48C
Analysis method	UV	GRAVIMETRIC	Beta Attenuation	IR
Start date	4/1/2000	9/14/2006	9/14/2006	4/1/2000
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1:1	1:6	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	7 m	6.5 m	5.4 m	7 m
Distance from supporting structure (meters)	_____	_____	_____	_____
Distance from obstructions on roof	_____	_____	_____	_____
Distance from obstructions not on roof (meters)	_____	_____	_____	_____
Distance from trees (meters)	37.5 m	37.5 m	37.5 m	37.5 m
Distance to furnace or incinerator flue (meters)	48.0 m	48.0 m	48.0 m	48.0 m
Distance between collocated monitors (meters)	_____	_____	_____	_____
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	TEFLON	_____	ALUMINUM	TEFLON
Residence time (seconds)	14.8	_____	_____	14
Frequency of flow rate verification for manual PM samplers audit	_____	QUARTERLY	_____	_____
Frequency of flow rate verification for automated PM analyzers audit	_____	_____	BI-WEEKLY	_____
Frequency of one-point QC check (gaseous)	1:1	_____	_____	1:1
Last Annual Performance Evaluation (gaseous)	10/7/2010	_____	_____	10/7/2010

Turlock (1 of 2) continued				
Pollutant	Ozone	PM10 FRM	PM2.5 FEM	CO
Last two semi-annual flow rate audits for PM monitors	_____	10/18/2010, 2/4/2011	4/28/2010, 9/27/2010	_____
Changes planned within the next 18 months (Y/N)	N	N	N	N

Turlock (2 of 2)			
Pollutant	NO₂	Met Parameters	
Parameter code	42602	Many	
Spatial scale	Neighborhood	Regional	
Site type	Population	General	
Monitor objective	Standards/strategy	Research, timely/public	
Monitor type	SLAMS	Other	
POC	1	1	
Method code	074	Many	
Sampling method (List Instrument)	42C	ITP-125-125 HV, OT-060A-2, BP-090D, WD-020C, WS-010C	
Analysis method	CL	_____	
Start date	4/1/2000	Wind speed and wind direction 4/1/2000	Outdoor temperature and barometric pressure 9/3/2008
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1	
Sampling season	ALL YEAR	ALL YEAR	
Probe height (meters)	7 m	7.7 m	7 m (OT)
Distance from supporting structure (meters)	_____	_____	
Distance from obstructions on roof	_____	_____	
Distance from obstructions not on roof (meters)	_____	_____	
Distance from trees (meters)	37.5 m	37.5 m	
Distance to furnace or incinerator flue (meters)	48.0 m	48.0 m	
Distance between collocated monitors (meters)	_____	_____	
Unrestricted airflow (degrees)	360	360	
Probe material (Teflon, etc.)	TEFLON	_____	
Residence time (seconds)	14.1	_____	
Frequency of flow rate verification for manual PM samplers audit	_____	_____	

Turlock (2 of 2) continued

Pollutant	NO₂	Met Parameters
Frequency of flow rate verification for automated PM analyzers audit	_____	_____
Frequency of one-point QC check (gaseous)	1:1	_____
Last Annual Performance Evaluation (gaseous)	3/24/2009	_____
Last two semi-annual flow rate audits for PM monitors	_____	_____
Changes planned within the next 18 months (Y/N)	N	N

Site name	Porterville
AIRS #	061072010
County	Tulare
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	3/8/2010
Pollutant Parameters	Ozone, PM2.5 FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	1839 S. Newcomb St., Porterville CA 93257
Latitude	N 36.031031
Longitude	W -119.055018
Elevation (m)	41
Location	Portable building on parking lot
Distance to road	160 m (east)
Traffic Count	
Ground Cover	Paved

Porterville			
Pollutant	Ozone	PM2.5 FEM	Met Parameters
Parameter code	44201	88101	Many
Spatial scale	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population
Monitor objective	Timely/public, standards/strategy, research support	Timely/public	Timely/public
Monitor type	SLAMS	SPM	SLAMS
POC	1	3	1
Method code	087	731	Many
Sampling method (List Instrument)	400 E	1020	ITP-125-125 HV, OT-060A-2, BP-092, WD-020C, WS-010C
Analysis method	UV	BETA-ATTENUATION	
Start date	3/8/2010	3/8/2010	3/8/2010
Operation schedule (e.g. 1:1, 1:3, 1-Hour)	1:1	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	5.4 m	5.4 m	9.6 m
Distance from supporting structure (meters)			
Distance from obstructions on roof			
Distance from obstructions not on roof (meters)	10 m	10 m	
Distance from trees (meters)			
Distance to furnace or incinerator flue (meters)			
Distance between collocated monitors (meters)			
Unrestricted airflow (degrees)	345	345	345
Probe material (Teflon, etc.)	TEFLON	ALUMINUM	
Residence time (seconds)	6.0		
Frequency of flow rate verification for manual PM samplers audit			
Frequency of flow rate verification for automated PM analyzers audit		BI-WEEKLY	
Frequency of one-point QC check (gaseous)	1:1		
Last Annual Performance Evaluation (gaseous)	7/20/2010		
Last two semi-annual flow rate audits for PM monitors	7/20/2010, 9/29/2010		
Changes planned within the next 18 months (Y/N)	N	N	N

Site name	Sequoia–Ash Mountain
AIRS #	061070009
County	Tulare
Collecting (Operating) Agency	All equipment operated by NPS
Reporting Agency	All data reported by NPS
Site Start Date	1/1/00
Pollutant Parameters	Ozone, PM2.5 FRM, PM2.5 FEM, CASTnet (dry deposition)
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, solar radiation
Address	Ash Mountain, Sequoia National Park CA
Latitude	N 36.48944
Longitude	-118.829
Elevation (m)	535
Location	
Distance to road	122 m
Traffic Count	1000
Ground Cover	Dirt

Sequoia–Ash Mountain				
Pollutant	Ozone	PM2.5 FRM	PM2.5 FEM	Met Parameters
Parameter code	44201	88501	88502	Many
Spatial scale	Regional	Regional	Regional	Regional
Site type	Regional transport	Regional transport	Regional transport	General
Monitor objective	Timely/public, standards/strategy, research support	Research support	Timely/public	Research, timely/public
Monitor type	Non-EPA Federal	Non-EPA Federal	Non-EPA Federal	Non-EPA Federal
POC	1	1	1	1
Method code	047	750	707	Many
Sampling method (List Instrument)	TECO 49, 49C			
Analysis method	UV	Gravimetric	Beta Attenuation	
Start date	2000	1992	2007	
Operation schedule (e.g. Hourly, 1:1, 1:3, 1-Hour)	1:1	1:6	1-Hour	1:1
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)	10	5	4	
Distance from supporting structure (meters)	3	2	1.5	
Distance from obstructions on roof	5			
Distance from obstructions not on roof (meters)	--			
Distance from trees (meters)	15 – 20	10 - 20	15 – 20	
Distance to furnace or incinerator flue (meters)	305	305	305	
Distance between collocated monitors (meters)	3	3	3	
Unrestricted airflow (degrees)	360	360	360	
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	
Residence time (seconds)	--			
Frequency of flow rate verification for manual PM samplers audit				
Frequency of flow rate verification for automated PM analyzers audit				
Frequency of one-point QC check (gaseous)				
Last Annual Performance Evaluation (gaseous)	March 2009		December 2008, August 2007	
Last two semi-annual flow rate audits for PM monitors				
Changes planned within the next 18 months (Y/N)	N	N	N	N

Site name	Sequoia–Lower Kaweah
AIRS #	061070006
County	Tulare
Collecting (Operating) Agency	All equipment operated by NPS
Reporting Agency	All data reported by NPS
Site Start Date	4/1/1981
Pollutant Parameters	Ozone, NADP (wet deposition)
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, solar radiation
Address	Lower Kaweah Campground, Sequoia National Park, CA
Latitude	N 36.56611
Longitude	-118.7776
Elevation (m)	1890
Location	
Distance to road	1500 m
Traffic Count	5000
Ground Cover	Dirt

Sequoia–Lower Kaweah		
Pollutant	Ozone	Met Parameters
Parameter code	44201	Many
Spatial scale	Regional	Regional
Site type	Regional transport	General
Monitor objective	Timely/public, standards/strategy, research support	Research, timely/public
Monitor type	Non-EPA Federal	Non-EPA Federal
POC	1	1
Method code	087	Many
Sampling method (List Instrument)	TECO 49, 49C	
Analysis method		
Start date	1982	
Operation schedule (e.g. 1:1, 1:3)	1:1	1:1
Sampling season	ALL YEAR	ALL YEAR
Probe height (meters)	10	
Distance from supporting structure (meters)		
Distance from obstructions on roof		
Distance from obstructions not on roof (meters)		
Distance from trees (meters)	15 – 20	
Distance to furnace or incinerator flue (meters)	750	
Distance between collocated monitors (meters)		
Unrestricted airflow (degrees)		
Probe material (Teflon, etc.)	Teflon	
Residence time (seconds)		
Frequency of flow rate verification for manual PM samplers audit		
Frequency of flow rate verification for automated PM analyzers audit		
Frequency of one-point QC check (gaseous)		
Last Annual Performance Evaluation (gaseous)	March 2009	
Last two semi-annual flow rate audits for PM monitors		
Changes planned within the next 18 months (Y/N)	N	N

Site name	Visalia–Airport
AIRS #	061073000
County	Tulare
Collecting (Operating) Agency	All equipment operated by SJVAPCD
Reporting Agency	All data reported by SJVAPCD
Site Start Date	September 2000
Pollutant Parameters	None
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, relative humidity, barometric pressure, solar radiation, radio acoustic sounding system (RASS)
Address	Airport, Visalia CA 93291
Latitude	N 36.31389
Longitude	W -119.392
Elevation (m)	90
Location	Municipal airport yard
Distance to road	81 m (west), 29.5 (parking lot)
Traffic Count	32000
Ground Cover	Vegetated

Visalia–Airport	
Pollutant	Met Parameters
Parameter code	Many
Spatial scale	Regional
Site type	General
Monitor objective	Research, timely/public
Monitor type	PAMS
POC	1
Method code	Many
Sampling method (List Instrument)	ITP-125-125 HV, OT-06A-2, BP-090D, RH-083-0-6, SRD-Mod. 8-48, WD-020C, WS-010B
Analysis method	_____
Start date	10/1/1999
Operation schedule (e.g. 1:1, 1:3)	1:1
Sampling season	ALL YEAR
Probe height (meters)	10 m
Distance from supporting structure (meters)	_____
Distance from obstructions on roof	_____
Distance from obstructions not on roof (meters)	_____
Distance from trees (meters)	8 m
Distance to furnace or incinerator flue (meters)	_____
Distance between collocated monitors (meters)	_____
Unrestricted airflow (degrees)	270
Probe material (Teflon, etc.)	_____
Residence time (seconds)	_____
Frequency of flow rate verification for manual PM samplers audit	_____
Frequency of flow rate verification for automated PM analyzers audit	_____
Frequency of one-point QC check (gaseous)	_____
Last Annual Performance Evaluation (gaseous)	_____
Last two semi-annual flow rate audits for PM monitors	_____
Changes planned within the next 18 months (Y/N)	N

Site name	Visalia—Church
AIRS #	061072002
County	Tulare
Collecting (Operating) Agency	All equipment operated by CARB
Reporting Agency	All data reported by CARB
Site Start Date	7/1/79
Pollutant Parameters	Ozone, PM10 FRM, PM2.5 FRM, PM2.5 FEM
Meteorological Parameters	Wind speed, wind direction, outdoor temperature, barometric pressure
Address	310 N. Church St., Visalia CA 93291
Latitude	N 36° 19' 57"
Longitude	W 119° 17' 27"
Elevation (m)	97
Location	Portable building
Distance to road	23 m
Traffic Count	10000
Ground Cover	Roof

Visalia—Church (1 of 2)				
Pollutant	Ozone	PM10 FRM	PM2.5 FRM	PM2.5 Non-FEM
Parameter code	44201	81102	88101	88501
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Site type	Population	Population	Population	Regional transport
Monitor objective	Unknown	Unknown	Population Exposure	Population Exposure
Monitor type	SLAMS	SLAMS	SLAMS	Non-regulatory
POC	1	2	1	3
Method code	087	063	118	731
Sampling method (List Instrument)	API/Teledyne 400	Sierra Anderson 1200	R&P 2025	Met One 1020
Analysis method	UV	Gravimetric	Gravimetric	Beta attenuation
Start date				
Operation schedule (e.g. 1:1, 1:3)	1:1	1:6	1:3	1-Hour
Sampling season	ALL YEAR	ALL YEAR	ALL YEAR	ALL YEAR
Probe height (meters)				
Distance from supporting structure (meters)				
Distance from obstructions on roof				
Distance from obstructions not on roof (meters)	None	None	None	None
Distance from trees (meters)	None	None	None	None
Distance to furnace or incinerator flue (meters)	None	None	None	None
Distance between collocated monitors (meters)	--	--	--	--
Unrestricted airflow (degrees)	360	360	360	360
Probe material (Teflon, etc.)	Teflon	Teflon	Teflon	Teflon
Residence time (seconds)	14.2	--	--	--
Frequency of flow rate verification for manual PM samplers audit	--	Once a month	Once a month	--
Frequency of flow rate verification for automated PM analyzers audit	--	--	--	Twice a month
Frequency of one-point QC check (gaseous)	Twice a month	--	--	--
Last Annual Performance Evaluation (gaseous)	01/20/2011	--	--	--
Last two semi-annual flow rate audits for PM monitors	--	04/05/2007	12/02/2010	05/19/2010
Changes planned within the next 18 months (Y/N)	N	N	N	N

Visalia—Church (2 of 2)		
Pollutant	Met Parameters	PM2.5 Speciation
Parameter code	Many	Many
Spatial scale	Regional	Neighborhood
Site type	General	
Monitor objective	Research, timely/public	
Monitor type	Many	Supplemental speciation
POC	1	5
Method code	Many	811/812
Sampling method (List Instrument)		
Analysis method		Gravimetric
Start date		
Operation schedule (e.g. 1:1, 1:3)	1:1	
Sampling season	ALL YEAR	
Probe height (meters)		
Distance from supporting structure (meters)		
Distance from obstructions on roof		
Distance from obstructions not on roof (meters)	None	
Distance from trees (meters)	None	
Distance to furnace or incinerator flue (meters)	None	
Distance between collocated monitors (meters)	--	
Unrestricted airflow (degrees)	360	
Probe material (Teflon, etc.)	Teflon	
Residence time (seconds)	--	

Visalia—Church (2 of 2) continued		
Pollutant	Met Parameters	PM2.5 Speciation
Frequency of flow rate verification for manual PM samplers audit	--	
Frequency of flow rate verification for automated PM analyzers audit	--	
Frequency of one-point QC check (gaseous)	--	
Last Annual Performance Evaluation (gaseous)	--	
Last two semi-annual flow rate audits for PM monitors	--	
Changes planned within the next 18 months (Y/N)	N	N