



DEC 26 2013

Dan Martin E & J Gallo Winery 18000 W River Rd Livingston, CA 95334

RE: Notice of Final Action - Authority to Construct Facility Number: N-1237 Project Number: N-1132991

Dear Mr. Martin:

The Air Pollution Control Officer has issued the Authority to Construct permits to E & J Gallo Winery for the installation of 20 wine storage tanks, at 18000 W River Rd, Livingston, CA. Enclosed are the Authority to Construct permits and a copy of the notice of final action to be published approximately three days from the date of this letter.

Notice of the District's preliminary decision to issue the Authority to Construct permits was published on November 15, 2013. The District's analysis of the proposal was also sent to CARB and US EPA Region IX on November 12, 2013. No comments were received following the District's preliminary decision on this project.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

.

> Seyed Sadredin Executive Director/Air Pollution Control Officer

Northern Region 4800 Enterprise Wey Modesto, CA 95356-8718 Tel: (209) 557-6400 FAX: (209) 557-6475 Central Region (Main Offica) 1990 E. Gettysburg Avenue Fresno, CA 93726-0244 Tel: (559) 230-6000 FAX: (559) 230-6061 Southern Region 34946 Flyover Court Bakersfield, CA 93308:9725 Tel: 661-392:6500 FAX: 661 392:5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

Mr. Dan Martin Page 2

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney at (559) 230-6000.

Sincerely,

David Warner Director of Permit Services

DW:jag

Enclosures

- Mike Tollstrup, CARB (w/enclosure) via email Gerardo C. Rios, EPA (w/enclosure) via email CC:
- CC:

.





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-697-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & J GALLO WINERY ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

35,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 363) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 25 lb, 2nd quarter 25 lb, 3rd quarter 25 lb, and fourth quarter 26 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 12.08 feet in diameter and 40 feet in height with a proposed volume of 35,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 35,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 700,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-698-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

35,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 364) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 25 lb, 2nd quarter 25 lb, 3rd quarter 25 lb, and fourth quarter 26 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 12.08 feet in diameter and 40 feet in height with a proposed volume of 35,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

237-698-0; Dec 23 2013 8; 18AM -- GARCIAJ ; Joint Inspection NOT Required

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 35,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 700,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-699-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

35,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 365) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 25 lb, 2nd quarter 25 lb, 3rd quarter 25 lb, and fourth quarter 26 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 12.08 feet in diameter and 40 feet in height with a proposed volume of 35,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services Joint Inspection NOT Requir

Conditions for N-1237-699-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 35,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 700,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-700-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

35,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 366) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 25 lb, 2nd quarter 25 lb, 3rd quarter 25 lb, and fourth quarter 26 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 12.08 feet in diameter and 40 feet in height with a proposed volume of 35,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services Joint Inspection NOT Required

Conditions for N-1237-700-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 35,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 700,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-701-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3217) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

Conditions for N-1237-701-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-702-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS:

ATTN: EHS MANAGER **18000 W RIVER RD** LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3218) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction 2. credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) 3. shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 4. gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District 5. Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

VARNER, Director of Permit Services

Conditions for N-1237-702-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-703-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS:

ATTN: EHS MANAGER **18000 W RIVER RD** LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3219) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction 2. credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 4. gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District 5. Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

23 2013 9:18AM - GARCIAJ

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-704-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & J GALLO WINERY ATTN: EHS_MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3220) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

Conditions for N-1237-704-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-705-0

LEGAL OWNER OR OPERATOR:E & J GALLO WINERYMAILING ADDRESS:ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3221) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

VARNER, Director of Permit Services Joint Inspection NOT Require

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

ISSUANCE DATE: 12/23/2013

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-706-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3222) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

AVID VVARINER, DIFECTOR OF PETITIN SERVICES

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-707-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & J GALLO WINERY

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3223) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 126 lb, 2nd quarter 126 lb, 3rd quarter 126 lb, and fourth quarter 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAV4D WARNER, Director of Permit Services

Conditions for N-1237-707-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-708-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

350,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 3224) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 126 lb, 2nd quarter - 126 lb, 3rd quarter - 126 lb, and fourth quarter - 127 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 39.08 feet in diameter and 40 feet in height with a proposed volume of 350,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

VARNER. Director of Permit Services

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 350,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 3,500,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-709-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6201) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 160 lb, 2nd quarter - 161 lb, 3rd quarter - 161 lb, and fourth quarter - 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

237-709-04 Dec 23 2013 9:18AM -- GARCIAJ : Joint Inspection NOT Required

Conditions for N-1237-709-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-710-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD⁻ LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6202) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 160 lb, 2nd quarter - 161 lb, 3rd quarter - 161 lb, and fourth quarter - 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

AVID/WARNER, Director of Permit Services

Conditions for N-1237-710-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-711-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: E & J GALLO WINERY ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6203) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 160 lb, 2nd quarter 161 lb, 3rd quarter 161 lb, and fourth quarter 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

AVILY VVARINER, DIFECTOR OF PERMIT SERVICES

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-712-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS:

ATTN: EHS MANAGER **18000 W RIVER RD** LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6204) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction 2. credits for the following quantities of emissions: 1st quarter - 160 lb, 2nd quarter - 161 lb, 3rd quarter - 161 lb, and fourth quarter - 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) 3. shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. 4. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID

VARNER, Director of Permit Services

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-713-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6205) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 160 lb, 2nd quarter 161 lb, 3rd quarter 161 lb, and fourth quarter 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER, Director of Permit Services

Conditions for N-1237-713-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-714-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6206) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 160 lb, 2nd quarter 161 lb, 3rd quarter 161 lb, and fourth quarter 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

WARNER **Director of Permit Services**

JAVILI WARNER, Director of Permit Services

Conditions for N-1237-714-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-715-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

E & J GALLO WINERY ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6207) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter - 160 lb, 2nd quarter - 161 lb, 3rd quarter - 161 lb, and fourth quarter - 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

ARMER. Director of Permit Services

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]





AUTHORITY TO CONSTRUCT

PERMIT NO: N-1237-716-0

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY MAILING ADDRESS: ATTN: EHS MANAGER

ATTN: EHS MANAGER 18000 W RIVER RD LIVINGSTON, CA 95334

LOCATION:

18000 W RIVER RD LIVINGSTON, CA 95334

EQUIPMENT DESCRIPTION:

629,000 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6208) WITH PRESSURE/VACUUM VALVE, OR EQUIVALENT

CONDITIONS

- 1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
- Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantities of emissions: 1st quarter 160 lb, 2nd quarter 161 lb, 3rd quarter 161 lb, and fourth quarter 161 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 4/21/11). [District Rule 2201]
- 3. ERC Certificate Numbers S-4025-1, S-4050-1, S-3807-1, and S-3805-1 (or a certificate split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
- 4. The nominal tank dimensions are 51 feet in diameter and 41 feet in height with a proposed volume of 629,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]
- 5. This wine storage tank shall be used exclusively for wine storage operations only and not for fermentation. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU <u>MUST</u> NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

ARNER, Director of Permit Services

LAVED WARNER, DIRECTOR OF Permit Services

Conditions for N-1237-716-0 (continued)

- 6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
- 7. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- 8. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
- 9. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
- 10. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201]
- 11. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201]
- 12. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201]
- 13. The operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- 14. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- 15. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201]
- 16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201]
- 17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- 18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]