



**JUN 15 2016**

Mr. Michael Donich  
The Wine Group Inc  
2916 S Reed Ave  
Sanger, CA 93657

**Re: Notice of Preliminary Decision – Title V Permit Renewal  
District Facility # C-120  
Project # C-1143239**

Dear Mr. Donich:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for The Wine Group Inc at 2916 S Reed Ave in Sanger, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet  
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email  
cc: Gerardo C. Rios, EPA (w/enclosure) via email

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585

# SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation  
The Wine Group Inc  
C-120

## TABLE OF CONTENTS

---

I.	PROPOSAL .....	1
II.	FACILITY LOCATION .....	1
III.	EQUIPMENT LISTING.....	1
IV.	GENERAL PERMIT TEMPLATE USAGE.....	2
V.	SCOPE OF EPA AND PUBLIC REVIEW.....	2
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS.....	2
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE .....	5
VIII.	PERMIT REQUIREMENTS.....	6
IX.	PERMIT SHIELD .....	16
X.	PERMIT CONDITIONS .....	17
XI.	ATTACHMENTS .....	17
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED FACILITY LIST	

# TITLE V PERMIT RENEWAL EVALUATION

## Winery

**Engineer:** Jesse A. Garcia  
**Date:** June 2, 2016

**Facility Number:** C-120  
**Facility Name:** The Wine Group Inc  
**Mailing Address:** 2916 S Reed Ave  
Sanger, CA 93657

**Contact Name:** Michael Donich  
**Phone:** (559) 638-3511

**Responsible Official:** Michael Donich  
**Title:** Plant Manager

**Project # :** C-1143239  
**Deemed Complete:** January 28, 2015

---

### I. PROPOSAL

The Wine Group Inc was issued their initial Title V permit on April 1, 2010. As required by District Rule 2520, the applicant is requesting a permit renewal.

The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

### II. FACILITY LOCATION

The Wine Group Inc is located at 2916 S Reed Ave in Sanger, CA.

### III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

Minor changes to the equipment descriptions were made to clarify the tank material (stainless steel, steel or concrete), whether or not a P/V valve was installed and whether or not the tanks are insulated.

#### **IV. GENERAL PERMIT TEMPLATE USAGE**

The applicant is not proposing to use any model general permit templates as a part of this Title V renewal project.

#### **V. SCOPE OF EPA AND PUBLIC REVIEW**

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

#### **VI. FEDERALLY ENFORCEABLE REQUIREMENTS**

##### **A. Rules Updated or Evaluated**

- District Rule 1070, Inspections, (amended December 17, 1992)
- District Rule 2020, Exemptions, (amended March 21, 2002 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule, (amended September 21, 2006 ⇒ amended February 18, 2016)
- District Rule 4320, Advanced Emissions Reduction Options For Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr, (amended October 16, 2008)<sup>1</sup>
- District Rule 4694, Wine Fermentation and Storage Tanks, (adopted December 15, 2005)<sup>2</sup>
- 40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

---

<sup>1</sup>Although Rule 4320 itself has not been updated since the time of the last permit renewal, this rule was approved by EPA and included in the SIP on March 25, 2011. In addition, at the time the last Title V permit renewal was processed for this facility, the Rule 4320 compliance deadlines had not passed yet for the boiler operated at this facility, so the rule requirements were not addressed in that project. Since the boiler is now subject to the requirements of Rule 4320 and the requirements have become federally enforceable, Rule 4320 will be addressed as a rule added within this evaluation.

<sup>2</sup>Although the rule itself has not been updated, the District's SIP submittal was amended on August 18, 2011 to exclude the fermentation requirements. The storage requirements were subsequently approved into the SIP on November 29, 2012, and have therefore become federally enforceable.

- 40 CFR Part 64, Compliance Assurance Monitoring Program

#### **B. Rules Removed**

None

#### **C. Rules Added**

- District Rule 2410, Prevention of Significant Deterioration, (adopted June 16, 2011)

#### **D. Rules Not Updated**

- District Rule 1081, Source Sampling, (amended December 16, 1993)
- District Rule 1100, Equipment Breakdown, (amended December 17, 1992)
- District Rule 1160, Emission Statements, (adopted November 18, 1992)
- District Rule 2010, Permits Required, (adopted December 17, 1992)
- District Rule 2031, Transfer of Permits, (adopted December 17, 1992)
- District Rule 2040, Applications, (adopted December 17, 1992)
- District Rule 2070, Standards for Granting Applications, (adopted December 17, 1992)
- District Rule 2080, Conditional Approval, (adopted December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits, (amended June 21, 2001 )
- District Rule 4101, Visible Emissions, (amended February 17, 2005 )
- District Rule 4201, Particulate Matter Concentration, (amended December 17, 1992)
- District Rule 4202, Particulate Matter Emission Rate, (amended December 17, 1992)
- District Rule 4301, Fuel Burning Equipment, (amended December 17, 1992)
- District Rule 4351, Boilers, Steam Generators and Process Heaters – Phase 1, (amended August 21, 2003)

- District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2, (amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators and Process Heaters – Phase 3, (amended October 16, 2008)
- District Rule 4601, Architectural Coatings, (amended December 17, 2009)
- District Rule 4801, Sulfur Compounds, (amended December 17, 1992)
- District Rule 8011, General Requirements, (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities, (amended August 19, 2004)
- District Rule 8031, Bulk Materials, (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout, (amended August 19, 2004)
- District Rule 8051, Open Areas, (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads, (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas, (amended September 16, 2004)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
- 40 CFR Part 82, Subpart F, Stratospheric Ozone

## VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

### A. Rules Added

None

### B. Rules Updated

#### 1. District Rule 4694, Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any winery fermenting wine and/or storing wine in bulk containers.

The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP). On August 18, 2011, the District approved an amended SIP submittal which excludes the fermentation provisions of the rule while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable. All other provisions are federally enforceable and will be discussed in Section VIII of this application review under District Rule 4694.

The following conditions are based on this rule and are not Federally Enforceable through Title V:

Permit Units	Permit Conditions
C-120-0-1	43 through 47
C-120-30-2 through -65-2	1
C-120-66-2 through -183-2	5

## C. Rules Not Updated

### 1. District Rule 4102, Nuisance

The following conditions are based on this rule and are not Federally Enforceable through Title V:

Permit Units	Permit Condition
C-120-0-1	42

## VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit.

### A. District Rule 1070 – Inspections

District Rule 1070 explains the District's authority in determining compliance with the requirements of rules and regulations. Although the Rule has not been amended, the ensure compliance with the existing annual heat input limit of permit unit C-120-3-8, permit condition 24 was added.

### B. District Rule 2020 – Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits, and specifies recordkeeping requirements to verify such exemptions. The rule was amended in August 18, 2011. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

### C. District Rule 2201– New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.26, defined as an action including at least one of the following items:

- 1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.
- 2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.



- 3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.
- 4) Addition of any new emissions unit which is subject to District permitting requirements.
- 5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Therefore, the updated requirements of this rule are not applicable to the permits being renewed as a part of this project and no further discussion is required.

However, EPA has provided the District with comments on other Title V permit projects and indicated that the District was issuing permits without appropriate and practical recordkeeping requirements for annual emissions limitations. According to EPA policy, annual emission limits must be practically enforceable, which also goes on to say that to be practically enforceable, annual limits must be enforced on a short-term basis.

The District had previously committed to 12-month rolling recordkeeping to enforce annual limits in all Title V permits. In accordance with that committal, the District revised condition 24 of permit C-120-3-8 accordingly.

#### **D. District Rule 2410 – Prevention of Significant Deterioration**

The prevention of significant deterioration (PSD) program is a preconstruction permitting program for new major stationary sources and major modifications to existing major stationary sources located in areas classified as attainment or in areas that are unclassifiable for any criteria air pollutant. The provisions of this rule apply to any source and the owner or operator of any source subject to any requirement under Title 40 Code of Federal Regulations (40 CFR) Part 52.21 as incorporated into this rule.

The requirements of this rule cannot be triggered by the renewal of a Title V permit, since permit renewal does not involve any construction or modification of the stationary source. A detailed analysis or applicability determination is therefore not required.

#### **E. District Rule 2520 - Federally Mandated Operating Permits**

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

**F. District Rule 4320 – Advanced Emission Reduction Option of Boilers, Steam Generators, and Process Heaters Greater Than 5.0 MMBtu/hr**

The purpose of this rule is to limit the emissions of NO<sub>x</sub>, CO, SO<sub>x</sub> and PM<sub>10</sub> from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a total rated heat input greater than 5 million Btu per hour.

Permit unit C-120-3-8 is a 40.26 MMBtu/hr natural gas-fired boiler and is subject to the requirements of this rule.

Section 5.2.1 states that units shall not be operated in a manner which exceeds the applicable NO<sub>x</sub> and CO emissions limits specified in table below:

<b>Rule 4320 Emissions Limits</b>		
<b>Category</b>	<b>Operated on gaseous fuel</b>	
	<b>NO<sub>x</sub> Limit</b>	<b>CO Limit</b>
B. Units with a total rated heat input > 20.0 MMBtu/hr, except for Categories C through G units	a) Standard Schedule 7 ppmv or 0.008 lb/MMBtu; or	400 ppmv
	b) Enhanced Schedule 5 ppmv or 0.0062 lb/MMBtu	

The following conditions ensure compliance with the requirements of this section.

<b>Permit Unit</b>	<b>Permit Conditions</b>
C-120-3-8	5

Section 5.3 applies to the Annual Fee Calculation requirements. Since the facility meets the emission requirements of Section 5.2, the requirements of this section are not applicable.

Section 5.4 states that to limit particulate matter emissions, an operator shall comply with one of the following requirements:

- Section 5.4.1.1: Fire units exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases;
- Section 5.4.1.2: Limit fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or

- Section 5.4.1.3: Install and properly operate an emission control system that reduces SO<sub>2</sub> emissions by at least 95% by weight; or limit exhaust SO<sub>2</sub> to less than or equal to 9 ppmv corrected to 3.0% O<sub>2</sub>.
- Section 5.4.1.4: Refinery units, which require modification of refinery equipment to reduce sulfur emissions, shall be in compliance with the applicable

The following condition ensures compliance with the requirements of these sections.

Permit Unit	Permit Condition
C-120-3-8	3

Section 5.5 applies to low-use units. This boiler is not a low use unit; therefore, it is not subject to the requirements of this section.

Section 5.6 states that the applicable emission limits of Sections 5.2 Table 1 and 5.5.2 shall not apply during start-up or shutdown, provided an operator complies with the requirements specified below.

- The duration of each start-up or each shutdown shall not exceed two hours, except as provided in Section 5.6.3.
- The emission control system shall be in operation and emissions shall be minimized insofar as technologically feasible during start-up or shutdown.

The permit unit does not have any start-up or shutdown provisions; therefore, this section is not applicable.

Section 5.7 requires either the use of an APCO approved Continuous Emissions Monitoring System (CEMS) for NO<sub>x</sub>, CO, and oxygen, or implementation of an APCO-approved Alternate Monitoring System.

In order to satisfy the requirements of District Rule 4320, the applicant has proposed to use pre-approved alternate monitoring scheme A (pursuant to District Policy SSP-1105), which requires that monitoring of NO<sub>x</sub>, CO and O<sub>2</sub> exhaust concentrations shall be conducted at least once per month (in which a source test is not performed) using a portable analyzer.

The following conditions ensure compliance with the requirements of this section.

Permit Unit	Permit Conditions
C-120-3-8	16 through 19

Section 5.7.6.1 states that operators complying with Sections 5.4.1.1 or 5.4.1.2 shall provide an annual fuel analysis to the District unless a more

frequent sampling and reporting period is included in the Permit To Operate. Sulfur analysis shall be performed in accordance with the test methods in Section 6.2.

Section 5.7.6.2 Operators complying with Section 5.4.1.3 by installing and operating a control device with 95% SO<sub>x</sub> reduction shall propose the key system operating parameters and frequency of the monitoring and recording. The monitoring option proposed shall be submitted for approval by the APCO.

Section 5.7.6.3 Operators complying with Section 5.4.1.3 shall perform an annual source test unless a more frequent sampling and reporting period is included in the Permit To Operate. Source tests shall be performed in accordance with the test methods in Section 6.2.

The following condition ensures compliance with the requirements of these sections.

<b>Permit Unit</b>	<b>Permit Condition</b>
C-120-3-8	10

Section 5.8.1 states that the operator of any unit shall have the option of complying with either the applicable heat input, in lb/MMBtu, emission limits or the concentration, in ppmv, emission limits specified in Section 5.2. The emission limits selected to demonstrate compliance shall be specified in the source test proposal pursuant to Rule 1081 (Source Sampling).

Section 5.8.2 states that all emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0.

Section 5.8.3 states that continuous Emissions Monitoring System (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes to demonstrate compliance with the applicable emission limits. Any 15-consecutive-minute block average CEMS measurement exceeding the applicable emission limits shall constitute a violation.

Section 5.8.4 states that for emissions monitoring pursuant to Sections 5.7.1, and 6.3.1 using a portable NO<sub>x</sub> analyzer as part of an APCO approved Alternate Emissions Monitoring System, emission readings shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15-

consecutive-minute sample reading or by taking at least five readings evenly spaced out over the 15-consecutive-minute period.

Section 5.8.5 states that for emissions source testing performed pursuant to Section 6.3.1 for the purpose of determining compliance with an applicable standard or numerical limitation of this rule, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit.

The following conditions ensure compliance with the requirements of these sections.

<b>Permit Unit</b>	<b>Permit Conditions</b>
C-120-3-8	7, 9, 18, and 20

Section 6.1 states that the records required by Sections 6.1.1 through 6.1.5 shall be maintained for five calendar years and shall be made available to the APCO and EPA upon request. Failure to maintain records or information contained in the records that demonstrate noncompliance with the applicable requirements of this rule shall constitute a violation of this rule.

Section 6.1.4 states that the operator performing start-up or shutdown of a unit shall keep records of the duration of start-up or shutdown.

Section 6.1.1, 6.1.2, 6.1.3, and 6.1.5 contain requirements that the boiler is not subject to; therefore, the requirements of these sections will be addressed.

The following conditions ensure compliance with the requirements of these sections.

<b>Permit Unit</b>	<b>Permit Conditions</b>
C-120-3-8	22

Section 6.2 states the following test methods shall be used unless otherwise approved by the APCO and EPA:

<b>Pollutant</b>	<b>Units</b>	<b>Test Method Required</b>
NO <sub>x</sub>	ppmv	EPA Method 7E or ARB Method 100
NO <sub>x</sub>	lb/MMBtu	EPA Method 19
CO	ppmv	EPA Method 10 or ARB Method 100
Stack Gas O <sub>2</sub>	%	EPA Method 3 or 3A, or ARB Method 100
Stack Gas Velocities	ft/min	EPA Method 2
Stack Gas Moisture Content	%	EPA Method 4
SO <sub>x</sub>	ppmv	EPA Method 6C or 8, or ARB Method 100

The following conditions ensure compliance with the requirements of this section.

<b>Permit Unit</b>	<b>Permit Conditions</b>
C-120-3-8	11 through 15

Section 6.3 states that each unit subject to the requirements in Section 5.2 shall be source tested to determine compliance with the applicable emission limits at least once every 12 months, (no more than 30 days before or after the required annual source test date).

Units that demonstrate compliance on two consecutive 12-month source tests may defer the following 12-month source test for up to 36 months (no more than 30 days before or after the required 36-month source test date). During the 36-month source testing interval, the operator shall tune the unit in accordance with the provisions of Section 5.5.1, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer to ensure compliance with the applicable emission limits specified in Section 5.2.

Tune-ups required by Sections 5.5.1 and 6.3.1 do not need to be performed for units that operate and maintain an APCO approved CEMS or an APCO approved Alternate Monitoring System where the applicable emission limits are periodically monitored.

If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits specified in Section 5.2, the source testing frequency shall revert to at least once every 12 months.

Failure to comply with the requirements of Section 6.3.1 or any source test results that exceed the applicable emission limits in Section 5.2 shall constitute a violation of this rule.

The following condition ensures compliance with the requirements of these sections.

Permit Unit	Permit Condition
C-120-3-8	6

**G. District Rule 4694 – Wine Fermentation and Storage Tanks**

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons.

This facility is a winery with VOC emissions greater than 10 tons per year. Each of the tanks operated at this facility are greater than 5,000 gallons in capacity. Therefore, the requirements of this rule are applicable to this facility.

As previously discussed in Section VII.A above, on August 18, 2011 the District approved an amended SIP submittal which excludes the fermentation provisions of District Rule 4694 while maintaining the storage provisions. Therefore, only the storage provisions are federally enforceable and will be discussed below.

Section 5.2 states that owners or operators of any wine storage tank having an internal volume equal to or greater than 5,000 gallons (except storage tanks constructed primarily of concrete or wood per Section 4.2) shall comply with the following requirements when storing wine:

- 5.2.1 The tank shall be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:
- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
  - The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and

- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
  - The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.
- 5.2.2 The temperature of the stored wine shall be maintained at or below 75° F.
- Temperature of the stored wine shall be determined and recorded at least once per week.
  - For each batch of wine, operators shall achieve the storage temperature of 75° F or less within 60 days after completing fermentation.

The following conditions ensure compliance with the requirements of these sections.

Permit Units	Permit Conditions
C-120-6-2, -7-2, -66-2 through-91-2, and -115-2 through -183-2	1, 2, and 3

Section 6.4 states that commencing January 1, 2007, the following records shall be maintained, retained on-site for a minimum of five years, and made available to the APCO upon request:

- 6.4.2 For each storage tank, operators shall record the following information on a weekly basis:
- Total gallons of wine contained in the tank, and
  - Maximum temperature of the stored wine.

The following conditions ensure compliance with the requirements of these sections.

Permit Units	Permit Conditions
C-120-6-2, -7-2, and -115-2 through -137-2	4 and 5
C-120-8-2 through-29-2, and -92-2 through -114-2	1 and 2
C-120-30-2 through -65-2	2 and 3
C-120-66-2 through -91-2, and -138-2 through - 169-2 and -172-2 through -183-2	4 and 6
C-120-170-3 and -171-3	9 and 11



**H. 40 CFR Part 60 Subpart Dc – Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units**

40 CFR Part 60, Subpart Dc applies to Small Industrial-Commercial-Institutional Steam Generators between 10 MMBtu/hr and 100 MMBtu/hr (post-6/9/89 construction, modification or, reconstruction).

40 CFR Part 60, Subpart A, section 14, defines the meaning of modification to which the standards are applicable. §60.14, paragraph (e)(5) states that the following will not be considered as a modification: *“the addition or use of any system or device whose primary function is the reduction of air pollutants, except when an emission control system is removed or replaced by a system which the Administrator determines to be less environmentally beneficial”*.

Unit C-120-3-8 is not newly constructed or a reconstructed unit, nor has the unit been modified (as defined above); therefore, unit -3-8 is not subject to this subpart. Since unit -3-8 is not subject to this subpart, all requirements and references on the permit have been removed.

**I. 40 CFR Part 64 - CAM**

**§64.2 – Applicability**

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

<b>Pollutant</b>	<b>Major Source Threshold (lb/year)</b>
VOC	20,000
NO <sub>x</sub>	20,000
CO	200,000
PM <sub>10</sub>	140,000
SO <sub>x</sub>	140,000

- a. C-120-3-8: 40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

- 1) This unit contains emission limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO and VOC.

- 2) This unit is served by a Flue Gas Recirculation (FGR) system to control NO<sub>x</sub> emissions. There are no add-on controls for SO<sub>x</sub>, PM<sub>10</sub>, VOC, or CO emissions. Therefore, this unit is not subject to CAM for SO<sub>x</sub>, PM<sub>10</sub>, VOC, or CO emissions
- 3) The FGR system will be assumed to have a 70% control efficiency.

**Pre-control Annual PE:**

$$\begin{aligned} \text{PE} &= \text{EF (lb/MMBtu)} \times \text{Heat Input (MMBtu/hr)} \times 8,760 \text{ hr/year} \\ &= (0.008 \text{ lb-NO}_x\text{/MMBtu}) \times (140,910 \text{ MMBtu/year}) \\ &= \mathbf{1,127 \text{ lb-NO}_x\text{/year}} \end{aligned}$$

$$\begin{aligned} \text{Pre-control PE} &= \text{PE} \div (1 - \text{CE}) \\ &= (1,127 \text{ lb-NO}_x\text{/year}) \div (1 - 0.7) \\ &= \mathbf{3,758 \text{ lb-NO}_x\text{/year}} \end{aligned}$$

Since 3,758 lb-NO<sub>x</sub>/yr < 20,000 lb-NO<sub>x</sub>/yr (Major Source threshold for NO<sub>x</sub>), this unit is not subject to CAM for NO<sub>x</sub> emissions.

b. C-120-6-2 through 183-2 – Wine Fermentation and/or Storage Tanks

These wine fermentation and/or storage tanks are not equipped with add-on or external control equipment. Since these tank permits are not equipped with add-on control devices, they are not subject to the CAM requirements of 40 CFR Subpart 64.

## IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

### A. Requirements Addressed by Model General Permit Templates

The applicant is not requesting to use any model general permit templates for this Title V renewal project.

**B. Requirements not Addressed by Model General Permit Templates**

The applicant is not requesting any new permit shields within this Title V renewal project. In addition, the applicant is not requesting any changes to the existing permit shields already included in their Title V operating permit. Therefore, all of the existing permit shields will be maintained on the revised permit for this renewal project.

**X. PERMIT CONDITIONS**

The draft renewed Title V operating permit is included as Attachment A.

**XI. ATTACHMENTS**

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Facility Report

---

# ATTACHMENT A

Draft Renewed Title V Operating Permit

---

# San Joaquin Valley Air Pollution Control District

FACILITY: C-120-0-1

EXPIRATION DATE: 06/30/2015

## FACILITY-WIDE REQUIREMENTS

1. {2285} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {2286} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {2287} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {2288} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {2289} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. {2290} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {2291} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {2292} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {2293} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

10. {2294} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {2295} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {2296} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {2297} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {2298} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {2299} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {2300} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {2301} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {2302} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {2303} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {2304} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {2305} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. {2306} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {2310} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {2311} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {2312} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. {2319} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {2320} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {2321} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {2322} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {2323} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {2324} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On June 30, 2010, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2018, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2016, and every three years thereafter on or before July 1. [District Rule 4694]
46. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District every year, on or before March 1. [District Rule 4694]
47. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-3-8

EXPIRATION DATE: 06/30/2015

## EQUIPMENT DESCRIPTION:

40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

## PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7.0 ppmv NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 400 ppmv CO @ 3% O2 or 0.296 lb-CO/MMBtu, or 0.004 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
11. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 1081, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Stack gas velocities for source test purposes shall be determined using EPA Method 2. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Stack gas moisture content for source test purposes shall be determined using EPA Method 4. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Maximum annual heat input of the unit, calculated on a rolling 12 month basis, shall not exceed 140,910 MMBtu per year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall maintain records of the annual heat input per 12 month rolling period, calculated monthly. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-6-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-7-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-8-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,846 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 301

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-9-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

66,237 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 302

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-10-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,898 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 303

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-11-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,986 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 304

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-12-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,202 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 305

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-13-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,724 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 306

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-14-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,380 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 307

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-15-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,931 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 308

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-16-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,994 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 309

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-17-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,731 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 310

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-18-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,461 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 311

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-19-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,291 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 312

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-20-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

34,242 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 313

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-21-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,603 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 314

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-22-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,390 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 315

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-23-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,011 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 316

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-24-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,156 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 317

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-25-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,224 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 318

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-26-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,408 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 319

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-27-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,743 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 320

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-28-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,811 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 321

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-29-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,508 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 322

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-30-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-31-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-32-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-33-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-34-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-35-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-36-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-37-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-38-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-39-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-40-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-41-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-42-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-43-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-44-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-45-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-46-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,713 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-47-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-48-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-49-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-50-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-51-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-52-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-53-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-54-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,763 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-55-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-56-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-57-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-58-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-59-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-60-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,737 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-61-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-62-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-63-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-64-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-65-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-66-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,736 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-67-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 450 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-68-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 451 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-69-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 452 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-70-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 453 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-71-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 454 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-72-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-73-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 462 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-74-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 463 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-75-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 464 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-76-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 465 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-77-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-78-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-79-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-80-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-81-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-82-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-83-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-84-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-85-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-86-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-87-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-88-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-89-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-90-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-91-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-92-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,542 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 501

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-93-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,137 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 502

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-94-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,983 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 503

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-95-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

96,175 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 504

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-96-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,754 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 505

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-97-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,201 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 506

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-98-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,625 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 507

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-99-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,302 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 508

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-100-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,008 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 509

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-101-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,895 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 510

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-102-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,015 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 511

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-103-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

101,516 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 512

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-104-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,076 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 513

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-105-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,231 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 514

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-106-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,605 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 515

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-107-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,256 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 516

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-108-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,655 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 517

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-109-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,366 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 518

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-110-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

104,801 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 519

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-111-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

105,495 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 520

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-112-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

103,715 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 521

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

PERMIT UNIT: C-120-113-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

105,085 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 522

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-114-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,097 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 523

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-115-2

**EXPIRATION DATE:** 08/30/2015

**EQUIPMENT DESCRIPTION:**

81,242 GALLON NON-INSULATED STEEL WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-116-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

81,415 GALLON NON-INSULATED STEEL WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-117-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

81,377 GALLON NON-INSULATED STEEL WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-118-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,655 GALLON NON-INSULATED STEEL WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-119-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-120-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-121-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-122-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-123-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-124-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 533 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-125-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,922 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-126-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,874 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 535 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-127-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,898 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-128-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,366 GALLON NON-INSULATED STEEL WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-129-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,479 GALLON NON-INSULATED STEEL WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-130-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,545 GALLON NON-INSULATED STEEL WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-131-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,359 GALLON NON-INSULATED STEEL WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-132-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-133-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,417 GALLON NON-INSULATED STEEL WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-134-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,508 GALLON NON-INSULATED STEEL WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-135-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,626 GALLON NON-INSULATED STEEL WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-136-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,469 GALLON NON-INSULATED STEEL WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-137-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-138-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 61T WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-139-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-140-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-141-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-142-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 615 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-143-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 616 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-144-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 617 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-145-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 618 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-146-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 619 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-147-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 620 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-148-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-149-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-150-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-151-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 625 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-152-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 626 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-153-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 627 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-154-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 628 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-155-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 630 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-156-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-157-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,629 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-158-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-159-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-160-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-161-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-162-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-163-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-164-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-165-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-166-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-167-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-168-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-169-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-170-3

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-171-3

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-172-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

12,569 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-173-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-174-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-175-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-176-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-177-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-178-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-179-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-180-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-181-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-182-2

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-183-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

---

# ATTACHMENT B

Previous Title V Operating Permit

---

# San Joaquin Valley Air Pollution Control District

FACILITY: C-120-0-0

EXPIRATION DATE: 06/30/2015

## FACILITY-WIDE REQUIREMENTS

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: THE WINE GROUP INC  
Location: 2916 S REED AVE, SANGER, CA 93657  
C-120-0-0 Jun 2 2016 6:26AM - GARCIAJ

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On June 30, 2010, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]
46. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
47. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-3-7

EXPIRATION DATE: 06/30/2015

## EQUIPMENT DESCRIPTION:

40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

## PERMIT UNIT REQUIREMENTS

---

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
5. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7.0 ppmv NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 400 ppmv CO @ 3% O2 or 0.296 lb-CO/MMBtu, or 0.004 lb-VOC/MMBtu. [District Rules 2201, 4301, 5.1 and 5.2, and 4306, 5.1] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4306, 6.3.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
7. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4306, 5.5.1 and 4320, 5.8] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4306, 5.5.5 and 4320, 5.8] Federally Enforceable Through Title V Permit
10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4306, 6.2.1; and 4320, 6.2.1] Federally Enforceable Through Title V Permit
11. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 1081, 4306, 6.2 and 4320, 5.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 1081, 4306, 6.2 and 4320, 5.8] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4306, 6.2 and 4320, 6.2] Federally Enforceable Through Title V Permit
14. Stack gas velocities for source test purposes shall be determined using EPA Method 2. [District Rules 1081, 4306, 6.2 and 4320, 5.8] Federally Enforceable Through Title V Permit
15. Stack gas moisture content for source test purposes shall be determined using EPA Method 4. [District Rules 1081, 4306, 6.2 and 4320, 5.8] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 2520, 9.3, 4306, 5.4.2 and 4320, 5.7] Federally Enforceable Through Title V Permit
17. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 2520, 9.3, 4306, 5.4.2 and 4320, 5.7] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 2520, 9.3, 4306, 5.4.2 and 4320, 5.7] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 2520, 9.3, 4306, 5.4.2 and 4320, 5.7] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4306, 5.5.2 and 4320, 5.8] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4306, 6.1 and 4320, 6.1] Federally Enforceable Through Title V Permit
23. The permittee shall keep daily records of the amount of natural gas combusted for a period of five years, and shall make records available for inspection upon request. [District Rule 2520, 9.4.2, and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. Maximum annual heat input of the unit shall not exceed 140,910 MMBtu per calendar year. [District Rule 2201]  
Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-6-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

13,632 GALLON STEEL WINE STORAGE TANK 117

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-7-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

13,632 GALLON STEEL WINE STORAGE TANK 118

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-8-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,846 GALLON CONCRETE WINE STORAGE TANK 301

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-9-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

66,237 GALLON CONCRETE WINE STORAGE TANK 302

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-10-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,898 GALLON CONCRETE WINE STORAGE TANK 303

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-11-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,986 GALLON CONCRETE WINE STORAGE TANK 304

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-12-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

67,202 GALLON CONCRETE WINE STORAGE TANK 305

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-13-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**  
67,724 GALLON CONCRETE WINE STORAGE TANK 306

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-14-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,380 GALLON CONCRETE WINE STORAGE TANK 307

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-15-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,931 GALLON CONCRETE WINE STORAGE TANK 308

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-16-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,994 GALLON CONCRETE WINE STORAGE TANK 309

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-17-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**  
33,731 GALLON CONCRETE WINE STORAGE TANK 310

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-18-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,461 GALLON CONCRETE WINE STORAGE TANK 311

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-19-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,291 GALLON CONCRETE WINE STORAGE TANK 312

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-20-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

34,242 GALLON CONCRETE WINE STORAGE TANK 313

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-21-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,603 GALLON CONCRETE WINE STORAGE TANK 314

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-22-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,390 GALLON CONCRETE WINE STORAGE TANK 315

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-23-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,011 GALLON CONCRETE WINE STORAGE TANK 316

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-24-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,156 GALLON CONCRETE WINE STORAGE TANK 317

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-25-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,224 GALLON CONCRETE WINE STORAGE TANK 318

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-26-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,408 GALLON CONCRETE WINE STORAGE TANK 319

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-27-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,743 GALLON CONCRETE WINE STORAGE TANK 320

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-28-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

32,811 GALLON CONCRETE WINE STORAGE TANK 321

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-29-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

33,508 GALLON CONCRETE WINE STORAGE TANK 322

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-30-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-31-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-32-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-33-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-34-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-35-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-36-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-37-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-38-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-39-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-40-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-41-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-42-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-43-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-44-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-45-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-46-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429

## **PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-47-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-48-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-49-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-50-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-51-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-52-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-53-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-54-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,763 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-55-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-56-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-57-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440

## **PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-58-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-59-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-60-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,736 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-61-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-62-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-63-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-64-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-65-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-66-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,736 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-67-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 450

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-68-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 451

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-69-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 452

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-70-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 453

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-71-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 454

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-72-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 455

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-73-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 462

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-74-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 463

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-75-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 464

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-76-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 461

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-77-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-78-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-79-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-80-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-81-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-82-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-83-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-84-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-85-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-86-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-87-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-88-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-89-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-90-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-91-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-92-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,543 GALLON CONCRETE WINE STORAGE TANK 501

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-93-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,137 GALLON CONCRETE WINE STORAGE TANK 502

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-94-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,983 GALLON CONCRETE WINE STORAGE TANK 503

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-95-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

96,175 GALLON CONCRETE WINE STORAGE TANK 504

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-96-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,754 GALLON CONCRETE WINE STORAGE TANK 505

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-97-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,201 GALLON CONCRETE WINE STORAGE TANK 506

## **PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-98-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

110,625 GALLON CONCRETE WINE STORAGE TANK 507

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-99-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

111,302 GALLON CONCRETE WINE STORAGE TANK 508

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-100-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,008 GALLON CONCRETE WINE STORAGE TANK 509

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-101-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,895 GALLON CONCRETE WINE STORAGE TANK 510

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-102-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,015 GALLON CONCRETE WINE STORAGE TANK 511

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-103-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

101,516 GALLON CONCRETE WINE STORAGE TANK 512

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-104-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,076 GALLON CONCRETE WINE STORAGE TANK 513

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-105-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,231 GALLON CONCRETE WINE STORAGE TANK 514

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-106-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

119,605 GALLON CONCRETE WINE STORAGE TANK 515

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-107-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

118,256 GALLON CONCRETE WINE STORAGE TANK 516

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-108-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,655 GALLON CONCRETE WINE STORAGE TANK 517

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-109-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,366 GALLON CONCRETE WINE STORAGE TANK 518

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-110-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

104,801 GALLON CONCRETE WINE STORAGE TANK 519

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-111-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

105,495 GALLON CONCRETE WINE STORAGE TANK 520

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-112-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

103,715 GALLON CONCRETE WINE STORAGE TANK 521

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



San Joaquin Valley  
Air Pollution Control District

**PERMIT UNIT:** C-120-113-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

105,085 GALLON CONCRETE WINE STORAGE TANK 522

**PERMIT UNIT REQUIREMENTS**

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-114-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,097 GALLON CONCRETE WINE STORAGE TANK 523

## PERMIT UNIT REQUIREMENTS

---

1. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
2. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-115-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

81,242 GALLON STEEL WINE STORAGE TANK 524

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-116-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

81,415 GALLON STEEL WINE STORAGE TANK 525

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-117-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

81,377 GALLON STEEL WINE STORAGE TANK 526

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-118-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

50,655 GALLON STEEL WINE STORAGE TANK 527

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-119-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,438 GALLON STAINLESS STEEL WINE STORAGE TANK 528

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-120-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,438 GALLON STAINLESS STEEL WINE STORAGE TANK 529

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-121-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 530

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-122-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 531

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-123-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 532

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-124-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 533

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-125-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,922 GALLON STAINLESS STEEL WINE STORAGE TANK 534

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-126-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,874 GALLON STAINLESS STEEL WINE STORAGE TANK 535

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-127-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

5,898 GALLON STAINLESS STEEL WINE STORAGE TANK 536

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-128-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,366 GALLON STEEL WINE STORAGE TANK 601

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-129-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,479 GALLON STEEL WINE STORAGE TANK 602

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-130-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,545 GALLON STEEL WINE STORAGE TANK 603

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-131-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,359 GALLON STEEL WINE STORAGE TANK 604

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-132-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,583 GALLON STEEL WINE STORAGE TANK 605

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-133-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,417 GALLON STEEL WINE STORAGE TANK 606

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-134-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,508 GALLON STEEL WINE STORAGE TANK 607

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-135-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,626 GALLON STEEL WINE STORAGE TANK 608

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-136-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,469 GALLON STEEL WINE STORAGE TANK 609

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-137-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

93,583 GALLON STEEL WINE STORAGE TANK 610

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-138-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 611

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-139-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 612

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-140-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 613

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-141-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 614

## **PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-142-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 615

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-143-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 616

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-144-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 617

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-145-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 618

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-146-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 619

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-147-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
620

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-148-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
621

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-149-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
622

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-150-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
623

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-151-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
625

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-152-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
626

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-153-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
627

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-154-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
628

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-155-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK  
630

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the maximum fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-156-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-157-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,629 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-158-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-159-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-160-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-161-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-162-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

260,529 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 637

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-163-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

258,548 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-164-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

258,548 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-165-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-166-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-167-1

EXPIRATION DATE: 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-168-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,457 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-169-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-120-170-2

EXPIRATION DATE: 06/30/2015

## EQUIPMENT DESCRIPTION:

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-171-2

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-172-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

12,569 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-173-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-174-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-175-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-176-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-177-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-178-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-179-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-180-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-181-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,457 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-182-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,090 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-183-1

**EXPIRATION DATE:** 06/30/2015

**EQUIPMENT DESCRIPTION:**

349,090 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694, 6.4.2]
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4]

These terms and conditions are part of the Facility-wide Permit to Operate.

---

# ATTACHMENT C

Detailed Facility Report

---



### Detailed Facility Report

For Facility=120

Sorted by Facility Name and Permit Number

<b>THE WINE GROUP INC</b>	<b>FAC #</b>	<b>C 120</b>	<b>TYPE:</b>	<b>TitleV</b>	<b>EXP. DATE:</b>
<b>2916 S REED AVE</b>	<b>STATUS:</b>	<b>A</b>	<b>TOXIC ID:</b>		<b>11 /</b>
<b>SANGER, CA 93657</b>	<b>TELEPHONE:</b>	<b>2095994111</b>			<b>09/16</b>

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-1-1	12 MMBTU/HR BOILER	3020-02 G	1	855.00	855.00	D	12 MMBTU/HR TITUSVILLE IRON WORKS #1 BOILER (S/N-18767-47/1) WITH STANDBY FUEL OIL BURNERS.
C-120-2-1	22 MMBTU/HR BOILER	3020-02 H	1	1,080.00	1,080.00	D	22 MMBTU/HR TITUSVILLE IRON WORKS #2 STEAM BOILER (S/N 17876-47/2) WITH STANDBY FUEL OIL BURNERS.
C-120-3-7	40.26 MMBtu/hr	3020-02 H	1	1,080.00	1,080.00	A	40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION
C-120-4-0	240 HP I.C. ENGINE	3020-10 C	1	252.00	252.00	D	240 HP CUMMINS MODEL# N-855-F DIESEL I.C. ENGINE (S/N 99486, ENGINE #10850642) SERVING A FIRE PUMP. DELETED AS PER C/O FROM INSPECTOR - KS 06/28/01
C-120-6-1	13,632 gallons	3020-05 B	1	98.00	98.00	A	13,632 GALLON STEEL WINE STORAGE TANK 117
C-120-7-1	13,632 gallons	3020-05 B	1	98.00	98.00	A	13,632 GALLON STEEL WINE STORAGE TANK 118
C-120-8-1	67,846 gallons	3020-05 D	1	194.00	194.00	A	67,846 GALLON CONCRETE WINE STORAGE TANK 301
C-120-9-1	66,237 gallons	3020-05 D	1	194.00	194.00	A	66,237 GALLON CONCRETE WINE STORAGE TANK 302
C-120-10-1	67,898 gallons	3020-05 D	1	194.00	194.00	A	67,898 GALLON CONCRETE WINE STORAGE TANK 303
C-120-11-1	67,986 gallons	3020-05 D	1	194.00	194.00	A	67,986 GALLON CONCRETE WINE STORAGE TANK 304
C-120-12-1	67,202 gallons	3020-05 D	1	194.00	194.00	A	67,202 GALLON CONCRETE WINE STORAGE TANK 305
C-120-13-1	67,724 gallons	3020-05 D	1	194.00	194.00	A	67,724 GALLON CONCRETE WINE STORAGE TANK 306
C-120-14-1	33,380 gallons	3020-05 C	1	142.00	142.00	A	33,380 GALLON CONCRETE WINE STORAGE TANK 307
C-120-15-1	33,931 gallons	3020-05 C	1	142.00	142.00	A	33,931 GALLON CONCRETE WINE STORAGE TANK 308
C-120-16-1	32,994 gallons	3020-05 C	1	142.00	142.00	A	32,994 GALLON CONCRETE WINE STORAGE TANK 309
C-120-17-1	33,731 gallons	3020-05 C	1	142.00	142.00	A	33,731 GALLON CONCRETE WINE STORAGE TANK 310
C-120-18-1	33,461 gallons	3020-05 C	1	142.00	142.00	A	33,461 GALLON CONCRETE WINE STORAGE TANK 311
C-120-19-1	33,291 gallons	3020-05 C	1	142.00	142.00	A	33,291 GALLON CONCRETE WINE STORAGE TANK 312
C-120-20-1	34,242 gallons	3020-05 C	1	142.00	142.00	A	34,242 GALLON CONCRETE WINE STORAGE TANK 313
C-120-21-1	33,603 gallons	3020-05 C	1	142.00	142.00	A	33,603 GALLON CONCRETE WINE STORAGE TANK 314
C-120-22-1	33,390 gallons	3020-05 C	1	142.00	142.00	A	33,390 GALLON CONCRETE WINE STORAGE TANK 315
C-120-23-1	33,011 gallons	3020-05 C	1	142.00	142.00	A	33,011 GALLON CONCRETE WINE STORAGE TANK 316
C-120-24-1	33,156 gallons	3020-05 C	1	142.00	142.00	A	33,156 GALLON CONCRETE WINE STORAGE TANK 317

**Detailed Facility Report**

For Facility=120  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-25-1	33,224 gallons	3020-05 C	1	142.00	142.00	A	33,224 GALLON CONCRETE WINE STORAGE TANK 318
C-120-26-1	33,408 gallons	3020-05 C	1	142.00	142.00	A	33,408 GALLON CONCRETE WINE STORAGE TANK 319
C-120-27-1	32,743 gallons	3020-05 C	1	142.00	142.00	A	32,743 GALLON CONCRETE WINE STORAGE TANK 320
C-120-28-1	32,811 gallons	3020-05 C	1	142.00	142.00	A	32,811 GALLON CONCRETE WINE STORAGE TANK 321
C-120-29-1	33,508 gallons	3020-05 C	1	142.00	142.00	A	33,508 GALLON CONCRETE WINE STORAGE TANK 322
C-120-30-1	40,681 gallons	3020-05 C	1	142.00	142.00	A	40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413
C-120-31-1	40,665 gallons	3020-05 C	1	142.00	142.00	A	40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414
C-120-32-1	40,561 gallons	3020-05 C	1	142.00	142.00	A	40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415
C-120-33-1	40,307 gallons	3020-05 C	1	142.00	142.00	A	40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416
C-120-34-1	40,747 gallons	3020-05 C	1	142.00	142.00	A	40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417
C-120-35-1	40,681 gallons	3020-05 C	1	142.00	142.00	A	40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418
C-120-36-1	41,739 gallons	3020-05 C	1	142.00	142.00	A	41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419
C-120-37-1	41,919 gallons	3020-05 C	1	142.00	142.00	A	41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420
C-120-38-1	41,419 gallons	3020-05 C	1	142.00	142.00	A	41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421
C-120-39-1	41,649 gallons	3020-05 C	1	142.00	142.00	A	41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422
C-120-40-1	41,824 gallons	3020-05 C	1	142.00	142.00	A	41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423
C-120-41-1	41,718 gallons	3020-05 C	1	142.00	142.00	A	41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424
C-120-42-1	42,008 gallons	3020-05 C	1	142.00	142.00	A	42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425
C-120-43-1	41,612 gallons	3020-05 C	1	142.00	142.00	A	41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426
C-120-44-1	41,550 gallons	3020-05 C	1	142.00	142.00	A	41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427

**Detailed Facility Report**

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-45-1	41,608 gallons	3020-05 C	1	142.00	142.00	A	41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428
C-120-46-1	41,718 gallons	3020-05 C	1	142.00	142.00	A	41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429
C-120-47-1	42,020 gallons	3020-05 C	1	142.00	142.00	A	42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430
C-120-48-1	41,650 gallons	3020-05 C	1	142.00	142.00	A	41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431
C-120-49-1	41,885 gallons	3020-05 C	1	142.00	142.00	A	41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432
C-120-50-1	41,541 gallons	3020-05 C	1	142.00	142.00	A	41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433
C-120-51-1	41,258 gallons	3020-05 C	1	142.00	142.00	A	41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434
C-120-52-1	41,598 gallons	3020-05 C	1	142.00	142.00	A	41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435
C-120-53-1	41,847 gallons	3020-05 C	1	142.00	142.00	A	41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436
C-120-54-1	41,736 gallons	3020-05 C	1	142.00	142.00	A	41,736 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437
C-120-55-1	41,911 gallons	3020-05 C	1	142.00	142.00	A	41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438
C-120-56-1	41,671 gallons	3020-05 C	1	142.00	142.00	A	41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439
C-120-57-1	41,647 gallons	3020-05 C	1	142.00	142.00	A	41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440
C-120-58-1	41,716 gallons	3020-05 C	1	142.00	142.00	A	41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441
C-120-59-1	41,835 gallons	3020-05 C	1	142.00	142.00	A	41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442
C-120-60-1	40,736 gallons	3020-05 C	1	142.00	142.00	A	40,736 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443
C-120-61-1	40,882 gallons	3020-05 C	1	142.00	142.00	A	40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444
C-120-62-1	40,489 gallons	3020-05 C	1	142.00	142.00	A	40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445

**Detailed Facility Report**

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-63-1	40,383 gallons	3020-05 C	1	142.00	142.00	A	40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446
C-120-64-1	40,832 gallons	3020-05 C	1	142.00	142.00	A	40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447
C-120-65-1	40,728 gallons	3020-05 C	1	142.00	142.00	A	40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448
C-120-66-1	10,736 gallons	3020-05 B	1	98.00	98.00	A	10,736 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449
C-120-67-1	50,230 gallons	3020-05 D	1	194.00	194.00	A	50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 450
C-120-68-1	50,230 gallons	3020-05 D	1	194.00	194.00	A	50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 451
C-120-69-1	50,230 gallons	3020-05 D	1	194.00	194.00	A	50,230 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 452
C-120-70-1	51,745 gallons	3020-05 D	1	194.00	194.00	A	51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 453
C-120-71-1	51,745 gallons	3020-05 D	1	194.00	194.00	A	51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 454
C-120-72-1	51,745 gallons	3020-05 D	1	194.00	194.00	A	51,745 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 455
C-120-73-1	14,049 gallons	3020-05 B	1	98.00	98.00	A	14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 462
C-120-74-1	14,069 gallons	3020-05 B	1	98.00	98.00	A	14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 463
C-120-75-1	14,049 gallons	3020-05 B	1	98.00	98.00	A	14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 464
C-120-76-1	14,049 gallons	3020-05 B	1	98.00	98.00	A	14,049 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 461
C-120-77-1	127,875 gallons	3020-05 E	1	258.00	258.00	A	127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470
C-120-78-1	127,875 gallons	3020-05 E	1	258.00	258.00	A	127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471
C-120-79-1	127,875 gallons	3020-05 E	1	258.00	258.00	A	127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472
C-120-80-1	127,875 gallons	3020-05 E	1	258.00	258.00	A	127,875 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473

### Detailed Facility Report

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-81-1	28,087 gallons	3020-05 C	1	142.00	142.00	A	28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474
C-120-82-1	28,087 gallons	3020-05 C	1	142.00	142.00	A	28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475
C-120-83-1	28,087 gallons	3020-05 C	1	142.00	142.00	A	28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476
C-120-84-1	28,087 gallons	3020-05 C	1	142.00	142.00	A	28,087 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477
C-120-85-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492
C-120-86-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493
C-120-87-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494
C-120-88-1	110,412 gallons	3020-05 E	1	258.00	258.00	A	110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495
C-120-89-1	110,412 gallons	3020-05 E	1	258.00	258.00	A	110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496
C-120-90-1	110,412 gallons	3020-05 E	1	258.00	258.00	A	110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497
C-120-91-1	110,412 gallons	3020-05 E	1	258.00	258.00	A	110,412 GALLON STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498
C-120-92-1	111,543 gallons	3020-05 E	1	258.00	258.00	A	111,543 GALLON CONCRETE WINE STORAGE TANK 501
C-120-93-1	111,137 gallons	3020-05 E	1	258.00	258.00	A	111,137 GALLON CONCRETE WINE STORAGE TANK 502
C-120-94-1	110,983 gallons	3020-05 E	1	258.00	258.00	A	110,983 GALLON CONCRETE WINE STORAGE TANK 503
C-120-95-1	96,175 gallons	3020-05 D	1	194.00	194.00	A	96,175 GALLON CONCRETE WINE STORAGE TANK 504
C-120-96-1	111,754 gallons	3020-05 E	1	258.00	258.00	A	111,754 GALLON CONCRETE WINE STORAGE TANK 505
C-120-97-1	110,201 gallons	3020-05 E	1	258.00	258.00	A	110,201 GALLON CONCRETE WINE STORAGE TANK 506
C-120-98-1	110,625 gallons	3020-05 E	1	258.00	258.00	A	110,625 GALLON CONCRETE WINE STORAGE TANK 507
C-120-99-1	111,302 gallons	3020-05 E	1	258.00	258.00	A	111,302 GALLON CONCRETE WINE STORAGE TANK 508
C-120-100-1	119,008 gallons	3020-05 E	1	258.00	258.00	A	119,008 GALLON CONCRETE WINE STORAGE TANK 509
C-120-101-1	118,895 gallons	3020-05 E	1	258.00	258.00	A	118,895 GALLON CONCRETE WINE STORAGE TANK 510
C-120-102-1	119,015 gallons	3020-05 E	1	258.00	258.00	A	119,015 GALLON CONCRETE WINE STORAGE TANK 511

**Detailed Facility Report**

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	TOTAL FEE	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-103-1	101,516 gallons	3020-05 E	1	258.00	258.00	A	101,516 GALLON CONCRETE WINE STORAGE TANK 512
C-120-104-1	119,076 gallons	3020-05 E	1	258.00	258.00	A	119,076 GALLON CONCRETE WINE STORAGE TANK 513
C-120-105-1	118,231 gallons	3020-05 E	1	258.00	258.00	A	118,231 GALLON CONCRETE WINE STORAGE TANK 514
C-120-106-1	119,605 gallons	3020-05 E	1	258.00	258.00	A	119,605 GALLON CONCRETE WINE STORAGE TANK 515
C-120-107-1	118,256 gallons	3020-05 E	1	258.00	258.00	A	118,256 GALLON CONCRETE WINE STORAGE TANK 516
C-120-108-1	182,655 gallons	3020-05 E	1	258.00	258.00	A	182,655 GALLON CONCRETE WINE STORAGE TANK 517
C-120-109-1	182,366 gallons	3020-05 E	1	258.00	258.00	A	182,366 GALLON CONCRETE WINE STORAGE TANK 518
C-120-110-1	104,801 gallons	3020-05 E	1	258.00	258.00	A	104,801 GALLON CONCRETE WINE STORAGE TANK 519
C-120-111-1	105,495 gallons	3020-05 E	1	258.00	258.00	A	105,495 GALLON CONCRETE WINE STORAGE TANK 520
C-120-112-1	103,715 gallons	3020-05 E	1	258.00	258.00	A	103,715 GALLON CONCRETE WINE STORAGE TANK 521
C-120-113-1	105,085 gallons	3020-05 E	1	258.00	258.00	A	105,085 GALLON CONCRETE WINE STORAGE TANK 522
C-120-114-1	106,097 gallons	3020-05 E	1	258.00	258.00	A	106,097 GALLON CONCRETE WINE STORAGE TANK 523
C-120-115-1	81,242 gallons	3020-05 D	1	194.00	194.00	A	81,242 GALLON STEEL WINE STORAGE TANK 524
C-120-116-1	81,415 gallons	3020-05 D	1	194.00	194.00	A	81,415 GALLON STEEL WINE STORAGE TANK 525
C-120-117-1	81,377 gallons	3020-05 D	1	194.00	194.00	A	81,377 GALLON STEEL WINE STORAGE TANK 526
C-120-118-1	50,655 gallons	3020-05 D	1	194.00	194.00	A	50,655 GALLON STEEL WINE STORAGE TANK 527
C-120-119-1	5,438 gallons	3020-05 B	1	98.00	98.00	A	5,438 GALLON STAINLESS STEEL WINE STORAGE TANK 528
C-120-120-1	5,438 gallons	3020-05 B	1	98.00	98.00	A	5,438 GALLON STAINLESS STEEL WINE STORAGE TANK 529
C-120-121-1	37,658 gallons	3020-05 C	1	142.00	142.00	A	37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 530
C-120-122-1	37,658 gallons	3020-05 C	1	142.00	142.00	A	37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 531
C-120-123-1	37,658 gallons	3020-05 C	1	142.00	142.00	A	37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 532
C-120-124-1	37,658 gallons	3020-05 C	1	142.00	142.00	A	37,658 GALLON STAINLESS STEEL WINE STORAGE TANK 533
C-120-125-1	5,922 gallons	3020-05 B	1	98.00	98.00	A	5,922 GALLON STAINLESS STEEL WINE STORAGE TANK 534
C-120-126-1	5,874 gallons	3020-05 B	1	98.00	98.00	A	5,874 GALLON STAINLESS STEEL WINE STORAGE TANK 535
C-120-127-1	5,898 gallons	3020-05 B	1	98.00	98.00	A	5,898 GALLON STAINLESS STEEL WINE STORAGE TANK 536
C-120-128-1	93,366 gallons	3020-05 D	1	194.00	194.00	A	93,366 GALLON STEEL WINE STORAGE TANK 601
C-120-129-1	93,479 gallons	3020-05 D	1	194.00	194.00	A	93,479 GALLON STEEL WINE STORAGE TANK 602
C-120-130-1	93,545 gallons	3020-05 D	1	194.00	194.00	A	93,545 GALLON STEEL WINE STORAGE TANK 603

### Detailed Facility Report

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-131-1	93,359 gallons	3020-05 D	1	194.00	194.00	A	93,359 GALLON STEEL WINE STORAGE TANK 604
C-120-132-1	93,583 gallons	3020-05 D	1	194.00	194.00	A	93,583 GALLON STEEL WINE STORAGE TANK 605
C-120-133-1	93,417 gallons	3020-05 D	1	194.00	194.00	A	93,417 GALLON STEEL WINE STORAGE TANK 606
C-120-134-1	93,508 gallons	3020-05 D	1	194.00	194.00	A	93,508 GALLON STEEL WINE STORAGE TANK 607
C-120-135-1	93,626 gallons	3020-05 D	1	194.00	194.00	A	93,626 GALLON STEEL WINE STORAGE TANK 608
C-120-136-1	93,469 gallons	3020-05 D	1	194.00	194.00	A	93,469 GALLON STEEL WINE STORAGE TANK 609
C-120-137-1	93,583 gallons	3020-05 D	1	194.00	194.00	A	93,583 GALLON STEEL WINE STORAGE TANK 610
C-120-138-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 611
C-120-139-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 612
C-120-140-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 613
C-120-141-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 614
C-120-142-1	182,785 gallons	3020-05 E	1	258.00	258.00	A	182,785 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 615
C-120-143-1	307,391 gallons	3020-05 E	1	258.00	258.00	A	307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 616
C-120-144-1	307,391 gallons	3020-05 E	1	258.00	258.00	A	307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 617
C-120-145-1	307,391 gallons	3020-05 E	1	258.00	258.00	A	307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 618
C-120-146-1	307,391 gallons	3020-05 E	1	258.00	258.00	A	307,391 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 619
C-120-147-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 620
C-120-148-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 621
C-120-149-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 622
C-120-150-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 623
C-120-151-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 625

### Detailed Facility Report

For Facility=120

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-152-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 626
C-120-153-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 627
C-120-154-1	106,062 gallons	3020-05 E	1	258.00	258.00	A	106,062 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 628
C-120-155-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND WINE STORAGE TANK 630
C-120-156-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631
C-120-157-1	260,629 gallons	3020-05 E	1	258.00	258.00	A	260,629 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632
C-120-158-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633
C-120-159-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634
C-120-160-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635
C-120-161-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636
C-120-162-1	260,529 gallons	3020-05 E	1	258.00	258.00	A	260,529 GALLON STAINLESS STEEL ENCLOSED TOP WHITE WHITE WINE FERMENTATION AND WINE STORAGE TANK 637
C-120-163-1	258,548 gallons	3020-05 E	1	258.00	258.00	A	258,548 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638
C-120-164-1	258,548 gallons	3020-05 E	1	258.00	258.00	A	258,548 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639
C-120-165-1	349,273 gallons	3020-05 E	1	258.00	258.00	A	349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640
C-120-166-1	349,273 gallons	3020-05 E	1	258.00	258.00	A	349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641
C-120-167-1	349,273 gallons	3020-05 E	1	258.00	258.00	A	349,273 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642
C-120-168-1	349,457 gallons	3020-05 E	1	258.00	258.00	A	349,457 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643
C-120-169-1	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710



**Detailed Facility Report**

For Facility=120  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-170-2	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE
C-120-171-2	10,620 gallons	3020-05 B	1	98.00	98.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE
C-120-172-1	12,569 gallons	3020-05 B	1	98.00	98.00	A	12,569 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713
C-120-173-1	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714
C-120-174-1	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715
C-120-175-1	10,620 gallons	3020-05 B	1	98.00	98.00	A	10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716
C-120-176-1	10,620 gallons	3020-05 B	1	98.00	98.00	A	10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717
C-120-177-1	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718
C-120-178-1	22,612 gallons	3020-05 C	1	142.00	142.00	A	22,612 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719
C-120-179-1	10,620 gallons	3020-05 B	1	98.00	98.00	A	10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720
C-120-180-1	10,620 gallons	3020-05 B	1	98.00	98.00	A	10,620 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721
C-120-181-1	349,457 gallons	3020-05 E	1	258.00	258.00	A	349,457 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722
C-120-182-1	349,090 gallons	3020-05 E	1	258.00	258.00	A	349,090 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723
C-120-183-1	349,090 gallons	3020-05 E	1	258.00	258.00	A	349,090 GALLON STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724
C-120-184-1	37,658 gallons	3020-05 C	1	142.00	142.00	D	37,658 GALLON DISTILLED SPIRITS STORAGE TANK (TANK 533) WITH INSULATION

Number of Facilities Reported: 1