

JUN 30 2016

Robert A. Bruna
Sacramento Container Corporation
909 Union St
Kingsburg, CA 93631

RE: Notice of Final Action - Authority to Construct
Facility Number: C-3609
Project Number: C-1160266

Dear Mr. Bruna:

The Air Pollution Control Officer has issued the Authority to Construct permits to Central California Sheets, LLC and Sacramento Container Corporation for the modification of the corrugated board manufacturing operation, permit unit C-8609-2, to increase the daily and annual throughput limit and the modification of the corrugated paper box manufacturing and printing machines, permit units C-3609-2, '-4, '-5, '-6, '-8 and '-9, to increase the combined annual VOC limit, at 909 Union St, Kingsburg. Enclosed are the Authority to Construct permits and a copy of the notice of final action to be published approximately three days from the date of this letter.

Notice of the District's preliminary decision to issue the Authority to Construct permits was published on May 10, 2016. The District's analysis of the proposal was also sent to CARB and US EPA Region IX on May 5, 2016. No comments were received following the District's preliminary decision on this project.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Mr. Robert A. Bruna
Page 2

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas at (559) 230-6000.

Sincerely,


for Arnaud Marjollet
Director of Permit Services

AM:jag

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
Gerardo C. Rios, EPA (w/enclosure) via email
Carla Presetyo Jo, Yorke Engineering, LLC (w/enclosure) via email



Facility # C-3609
SACRAMENTO CONTAINER CORPORATION
4841 URBANI AVE
MCCLELLAN, CA 95652

AUTHORITY TO CONSTRUCT (ATC)

QUICK START GUIDE

1. **Pay Invoice:** Please pay enclosed invoice before due date.
2. **Fully Understand ATC:** Make sure you understand ALL conditions in the ATC prior to construction, modification and/or operation.
3. **Follow ATC:** You must construct, modify and/or operate your equipment as specified on the ATC. Any unspecified changes may require a new ATC.
4. **Notify District:** You must notify the District's Compliance Department, at the telephone numbers below, upon start-up and/or operation under the ATC. Please record the date construction or modification commenced and the date the equipment began operation under the ATC. You may NOT operate your equipment until you have notified the District's Compliance Department. A startup inspection may be required prior to receiving your Permit to Operate.
5. **Source Test:** Schedule and perform any required source testing. See http://www.valleyair.org/busind/comply/source_testing.htm for source testing resources.
6. **Maintain Records:** Maintain all records required by ATC. Records are reviewed during every inspection (or upon request) and must be retained for at least 5 years.

By operating in compliance, you are doing your part to improve air quality for all Valley residents.

**For assistance, please contact District Compliance staff at
any of the telephone numbers listed below.**

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-2-2

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF MARTIN MODEL 924 FLEXO-PRINTER/FOLDER/GLUER CORRUGATED PAPER BOX MANUFACTURING MACHINE WITH A PERMIT EXEMPT DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-2-1 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-4-4, '-5-2, '-6-2, '-8-1, '-9-1. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


Arnaud Marjollet, Director of Permit Services

C-3609-2-2 Jun 22 2016 10:29PM -- GARCIAJ Joint Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks and adhesives shall not exceed 4.8 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content of adhesive products used in this operation shall not exceed 3.74 g/l (equivalent to 0.0312 lb/gal). [District Rules 2201, 4607 and 4653]
15. VOC content (less water and exempt compounds) of low-end flexographic inks shall not exceed 0.3 lb/gallon. [District Rules 2201 and 4607]
16. VOC content (less water and exempt compounds) of high-end flexographic inks shall not exceed 0.88 lb/gallon. [District Rules 2201 and 4607]
17. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
18. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
19. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
20. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
21. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, adhesives, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]

CONDITIONS CONTINUE ON NEXT PAGE

22. Permittee shall maintain a current file of coatings, inks, adhesives, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]
23. For each ink, adhesive, and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]
24. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
25. Permittee shall maintain a record of the combined annual VOC emissions from permits C-3609-2, '4, '5, '6, '8, and '9, updated monthly. [District Rule 2201]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
27. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-4-2

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF MARTIN MODEL 924 FLEXP-PRINTER/FOLDER/GLUER CORRUGATED PAPER BOX MANUFACTURING MACHINE WITH A PERMIT EXEMPT DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-4-1 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-2-2, '-5-2, '-6-2, '-8-1, '-9-1. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-3609-4-2 Jun 22 2016 10:29PM - GARCIAJ Joint Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks and adhesives shall not exceed 4.8 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content of adhesive products used in this operation shall not exceed 3.74 g/l (equivalent to 0.0312 lb/gal). [District Rules 2201, 4607 and 4653]
15. VOC content (less water and exempt compounds) of low-end flexographic inks shall not exceed 0.3 lb/gallon. [District Rules 2201 and 4607]
16. VOC content (less water and exempt compounds) of high-end flexographic inks shall not exceed 0.88 lb/gallon. [District Rules 2201 and 4607]
17. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
18. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
19. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
20. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
21. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, adhesives, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]

22. Permittee shall maintain a current file of coatings, inks, adhesives, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]
23. For each ink, adhesive, and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]
24. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
25. Permittee shall maintain a record of the combined annual VOC emissions from permits C-3609-2, '4, '5, '6, '8, and '9, updated monthly. [District Rule 2201]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
27. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-5-2

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF WARD MODEL 4-C FLEXO-PRINTER/FOLDER/GLUER CORRUGATED PAPER BOX MANUFACTURING MACHINE WITH A PERMIT EXEMPT DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-5-1 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-2-2, '-4-4, '-6-2, '-8-1, '-9-1. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


for Arnaud Marjollet, Director of Permit Services
C-3609-5-2 Jun 22 2016 10:29PM - GARCIAJ Joint Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks and adhesives shall not exceed 4.8 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content of adhesive products used in this operation shall not exceed 3.74 g/l (equivalent to 0.0312 lb/gal). [District Rules 2201, 4607 and 4653]
15. VOC content (less water and exempt compounds) of low-end flexographic inks shall not exceed 0.3 lb/gallon. [District Rules 2201 and 4607]
16. VOC content (less water and exempt compounds) of high-end flexographic inks shall not exceed 0.88 lb/gallon. [District Rules 2201 and 4607]
17. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
18. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
19. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
20. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
21. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, adhesives, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]

CONDITIONS CONTINUE ON NEXT PAGE

22. Permittee shall maintain a current file of coatings, inks, adhesives, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]
23. For each ink, adhesive, and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]
24. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
25. Permittee shall maintain a record of the combined annual VOC emissions from permits C-3609-2, '4, '5, '6, '8, and '9, updated monthly. [District Rule 2201]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
27. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-6-2

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF WARD MODEL # 16000 SV (S/N 16331) 4-COLOR FLEXOGRAPHIC PRINTER CORRUGATED PAPER BOX MACHINE WITH A PERMIT EXEMPT ROTARY DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-6-1 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-2-2, '-4-4, '-5-2, '-8-1, '-9-1. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-3609-6-2 Jun 22 2016 10:29PM - GARCIA/JC Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks shall not exceed 4.4 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
15. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
16. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
17. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
18. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]
19. Permittee shall maintain a current file of coatings, inks, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content, as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]
20. For each ink and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]

CONDITIONS CONTINUE ON NEXT PAGE

21. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
22. Permittee shall maintain a record of the combined annual VOC emissions from permits C-3609-2, '4, '5, '6, '8, and '9, updated monthly. [District Rule 2201]
23. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
24. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-8-1

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF MARTIN MODEL 924 FLEXO-PRINTER/FOLDER/GLUER CORRUGATED PAPER BOX MANUFACTURING MACHINE WITH A PERMIT EXEMPT DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-8-0 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-2-2, '-4-4, '-5-2, '-6-2, '-9-1. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


Arnaud Marjollet, Director of Permit Services

C-3609-8-1 Jun 22 2016 10:29PM - GARCIAJ Permit Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks and adhesives shall not exceed 4.8 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content of adhesive products used in this operation shall not exceed 3.74 g/l (equivalent to 0.0312 lb/gal). [District Rules 2201, 4607 and 4653]
15. VOC content (less water and exempt compounds) of low-end flexographic inks shall not exceed 0.3 lb/gallon. [District Rules 2201 and 4607]
16. VOC content (less water and exempt compounds) of high-end flexographic inks shall not exceed 0.88 lb/gallon. [District Rules 2201 and 4607]
17. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
18. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
19. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
20. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
21. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, adhesives, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]

CONDITIONS CONTINUE ON NEXT PAGE

22. Permittee shall maintain a current file of coatings, inks, adhesives, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]
23. For each ink, adhesive, and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]
24. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
25. Permittee shall maintain a record of the combined annual VOC emissions from permits C-3609-2, '4, '5, '6, '8, and '9, updated monthly. [District Rule 2201]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
27. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]

AUTHORITY TO CONSTRUCT

PERMIT NO: C-3609-9-1

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: SACRAMENTO CONTAINER CORPORATION

MAILING ADDRESS: 4841 URBANI AVE
MCCLELLAN, CA 95652

LOCATION: 909 UNION ST
KINGSBURG, CA 93631-0007

EQUIPMENT DESCRIPTION:

MODIFICATION OF WARD MODEL # 16000 SV (S/N 16331) 4-COLOR FLEXOGRAPHIC PRINTER CORRUGATED PAPER BOX MACHINE WITH A PERMIT EXEMPT ROTARY DIE CUTTER SERVED BY A SCRAP COLLECTION SYSTEM WITH A BAGHOUSE (UNCONTROLLED PM10 EMISSIONS LESS THAN 2.0 LB/DAY): INCREASE SPECIFIC LIMITING CONDITION FROM 1,881 LBS-VOC/YEAR TO 6,184 LBS-VOC/YEAR

CONDITIONS

1. Authority to Construct (ATC) C-3609-9-0 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. This Authority to Construct (ATC) shall be implemented concurrently with ATCs C-3609-2-2, '-4-4, '-5-2, '-6-2, '-8-2. [District Rule 2201]
3. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
4. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
5. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


for Arnaud Marjollet, Director of Permit Services

C-3609-9-1 Jun 22 2016 10 28PM - GARCIAJ Joint Inspection NOT Required

7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
9. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]
10. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
11. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
12. VOC emissions from the use of inks shall not exceed 4.4 pounds in any one day. [District Rule 2201]
13. Combined VOC emissions from the equipment listed in permits C-3609-2, '4, '5, '6, '8, and '9 shall not exceed 6,184 pounds in any one year, based on a 12 month rolling average. [District Rule 2201]
14. VOC content (less water and exempt compounds) of low-end flexographic inks shall not exceed 0.3 lb/gallon. [District Rules 2201 and 4607]
15. VOC content (less water and exempt compounds) of high-end flexographic inks shall not exceed 0.88 lb/gallon. [District Rules 2201 and 4607]
16. VOC content of cleaning solvents shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for ink or adhesive application: 25 g/l (0.21 lb/gal); repair and maintenance cleaning: 25 g/l (0.21 lb/gal); cleaning of ink application equipment: 25 g/l (0.21 lb/gal). [District Rule 4607]
17. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, the permittee shall not use VOC-containing material to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose component part(s) being cleaned during washing, rinsing, draining procedures and it must be used according to manufacturer's recommendations and must be closed when not in use. [District Rule 4607]
18. For a permittee using any solvent containing more than 25 g/l of VOC for organic solvent cleaning, solvent shall not be atomized into the open air. This provision shall not apply to operations where roller or blanket wash is applied automatically and the cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with non-propellant-induced, hand-held spray bottles. [District Rule 4607]
19. Cleaning activities that use solvents with a VOC content greater than 25 g/l (0.21 lb/gallon) shall be performed by one or more of the following methods: (1) wipe cleaning; or (2) application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; or (3) non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or (4) solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4607]
20. Permittee shall store or dispose of fresh or spent solvents, waste solvent cleaning materials, coatings, catalysts, thinners, and inks in closed, non-absorbent, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 2201 and 4607]
21. Permittee shall maintain a current file of coatings, inks, fountain solutions, wash primers, and solvents in use and in storage. The file shall include material safety data sheet (MSDS) or product data sheet showing the material name, manufacturer's name, VOC content, as applied (or sufficient composition data to calculate this value), material VOC content (or VOC content "as packaged" from manufacturer), mixing instruction, and density. [District Rule 4607]

CONDITIONS CONTINUE ON NEXT PAGE

22. For each ink and solvent used in this operation, the permittee shall record on a monthly basis the product/material name, material type (e.g. ink), amount used (gallons), VOC content, less water and exempt compounds (lb-VOC/gal), and material VOC content (lb-VOC/gal). [District Rules 2201 and 4607]
23. Permittee shall maintain a record of the average daily VOC emissions to be calculated from monthly records of inks, adhesives, solvents and cleaning materials used in a calendar month, and the number days this unit is operated in a calendar month. [District Rule 2201]
24. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4607]
25. Facilities C-3609 (Sacramento Container Corporation) and C-8609 (Central California Sheets, LLC) are the same Stationary Source. [District Rule 2010]



JUN 3 0 2016

Jason J. Cook
Central California Sheets, LLC
909 Union St
Kingsburg, CA 93631

RE: Notice of Final Action - Authority to Construct
Facility Number: C-8609
Project Number: C-1160267

Dear Mr. Cook:

The Air Pollution Control Officer has issued the Authority to Construct permits to Central California Sheets, LLC and Sacramento Container Corporation for the modification of the corrugated board manufacturing operation, permit unit C-8609-2, to increase the daily and annual throughput limit and the modification of the corrugated paper box manufacturing and printing machines, permit units C-3609-2, '-4, '-5, '-6, '-8 and '-9, to increase the combined annual VOC limit and the, at 909 Union St, Kingsburg. Enclosed are the Authority to Construct permits and a copy of the notice of final action to be published approximately three days from the date of this letter.

Notice of the District's preliminary decision to issue the Authority to Construct permits was published on May 10, 2016. The District's analysis of the proposal was also sent to CARB and US EPA Region IX on May 5, 2016. No comments were received following the District's preliminary decision on this project.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Mr. Jason J. Cook
Page 2

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas at (559) 230-6000.

Sincerely,


for Arnaud Marjollet
Director of Permit Services

AM:jag

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
Gerardo C. Rios, EPA (w/enclosure) via email
Carla Presetyo Jo, Yorke Engineering, LLC (w/enclosure) via email

Facility # C-8609
CENTRAL CALIFORNIA SHEETS, LLC
909 UNION ST
KINGSBURG, CA 93631

AUTHORITY TO CONSTRUCT (ATC)

QUICK START GUIDE

1. **Pay Invoice:** Please pay enclosed invoice before due date.
2. **Fully Understand ATC:** Make sure you understand ALL conditions in the ATC prior to construction, modification and/or operation.
3. **Follow ATC:** You must construct, modify and/or operate your equipment as specified on the ATC. Any unspecified changes may require a new ATC.
4. **Notify District:** You must notify the District's Compliance Department, at the telephone numbers below, upon start-up and/or operation under the ATC. Please record the date construction or modification commenced and the date the equipment began operation under the ATC. You may NOT operate your equipment until you have notified the District's Compliance Department. A startup inspection may be required prior to receiving your Permit to Operate.
5. **Source Test:** Schedule and perform any required source testing. See http://www.valleyair.org/busind/comply/source_testing.htm for source testing resources.
6. **Maintain Records:** Maintain all records required by ATC. Records are reviewed during every inspection (or upon request) and must be retained for at least 5 years.

By operating in compliance, you are doing your part to improve air quality for all Valley residents.

**For assistance, please contact District Compliance staff at
any of the telephone numbers listed below.**

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

AUTHORITY TO CONSTRUCT

PERMIT NO: C-8609-2-1

ISSUANCE DATE: 06/22/2016

LEGAL OWNER OR OPERATOR: CENTRAL CALIFORNIA SHEETS, LLC

MAILING ADDRESS: 909 UNION ST
KINGSBURG, CA 93631

LOCATION: 909 UNION ST
KINGSBURG, CA 93631

EQUIPMENT DESCRIPTION:

MODIFICATION OF CORRUGATED BOARD MANUFACTURING OPERATION AND A STARCH-BASED ADHESIVE MIXING SYSTEM WITH PERMIT EXEMPT SCRAP HANDLING SYSTEM SERVED BY A BAGHOUSE (LOW EMITTING UNIT): INCREASE CORRUGATED BOARD PROCESSED LIMIT FROM 7,000,000 SQ FT/DAY AND 1,500,000,000 SQ FT/YEAR TO 8,000,000 SQ FT/DAY AND 2,200,000,000 SQ FT/YEAR

CONDITIONS

1. Prior to operating equipment under this Authority to Construct (ATC), permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3,297 lb, 2nd quarter - 3,298 lb, 3rd quarter - 3,298 lb, and fourth quarter - 3,298 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 2/18/16) for the ERC specified below. [District Rule 2201]
2. ERC Certificate Number S-4675-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. Permittee shall submit an application to comply with SJVUAPCD District Rule 2520 - Federally Mandated Operating Permits within 12 months of implementing this ATC. [District Rule 2520]
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
6. The building exhaust vent located within 1,000 feet of the outer boundary of a K-12 school shall be permanently closed. [CH&SC 42301.6]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for 
Arnaud Marjollet, Director of Permit Services

C-8609-2-1 Jun 27 2016 7:25AM -- GARCIAJ Inspection NOT Required

7. The building emergency doors located within 1,000 feet of the outer boundary of a K-12 school shall remain closed during all operating hours. [CH&SC 42301.6]
8. The building roof intake hood located within 1,000 feet of the outer boundary of a K-12 school shall be operated with backdraft protection during all operating hours. [CH&SC 42301.6]
9. VOC emissions from the corrugator shall not exceed 8 pounds per million square feet of corrugated boards produced. [District Rule 2201]
10. The quantity of corrugated board processed shall not exceed any of the following: 8,000,000 square feet in any one day and 2,200,000,000 square feet in any one year. [District Rule 2201]
11. Adhesives used shall not contain any VOC. [District Rule 2201]
12. The permittee shall keep records of the date and total amount of the corrugated boards produced in million square feet. [District Rule 2201]
13. All records shall be retained on-site for a minimum of five years and shall be made available to the District upon request. [District Rule 1070]
14. Facilities C-8609 (Central California Sheets, LLC) and C-3609 (Sacramento Container Corporation) are the same Stationary Source. [District Rule 2010]