



DEC 08 2016

Mr. Gregory Pritchett
Chevron USA Inc
PO Box 1392
Bakersfield, CA 93302

**Re: Notice of Final Action - Title V Permit Renewal
District Facility # S-2010
Project # 1153623**

Dear Mr. Pritchett:

The District has issued the Final Renewed Title V Permit for Chevron USA Inc (see enclosure). The preliminary decision for this project was made on August 22, 2016. No comments were received subsequent to the District preliminary decision.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Syed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Permit to Operate

FACILITY: S-2010

EXPIRATION DATE: 02/29/2016

LEGAL OWNER OR OPERATOR:

CHEVRON USA INC

MAILING ADDRESS:

PO BOX 1392
BAKERSFIELD, CA 93302

FACILITY LOCATION:

LIGHT OIL WESTERN STATIONARY SOURCE
CA

FACILITY DESCRIPTION:

OIL AND NATURAL GAS PRODUCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: S-2010-0-3

EXPIRATION DATE: 02/29/2016

FACILITY-WIDE REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
4. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
5. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
6. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
7. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
8. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
10. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: CHEVRON USA INC
Location: LIGHT OIL WESTERN STATIONARY SOURCE, CA
S-2010-0-3 : Dec 5 2010 12:23PM - VELASCOA

11. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
12. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
13. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
14. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
15. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
16. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
17. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
18. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
22. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
23. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
25. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
26. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
27. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
28. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
29. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
30. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
31. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
32. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
33. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
34. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
35. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit
36. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

37. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
38. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
39. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-3-13

EXPIRATION DATE: 02/29/2016

SECTION: 29 TOWNSHIP: 32S RANGE: 24E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK "T-2" WITH VAPOR CONTROL SYSTEM SHARED WITH S-2010-8 AND '9 DISCHARGED TO THE GAS SALES PIPELINE, AND/OR THE 31E BOOSTER STATION, AND/OR FLARE S-1210-317 (29D OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank. The vapor recovery system shall be APCO-approved, maintained in a leak-free condition, and capable of reducing VOC emissions by at least 99% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District NSR Rule and 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. The permittee shall maintain records of number and type of components installed. Permittee shall update such records when new components are installed. Compliance with permitted VOC emissions shall be calculated from the permittee's records of the number and type of components installed. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Fugitive VOC emissions from component leaks shall be calculated using the EPA Protocol for Equipment Leak Emission Estimate, 1995, Table 2-4, Oil and Gas Production Operations Average Emission Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Fugitive VOC emissions from component leaks shall not exceed 36.5 lb/day and 13,323 lb/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
9. The operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during four consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. The operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
18. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. The permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
22. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosive limit (LEL), whichever is less; or (2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
24. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
25. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, refilling the tank with an organic liquid, and maintenance operations. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
26. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
27. While performing tank cleaning activities, operators may only use the following cleaning agents: water, hot water, diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. The tank sediment may be used as road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
28. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
29. During sludge removal from tanks containing organic liquids with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
30. The permittee shall only transport removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
31. The permittee shall store removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

32. The permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
33. The operator shall maintain records of required monitoring data and support information for inspection at any time for a period of five years. The records shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-4-11

EXPIRATION DATE: 02/29/2016

SECTION: 15 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF WASH TANK WITH VAPOR RECOVERY SYSTEM SERVING TANKS S-2010-4, '10, '11, '266, '267, '291, '292, '293, AND RECEIVING CRUDE OIL FROM FACILITY S-1130, WITH COLLECTED VAPORS PIPED TO GAS PLANT S-49

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test method specified in Section 6.4.7. [District Rule 2201, Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520] Federally Enforceable Through Title V Permit
7. Fugitive emissions from tank components in vapor service, gas/liquid separator vessel, compressor skids, and shared tank vapor control piping shall not exceed 17.9 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

18. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
19. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
20. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
21. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
22. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
25. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
27. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
28. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-8-7

EXPIRATION DATE: 02/29/2016

SECTION: 29 TOWNSHIP: 32S RANGE: 24E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF CRUDE OIL REJECT TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-2010-3 (29D OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. The tank shall vent only to the vapor control system listed on S-2010-3 except during periods of tank cleaning and maintenance as provided in this permit. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District NSR Rule and 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. The operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during four consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. The operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, refilling the tank with an organic liquid, and maintenance operations. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
24. While performing tank cleaning activities, operators may only use the following cleaning agents: water, hot water, diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. The tank sediment may be used as road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
26. During sludge removal from tanks containing organic liquids with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
27. The permittee shall only transport removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
28. The permittee shall store removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit
29. The permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
30. The operator shall maintain records of required monitoring data and support information for inspection at any time for a period of five years. The records shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-9-7

EXPIRATION DATE: 02/29/2016

SECTION: 29 TOWNSHIP: 32S RANGE: 24E

EQUIPMENT DESCRIPTION:

3,300 BBL FIXED ROOF CRUDE OIL STORAGE TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON PERMIT S-2010-3 (29D OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. The tank shall vent only to the vapor control system listed on S-2010-3 except during periods of tank cleaning and maintenance as provided in this permit. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. The operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during four consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. The operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, refilling the tank with an organic liquid, and maintenance operations. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
24. While performing tank cleaning activities, operators may only use the following cleaning agents: water, hot water, diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. The tank sediment may be used as road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
26. During sludge removal from tanks containing organic liquids with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
27. The permittee shall only transport removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
28. The permittee shall store removed sludge from tanks containing organic liquids with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit
29. The permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
30. The operator shall maintain records of required monitoring data and support information for inspection at any time for a period of five years. The records shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-10-5

EXPIRATION DATE: 02/29/2016

SECTION: 15 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

210,000 GAL FIXED ROOF STORAGE TANK RECEIVING PRODUCED CRUDE OIL FROM S-1130, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
2. If the API gravity of crude oil stored in this tank is equal to or greater than 30 degrees, then tank is subject to applicable requirements of Rule 4409. [District Rule 4409, 3.22] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Tank roof appurtenances shall be maintained leak-free. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, as methane, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. An instrument reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute are violations of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
8. The operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. The operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Sludge from tanks with a TVP of = 1.5 psia must be stored in tanks that have a vapor control efficiency of at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 24 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-11-5

EXPIRATION DATE: 02/29/2016

SECTION: 15 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

210,000 GAL FIXED ROOF BALANCE TANK RECEIVING PRODUCED CRUDE OIL FROM S-1130, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
2. If the API gravity of crude oil stored in this tank is equal to or greater than 30 degrees, then tank is subject to applicable requirements of Rule 4409. [District Rule 4409, 3.22] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Tank roof appurtenances shall be maintained leak-free. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, as methane, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. An instrument reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute are violations of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
8. The operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. The operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Sludge from tanks with a TVP of = 1.5 psia must be stored in tanks that have a vapor control efficiency of at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 24 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-12-7

EXPIRATION DATE: 02/29/2016

SECTION: 08 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

84,000 GAL FIXED ROOF WASH TANK #1 SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-2010-15

PERMIT UNIT REQUIREMENTS

1. The tank shall be fully enclosed and shall be equipped with a closed system that collects all VOCs from the storage tank. Collected vapors shall be routed to the gas gathering system that connects to the 17Z gas processing plant. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test method specified in Section 6.4.7. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 4623] Federally Enforceable Through Title V Permit
7. VOC emissions from components in light oil and gas service associated with tank up to vapor control system trunk line shall not exceed 9.4 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. VOC emissions from the components associated with the vapor control system shall not exceed 20.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District Rule 2201 and 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
11. All piping, fittings, and valves directly affixed to and within 5 ft of this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
12. If any of the tank components directly affixed to and within 5 ft of this tank are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
13. Upon detection of any leaking components directly affixed to and within 5 ft of this tank (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
14. Leaking components directly affixed to and within 5 ft of this tank that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
15. If a component type which is directly affixed to and within 5 ft of this tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
16. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Any component directly affixed to and within 5 ft of this tank found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
20. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

21. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
23. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
24. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
25. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
26. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
27. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
29. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
31. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
33. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
34. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-15-7

EXPIRATION DATE: 02/29/2016

SECTION: 08 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

84,000 GAL FIXED ROOF PETROLEUM POWER OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-2010-12

PERMIT UNIT REQUIREMENTS

1. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves directly affixed to and within 5 ft of this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
6. If any of the tank components directly affixed to and within 5 ft of this tank are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
7. Upon detection of any leaking components directly affixed to and within 5 ft of this tank (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
8. Leaking components directly affixed to and within 5 ft of this tank that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CHEVRON USA INC

Location: LIGHT OIL WESTERN STATIONARY SOURCE, CA

8-2010-15-7 : Dec 5 2015 12:23PM - VELASCOA

9. If a component type which is directly affixed to and within 5 ft of this tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
10. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Any component directly affixed to and within 5 ft of this tank found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
14. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
15. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
20. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
21. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
23. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-20-8

EXPIRATION DATE: 02/29/2016

SECTION: SW29 TOWNSHIP: 32S RANGE: 24E

EQUIPMENT DESCRIPTION:

10,500 GALLON DRAIN TANK #4 WITH PRESSURE VACUUM VENT - 29D OIL CLEANING PLANT, MIDWAY SUNSET

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in a leak-free condition except when the operating pressure exceeds the valve's set pressure or as otherwise provided in this permit. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak free. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, all valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-23-31

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BARREL FIXED ROOF WASH TANK WITH VAPOR CONTROL- (CAHN 3 OIL TREATING PLANT)

PERMIT UNIT REQUIREMENTS

1. Except as otherwise provided in this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The vapor recovery system shall be maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. A gas or liquid leak is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Vapor control system compressor shall activate before the pressure relief valve on any of the units served by the vapor control system vents. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The vapor control system shall reduce VOC emissions by at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. The vapor control system shall route all collected vapors to a sales pipeline. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520] Federally Enforceable Through Title V Permit
10. Vapor control system shall include piping from 4 Wemcos, separators and knockouts, tanks S-2010-23, -24, -25, -26, -201, -203, -204, -205, -206, -207, -208, -209, -210, -211, -212, -213, -214, -217, -220, -221, -226, -227, -228, -229, -245, -250, -264, -313, -314, vapor compressors K-301, K-302, and K-303, inlet scrubber V-301, knockout vessel V-302, sulfur vessels V-310 and V-311, gas/liquid separator V-101, Unicels M-210A and M-210B, vapor compressors K-731A and K-731B and air-cooled heat exchanger with separator vessel V-303. [District Rule 2201]
11. Volume of separator vessel V-303 shall not exceed 100 bbls. [District Rule 2020] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. The Unicel water treatment vessels M-210A and M-210B may be open to the atmosphere if the piping connecting them to the vapor control system is closed and leak-free. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Fugitive VOC emission rate from vapor control system shall not exceed 226.2 lb/day. [District Rule 2201]
14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
15. Only operators who elect to participate in the voluntary tank preventive inspection and maintenance, and tank interior cleaning program (program) shall be allowed to use the provisions specified in Tables 3 to 5 and Section 5.7.5. When using Tables 3 to 5 and Section 5.7.5 provisions, operators shall perform the procedures as expeditiously as practicable and minimize emissions to the maximum extent practicable. To participate in this program, the operator shall comply with the requirements of Sections 5.7.1 through 5.7.4. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
19. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
20. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
21. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
22. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

23. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
24. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
25. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
26. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
27. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
28. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
29. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
31. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
32. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
33. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
34. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

35. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520] Federally Enforceable Through Title V Permit
36. Permittee shall maintain with the permit accurate fugitive component counts and the resulting emissions calculated using U.S. EPA document "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors, and shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
37. Records of all required monitoring data and support information shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rules 1070, 2520 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-24-7

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF WASH TANK T-102 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-25-8

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

8,000 BBL FIXED ROOF WASH/REJECT/SHIPPING TANK T-103 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - (CAHN 3)

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-26-6

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

8,000 BBL FIXED ROOF SHIPPING/REJECT TANK T-104 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-123-6

EXPIRATION DATE: 02/29/2016

SECTION: SW29 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

45,486 GALLON FIXED ROOF PETROLEUM WASH TANK #T-1 WITH VAPOR RECOVERY SYSTEM SERVING TANKS -123 AND -124

PERMIT UNIT REQUIREMENTS

1. Vapor control system shall include 25 HP compressor, liquid knockout vessel, backpressure regulators, pressure relief valves, piping to existing gas gathering system, and a 30" dia. X 10' tall pressure vessel on make-up gas pipeline. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Recovered liquids shall be sent to Tank #T-2 (S-2010-124) for processing. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
4. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-124-3

EXPIRATION DATE: 02/29/2016

SECTION: SW29 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

45,486 GALLON FIXED ROOF SHIPPING TANK #T-2 WITH SHARED VAPOR RECOVERY SYSTEM LISTED ON S-2010-123

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-142-20

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK (#T-3) CONNECTED TO VAPOR CONTROL SYSTEM CONSISTING OF FOUR VAPOR COMPRESSOR SKIDS, TANK BLANKET GAS SCRUBBER, AND VAPOR PIPING (LOCATED AT 32 U.S. OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank. The vapor control system shall be APCO-approved and maintained in leak-free condition. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. The following tanks shall be connected to vapor control system: S-2010-142 (T-3), S-2010-143 (T-8), S-2010-144 (T-12), S-2010-146 (T-2), S-2010-148 (T-7), S-2010-223 (T-12A), S-2010-224 (T-8A), and S-2010-297 (T-301). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vapor control system shall consist of vapor collection piping and four vapor compressor skids. Each vapor compressor skid shall consist of one compressor, liquid knockout vessel(s) and/ or scrubber(s), condensate and/ or lube oil pump(s). Vapors are sent to sales gas pipeline or used as a tank blanket gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank, compressor skids, and tank vapor control piping according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive emissions from tank, compressor skids, and tank vapor control piping shall not exceed 2.4 lb VOC/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The vapor control system shall reduce VOC emissions by at least 95%. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
8. If the source can demonstrate compliance with the provisions of Rule 4623, Section 5.7 (amended 5/19/05), then any deviations that are addressed under the provisions of Tables 3 through 5 shall not be in violation of Rule 4623. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak-free. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
12. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
14. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
15. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
16. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event shall the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
17. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623, Section 5.7 (amended 12/20/01). However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623, Section 5.7 (amended 12/20/01). [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
18. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
19. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, Section 5.7 (amended 12/20/01), even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-143-6

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

84,546 GALLON FIXED ROOF PETROLEUM STORAGE TANK #T-8 WITH VAPOR CONTROL SYSTEM LISTED UNDER S-2010-142

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control system S-2010-142. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, the operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-144-4

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #T-12 WITH VAPOR CONTROL (32 US OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control system S-2010-142. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak-free. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, tank gauging and sampling devices shall be equipped with leak-free covers which shall remain closed at all times except during gauging and sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Except as otherwise provided in this permit, the operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-146-4

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

84,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #T-2 WITH VAPOR CONTROL (32 US OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control system S-2010-142. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak-free. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, tank gauging and sampling devices shall be equipped with leak-free covers which shall remain closed at all times except during gauging and sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Except as otherwise provided in this permit, the operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-148-7

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

16,507 GALLON (393 BBL) FIXED ROOF CRUDE OIL DRAIN TANK (#T-7) CONNECTED TO VAPOR CONTROL SYSTEM REFERENCED ON S-2010-142 (LOCATED AT 32 U.S. OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from tank shall be less than 0.5 lb/ day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The vapor control system shall reduce VOC emissions by at least 95%. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
6. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7 (amended 5/19/05), then any deviations that are addressed under the provisions of Table 3 through 6 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak-free. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Except as otherwise provided in this permit, the operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-198-6

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

10.5 MMBTU/HR NATURAL GAS-FIRED TANK HEATING BOILER #401 WITH A POWER FLAME MODEL NVC6-G-30 LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. This unit may be designated as a dormant emissions unit or an active emissions unit. The permittee shall notify the District's Compliance Division by US mail, email or Fax upon redesignating the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. While dormant, normal monitoring and recordkeeping shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
7. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
9. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
10. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
11. Total sulfur content of natural gas combusted shall not exceed 0.75 grain/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmv NO_x @ 3% O₂ or 0.036 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.0076 lb-PM₁₀/MMBtu, 115 ppmv CO @ 3% O₂ or 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
14. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. Source testing to measure natural gas-combustion NO_x and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
19. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
21. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
22. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
23. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
26. This unit is not used in the process of burning fuel for the primary purpose of producing heat or power by indirect heat transfer. Therefore, the requirements of District Rule 4301 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
27. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit
29. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit
31. Formerly S-1128-391.

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-199-6

EXPIRATION DATE: 02/29/2016

SECTION: 03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

10.5 MMBTU/HR NATURAL GAS FIRED TANK HEATING BOILER #B402, WITH A POWER FLAME NOVA PLUS MODEL NVCR6-G-30 LOW NOX BURNER (SERIAL # 120519797)

PERMIT UNIT REQUIREMENTS

1. This unit may be designated as a dormant emissions unit or an active emissions unit. The permittee shall notify the District's Compliance Division by US mail, email or Fax upon redesignating the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. While dormant, normal monitoring and recordkeeping shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
7. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
9. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
10. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
11. Total sulfur content of natural gas combusted shall not exceed 0.75 grain/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 30 ppmvd NO_x @ 3% O₂ or 0.036 lb-NO_x/MMBtu, 0.00214 lb-SO_x/MMBtu or 0.75 gr-S/100 scf, 0.0076 lb-PM₁₀/MMBtu, 115 ppmvd CO @ 3% O₂ or 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
14. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. Source testing to measure natural gas-combustion NO_x and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
19. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
21. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
22. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
23. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
26. This unit is not used in the process of burning fuel for the primary purpose of producing heat or power by indirect heat transfer. Therefore, the requirements of District Rule 4301 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
27. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit
29. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit
31. Formerly S-1128-392.

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-200-11

EXPIRATION DATE: 02/29/2016

SECTION: SW29 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

30.0 MMBTU/HR STRUTHERS NATURAL GAS, PROPANE, AND BUTANE FIRED PORTABLE STEAM GENERATOR S/N 75/76-37153-2 A WITH NORTH AMERICAN BURNER MODEL 4211-30-LE AND O2 CONTROLLER. PERMITTED AS S-1128-952 IN WESTERN HEAVY OIL STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. This unit may be designated as a dormant emissions unit or an active emissions unit. The permittee shall notify the District's Compliance Division by US mail, email or Fax upon redesignating the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070]
7. If this unit has been designated as dormant because it does not comply with District Rules, or if the unit becomes out of compliance with District Rules while it is dormant, operation of the unit is not authorized until an Authority to Construct permit is issued approving all necessary retrofits and permit changes required to comply with the respective District Rules. [District Rule 2010] Federally Enforceable Through Title V Permit
8. This steam generator is authorized to operate at CUSA's light oil western stationary source (LOWSS) as permit S-2010-200 or CUSA's heavy oil western stationary source as permit S-1128-952. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The District shall be notified at least 7 days prior to each transfer between District approved locations, giving the exact location of the move. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Production from wells thermally enhanced by this steam generator shall be routed only to existing vapor controlled tanks. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Total sulfur content of fuel combusted shall not exceed 1.0 grain/100 scf. [District Rules 2201, 4320, 4406, and 4801] Federally Enforceable Through Title V Permit
12. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The duration of each startup and shutdown period shall not exceed 2.0 hours. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit
14. Except during startup and shutdown emission rates shall not exceed any of the following: PM10: 0.0076 lb/MMBtu, NOx (as NO2): 12 ppmv @ 3% O2 or 0.014 lb/MMBtu, VOC: 0.0055 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District NSR Rule and Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. Source testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. Source testing for NOx and CO for each approved fuel shall be conducted within 60 days of first firing on fuel. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. Source testing to demonstrate compliance with NOx and CO emission limits shall be demonstrated not less than once every 36 months if compliance is demonstrated on two consecutive annual compliance tests. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. If permittee fails any compliance demonstration for NOx and/or CO emission limits when testing not less than once every 36 months, compliance with NOx and CO emission limits shall be demonstrated not less than once every 12 months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
19. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. The following test methods shall be used: NOx (lb/MMBtu) - EPA Method 19, NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, PM10 - EPA Method 5, and gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit
22. Compliance source testing shall be conducted under conditions representative of normal operation. [District Rule 1081] Federally Enforceable Through Title V Permit
23. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using an approved portable emission analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
24. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
25. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

26. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
27. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
28. Copies of all fuel invoices, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
29. Particulate matter emissions shall not exceed 0.1 grain/dscf, calculated to 12% CO₂, nor 10 lb/hr. [District Rule 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
30. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO₂. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.3.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
31. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
32. When complying with SO_x emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6B; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
33. If the unit is fired on noncertified gaseous fuel and compliance with SO_x emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D1072, D3031, D4084, D3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
34. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: ASTM D 240 or D 2382 for liquid hydrocarbon fuels; ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2, 4305, 6.2.1, and 4306] Federally Enforceable Through Title V Permit
35. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2 and Kern County Rule 407] Federally Enforceable Through Title V Permit
36. Nitrogen oxide (NO_x) emissions shall not exceed 140 lb/hr, calculated as NO₂. [District Rules 4301, 5.2.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Exhaust gas stack shall be equipped with adequate provisions facilitating the collection of gas samples consistent with EPA Test Methods. [District NSR Rule and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

38. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
39. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
40. Unit shall not be located within 1000 ft of a school. [CH&SC 42301.6]
41. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit
43. Formerly S-1128-927.

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-201-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF PRODUCED WATER TANK T-201 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-203-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF PRODUCED WATER TANK T-203 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-204-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF DRAIN OVERFLOW TANK T-204 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-205-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FILTER BACKWASH TANK T-504 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-206-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF TANK T-500 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-207-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF TANK T-501 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-208-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF FILTER WATER TANK T-502 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-209-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF WATER TANK T-503 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CHEVRON USA INC

Location: LIGHT OIL WESTERN STATIONARY SOURCE, CA

S-2010-209-3 : Dec 5 2016 12:24PM - VELASCOA

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-210-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF FILTER BACKWASH TANK T-505 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-211-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

6,500 BBL FIXED ROOF WASTEWATER TANK T-201B VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23
- CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-212-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

29,000 BBL FIXED ROOF PRODUCED WATER TANK T-205 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-213-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

9,600 BBL FIXED ROOF PRODUCED WATER TANK T-206 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-214-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,700 BBL FIXED ROOF PRODUCED WATER TANK T-207 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23 - CAHN 3

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
3. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-217-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF WASH TANK T-105 VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23

PERMIT UNIT REQUIREMENTS

1. Tank shall operate at constant level. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
4. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7, then any deviations that are addressed under the provisions of Table 3 through 5 shall not be in violation of this permit. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, this tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-219-5

EXPIRATION DATE: 02/29/2016

SECTION: SW 3 **TOWNSHIP:** T27S **RANGE:** R21E

EQUIPMENT DESCRIPTION:

SAND AND SOLIDS SEPARATION OPERATION WITH TWO 17,682 GALLON BELOW GRADE BASINS , 28' WIDE BY 75' LONG WITH SLOPING BOTTOM FROM 0' TO 4' DEEP AND 3' OVERFLOW WEIR, ONE 10,200 GALLON TRENCH, 8' WIDE BY 57' LONG BY 6' DEEP

PERMIT UNIT REQUIREMENTS

1. Sand basins and trench shall be covered at all times by sunscreen tarps except when empty of all petroleum containing materials or during maintenance and clean out operations. [District NSR Rule] Federally Enforceable Through Title V Permit
2. VOC emissions from this operation shall not exceed 23.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Sand basins shall not receive material on continuous basis. Continuous basis means receiving material through a permanent or non-permanent pipeline connection from a tank or other storage device, including pits, pounds or impoundments. [District Rule 4402] Federally Enforceable Through Title V Permit
4. Sand basins shall receive only liquids and solids generated from oil production operations. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall pump off fluids from overflow trench to maintain the level in the trench at it's minimum practical level. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Solids removed from basins shall only be disposed of at an approved disposal site or recycling facility or be used to make road base for use on roads owned or maintained by Chevron USA. [District NSR Rule] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-220-8

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

2,300 BARREL FIXED ROOF CRUDE OIL STORAGE TANK (T-208) CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23

PERMIT UNIT REQUIREMENTS

1. Tank vapors space shall vent only to the vapor control system identified on S-2010-23. [District NSR Rule and District Rules 4623] Federally Enforceable Through Title V Permit
2. Vapor control system efficiency shall be maintained at no less than 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank safety pressure relief valve(s) shall be set to open only when tank vapor space pressure is higher than vapor control system compressor activation pressure. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Tank vapor space appurtenances shall be maintained leak-free as defined in Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all tank seams, welds, joints, piping, valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, all tank gauging or sampling devices, relief valves, manholes, etc. on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 3.17] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
21. Interior tank cleaning shall be performed in accordance with provisions specified in Table 3 of Rule 4623. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
22. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-221-3

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

500 BARREL FIXED ROOF PRODUCED WATER TANK VENTED TO VAPOR CONTROL SYSTEM LISTED IN S-2010-23

PERMIT UNIT REQUIREMENTS

1. Tank shall operate at constant level. [District NSR Rule] Federally Enforceable Through Title V Permit
2. There shall be no leaks in excess of 10,000 ppm when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Except as otherwise provided in this permit, all tank gauging or sampling devices, relief valves, manholes, etc. on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 3.17] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-223-3

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

2,500 BBL CRUDE OIL WASH TANK (#T-12A)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from tank shall be less than 0.5 lb/ day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The vapor control system shall reduce VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak free. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
11. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-224-4

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-8A WITH VAPOR CONTROL SYSTEM LISTED IN S-2010-142

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from tank shall be less than 0.5 lb/ day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The vapor control system shall reduce VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak free. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
11. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permit holder shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
13. Permit holder shall comply with all applicable Tank Interior Cleaning Program requirements specified in Rule 4623. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
14. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
15. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7, Table 3] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-226-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

2,300 BBL FIXED-ROOF PETROLEUM STORAGE TANK (T-208A) CONNECTED TO SHARED VAPOR CONTROL SYSTEM LISTED ON S-2010-23

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit
15. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
18. Interior tank cleaning shall be performed in accordance with provisions specified in Rule 4623. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-227-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED-ROOF PETROLEUM STORAGE TANK (T-209A) CONNECTED TO SHARED VAPOR CONTROL SYSTEM LISTED ON S-2010-23

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit
15. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
18. Interior tank cleaning shall be performed in accordance with provisions specified in Rule 4623. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-228-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED-ROOF PETROLEUM STORAGE TANK (T-209-B) CONNECTED TO SHARED VAPOR CONTROL SYSTEM LISTED ON S-2010-23

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit
15. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
18. Interior tank cleaning shall be performed in accordance with provisions specified in Rule 4623. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-229-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK (T-210) CONNECTED TO SHARED VAPOR CONTROL SYSTEM LISTED ON S-2010-23

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
3. All piping, valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623, and shall be reported as a deviation. A liquid leak is defined as the dripping of an organic liquid at a rate of greater than 3 drops per minute. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
5. Except as otherwise provided in this permit, a reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit
15. Fugitive VOC emission rate shall not exceed that listed in S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
18. Interior tank cleaning shall be performed in accordance with provisions specified in Rule 4623. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-245-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

8,000 BARREL FIXED ROOF CRUDE OIL STORAGE TANK (T-106) VENTING TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23 (CAHN 3 OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-2010-23. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Fugitive VOC emissions rate shall be calculated using the Oil and Gas Production Operations Average Emission Factors, EPA Protocol for Equipment Leak Emission Estimates, Table 2-4, (EPA-453/R-95-017) November 1995 from the total number of vapor components and light oil (i.e. oil with an API gravity of 30 degrees or greater) liquid components associated with tank and equipment specified on this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
4. Daily fugitive VOC emission rate shall not exceed 4.4 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Vapor control system compressor shall activate before the pressure relief valve on this tank vents. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
6. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
18. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
21. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
22. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
25. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
26. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
27. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit
28. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-250-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

8,000 BARREL FIXED ROOF CRUDE OIL STORAGE TANK (T-107) VENTING TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23 (CAHN 3 OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-2010-23. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Fugitive VOC emissions rate shall be calculated using the Oil and Gas Production Operations Average Emission Factors, EPA Protocol for Equipment Leak Emission Estimates, Table 2-4, (EPA-453/R-95-017) November 1995 from the total number of vapor components and light oil (i.e. oil with an API gravity of 30 degrees or greater) liquid components associated with tank and equipment specified on this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
4. Daily fugitive VOC emission rate shall not exceed 4.4 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Vapor control system compressor shall activate before the pressure relief valve on this tank vents. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
6. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
18. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
21. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
22. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
25. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
26. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
27. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit
28. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-264-4

EXPIRATION DATE: 02/29/2016

SECTION: SW03 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

18,000 BARREL FIXED ROOF CRUDE OIL STORAGE TANK (T-211) VENTING TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23 (CAHN 3 OIL CLEANING PLANT)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-2010-23. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Vapor control system compressor shall activate before the pressure relief valve on this tank vents. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions rate shall be calculated using the Oil and Gas Production Operations Average Emission Factors, EPA Protocol for Equipment Leak Emission Estimates, Table 2-4, (EPA-453/R-95-017) November 1995 from the total number of vapor components and light oil (i.e. oil with an API gravity of 30 degrees or greater) liquid components associated with tank and equipment specified on this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
5. Daily fugitive VOC emission rate shall not exceed 4.6 lb-VOC/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4 and 40 CFR 60.110(b)] Federally Enforceable Through Title V Permit
7. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing to ensure the appropriate TVP test method is used. [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
10. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit
12. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
13. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following criteria are met: (1) The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test; (2) One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery (3) the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells; (4) The stored organic liquid in each of the represented tanks is the same and came from the same source; and (5) The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
14. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
15. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 2080] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
23. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
24. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 2080] Federally Enforceable Through Title V Permit
25. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 2080] Federally Enforceable Through Title V Permit
26. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 2080] Federally Enforceable Through Title V Permit
27. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
28. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 2080] Federally Enforceable Through Title V Permit
29. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 2080] Federally Enforceable Through Title V Permit
30. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-266-4

EXPIRATION DATE: 02/29/2016

SECTION: 15 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

100 BBL FIXED ROOF DRAIN TANK (T-4) SERVED BY THE VAPOR CONTROL SYSTEM LISTED ON S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be connected to the vapor recovery system listed on S-2010-4 consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test methods specified in Rule 4623, Section 6.4.6. [District NSR Rule, Rule 4623] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
5. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
6. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
7. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
8. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
11. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Fugitive emissions from tank components shall not exceed 9.1 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
15. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
21. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
23. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
26. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit
27. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-267-4

EXPIRATION DATE: 02/29/2016

SECTION: 15 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF SLOP OIL TANK (T-5) SERVED BY THE VAPOR CONTROL SYSTEM LISTED ON S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be connected to the vapor recovery system listed on S-2010-4 consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test methods specified in Rule 4623, Section 6.4.6. [District NSR Rule, Rule 4623] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
5. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
6. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
7. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
8. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
11. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Fugitive emissions from tank components shall not exceed 6.4 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
15. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
21. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
23. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
26. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit
27. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-268-3

EXPIRATION DATE: 02/29/2016

SECTION: SW08 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

91 BBL CRUDE OIL VESSEL WITH PRV (8Z NEMU)

PERMIT UNIT REQUIREMENTS

1. This vessel shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the vessel, be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
2. Any vessel gauging or sampling devices(s) shall be equipped with a leak-free cover which shall be closed at all times except for gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. True vapor pressure of any organic liquid introduced to the vessel shall be less than 6.5 psia [District NSR Rule] Federally Enforceable Through Title V Permit
4. Vessel liquid throughput shall not exceed 2000 barrels per day and 18,250 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Fugitive emissions from tank liquid service components shall not exceed 4.7 lb/VOC/day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070] Federally Enforceable Through Title V Permit
14. This permit authorizes vessel cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
15. Interior vessel cleaning shall be performed in accordance with provisions specified in Section 5.7.5.3 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of dates of periodic vessel inspections, start and completion dates/times of vessel cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
17. The permittee shall keep accurate records of each organic liquid stored in the vessel including its TVP, API gravity, and throughput for a period of five years, and shall make such records available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall conduct API gravity, true vapor pressure (TVP) testing of the organic liquid stored in this vessel, or a representative vessel as provided in Section 6.2.2 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
19. TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the vessel's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Board's (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 20 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
20. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Instead of testing each uncontrolled vessel, the permittee may conduct a TVP test of the organic liquid stored in a representative vessel provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
22. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-288-5

EXPIRATION DATE: 02/29/2016

SECTION: 29 **TOWNSHIP:** 26S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR WITH NORTH AMERICAN MODEL 4231-85-GLE LOW-NOX BURNER ASSEMBLY, OR EQUIVALENT LOW-NOX BURNER, WITH FLUE GAS RECIRCULATION, APPROVED TO OPERATE AT VARIOUS SPECIFIED LOCATIONS

PERMIT UNIT REQUIREMENTS

1. This unit may be designated as a dormant emissions unit or an active emissions unit. The permittee shall notify the District's Compliance Division by US mail, email or Fax upon redesignating the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing and monitoring shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing and monitoring shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. If this unit has been designated as dormant because it does not comply with District Rules, or if the unit becomes out of compliance with District Rules while it is dormant, operation of the unit is not authorized until an Authority to Construct permit is issued approving all necessary retrofits and permit changes required to comply with the respective District Rules. [District Rule 2010] Federally Enforceable Through Title V Permit
8. This steam generator is permitted to operate at the following locations: Section 29 T26S/R21E, SE or SW 1/4 Section 32, T26S/R21E, and NW or SW 1/4 Section 33 T26S/R21E. [District Rule 4102] Federally Enforceable Through Title V Permit
9. The permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070] Federally Enforceable Through Title V Permit
10. Flue gas recirculation (FGR) shall be utilized as necessary in conjunction with low-NOx burner to maintain ongoing compliance with permitted emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Natural gas fuel sulfur content shall not exceed 1.0 grains-S/100 scf. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Emission rates, except during startup and shutdown shall not exceed: NO_x (as NO₂): 7 ppmvd @ 3% O₂ or 0.008 lb/MMBtu; or CO: 25 ppmvd @ 3% O₂ or 0.0185 lb/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Emission rates shall not exceed any of the following: PM₁₀: 0.0032 lb/MMBtu; or VOC: 0.0055 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Permittee shall maintain a record of the duration of each startup and shutdown of this unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Emission rates during startup and shutdown shall not exceed: NO_x - 0.14 lb/MMBtu or 116 ppmv @ 3% O₂; CO - 0.296 lb/MMBtu or 400 ppmv @ 3% O₂ [District Rule 2201] Federally Enforceable Through Title V Permit
17. Emissions rate of NO_x shall not exceed 45.0 lb/day nor 4380 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Emissions rate of CO shall not exceed 97.1 lb/day nor 10,129 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
19. If the unit is fired on noncertified gaseous fuel and compliance with SO_x emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 3246, D 4084, D 4468, D 6667 or grab sample analysis by GC-FPD/TCD or double GC performed in the laboratory. [District Rules 1070, 2201, 2520, and 4320] Federally Enforceable Through Title V Permit
20. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 1070, 2201, 2520, and 4320] Federally Enforceable Through Title V Permit
21. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 1070, 2201, 2520, and 4320] Federally Enforceable Through Title V Permit
22. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

24. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
27. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
28. Source testing to measure natural gas-combustion NO_x and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
31. The following test methods shall be used: NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SO_x (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B, 6C, or 8, or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D3031, D3246, D4084, D4468, D6667 or double GC for H₂S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
32. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in District Rules 4306 and 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel sources, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. All records shall be maintained and retained on-site for a minimum period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-291-2

EXPIRATION DATE: 02/29/2016

SECTION: 15 TOWNSHIP: 30S RANGE: 22E

EQUIPMENT DESCRIPTION:

3,100 BBL FIXED ROOF PRODUCED WATER TANK (T-700A) SERVED BY THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be connected to the vapor recovery system listed on S-2010-4 consisting of a closed vent system that collects VOCs from the storage tank, and a VOC control device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test methods specified in Rule 4623, Section 6.4.6. [District Rule 2201, Rule 4623] Federally Enforceable Through Title V Permit
2. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Fugitive emissions from tank components in vapor service, compressor skids, and shared tank vapor control piping shall not exceed 10.7 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District 2201] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
16. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
18. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
19. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
21. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
27. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-292-2

EXPIRATION DATE: 02/29/2016

SECTION: 15 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

3,100 BBL FIXED ROOF PRODUCED WATER TANK (T-700B) SERVED BY THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be connected to the vapor recovery system listed on S-2010-4 consisting of a closed vent system that collects VOCs from the storage tank, and a VOC control device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test methods specified in Rule 4623, Section 6.4.6. [District Rule 2201, Rule 4623] Federally Enforceable Through Title V Permit
2. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Fugitive emissions from tank components in vapor service, compressor skids, and shared tank vapor control piping shall not exceed 10.7 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District 2201] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
16. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
18. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
19. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
21. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
27. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-293-2

EXPIRATION DATE: 02/29/2016

SECTION: 15 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

3,100 BBL FIXED ROOF PRODUCED WATER TANK (T-710) RECEIVING FLUID FROM TWO UNVENTED LIQUID FILTER VESSELS AND SERVED BY THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-2010-4

PERMIT UNIT REQUIREMENTS

1. The tank shall be connected to the vapor recovery system listed on S-2010-4 consisting of a closed vent system that collects VOCs from the storage tank, and a VOC control device that reduces the inlet VOC emissions by at least 99% by weight as determined by the test methods specified in Rule 4623, Section 6.4.6. [District Rule 2201, Rule 4623] Federally Enforceable Through Title V Permit
2. All piping, valves, fittings and tank roof appurtenances shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Fugitive emissions from tank components in vapor service, compressor skids, and shared tank vapor control piping shall not exceed 10.7 lb VOC/ day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District 2201] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 4623] Federally Enforceable Through Title V Permit
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the deadlines specified in the Emissions Minimization requirements, shall not constitute a violation of this rule. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within deadlines specified in the Emissions Minimization requirements, shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 30 drops per minute shall be repaired within 8 hours after detection. Liquid components directly affixed to the tank or within 5 feet of the tank that have a liquid leak rate equal to or greater than 3 and less than 30 drops per minute shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
16. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time the tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Tank degassing shall be accomplished by emptying the tank of organic liquid having a TVP of 0.5 psia or greater, and minimizing organic vapors in the tank vapor space by one of the following methods: 1) tank shall be degassed before commencing interior cleaning by exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) tank shall be degassed before commencing interior cleaning by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
18. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
19. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
21. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. During sludge removal from a tank containing an organic liquid with a TVP of 1.5 psia or greater, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall only transport removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Permittee shall store removed sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Intermediate storage of sludge from a tank containing an organic liquid with a TVP of 1.5 psia or greater while determining suitability for use as roadmix must be in vapor leak free containers or in tanks complying with the vapor control requirements of Rule 4623. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623] Federally Enforceable Through Title V Permit
27. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Permittee shall maintain records of dates of periodic tank inspections, start and completion dates/times of tank cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-294-3

EXPIRATION DATE: 02/29/2016

EQUIPMENT DESCRIPTION:

UP TO 462 BBL FIXED ROOF CRUDE OIL DRAIN TANK WITH PV VALVE AUTHORIZED TO OPERATE AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL WESTERN STATIONARY SOURCE (CAN BE OWNED BY PERMITTEE OR RENTED ON AN AS-NEEDED BASIS)

PERMIT UNIT REQUIREMENTS

1. The equipment shall not be located within 1,000 feet of the outer boundary of any K-12 school. [CH&SC 42301.6]
2. Permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District NSR Rule] Federally Enforceable Through Title V Permit
3. This vessel shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the vessel, be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit
4. Any vessel gauging or sampling devices(s) shall be equipped with a gas-tight (as defined in Rule 4623) cover which shall be closed at all times except for gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. True vapor pressure of any organic liquid introduced to the vessel shall be less than 6.17 psia [District NSR Rule] Federally Enforceable Through Title V Permit
6. Vessel liquid throughput shall not exceed 150 barrels per day and 54,750 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive emissions from vessel liquid service components shall not exceed 3.2 lb/VOC/day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If tank is left on site for more than six months, permittee shall notify the APCO in writing at least three (3) days prior to performing tank interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank, 2) the date and time that tank cleaning activities will begin, 3) the method to be used to clean the tank, including any solvents to be used, and 4) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. This tank shall not be required to de-gas before commencing cleaning activities. All other applicable requirements shall be complied with before, during, and after tank cleaning activities. [District Rule 4623] Federally Enforceable Through Title V Permit
18. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
20. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
21. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Permittee shall maintain records of dates of periodic vessel inspections, start and completion dates/times of vessel cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
24. The permittee shall keep accurate records of each organic liquid stored in the vessel including its TVP, API gravity, and throughput for a period of five years, and shall make such records available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall conduct API gravity, true vapor pressure (TVP) testing of the organic liquid stored in this vessel, or a representative vessel as provided in Section 6.2.2 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
26. TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the vessel's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Board's (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 20 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
27. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Instead of testing each uncontrolled vessel, the permittee may conduct a TVP test of the organic liquid stored in a representative vessel provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
29. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-295-3

EXPIRATION DATE: 02/29/2016

EQUIPMENT DESCRIPTION:

UP TO 462 BBL FIXED ROOF CRUDE OIL DRAIN TANK WITH PV VALVE AUTHORIZED TO OPERATE AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL WESTERN STATIONARY SOURCE (CAN BE OWNED BY PERMITTEE OR RENTED ON AN AS-NEEDED BASIS)

PERMIT UNIT REQUIREMENTS

1. The equipment shall not be located within 1,000 feet of the outer boundary of any K-12 school. [CH&SC 42301.6]
2. Permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District NSR Rule] Federally Enforceable Through Title V Permit
3. This vessel shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the vessel, be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
4. Any vessel gauging or sampling devices(s) shall be equipped with a gas-tight (as defined in Rule 4623) cover which shall be closed at all times except for gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. True vapor pressure of any organic liquid introduced to the vessel shall be less than 6.17 psia [District NSR Rule] Federally Enforceable Through Title V Permit
6. Vessel liquid throughput shall not exceed 150 barrels per day and 54,750 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive emissions from vessel liquid service components shall not exceed 3.2 lb/VOC/day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If tank is left on site for more than six months, permittee shall notify the APCO in writing at least three (3) days prior to performing tank interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank, 2) the date and time that tank cleaning activities will begin, 3) the method to be used to clean the tank, including any solvents to be used, and 4) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. This tank shall not be required to de-gas before commencing cleaning activities. All other applicable requirements shall be complied with before, during, and after tank cleaning activities. [District Rule 4623] Federally Enforceable Through Title V Permit
18. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
20. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
21. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Permittee shall maintain records of dates of periodic vessel inspections, start and completion dates/times of vessel cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
24. The permittee shall keep accurate records of each organic liquid stored in the vessel including its TVP, API gravity, and throughput for a period of five years, and shall make such records available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall conduct API gravity, true vapor pressure (TVP) testing of the organic liquid stored in this vessel, or a representative vessel as provided in Section 6.2.2 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
26. TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the vessel's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Board's (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 20 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
27. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Instead of testing each uncontrolled vessel, the permittee may conduct a TVP test of the organic liquid stored in a representative vessel provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
29. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-296-3

EXPIRATION DATE: 02/29/2016

EQUIPMENT DESCRIPTION:

UP TO 462 BBL FIXED ROOF CRUDE OIL DRAIN TANK WITH PV VALVE AUTHORIZED TO OPERATE AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL WESTERN STATIONARY SOURCE (CAN BE OWNED BY PERMITTEE OR RENTED ON AN AS-NEEDED BASIS)

PERMIT UNIT REQUIREMENTS

1. The equipment shall not be located within 1,000 feet of the outer boundary of any K-12 school. [CH&SC 42301.6]
2. Permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District NSR Rule] Federally Enforceable Through Title V Permit
3. This vessel shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the vessel, be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule & 4623] Federally Enforceable Through Title V Permit
4. Any vessel gauging or sampling devices(s) shall be equipped with a gas-tight (as defined in Rule 4623) cover which shall be closed at all times except for gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. True vapor pressure of any organic liquid introduced to the vessel shall be less than 6.17 psia [District NSR Rule] Federally Enforceable Through Title V Permit
6. Vessel liquid throughput shall not exceed 150 barrels per day and 54,750 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive emissions from vessel liquid service components shall not exceed 3.2 lb/VOC/day based on EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-4, Oil and Gas Production Operations Average Emissions Factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Fugitive VOC limit listed above does not include components handling produced fluids with an API gravity less than 30 degrees, or components in water/oil service (condensate) with a water content equal to or greater than 50% by weight, or components handling fluid streams with a VOC content of 10% or less by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. If tank is left on site for more than six months, permittee shall notify the APCO in writing at least three (3) days prior to performing tank interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank, 2) the date and time that tank cleaning activities will begin, 3) the method to be used to clean the tank, including any solvents to be used, and 4) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
17. This tank shall not be required to de-gas before commencing cleaning activities. All other applicable requirements shall be complied with before, during, and after tank cleaning activities. [District Rule 4623] Federally Enforceable Through Title V Permit
18. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
20. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
21. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. If tank is left on site for more than six months and contained organic liquid with a TVP of 1.5 psia or greater, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Permittee shall maintain records of dates of periodic vessel inspections, start and completion dates/times of vessel cleaning activities, and methods of cleaning used. [District Rule 4623] Federally Enforceable Through Title V Permit
24. The permittee shall keep accurate records of each organic liquid stored in the vessel including its TVP, API gravity, and throughput for a period of five years, and shall make such records available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
25. Permittee shall conduct API gravity, true vapor pressure (TVP) testing of the organic liquid stored in this vessel, or a representative vessel as provided in Section 6.2.2 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
26. TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the vessel's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B. Appendix B is an excerpt from the oil and gas section of "California Air Resources Board's (ARB) Technical Guidance Document to the Criteria and Guidelines Regulation for AB 2588", dated August 1989. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 20 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
27. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the vessel. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Instead of testing each uncontrolled vessel, the permittee may conduct a TVP test of the organic liquid stored in a representative vessel provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
29. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-297-2

EXPIRATION DATE: 02/29/2016

SECTION: NW32 TOWNSHIP: 26S RANGE: 21E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-301 WITH VAPOR CONTROL SYSTEM LISTED ON S-2010-142

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
2. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from tank shall be less than 1.0 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The vapor control system shall reduce VOC emissions by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak free. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
9. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
11. Permit holder shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
12. Permit holder shall comply with all applicable Inspection and Maintenance requirements specified in Table 3 of Rule 4623. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 4623] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-300-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1490 BHP CUMMINS MODEL QST3Q-G5NR2 TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District NSR Rule and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 4.3 g-NO_x/bhp-hr, 0.5 g-CO/bhp-hr, or 0.3 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.08 g-PM₁₀/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-301-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1502 BHP CATERPILLAR MODEL C32 (SN #S4C00932) TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE
POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 4.0 g-NO_x/bhp-hr, 1.2 g-CO/bhp-hr, or 0.3 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.1 g-PM₁₀/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-302-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1502 BHP CATERPILLAR MODEL C32 (SN #S4C00997) TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 4.0 g-NOx/bhp-hr, 1.2 g-CO/bhp-hr, or 0.3 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.1 g-PM10/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-303-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 TOWNSHIP: 27S RANGE: 21E

EQUIPMENT DESCRIPTION:

2206 BHP CATERPILLAR MODEL 3512CGD TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 3.8 g-NOx/bhp-hr, 1.2 g-CO/bhp-hr, or 0.2 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.1 g-PM10/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-304-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

2220 BHP CUMMINS MODEL QSK50-G4NR2 TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 4.2 g-NO_x/bhp-hr, 0.9 g-CO/bhp-hr, or 0.3 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.06 g-PM₁₀/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-305-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

3251 BHP CUMMINS MODEL QSKTA60-GE TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District NSR Rule and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 3.8 g-NOx/bhp-hr, 0.4 g-CO/bhp-hr, or 0.2 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.07 g-PM10/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-306-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

3251 BHP CUMMINS MODEL QSK60-B6 TIER 2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District NSR Rule and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 3.8 g-NOx/bhp-hr, 0.4 g-CO/bhp-hr, or 0.2 g-VOC/bhp-hr. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. Emissions from this IC engine shall not exceed 0.07 g-PM10/bhp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule, 40 CFR 60.4205, 13CCR 2423 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-308-2

EXPIRATION DATE: 02/29/2016

SECTION: 29 **TOWNSHIP:** 26S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

TEOR SYSTEM WITH UP TO 130 STEAM ENHANCED WELLS OPERATED WITH CLOSED CASING VENTS, PERMIT EXEMPT WELL TESTERS, PRESSURE VESSELS, RELIEF TANK, AND MASTER TRAP(S) VENTED TO H2S REMOVAL SYSTEM AND THE FIELD GAS GATHERING PIPELINE

PERMIT UNIT REQUIREMENTS

1. Operation of H2S scrubber is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. Emissions rate of VOC associated with the fugitive emissions from TEOR system and ancillary equipment 94.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Production from TEOR operation shall be sent only to tanks equipped with 99% vapor control. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
5. This permit authorizes 10 leaks exceeding an instrument reading of 10,000 ppmv. Leaks greater in number than 10 and exceeding 10,000 ppmv are a violation of this permit. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Except as otherwise provided in this permit, casing vent valves shall be closed and plugged. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
7. Permittee shall maintain records of the date and well identification where steam injection or well stimulation occurs, current list of all thermally enhanced production wells associated with this operation, permit numbers of tanks receiving production from the TEOR operation, leak inspection results, and accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) . [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
8. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401 3.20] Federally Enforceable Through Title V Permit
9. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.6.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
12. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.6.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.9 of Rule 4401. [District Rule 4401 5.7.1] Federally Enforceable Through Title V Permit
13. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401 5.7.2] Federally Enforceable Through Title V Permit
14. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401 5.7.3] Federally Enforceable Through Title V Permit
15. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401 5.8.1] Federally Enforceable Through Title V Permit
16. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.2] Federally Enforceable Through Title V Permit
17. In addition to the inspections required by Section 5.8.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.3] Federally Enforceable Through Title V Permit
18. In addition to the inspections required by Sections 5.8.1, 5.8.2 and 5.8.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.8.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401 5.8.4] Federally Enforceable Through Title V Permit
19. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401 5.8.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

20. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401 5.8.6] Federally Enforceable Through Title V Permit
21. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401 5.9.1] Federally Enforceable Through Title V Permit
22. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and 5.9.2.3 of Rule 4401, or the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.2] Federally Enforceable Through Title V Permit
23. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401 5.9.3] Federally Enforceable Through Title V Permit
24. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
25. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
26. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.5] Federally Enforceable Through Title V Permit
27. The time of the initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.6] Federally Enforceable Through Title V Permit
28. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401 5.9.7] Federally Enforceable Through Title V Permit
29. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401 6.1.1] Federally Enforceable Through Title V Permit
30. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401 6.1.3] Federally Enforceable Through Title V Permit
31. The results of source tests conducted pursuant to Section 4.6.2 of Rule 4401 shall be submitted to the APCO within 60 days after the completion of the source test. [District Rule 4401 6.1.4] Federally Enforceable Through Title V Permit
32. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401 6.1.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

33. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401 6.1.6] Federally Enforceable Through Title V Permit
34. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1.7] Federally Enforceable Through Title V Permit
35. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401 6.1.8] Federally Enforceable Through Title V Permit
36. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401 6.1.11] Federally Enforceable Through Title V Permit
37. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 6.2.1] Federally Enforceable Through Title V Permit
38. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401 6.2.2] Federally Enforceable Through Title V Permit
39. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 for a vapor control system which does not have a VOC destruction device. [District Rule 4401 6.2.3] Federally Enforceable Through Title V Permit
40. An operator seeking approval pursuant to Section 6.2.2 or Section 6.2.3 shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401 6.2.4] Federally Enforceable Through Title V Permit
41. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401 6.3.1] Federally Enforceable Through Title V Permit
42. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401 6.3.2] Federally Enforceable Through Title V Permit
43. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401 6.3.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

44. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401 6.3.5] Federally Enforceable Through Title V Permit
45. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-309-1

EXPIRATION DATE: 02/29/2016

SECTION: SW 3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,600 SQ FT SURFACE AREA (MAXIMUM) VACUUM TRUCK UNLOADING BASIN

PERMIT UNIT REQUIREMENTS

1. VOC emissions from this operation shall not exceed 9.6 lb/day. [District Rule 2201]
2. Vacuum truck unloading sand basin shall only operate periodically and not continuously. [District Rule 4402]
3. Vacuum truck unloading sand basin shall be covered by a tarp (sun screen) to aid in reducing potential air contaminant emissions except during maintenance and clean out operations. [District Rule 2201]
4. During the clean out operation, the solids and liquids shall be removed from the vacuum truck unloading sand basin in a timely manner to minimize VOC emissions. [District Rule 2201]
5. The exposed liquid surface area shall not exceed 1,600 sq.ft. [District Rule 2201]
6. Vacuum truck unloading sand basin shall not receive new material on a continuous basis. Continuous basis means receiving new material through a permanent or non-permanent pipeline connection from a tank or other storage device, including pits, ponds, or impoundments. This requirement does not apply to the onsite handling of existing material originally unloaded at the unloading station. [District Rule 4402]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-310-1

EXPIRATION DATE: 02/29/2016

SECTION: SW 3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,600 SQ FT SURFACE AREA (MAXIMUM) VACUUM TRUCK UNLOADING BASIN

PERMIT UNIT REQUIREMENTS

1. VOC emissions from this operation shall not exceed 9.6 lb/day. [District Rule 2201]
2. Vacuum truck unloading sand basin shall only operate periodically and not continuously. [District Rule 4402]
3. Vacuum truck unloading sand basin shall be covered by a tarp (sun screen) to aid in reducing potential air contaminant emissions except during maintenance and clean out operations. [District Rule 2201]
4. During the clean out operation, the solids and liquids shall be removed from the vacuum truck unloading sand basin in a timely manner to minimize VOC emissions. [District Rule 2201]
5. The exposed liquid surface area shall not exceed 1,600 sq.ft. [District Rule 2201]
6. Vacuum truck unloading sand basin shall not receive new material on a continuous basis. Continuous basis means receiving new material through a permanent or non-permanent pipeline connection from a tank or other storage device, including pits, ponds, or impoundments. This requirement does not apply to the onsite handling of existing material originally unloaded at the unloading station. [District Rule 4402]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-311-1

EXPIRATION DATE: 02/29/2016

SECTION: SW 3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1,600 SQ FT SURFACE AREA (MAXIMUM) VACUUM TRUCK UNLOADING BASIN

PERMIT UNIT REQUIREMENTS

1. VOC emissions from this operation shall not exceed 9.6 lb/day. [District Rule 2201]
2. Vacuum truck unloading sand basin shall only operate periodically and not continuously. [District Rule 4402]
3. Vacuum truck unloading sand basin shall be covered by a tarp (sun screen) to aid in reducing potential air contaminant emissions except during maintenance and clean out operations. [District Rule 2201]
4. During the clean out operation, the solids and liquids shall be removed from the vacuum truck unloading sand basin in a timely manner to minimize VOC emissions. [District Rule 2201]
5. The exposed liquid surface area shall not exceed 1,600 sq.ft. [District Rule 2201]
6. Vacuum truck unloading sand basin shall not receive new material on a continuous basis. Continuous basis means receiving new material through a permanent or non-permanent pipeline connection from a tank or other storage device, including pits, ponds, or impoundments. This requirement does not apply to the onsite handling of existing material originally unloaded at the unloading station. [District Rule 4402]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-312-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** T27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

DEWATERING AND OIL RECOVERY OPERATION WITH DRY MATERIAL HOPPER ME-722 SERVED BY DUST COLLECTOR, 1000 GALLON POLYMER TANK T-721, MACERATOR, SOLIDS CONVEYOR(S), 1000 BBL SLURRY MIXING TANK T-711, CENTRISYS CA21-4 HC THREE PHASE CENTRIFUGE (OR EQUIVALENT), SOLIDS DISCHARGE CONVEYOR AND TEMPORARY SOLIDS STORAGE PAD (CAHN 3 OIL TREATING PLANT)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. Visible emissions from the dust collector serving hopper shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Dust collector serving hopper shall be in operation whenever bags are loaded to the hopper. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. The dust collector shall be maintained and operated according to manufacturer's specifications. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
5. The dust collector cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
6. Material removed from the dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
7. The dust collector shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
8. The differential pressure gauge reading range shall be established per manufacturer's recommendation at time of start up inspection. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Centrifuge liquids shall only be sent to vapor controlled tanks S-2010-313 and '-314. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Centrifuge shall be enclosed except for solids discharge opening. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Centrifuge solids shall be sent only to temporary solids storage pad prior to load-out. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Slurry mixing tank T-711 shall receive material from vacuum truck unloading basins S-2101-309 through '-311, hopper, polymer tank T-721, and shall be enclosed. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Conveyor from hopper to slurry tank shall be enclosed and include flexible spout at slurry tank inlet. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. PM10 emissions from hopper shall not exceed 0.0011 lb/ton of dry material loaded through the feed hopper. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Emissions from the dewatering and oil recovery operation shall not exceed any of the following limits: 0.1 lb-PM10/day or 2.2 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Dry material additive sacks shall be opened only inside enclosed hopper. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Dry material additive sacks shall be disposed of immediately after use and in a manner that minimizes fugitive dust emissions. [District Rule 4102] Federally Enforceable Through Title V Permit
18. Dry material spills shall be cleaned up immediately and solids disposed of properly in a manner which minimizes fugitive dust emissions. [District Rule 4102] Federally Enforceable Through Title V Permit
19. Daily throughput of dry material loaded through the feed hopper shall not exceed 6 tons. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Records of daily throughput of dry material loaded through the hopper shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-313-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL STORAGE TANK T-714 WITH COMPRESSORS K-731A AND K-731B DISCHARGING TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23 (CAHN 3 OIL TREATING PLANT)

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of hydrocarbons in the vapor handling components shall not exceed 50% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC content shall be tested initially and annually thereafter using methods and procedures approved by the District. VOC sampling shall be conducted under circumstances representative of normal operation. VOC content shall be analyzed using the latest version of ASTM D-1945, EPA Method 18 referenced as methane, and ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be analyzed by CARB Method 422. [District Rule 1070] Federally Enforceable Through Title V Permit
3. VOC emissions from the components in gas and light liquid service associated with vessel up to vapor control system truck line shall not exceed 3.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas and light liquid service associated with compressors K-731A and K-731B shall not exceed 13.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
6. Tank shall vent only to vapor control system listed on S-2010-23. [District Rule 2201] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit
10. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 1070 and 4623] Federally Enforceable Through Title V Permit
12. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
13. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit
18. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
20. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
24. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
25. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
26. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
27. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
28. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
29. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
30. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
31. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
32. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
33. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-314-2

EXPIRATION DATE: 02/29/2016

SECTION: SW3 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF CRUDE OIL/WATER STORAGE TANK T-715 VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-2010-23 (CAHN 3 OIL TREATING PLANT)

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of hydrocarbons in the vapor handling components shall not exceed 50% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC content shall be tested initially and annually thereafter using methods and procedures approved by the District. VOC sampling shall be conducted under circumstances representative of normal operation. VOC content shall be analyzed using the latest version of ASTM D-1945, EPA Method 18 referenced as methane, and ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be analyzed by CARB Method 422. [District Rule 1070] Federally Enforceable Through Title V Permit
3. VOC emissions from the components in gas and light oil service associated with vessel up to vapor control system truck line shall not exceed 3.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
5. Tank shall vent only to vapor control system listed on S-2010-23. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 1070 and 4623] Federally Enforceable Through Title V Permit
11. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit
17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
19. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
23. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
25. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
26. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
27. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
28. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
29. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
30. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
31. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
32. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-315-3

EXPIRATION DATE: 02/29/2016

SECTION: SW04 **TOWNSHIP:** 27S **RANGE:** 21E

EQUIPMENT DESCRIPTION:

100 BBL FIXED ROOF CRUDE OIL EMERGENCY DRAIN/RELIEF TANK WITH PVRV - LOST HILLS GAUGE SETTING (GS) #10

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free (as defined in Rule 4623, amended May 19, 2005) condition except when the operating pressure exceeds the valve's set pressure. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. The tank and all piping, valves, and fittings shall be maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A gas leak or a liquid leak is a violation of this permit and Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
5. An emergency is defined as an unforeseeable failure or malfunction of operating equipment that: 1) is not due to neglect or disregard of air pollution laws or rules; 2) is not intentional or the result of negligence; 3) is not due to improper maintenance; and 4) is necessary to prevent or control an unsafe situation. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The owner or operator shall notify the District of any emergency use of the tank within 48 hours after organic liquid is introduced into the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall be emptied within 48 hours of resolving the emergency event and after it is safe to enter the area. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
8. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of no greater than 1.4 psia under all storage conditions. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Crude oil throughput shall not exceed 16,000 barrels per emergency event. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Crude oil throughput during non-emergency use shall not exceed 4 barrels per monthly average day nor 480 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank within 60 days of startup to verify compliance with tvp permit limit and at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct API gravity testing. [District Rule 2201] Federally Enforceable Through Title V Permit
13. For crude oil with an API gravity of greater than 26 degrees, the TVP shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting RVP to TVP at the tanks maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in Appendix B of Rule 4623. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range greater than 26 degrees up to 30 degrees so may be determined by using other equivalent test methods approved by APCO, ARB, and US EPA. [District Rule 2201] Federally Enforceable Through Title V Permit
14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall report to the District in writing within 30 days of the resolution of the emergency. The report shall include: 1) date(s) the organic liquid is first introduced into the tank; 2) the date(s) the tank is fully drained; 3) a description of each emergency event; 4) the barrels (or gallons) of organic liquid introduced into the tank during each emergency event; 5) a statement that the failure or malfunction has been corrected, the date corrected, and proof of correction; 6) a specific statement of the reason or cause for the occurrence; and 7) a description of the corrective measures undertaken and/or to be undertaken to avoid such an occurrence in the future. [District Rule 2201] Federally Enforceable Through Title V Permit
17. For non-emergency use, permittee shall maintain monthly records of average daily crude oil throughput and shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 2201] Federally Enforceable Through Title V Permit
18. For emergency use, permittee shall maintain records showing: 1) date(s) the organic liquid is first introduced into the tank; 2) the date(s) the tank is fully drained; 3) a description of each emergency event; and 4) the barrels (or gallons) of organic liquid introduced into the tank during each emergency event. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-2010-317-1

EXPIRATION DATE: 02/29/2016

EQUIPMENT DESCRIPTION:

25 MMBTU/HR LIMITED USE, TRANSPORTABLE, AIR-ASSISTED FLARE SERVING TANK AND TEOR VAPOR CONTROL SYSTEMS (ALSO PERMITTED AS S-1128-1004) - VARIOUS UNSPECIFIED LOCATIONS CHEVRON USA INC'S LIGHT OIL WESTERN STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1/4 or 5% opacity. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Flare shall not operate within 1000 ft from a receptor (business or residence). [District Rule 4102]
4. The equipment shall not be located within 1000 ft. of any K-12 school. [CH&SC 42301.6]
5. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site when in use. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
6. Gas line to flare shall be equipped with operational, volumetric flow rate indicator. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
7. Permittee shall inspect the flare in operation for visible emissions at each new location. If visible emissions are observed, corrective action shall be taken. If visible emissions persist, an EPA Method 9 test shall be performed within 72 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The flame shall be present at all times when combustible gases are vented through the flare. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
9. Flare shall be equipped with operational automatic re-ignition provisions. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
10. Daily flared gas heat input, except pilot fuel, shall not exceed 600 MMBtu per day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual flared gas heat input, except pilot fuel, shall not exceed 60 billion Btu per year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Flared gas sulfur content shall not exceed 50.0 gr S/100 scf or 800 ppmv H₂S. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Emission rates shall not exceed any of the following: 0.008 lb-PM₁₀/MMBtu, 0.068 lb-NO_x/MMBtu (as NO₂), 0.063 lb-VOC/MMBtu, or 0.37 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permittee shall document compliance with flared gas sulfur content at each new location of operation of the flare by performing H₂S analysis of flared gas using Draeger tube analysis. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. Permittee shall determine sulfur content of gas flared at startup and at least once per year using ASTM method D3246 or double GC for H₂S and mercaptans. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall determine hhv of gas flared at time of sulfur testing by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall maintain accurate daily records indicating flare location, flared gas sulfur content, and daily and annual flared gas heat input rates; and such records shall be made readily available for District inspection upon request for a minimum of 5 years. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.