



AUG 01 2017

Mr. Larry Alexander
Crimson California Pipeline LP
3760 Kilroy Airport Way #300
Long Beach, CA 90806

**Re: Notice of Final Action - Title V Permit Renewal
District Facility # C-306
Project # C-1160648**

Dear Mr. Alexander:

The District has issued the Final Renewed Title V Permit for Crimson California Pipeline LP (see enclosure). The preliminary decision for this project was made on June 6, 2017. No comments were received subsequent to the District preliminary decision.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

San Joaquin Valley Air Pollution Control District

FACILITY: C-306-0-2

EXPIRATION DATE: 11/30/2021

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: CRIMSON CALIFORNIA PIPELINE, LP
Location: INTERSTATE 5 & HIGHWAY 41, KETTLEMAN CITY, CA 93239
C-306-0-2: Jul 27 2017 8:21AM - GARCIA/C

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. On June 30, 2012, the Initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based on this date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-306-1-4

EXPIRATION DATE: 11/30/2021

SECTION: SW19 **TOWNSHIP:** 22S **RANGE:** 19E

EQUIPMENT DESCRIPTION:

ONE 134,000 BBL RIVETED SILVER EXTERNAL FLOATING ROOF CRUDE OIL STORAGE TANK WITH A SPRING-TYPE FLEX-A-SEAL PRIMARY SEAL AND AN INSUGER WIPER TYPE SECONDARY SEAL WITH A 16 GAUGE GALVANIZED CONTINUOUS WEATHER-STRIP (TANK ID #232)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of the organic liquid stored in the tank shall be less than 11.0 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with a closure device between the tank shell and roof edge consisting of two seals mounted one above the other; the one below shall be referred to as the primary seal, and the one above shall be referred as the secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 2 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The cumulative length of all primary seal gaps greater than 1 1/2 inches shall not exceed 10% of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
7. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
8. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the secondary seal greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The metallic-shoe type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 5 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The secondary seal shall allow easy insertion of probes up to 2 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
14. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Except for primary seals, secondary seals, floating roof deck fittings, floating roof automatic bleeder valves, and pressure-vacuum relief valves, the tank's components shall be inspected annually for leaks. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
18. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Except for automatic bleeder vents, rim vents and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623] Federally Enforceable Through Title V Permit
24. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak-free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623] Federally Enforceable Through Title V Permit
25. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
26. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
28. The slotted guidepole well on an external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
30. The permittee of external floating roof tanks shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
31. The permittee shall inspect all floating tanks at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623] Federally Enforceable Through Title V Permit
32. The permittee shall inspect the primary and secondary seals for compliance with the requirements of this rule every time a tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623] Federally Enforceable Through Title V Permit
33. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
34. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
35. The permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
36. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
37. Compliance with permit conditions in the Title V permit shall be deemed in compliance with SJVUAPCD Rule 4623 (Amended May 19, 2005). [District Rule 2520, Section 13.2] Federally Enforceable Through Title V Permit
38. This unit was constructed prior to 1970 and has not undergone reconstruction or modification as defined in 40 CFR 60 Subpart A; therefore, 40 CFR 60 Subpart K, Subpart Ka, and Subpart Kb do not apply to this source. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-306-3-3

EXPIRATION DATE: 11/30/2021

SECTION: SW19 TOWNSHIP: 22S RANGE: 19E

EQUIPMENT DESCRIPTION:

ONE 52,720 BBL RIVETED SILVER EXTERNAL FLOATING ROOF CRUDE OIL STORAGE TANK WITH AN INSULATED FLOATING PAN-TYPE ROOF WITH A FOAM AND FINGER MULTI-LAYERED WIPER ASSEMBLY ON BOTH PRIMARY AND SECONDARY SEALS (TANK ID #226)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of the organic liquid stored in the tank shall be less than 11.0 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with a closure device between the tank shell and roof edge consisting of two seals mounted one above the other; the one below shall be referred to as the primary seal, and the one above shall be referred as the secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 2 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The cumulative length of all primary seal gaps greater than 1 1/2 inches shall not exceed 10% of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
7. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
8. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The metallic-shoe type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 5 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The secondary seal shall allow easy insertion of probes up to 2 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
14. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Except for primary seals, secondary seals, floating roof deck fittings, floating roof automatic bleeder valves and pressure-vacuum relief valves, the tank's components shall be inspected annually for leaks. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
18. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623] Federally Enforceable Through Title V Permit
24. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak-free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623] Federally Enforceable Through Title V Permit
25. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
26. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
28. The slotted guidepole well on an external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
30. The permittee of external floating roof tanks shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
31. The permittee shall inspect all floating tanks at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623] Federally Enforceable Through Title V Permit
32. The permittee shall inspect the primary and secondary seals for compliance with the requirements of this rule every time a tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623] Federally Enforceable Through Title V Permit
33. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
34. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
35. The permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
36. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
37. Compliance with permit conditions in the Title V permits shall be deemed in compliance with SJVUAPCD Rule 4623 (amended May 19, 2005). [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
38. This unit was constructed prior to 1970 and has not undergone reconstruction or modification as defined in 40 CFR 60 Subpart A; therefore, 40 CFR 60 subpart K, Subpart Ka, and Subpart Kb do not apply to this source. [District Rule 2520, 13.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-306-9-6

EXPIRATION DATE: 11/30/2021

SECTION: SW19 **TOWNSHIP:** 22S **RANGE:** 19E

EQUIPMENT DESCRIPTION:

ORGANIC LIQUID (CRUDE OIL) UNLOADING OPERATION CONSISTING OF TWO UNLOADING RACKS (RACK #1 AND RACK #2)

PERMIT UNIT REQUIREMENTS

1. The unloading equipment shall be designed, installed, maintained, and operated such that there are no leaks or excess organic liquid drainage at disconnection. [District Rule 4624] Federally Enforceable Through Title V Permit
2. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above background as methane. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Excess liquid drainage shall be defined as exceeding 10 milliliters based on an average from 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
4. Gaseous or vapor emissions with a concentration of VOC greater than 10,000 ppmv above a background as methane and liquid leaks at a rate of more than three (3) drops per minute shall constitute a leak and are violations of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The operator shall inspect each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the test method prescribed in this permit. [District Rule 4624] Federally Enforceable Through Title V Permit
6. Any component that is found to be leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be re-inspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit
7. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4624] Federally Enforceable Through Title V Permit
8. Fugitive VOC emissions from components in gas, light liquid, and light oil service shall not exceed 0.38 lb/day. VOC emissions from disconnects shall not exceed 0.86 lb/day, and there shall be no more than 80 liquid line disconnects per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The emission of VOC from the transfer operation shall not exceed 0.08 pounds VOC per 1,000 gallons of organic liquid transferred. [District Rule 4624] Federally Enforceable Through Title V Permit
10. Fugitive VOC emissions rate shall be calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) from the total number of components in gas, light liquid, and light crude oil service. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Permittee may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks are found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the frequency shall revert back to quarterly, and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit
12. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4624] Federally Enforceable Through Title V Permit
13. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The operator shall maintain records of the results of all required leak inspections. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The operator shall maintain daily records of liquid throughput and number of disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.