



**FEB 05 2018**

Mr. Glen Mears  
Plains LPG Services LP  
19430 Beech Ave  
Shafter, CA 93263

**Re: Notice of Final Action - Title V Permit Renewal**  
**Facility Number: S-71**  
**Project Number: S-1170879**

Dear Mr. Mears:

The District has issued the Final Renewed Title V Permit for Plains LPG Services LP (see enclosure). The preliminary decision for this project was made on November 30, 2017. No comments were received subsequent to the District preliminary decision.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet  
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email  
cc: Gerardo C. Rios, EPA (w/enclosure) via email

**Seyed Sadredin**  
Executive Director/Air Pollution Control Officer

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585



Facility # S-71  
PLAINS LPG SERVICES LP  
19430 BEECH AVE  
SHAFTER, CA 93263

## Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.\* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

Modesto:	(209) 557-6446
Fresno:	(559) 230-5888
Bakersfield:	(661) 392-5665

\*Failure to comply with the permit unit requirements may result in enforcement action.

**Sayed Sadredin**  
Executive Director/Air Pollution Control Officer

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585

# Permit to Operate

**FACILITY:** S-71 **EXPIRATION DATE:** 08/31/2022

**LEGAL OWNER OR OPERATOR:** PLAINS LPG SERVICES LP  
**MAILING ADDRESS:** 19430 BEECH AVE  
SHAFTER, CA 93263

**FACILITY LOCATION:** 7TH STANDARD RD & BEECH AVE  
SHAFTER, CA 93263

**FACILITY DESCRIPTION:** NATURAL GAS PRODUCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin  
Executive Director / APCO

Arnaud Marjollet  
Director of Permit Services

# San Joaquin Valley Air Pollution Control District

FACILITY: S-71-0-2

EXPIRATION DATE: 08/31/2022

## FACILITY-WIDE REQUIREMENTS

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: PLAINS LPG SERVICES LP  
Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263  
S-71-0-2 Jan 30 2018 11:17AM -- AHMADS



10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of each year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-1-9

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

LPG/NGL DISTILLATION OPERATION INCLUDING ONE DE-PROPANIZER/DE-BUTANIZER, ONE DE-PROPANIZER/STRIPPER, UNFIRED DE-ISOBUTANIZER REBOILER/LPG VAPORIZER, ONE DE-ISOBUTANIZER, AND ONE DE-BUTANIZER

## PERMIT UNIT REQUIREMENTS

---

1. Process heat shall be supplied by hot oil system (Permit #'s S-71-4 and '-14) or hydrogen plant steam methane/LPG reformer furnace (Permit #S-71-5). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Heat exchangers using cooling water shall be maintained leak-free as defined in Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
3. Steam for steam driven pumps shall be supplied from steam methane/LPG reformer furnace waste heat boiler (Permit No. S-71-5) only. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall comply with all applicable inspection, maintenance, testing, and recordkeeping requirements of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Fugitive VOC emissions from permit unit shall not exceed 59.0 lb per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas compressor seals and pump seals shall have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Gas compressor seals and pump seals shall have no leak of VOC in excess of 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except for 1.3% of the valves, 0.5% of the connectors, and 0.5% of the flanges, fugitive piping components as defined in CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" shall have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Fugitive components shall have no leaks of VOC in excess of 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. For the following equipment :V-1 fractionating tower, V-1 feed piping, V-1 bottoms piping, V-1 overhead piping, P-5A/B, P12A/B, five heat exchangers, V-20, V-4 fractionating tower, V-4 feed piping, V-4 piping to storage, six heat exchangers, pumps P-4A/B, inlet piping to E-9 LPG fuel gas vaporizer and outlet piping from E-9 LPG fuel gas vaporizer to off-gas system, any valve, flange, or connector with a vapor leak greater than 100 ppmv above background or any compressor seal or pump seal with a vapor leak greater than 500 ppmv above background (when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21) shall be repaired in a manner consistent with the procedures specified in Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
10. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
11. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of >10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
12. For pressure relief devices (PRDs); a major gas leak is a detection of >10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
13. For pumps, compressors, and other components; a major gas leak is a detection of >10,000 ppmv as methane; a minor gas leak is a detection of 500 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
14. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
15. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
16. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
17. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

18. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
19. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
20. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
21. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
22. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
23. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
24. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
25. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
26. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak >10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
27. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit
28. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
29. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
30. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

31. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
32. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
33. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
34. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
35. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
36. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
37. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
38. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
39. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
40. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



42. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has an overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
43. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are >10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are >50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
44. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are >10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
45. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
46. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
47. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

48. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
49. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
50. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
51. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
52. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
53. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
54. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
55. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
56. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
57. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
58. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-2-14

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

NATURAL GASOLINE AND LPG LOADING AND UNLOADING OPERATION WITH VAPOR CONTROL, TWO NATURAL GASOLINE AND LPG LOADING/UNLOADING RACKS, TWO LPG LOADING/UNLOADING RACKS, THREE 20,850 GALLON PRESSURIZED STORAGE TANKS, TWO 25 HP COMPRESSORS, PIPING TO PRESSURIZED (PERMIT EXEMPT) LPG TANKS, AND NITROGEN PURGE SYSTEM FOR LIQUID LINES, COMPRESSOR SEALS, AND COMPRESSOR CRANKCASES

## PERMIT UNIT REQUIREMENTS

---

1. The loading racks shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 4624] Federally Enforceable Through Title V Permit
2. Permittee shall comply with all applicable inspection, maintenance, testing, and recordkeeping requirements of Rule 4624 for organic liquid loading operations. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Nitrogen purge system shall be a closed loop system and shall not vent to the atmosphere during operation of the system. [District Rule 2201] Federally Enforceable Through Title V Permit
4. After completion of truck loading/unloading, liquid lines shall be purged with nitrogen prior to disconnection. [District Rule 4624] Federally Enforceable Through Title V Permit
5. The nitrogen purge system serving the compressor seals and compressor crankcases shall vent through two activated charcoal canisters connected in series, except during scheduled maintenance or repair activities. During repair and maintenance (such as charcoal bed change out) VOC emissions shall be minimized to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The nitrogen purge system's used activated charcoal canisters shall be handled and disposed of in sealed containers, preventing VOC emissions to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The nitrogen purge system's activated charcoal canisters shall be replaced to maintain the VOC concentration from the canister vent less than 4,500 ppmv-VOC or periodically as recommended by the manufacturer, whichever occurs first. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Fugitive VOC emission rate shall not exceed 32.19 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum VOC emissions from truck loading/unloading liquid hose connects/disconnects shall not exceed 3.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Maximum VOC emissions from truck loading/unloading vapor hose connects/disconnects shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-2-14 Jan 30 2018 11:17AM - AHMADS

11. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-2c: CAPCOA Oil and Gas Production Screening Value Range Emission Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
12. There shall be no more than 192 liquid hose connects/disconnects in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. There shall be no more than 192 vapor hose connects/disconnects in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permittee shall maintain accurate daily records of the number of truck loading/unloading vapor hose connects/disconnects and truck loading/unloading liquid hose connects/disconnects. [District Rule 1070] Federally Enforceable Through Title V Permit
15. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455, 5.0] Federally Enforceable Through Title V Permit
16. Except as follows, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
17. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within the Rule. [District Rule 4455, 5.1.1] Federally Enforceable Through Title V Permit
18. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455, 5.1.2] Federally Enforceable Through Title V Permit
19. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be re-inspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of the Rule. [District Rule 4455, 5.2.1 and 5.2.2] Federally Enforceable Through Title V Permit
20. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455, 5.2.3, 5.2.4, 5.2.5, 5.2.6, and 5.2.7] Federally Enforceable Through Title V Permit
21. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of the rule. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs, which shall continue to be inspected on a quarterly basis. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of the Rule exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this Rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
23. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455, 5.2.11] Federally Enforceable Through Title V Permit
24. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455, 5.2.12] Federally Enforceable Through Title V Permit
25. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this Rule. [District Rule 4455, 5.3.1 and 5.3.2] Federally Enforceable Through Title V Permit
26. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455, 5.3.3] Federally Enforceable Through Title V Permit
27. All component leaks shall be immediately minimized to the extent possible, but not later than one hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of the Rule, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of the Rule shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455, 5.3.5] Federally Enforceable Through Title V Permit
28. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this Rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455, 5.3.6] Federally Enforceable Through Title V Permit
29. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 months after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of the rule, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of the Rule, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455, 5.3.7] Federally Enforceable Through Title V Permit
30. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

31. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of the Rule. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455, 5.4.3 and 5.4.4] Federally Enforceable Through Title V Permit
32. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455, 5.5] Federally Enforceable Through Title V Permit
33. The operator shall keep a copy of the OMP at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved Operator Management Plan. [District Rule 4455, 6.1.2] Federally Enforceable Through Title V Permit
34. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of the Rule. [District Rule 4455, 6.2.1] Federally Enforceable Through Title V Permit
35. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty calendar days of following notification of process PRD release subject to 6.3.1 of the rule. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of the Rule. [District Rule 4455, 6.3] Federally Enforceable Through Title V Permit
36. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of the Rule. [District Rule 4455, 6.4] Federally Enforceable Through Title V Permit
37. The organic liquid loading operation shall be bottom loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
38. The VOCs from the organic liquid transfer operation shall be routed to: a vapor collection and control system; or a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a floating roof container that meets the control requirements in Rule 4623; or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623; or a closed VOC emission control system. [District Rule 4624] Federally Enforceable Through Title V Permit
39. When utilizing a closed VOC emission control system or utilizing a container that meets the control requirements of Rule 4623 (Storage of Organic Liquids) to meet the emission control requirements of this permit, the transfer operation shall demonstrate compliance by complying with the leak inspection requirements of Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
40. The vapor collection and control system, except when transferring liquefied petroleum gas, shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
41. For this Class 1 organic liquid transfer operation, the emission of VOC from the transfer operation shall not exceed 0.08 pounds per 1,000 gallons of organic liquid transferred. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

42. The maximum liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 4624]  
Federally Enforceable Through Title V Permit
43. Transfer rack shall be maintained and operated in accordance with the manufacturer's specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined in Rule 4624. [District Rule 4624]  
Federally Enforceable Through Title V Permit
44. Except for components subject to Rule 4455, a leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from equipment into a container is not considered a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4624] Federally Enforceable Through Title V Permit
45. Except for components subject to Rule 4455, permittee shall inspect the loading rack for leaks during transfer at least once every calendar quarter using a portable hydrocarbon detection instrument in accordance with EPA Method 21 or alternative method approved in writing by the APCO and EPA. [District Rule 4624] Federally Enforceable Through Title V Permit
46. Except for components subject to Rule 4455, all equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replaced equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit
47. Except for components subject to Rule 4455, an operator may apply for a written approval from the APCO to change the inspection frequency required by Rule 4624 from quarterly to annually provided no leaks were found during inspections required under provisions of Sections 5.9.1 and 5.9.2 of Rule 4624 during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection the frequency shall revert back to quarterly and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit
48. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-3-13

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

LPG TRUCK LOADING/UNLOADING RACKS #4 & #5 INCLUDING (2) 25 HP COMPRESSORS, (4) 2" LIQUID UNLOADING HOSES, (4) 1" VAPOR RECOVERY HOSES, PIPING TO PERMIT EXEMPT LPG TANK, AND NITROGEN PURGE SYSTEM SERVING LIQUID LINES AND COMPRESSOR SEALS AND CRANKCASES

## PERMIT UNIT REQUIREMENTS

---

1. After completion of truck unloading, liquid lines shall be purged with nitrogen prior to disconnection. [District Rule 4624] Federally Enforceable Through Title V Permit
2. The permittee shall comply with all inspection, maintenance, testing, and recordkeeping requirements of Rule 4624 for the organic liquid loading operation. [District Rule 4624] Federally Enforceable Through Title V Permit
3. The nitrogen purge system serving the liquid lines shall be a closed loop system and shall not vent to the atmosphere during operation of the system. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The nitrogen purge system serving the compressor seals and compressor crankcases shall vent through two activated charcoal canisters connected in series, except during scheduled maintenance or repair activities. During repair and maintenance (such as charcoal bed change out) VOC emissions shall be minimized to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The nitrogen purge system's used activated charcoal canisters shall be handled and disposed of in sealed containers, preventing VOC emissions to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The nitrogen purge system's activated charcoal canisters shall be replaced to maintain the VOC concentration from the canister vent less than 4,500 ppmv-VOC or periodically as recommended by the manufacturer, whichever occurs first. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Fugitive VOC emission rate shall not exceed 17.6 lb per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The operator shall keep a copy of the APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4455] Federally Enforceable Through Title V Permit
10. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, process pressure relief device (PRD), component identification, recordkeeping and notification requirements of Rule 4455 for all components containing or contacting VOC at the this gas liquids processing facility, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Condition 13 applies to the following equipment: V-1/V-4 bottoms rundown to east tank farm unloading operation and V-1 bottoms rundown to east tank farm storage and center row unloading operation. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Any valve, flange, or connector with a vapor leak greater than 100 ppmv above background or any compressor seal or pump seal with a vapor leak greater than 500 ppmv above background (when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21) shall be repaired in a manner consistent with the procedures specified in Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
13. The loading and vapor collection equipment shall be maintained and operated such that there are no leaks or no excess organic liquid drainage (as defined in Rule 4624) at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
14. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit
15. The organic liquid loading operation shall be bottom loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
16. The VOCs from the organic liquid transfer operation shall be routed to: a vapor collection and control system; or a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a floating roof container that meets the control requirements in Rule 4623; or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623; or a closed VOC emission control system. [District Rule 4624] Federally Enforceable Through Title V Permit
17. When utilizing a closed VOC emission control system or utilizing a container that meets the control requirements of Rule 4623 (Storage of Organic Liquids) to meet the emission control requirements of this permit, the transfer operation shall demonstrate compliance by complying with the leak inspection requirements of Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
18. The vapor collection and control system, except when transferring liquefied petroleum gas, shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
19. For this Class 1 organic liquid transfer operation, the emission of VOC from the transfer operation shall not exceed 0.08 pounds per 1,000 gallons of organic liquid transferred. [District Rule 4624] Federally Enforceable Through Title V Permit
20. The maximum liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 4624] Federally Enforceable Through Title V Permit
21. Transfer rack shall be maintained and operated in accordance with the manufacturer's specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined in Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
22. Except for components subject to Rule 4455, a leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from equipment into a container is not considered a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4624] Federally Enforceable Through Title V Permit
23. Except for components subject to Rule 4455, permittee shall inspect the loading rack for leaks during transfer at least once every calendar quarter using a portable hydrocarbon detection instrument in accordance with EPA Method 21 or alternative method approved in writing by the APCO and EPA. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. Except for components subject to Rule 4455, all equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replaced equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit
25. Except for components subject to Rule 4455, an operator may apply for a written approval from the APCO to change the inspection frequency required by Rule 4624 from quarterly to annually provided no leaks were found during inspections required under provisions of Sections 5.9.1 and 5.9.2 of Rule 4624 during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection the frequency shall revert back to quarterly and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-4-17

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

BUTAMER-BUTANE ISOMERIZATION UNIT INCLUDING TWO BUTANE FEED DRYERS V-102A/B, HYDROGEN MAKE-UP DRYER V-106, TWO REGENERANT DRYERS V-107A/B, ONE 80 MMBTU/HR GAS-FIRED PROCESS OIL HEATER H-201 WITH SIX MODEL CUBR-10W LOW-NOX BURNERS AND FUEL PIPING SHARED WITH PERMIT #S-71-1

## PERMIT UNIT REQUIREMENTS

---

1. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel gas combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include feed surge drum V-103, one product separator V-104, two reactors R-101A/B, stabilizer receiver V-109, and one perchloroethylene storage/injection vessel V-105. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
3. Operation shall include one spent caustic de-gas drum V-112, one stabilizer column V-108, and one net gas scrubber V-110. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Operation shall include one de-isobutanizer tower T-201, one de-isobutanizer overhead accumulator V-201, one 125 HP recycle gas compressor C-101, and one hydrogen make-up knock-out drum V-115. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Operation shall include hot oil circulation piping, exchangers, and miscellaneous vessels. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hot oil drum shall be equipped with a pressure relief valve set at a minimum 100 psig and no greater than maximum pressure rating recommended by ASME or other recognized authority. [District Rule 2201] Federally Enforceable Through Title V Permit
7. All VOC sampling connections, open-ended valves, and lines shall be equipped with two closed valves or be sealed with blind flanges, caps, or threaded plugs except during actual use. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Perchloroethylene storage vessel shall be blanketed with inert gas. [District Rule 4102]
9. Perchloroethylene storage vessel shall be equipped with a pressure relief valve set at a minimum pressure of 50 psig. [District Rule 4102]
10. Hot oil drum shall be fuel gas blanketed with vent to fuel gas system. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Fuel gas combusted in fired equipment may be comprised of process off-gas (including hydrogen), propane, butane, natural gas, or any combination thereof. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The heating value of the fuel gas (Btu/scf @ hhv) combusted in fired equipment shall be determined by sample analysis at least annually. Results of sample analysis shall be retained on site and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Total heat input of fuel gas combusted in units S-71-4, '5, '14 and '15 shall not exceed 1,602,019 MM Btu/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Perchloroethylene receiving line shall be blown dry to storage vessel using an inert gas upon completion of transfer. [District Rule 4102]
15. Only heat transfer fluid manufactured and marketed for such use shall be used in a closed loop as heat transfer medium. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All excess gas shall be incinerated in process heater firebox or existing boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Fugitive VOC emission rate shall not exceed 46.40 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-2c: CAPCOA Oil and Gas Production Screening Value Range Emission Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Emission rates shall not exceed any of the following: PM10: 0.005 lb/MMBtu; NO<sub>x</sub> (as NO<sub>2</sub>): 25 ppmv @ 3% O<sub>2</sub>; VOC: 0.00275 lb/MMBtu; SO<sub>x</sub> (as SO<sub>2</sub>): 0.0005 lb/MMBtu; or CO: 50 ppmv @ 3% O<sub>2</sub>. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Hot oil heater stack shall be equipped with sampling facilities for source testing in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 2201] Federally Enforceable Through Title V Permit
21. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455, 5.0] Federally Enforceable Through Title V Permit
22. Except as follows, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
23. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within the Rule. [District Rule 4455, 5.1.1] Federally Enforceable Through Title V Permit
24. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455, 5.1.2] Federally Enforceable Through Title V Permit
25. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be re-inspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of the Rule. [District Rule 4455, 5.2.1 and 5.2.2] Federally Enforceable Through Title V Permit
26. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455, 5.2.3, 5.2.4, 5.2.5, 5.2.6, and 5.2.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of the rule. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs, which shall continue to be inspected on a quarterly basis. [District Rule 4455] Federally Enforceable Through Title V Permit
28. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of the Rule exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this Rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
29. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455, 5.2.11] Federally Enforceable Through Title V Permit
30. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455, 5.2.12] Federally Enforceable Through Title V Permit
31. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this Rule. [District Rule 4455, 5.3.1 and 5.3.2] Federally Enforceable Through Title V Permit
32. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455, 5.3.3] Federally Enforceable Through Title V Permit
33. All component leaks shall be immediately minimized to the extent possible, but not later than one hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of the Rule, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of the Rule shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455, 5.3.5] Federally Enforceable Through Title V Permit
34. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this Rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455, 5.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

35. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 months after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of the rule, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of the Rule, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455, 5.3.7] Federally Enforceable Through Title V Permit
36. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455, 5.4.1] Federally Enforceable Through Title V Permit
37. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of the Rule. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455, 5.4.3 and 5.4.4] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455, 5.5] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the OMP at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved Operator Management Plan. [District Rule 4455, 6.1.2] Federally Enforceable Through Title V Permit
40. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of the Rule. [District Rule 4455, 6.2.1] Federally Enforceable Through Title V Permit
41. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty calendar days of following notification of process PRD release subject to 6.3.1 of the rule. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of the Rule. [District Rule 4455, 6.3] Federally Enforceable Through Title V Permit
42. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of the Rule. [District Rule 4455, 6.4] Federally Enforceable Through Title V Permit
43. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
44. The duration of each startup and shutdown period for the 80 MMBtu/hr gas-fired process oil heater shall not exceed 5.5 hours and 2.0 hours respectively. Emission limits of Rules 4305, 4306, and 4320 are waived during periods of startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



45. The permittee shall maintain records of the duration of each startup period for the 80 MMBtu/hr gas-fired process oil heater. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
46. The permittee shall monitor and record the stack concentration of NO<sub>x</sub> (as NO<sub>2</sub>), CO, and O<sub>2</sub> at least once every month using a portable emission monitor. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
47. If the NO<sub>x</sub> and/or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
48. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
49. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
50. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
51. This unit shall be tested for compliance with the NO<sub>x</sub>, CO, and SO<sub>x</sub> emissions limits at least once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
52. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. NO<sub>x</sub> emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
53. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. CO emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
54. SO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 19. [District Rule 1081] Federally Enforceable Through Title V Permit
55. Stack gas oxygen for source test purposes shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
56. If permittee fails any compliance demonstration for NO<sub>x</sub>, CO, or SO<sub>x</sub> emission limits when testing not less than once every 36 months, compliance with NO<sub>x</sub>, CO, and SO<sub>x</sub> emission limits shall be demonstrated not less than once every 12 months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
57. Permittee shall maintain accurate records of perchloroethylene usage, fuel gas heating value, and daily, monthly and annual records of fuel gas use. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

58. Permittee shall maintain accurate monthly records of the combined heat input of the fuel gas combusted in units S-71-4, '5, '14 and '15. [Districts Rules 1070 and 2201] Federally Enforceable Through Title V Permit
59. When the LPG supply source for make up fuel to the fuel gas system changes, the stack concentrations of NO<sub>x</sub>, CO, and O<sub>2</sub> shall be measured with a District approved portable analyzer to verify emissions compliance. This is to be done anytime that LPG is being vaporized to supply make up fuel to the fuel gas system. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
60. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit
61. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
62. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-5-10

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

10.28 MMBTU/HR HYDROGEN PLANT INCLUDING ONE STEAM METHANE REFORMER FURNACE #H-301 EQUIPPED WITH CALLIDUS, MODEL LE-CSG-8W-PSA, LOW-NOX BURNER, AND TWO HYDRODESULFURIZER REACTORS (R-301 A/B)

## PERMIT UNIT REQUIREMENTS

---

1. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel gas combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include one steam drum V-301, two 5 HP boiler feed pumps, two 3 HP hydrocarbon feed pumps, one high temp. shift conversion reactor R-302, one deaerator vessel V-303, and one condensate separator V-304. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include four pressure swing absorption purification vessels V-305A/B/C/D, two 40 HP and one 100 HP hydrogen product compressors, one PSA off gas fuel surge drum V-306, and reformer piping to steam distribution. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Gas-fired emission rates shall not exceed any of the following limits: PM10: 0.0137 lb/MMBtu; SOx (as SO2): 0.0006 lb MMBtu; or VOC: 0.00278 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions shall not exceed either of the following limits: 0.036 lb NOx/MMBtu (or 30 ppmv @ 3% O2) or 400 ppmv CO @ 3% O2. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Steam methane reformer stack shall be equipped with sampling facilities for source testing in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
7. Waste gas shall only be ducted to and incinerated in methane reformer fire box only. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All VOC sampling connections, open-ended valves, and lines shall be equipped with two closed valves or be sealed with blind flanges, caps or threaded plugs except during actual use. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Process heat shall be supplied by steam methane reformer furnace only. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Process heat from the steam methane reformer furnace may be used in the LPG/NGL distillation operation (Permit #S-71-1). [District Rule 2201] Federally Enforceable Through Title V Permit
11. Steam methane reformer furnace shall be gas-fired only. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Fuel gas combusted in fired equipment may be comprised of process off-gas (including hydrogen), propane, butane, natural gas, or any combination thereof. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The heating value of the fuel gas (Btu/scf @ the hhv) combusted in fired equipment shall be determined by sample analysis at least annually. Results of sample analysis shall be retained on site and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Total heat input of fuel gas combusted in units S-71-4, '5, '14 and '15 shall not exceed 1,602,019 MM Btu/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Permittee shall maintain accurate records of the fuel gas heating value and daily, monthly and annual records of fuel gas use. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. Permittee shall maintain accurate monthly records of the combined heat input of the fuel gas combusted in units S-71-4, '5, '14 and '15. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. The duration of each startup and shutdown period for the 10.28 MMBtu/hr hydrogen plant shall not exceed 12.0 hours and 2.0 hours respectively. Emission limits of Rules 4305, 4306 and 4320 are waived during periods of startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of the duration of each startup period for the 10.28 MMBtu/hr hydrogen plant. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall monitor and record the stack concentration of NO<sub>x</sub> (as NO<sub>2</sub>), CO, and O<sub>2</sub> at least once every month using a portable emission monitor. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. If the NO<sub>x</sub> and/or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. This unit shall be tested for compliance with the NO<sub>x</sub>, CO, and SO<sub>x</sub> emissions limits at least once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. NOx emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
27. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. CO emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. SOx emissions for source test purposes shall be determined using EPA Method 19. [District Rule 1081] Federally Enforceable Through Title V Permit
29. Stack gas oxygen for source test purposes shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. If permittee fails any compliance demonstration for NOx, CO, or SOx emission limits when testing not less than once every 36 months, compliance with NOx, CO, and SOx emission limits shall be demonstrated not less than once every 12 months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
31. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit
34. On and after July 1, 2012, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-6-7

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

LPG TRUCK LOADING/UNLOADING RACKS #6 & #7 INCLUDING (10) LOADING/CHARGE PUMPS NOT TO EXCEED 30 HP EACH, (6) LIQUID UNLOADING HOSES, (6) VAPOR RECOVERY HOSES, NITROGEN PURGE SYSTEM FOR LIQUID LINES, AND PIPING TO/FROM PERMIT EXEMPT LPG TANK

## PERMIT UNIT REQUIREMENTS

---

1. LPG shall only be loaded into trucks dedicated to LPG service. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor return hose shall be connected to LPG tank vapor space whenever butane is being loaded. [District Rule 2201] Federally Enforceable Through Title V Permit
3. There shall be no more than two liquid hose connects/disconnects per truck load. [District Rule 2201] Federally Enforceable Through Title V Permit
4. After completion of truck unloading, liquid lines shall be purged with nitrogen prior to disconnection. [District Rule 4624] Federally Enforceable Through Title V Permit
5. The loading and vapor collection equipment shall be maintained and operated such that there are no leaks or no excess organic liquid drainage (as defined in Rule 4624) at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
6. Volatile organic compound (VOC) emission rate shall not exceed 18.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall keep a copy of the APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4455] Federally Enforceable Through Title V Permit
9. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, process pressure relief device (PRD), component identification, recordkeeping and notification requirements of Rule 4455 for all components containing or contacting VOC at the this gas liquids processing facility, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455] Federally Enforceable Through Title V Permit
10. Except for those components specified in condition 12, a component shall be considered leaking if one or more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit
13. The organic liquid loading operation shall be bottom loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
14. The VOCs from the organic liquid transfer operation shall be routed to: a vapor collection and control system; or a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a floating roof container that meets the control requirements in Rule 4623; or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623; or a closed VOC emission control system. [District Rule 4624] Federally Enforceable Through Title V Permit
15. When utilizing a closed VOC emission control system or utilizing a container that meets the control requirements of Rule 4623 (Storage of Organic Liquids) to meet the emission control requirements of this permit, the transfer operation shall demonstrate compliance by complying with the leak inspection requirements of Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
16. The vapor collection and control system, except when transferring liquefied petroleum gas, shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
17. For this Class 1 organic liquid transfer operation, the emission of VOC from the transfer operation shall not exceed 0.08 pounds per 1,000 gallons of organic liquid transferred. [District Rule 4624] Federally Enforceable Through Title V Permit
18. The maximum liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 4624] Federally Enforceable Through Title V Permit
19. Transfer rack shall be maintained and operated in accordance with the manufacturer's specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined in Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
20. Except for components subject to Rule 4455, a leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from equipment into a container is not considered a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4624] Federally Enforceable Through Title V Permit
21. Except for components subject to Rule 4455, permittee shall inspect the loading rack for leaks during transfer at least once every calendar quarter using a portable hydrocarbon detection instrument in accordance with EPA Method 21 or alternative method approved in writing by the APCO and EPA. [District Rule 4624] Federally Enforceable Through Title V Permit
22. Except for components subject to Rule 4455, all equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replaced equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



23. Except for components subject to Rule 4455, an operator may apply for a written approval from the APCO to change the inspection frequency required by Rule 4624 from quarterly to annually provided no leaks were found during inspections required under provisions of Sections 5.9.1 and 5.9.2 of Rule 4624 during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection the frequency shall revert back to quarterly and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-7-4

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

320 BHP CUMMINS MODEL NT 855-F4 (S/N 11547983) DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 65 hours per year. [District Rules 2201 and 4702; and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.) and the type of fuel used. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.05% sulfur by weight is to be used. [District Rules 2201 and 4801; and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Particulate matter (PM-10) emission rate shall not exceed 0.36 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Nitrogen oxide emission rate shall not exceed 4.94 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Volatile organic compound (VOC) emission rate shall not exceed 0.40 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Carbon monoxide (CO) emission rate shall not exceed 1.06 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The engine shall be in compliance with all emission limitations and operating limitations that apply at all times. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-8-4

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

55 BHP WAUKESHA MODEL 135GZ (S/N 1041467) NATURAL GAS-FIRED EMERGENCY IC ENGINE POWERING A WATER WELL PUMP

## PERMIT UNIT REQUIREMENTS

---

1. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702; 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per year. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine shall be in compliance with all emission limitations and operating limitations that apply at all times. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-10-5

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25W

**EQUIPMENT DESCRIPTION:**

208 BHP CUMMINS MODEL 6BTA5.9 (S/N 44419184) DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 65 hours per year. [District Rules 2201 and 4702; and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.) and the type of fuel used. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.05% sulfur by weight is to be used. [District Rules 2201 and 4801; and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Injection timing shall be retarded to 4 degrees BTDC. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Nitrogen oxide emission rate shall not exceed 3.33 lb/hr as NO<sub>2</sub>. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Volatile organic compound (VOC) emission rate shall not exceed 0.27 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Carbon monoxide (CO) emission rate shall not exceed 0.72 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The engine shall be in compliance with all emission limitations and operating limitations that apply at all times. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-12-11

**EXPIRATION DATE:** 08/31/2022

**SECTION:** 35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

RAILCAR LPG/NATURAL GASOLINE LOADING/UNLOADING OPERATION WITH FIFTEEN LPG/NATURAL GASOLINE LOADING/UNLOADING STATIONS INCLUDING: ELEVATED RACK SYSTEM UTILIZING HARD PIPING AND SWIVEL JOINTS; AND NITROGEN PURGE SYSTEM SERVING LIQUID LINES, COMPRESSOR SEALS, AND COMPRESSOR CRANKCASES

## PERMIT UNIT REQUIREMENTS

---

1. Operation shall include 15 railcar loading/unloading stations each equipped with two (2) liquid lines and one (1) vapor return line for a total of 45 loading arms with 225 swivel joints. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The nitrogen purge system serving the liquid lines shall be a closed loop system and shall not vent to the atmosphere during operation of the system. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The nitrogen purge system serving the compressor seals and compressor crankcases shall vent through two activated charcoal canisters connected in series, except during scheduled maintenance or repair activities. During repair and maintenance (such as charcoal bed change out) VOC emissions shall be minimized to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The nitrogen purge system's used activated charcoal canisters shall be handled and disposed of in sealed containers, preventing VOC emissions to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The nitrogen purge system's activated charcoal canisters shall be replaced to maintain the VOC concentration from the canister vent less than 4,500 ppmv-VOC or periodically as recommended by the manufacturer, whichever occurs first. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Operation shall include three vapor compressors equipped with knock-out vessels and not exceeding 100 hp each, three compressor knock-out drum pumps, and five turbine pumps. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Fugitive VOC emissions from valves, flanges, connectors, pump seals, and other fugitive components associated with this permit unit shall not exceed 71.88 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum VOC emissions from railcar loading/unloading (vapor and liquid losses combined) operation shall not exceed 2.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using "California Implementation Guidelines for estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities", Oil and Gas Production Operations Screening Value Ranges Emission Factors Table IV-2c Feb 1999. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall comply with all inspection, maintenance, testing, and recordkeeping requirements of Rule 4624 for the organic liquid loading operation. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. The loading racks shall be equipped with a vapor return system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 95%. [District Rule 2201] Federally Enforceable Through Title V Permit
12. There shall be no more than 120 liquid hose connects/disconnects in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. There shall be no more than 60 vapor hose connect/disconnect in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permittee shall keep accurate records of railcar loadings/unloadings, connects/disconnects, and liquid types. [District Rule 1070] Federally Enforceable Through Title V Permit
15. Records required by this permit shall be retained on site for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
16. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455] Federally Enforceable Through Title V Permit
17. Except as follows, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
18. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
19. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
20. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be re-inspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
21. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455] Federally Enforceable Through Title V Permit
22. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of the rule. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs, which shall continue to be inspected on a quarterly basis. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of the Rule exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this Rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
24. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
25. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455] Federally Enforceable Through Title V Permit
26. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
27. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455] Federally Enforceable Through Title V Permit
28. All component leaks shall be immediately minimized to the extent possible, but not later than one hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of the Rule, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of the Rule shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455] Federally Enforceable Through Title V Permit
29. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this Rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455] Federally Enforceable Through Title V Permit
30. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 months after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of the rule, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of the Rule, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of the Rule. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455] Federally Enforceable Through Title V Permit
33. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall keep a copy of the OMP at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved Operator Management Plan. [District Rule 4455] Federally Enforceable Through Title V Permit
35. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
36. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty calendar days of following notification of process PRD release subject to 6.3.1 of the rule. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
37. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
38. The organic liquid loading operation shall be bottom loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
39. The VOCs from the organic liquid transfer operation shall be routed to: a vapor collection and control system; or a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a floating roof container that meets the control requirements in Rule 4623; or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623; or a closed VOC emission control system. [District Rule 4624] Federally Enforceable Through Title V Permit
40. When utilizing a closed VOC emission control system or utilizing a container that meets the control requirements of Rule 4623 (Storage of Organic Liquids) to meet the emission control requirements of this permit, the transfer operation shall demonstrate compliance by complying with the leak inspection requirements of Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
41. The vapor collection and control system, except when transferring liquefied petroleum gas, shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
42. For this Class 1 organic liquid transfer operation, the emission of VOC from the transfer operation shall not exceed 0.08 pounds per 1,000 gallons of organic liquid transferred. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. The maximum liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 4624] Federally Enforceable Through Title V Permit
44. Transfer rack shall be maintained and operated in accordance with the manufacturer's specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined in Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
45. Except for components subject to Rule 4455, a leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from equipment into a container is not considered a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4624] Federally Enforceable Through Title V Permit
46. Except for components subject to Rule 4455, permittee shall inspect the loading rack for leaks during transfer at least once every calendar quarter using a portable hydrocarbon detection instrument in accordance with EPA Method 21 or alternative method approved in writing by the APCO and EPA. [District Rule 4624] Federally Enforceable Through Title V Permit
47. Except for components subject to Rule 4455, all equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replaced equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit
48. Except for components subject to Rule 4455, an operator may apply for a written approval from the APCO to change the inspection frequency required by Rule 4624 from quarterly to annually provided no leaks were found during inspections required under provisions of Sections 5.9.1 and 5.9.2 of Rule 4624 during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection the frequency shall revert back to quarterly and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit
49. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-14-15

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

## **EQUIPMENT DESCRIPTION:**

BUTAMER-BUTANE ISOMERIZATION UNIT #2 WITH 105 MMBTU/HR GAS-FIRED HOT OIL HEATER H-202 EQUIPPED WITH CALLIDUS MODEL CUBR-12W LOW-NOX BURNERS AND INTERNAL FGR, WITH NITROGEN PURGE SYSTEM SERVING COMPRESSOR SEALS AND COMPRESSOR CRANKCASES

## **PERMIT UNIT REQUIREMENTS**

---

1. Operation shall include deisobutanizer tower T-202, stabilizer tower V-503, caustic scrubber tower V-110A, two butamer reactor vessels V-501 A/B, stabilizer receiver vessel V-502, and deisobutanizer overhead accumulator vessel V-203. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include seventeen shell & tube heat exchangers, four air-cooled heat exchangers, 350 hp recycle gas compressor C-401, and 20 hp emergency vent drum vapor compressor C-501. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Perchloroethylene shall be received, stored, and transferred using a pressurized and/or enclosed system shared with permit unit #S-71-4. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel gas combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas combusted in fired equipment may be comprised of process off-gas (including hydrogen), propane, butane, natural gas, or any combination thereof. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The heating value of the fuel gas (Btu/scf @ the hhv) combusted in fired equipment shall be determined by sample analysis at least annually. Results of sample analysis shall be retained on site and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Total heat input of fuel gas combusted in units S-71-4, '5, '14 and '15 shall not exceed 1,602,019 MMBtu/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The nitrogen purge system serving the liquid lines shall be a closed loop system and shall not vent to the atmosphere during operation of the system. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The nitrogen purge system serving the compressor seals and compressor crankcases shall vent through two activated charcoal canisters connected in series, except during scheduled maintenance or repair activities. During repair and maintenance (such as charcoal bed change out) VOC emissions shall be minimized to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The nitrogen purge system's used activated charcoal canisters shall be handled and disposed of in sealed containers, preventing VOC emissions to the fullest extent possible. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The nitrogen purge system's activated charcoal canisters shall be replaced to maintain the VOC concentration from the canister vent less than 4,500 ppmv-VOC or periodically as recommended by the manufacturer, whichever occurs first. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Maximum fugitive VOC emissions from permits #S-71-14 and '-15 shall not exceed 59.74 lb per day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-2c: CAPCOA Oil and Gas Production Screening Value Range Emission Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Emission rates shall not exceed any of the following limits: NOx (as NO2): 25 ppmv @ 3% O2; SOx (as SO2): 0.0006 lb MMBtu; PM10: 0.0137 lb/MMBtu; CO: 50 ppmv @ 3% O2; or VOC; 0.00141 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Process oil heater stack shall be equipped with sampling facilities for source testing in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
16. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis using District approved portable analyzers. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2, and the O2 concentration. The records shall also include a description of any corrective action taken to maintain the emissions in the acceptable range. These records shall be retained at the facility for a period of no less than five years and shall be made readily available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. If the NOx and/or CO concentrations, as measured by the portable analyzer, exceed the permitted emission limits, the permittee or third party shall notify the District and return the NOx and CO concentrations to the permitted emission limits as soon as possible but no longer than one (1) hour after detection. If the portable analyzer readings continue to exceed the permitted emission limits after (1) hour, the permittee shall conduct a source test within 60 days, of the first exceedance to demonstrate compliance with the permitted emission limits. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. District witnessed compliance source testing for NOx, CO, and SOx emission limits shall be conducted at least once every 12 months, except as provided below. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. District witnessed source testing to demonstrate compliance with NOx, CO, and SOx emission limits shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. If permittee fails any compliance demonstration for NOx, CO, or SOx emission limits when testing not less than once every 36 months, compliance with NOx, CO, and SOx emission limits shall be demonstrated not less than once every 12 months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. For the purposes of source testing, the following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, SOx (lb/MMBtu) - EPA Method 19, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. When the LPG supply source for make up fuel to the fuel gas system changes, the stack concentrations of NO<sub>x</sub>, CO, and O<sub>2</sub> shall be measured with a District approved portable analyzer to verify emissions compliance. This is to be done anytime that LPG is being vaporized to supply make up fuel to the fuel gas system. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
27. Permittee shall maintain accurate records of perchloroethylene usage, fuel gas heating value and daily, monthly and yearly records of fuel gas use. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
28. Permittee shall maintain accurate monthly records of the combined fuel gas combusted in units S-71-4, '5, '14 and '15. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
29. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455, 5.0] Federally Enforceable Through Title V Permit
30. Except as follows, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
31. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within the Rule. [District Rule 4455, 5.1.1] Federally Enforceable Through Title V Permit
32. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455, 5.1.2] Federally Enforceable Through Title V Permit
33. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be re-inspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of the Rule. [District Rule 4455, 5.2.1 and 5.2.2] Federally Enforceable Through Title V Permit
34. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455, 5.2.3, 5.2.4, 5.2.5, 5.2.6, and 5.2.7] Federally Enforceable Through Title V Permit
35. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of the rule. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs, which shall continue to be inspected on a quarterly basis. [District Rule 4455] Federally Enforceable Through Title V Permit
36. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of the Rule exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this Rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455, 5.2.11] Federally Enforceable Through Title V Permit
38. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455, 5.2.12] Federally Enforceable Through Title V Permit
39. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this Rule. [District Rule 4455, 5.3.1 and 5.3.2] Federally Enforceable Through Title V Permit
40. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455, 5.3.3] Federally Enforceable Through Title V Permit
41. All component leaks shall be immediately minimized to the extent possible, but not later than one hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of the Rule, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of the Rule shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455, 5.3.5] Federally Enforceable Through Title V Permit
42. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this Rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455, 5.3.6] Federally Enforceable Through Title V Permit
43. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 months after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of the rule, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of the Rule, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455, 5.3.7] Federally Enforceable Through Title V Permit
44. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455, 5.4.1] Federally Enforceable Through Title V Permit
45. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of the Rule. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455, 5.4.3 and 5.4.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



46. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455, 5.5] Federally Enforceable Through Title V Permit
47. The operator shall keep a copy of the OMP at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved Operator Management Plan. [District Rule 4455, 6.1.2] Federally Enforceable Through Title V Permit
48. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of the Rule. [District Rule 4455, 6.2.1] Federally Enforceable Through Title V Permit
49. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty calendar days of following notification of process PRD release subject to 6.3.1 of the rule. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of the Rule. [District Rule 4455, 6.3] Federally Enforceable Through Title V Permit
50. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of the Rule. [District Rule 4455, 6.4] Federally Enforceable Through Title V Permit
51. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit
52. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
53. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-15-13

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

SAFECAT FEEDSTOCK TREATMENT UNIT WITH 23 MMBTU/HR GAS-FIRED HEATER H-401 EQUIPPED WITH CALLIDUS MODEL CUBR-8P LOW-NOX BURNERS AND INTERNAL FGR

## PERMIT UNIT REQUIREMENTS

---

1. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel gas combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include SafeCat feed surge drum V-401, SafeCat reactor vessel V-402, SafeCat product separator vessel V-403, depropanizer receiver boot V-7, sulfur injection drum V-407, and three SafeCat adsorber vessels V-405 A/B/C. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include two SulfaTreat adsorber vessels V-102 A/B, SafeCat Feed prefilter vessel F-401, five shell & tube heat exchangers, and air-cooled heat exchanger. [District Rule 2201] Federally Enforceable Through Title V Permit
4. SafeCat feedstock treatment system gas shall be routed only to SafeCat feed stream or SulfaTreat sulfur removal equipment prior to introduction into facility fuel gas system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. No on-site regeneration of SulfaTreat chemical is authorized. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Gas combusted in fired equipment may be comprised of process off-gas (including hydrogen), propane, butane, natural gas, or any combination thereof. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The heating value of the fuel gas (Btu/scf @ the hhv) combusted in fired equipment shall be determined by sample analysis at least annually. Results of sample analysis shall be retained on site and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total heat input of fuel gas combusted in units S-71-4, '5, '14 and '15 shall not exceed 1,602,019 MM Btu/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Leaks from valves, connectors, and other components (not including pump and compressor seals) subject to a BACT requirement and subject to the provisions of Rule 4455 shall be defined as a reading of methane on a portable hydrocarbon detection instrument in excess of 100 ppmv above background when measured as close as possible but not greater than one (1) cm from the potential source. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Leaks from pump and compressor seals subject to a BACT requirement and subject to the provisions of Rule 4455 shall be defined as a reading of methane on a portable hydrocarbon detection instrument in excess of 500 ppmv above background when measured as close as possible but not greater than one (1) cm from potential source. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Maximum fugitive VOC emissions from permits #S-71-14 and '-15 shall not exceed 59.74 lb per day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-2c: CAPCOA Oil and Gas Production Screening Value Range Emission Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Emission rates shall not exceed any of the following limits: NO<sub>x</sub> (as NO<sub>2</sub>): 25 ppmv @ 3% O<sub>2</sub>; SO<sub>x</sub> (as SO<sub>2</sub>): 0.0006 lb MMBtu; PM<sub>10</sub>: 0.0137 lb/MMBtu; CO: 50 ppmv @ 3% O<sub>2</sub>; or VOC: 0.00279 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
14. SafeCat heater stack shall be equipped with sampling facilities for source testing in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
15. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The duration of each startup and shutdown period for the 23 MMBtu/hr gas-fired heater shall not exceed 7.7 hours and 2.0 hours respectively. Emission limits of Rules 4305, 4306, and 4320 are waived during periods of startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. The permittee shall maintain records of the duration of each startup period for the 23 MMBtu/hr gas-fired heater. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NO<sub>x</sub> (as NO<sub>2</sub>), CO, and O<sub>2</sub> at least once every month using a portable emission monitor. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. If the NO<sub>x</sub> and/or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
22. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
23. This unit shall be tested for compliance with the NO<sub>x</sub>, CO, and SO<sub>x</sub> emissions limits at least once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. NO<sub>x</sub> emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. CO emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. SO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 19. [District Rule 1081] Federally Enforceable Through Title V Permit
27. Stack gas oxygen for source test purposes shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. If permittee fails any compliance demonstration for NO<sub>x</sub>, CO, or SO<sub>x</sub> emission limits when testing not less than once every 36 months, compliance with NO<sub>x</sub>, CO, and SO<sub>x</sub> emission limits shall be demonstrated not less than once every 12 months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. When the LPG supply source for make up fuel to the fuel gas system changes, the stack concentrations of NO<sub>x</sub>, CO, and O<sub>2</sub> shall be measured with a District approved portable analyzer to verify emissions compliance. This is to be done anytime that LPG is being vaporized to supply make up fuel to the fuel gas system. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. Permittee shall maintain accurate records of perchloroethylene usage, fuel gas heat input, and daily, monthly and yearly records of fuel gas use. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
31. Permittee shall maintain accurate monthly records of the combined heat input of the fuel gas combusted in units S-71-4, '5, '14 and '15. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
32. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455] Federally Enforceable Through Title V Permit
33. Except as follows, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
34. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
35. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
36. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be re-inspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455] Federally Enforceable Through Title V Permit
38. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of the rule. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs, which shall continue to be inspected on a quarterly basis. [District Rule 4455] Federally Enforceable Through Title V Permit
39. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of the Rule exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this Rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
40. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
41. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
43. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All component leaks shall be immediately minimized to the extent possible, but not later than one hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of the Rule, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of the Rule shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455] Federally Enforceable Through Title V Permit
45. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this Rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

46. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 months after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of the rule, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of the Rule, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of the Rule. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455] Federally Enforceable Through Title V Permit
49. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
50. The operator shall keep a copy of the OMP at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing approved Operator Management Plan. [District Rule 4455] Federally Enforceable Through Title V Permit
51. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
52. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty calendar days of following notification of process PRD release subject to 6.3.1 of the rule. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
53. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of the Rule. [District Rule 4455] Federally Enforceable Through Title V Permit
54. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070 and 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

55. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
56. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-17-3

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

267 BHP CATERPILLAR MODEL 3306 (S/N 54219873) DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

## PERMIT UNIT REQUIREMENTS

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The engine shall be equipped with a turbocharger and with an aftercooler or intercooler. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 65 hours per year. [District Rules 2201 and 4702; and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.) and the type of fuel used. Such records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel containing not more than 0.05% sulfur by weight is to be used. [District Rules 2201 and 4801; and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions rates from this engine shall not exceed NO<sub>x</sub>, 4.24 lb/hr; PM<sub>10</sub>, 0.59 lb/hr; CO, 1.78 lb/hr or VOC, 0.67 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operation of the engine shall not exceed 23 hours per day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



13. The engine shall be in compliance with all emission limitations and operating limitations that apply at all times. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-18-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

14,544 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #1

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-18-2 Jan 30 2018 11:18AM - AHMADS

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-19-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

14,544 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #2

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-20-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW25 **TOWNSHIP:** 28E **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

16,505 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #3

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-20-2 Jan 30 2018 11 18AM - AHMAADS

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-21-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

15,000 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #4

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-21-2 Jan 30 2018 11:18AM - AHMAOS

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-22-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

15,249 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #5

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has an overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-23-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

15,187 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #6

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-23-2 Jan 30 2018 11:18AM - AHMADS



8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-24-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

98,913 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #64

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-24-2 Jan 30 2018 11:18AM - AHMADS

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-25-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

98,913 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #65

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-26-2

**EXPIRATION DATE:** 08/31/2022

**SECTION:** SW35 **TOWNSHIP:** 28S **RANGE:** 25E

**EQUIPMENT DESCRIPTION:**

98,913 GALLON HORIZONTAL CYLINDRICAL NATURAL GASOLINE/LPG STORAGE TANK #66

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
3. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
4. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
6. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
7. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-26-2 Jan 30 2018 11 18AM - AHMAOS

8. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
9. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
10. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
11. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
12. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
13. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
14. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
15. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
16. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
17. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
18. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
20. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
21. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
22. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
23. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
27. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
28. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
29. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
30. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
31. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
35. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
36. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
38. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
40. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit
41. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name, or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
42. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
45. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
47. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-27-2

**EXPIRATION DATE:** 08/31/2022

**EQUIPMENT DESCRIPTION:**

108,047 GALLON NATURAL GASOLINE/LPG STORAGE TANK

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere (required to be considered exempt from Rule 4623). [District Rule 4623] Federally Enforceable Through Title V Permit
2. Equipment shall be maintained gas and liquid leak free as defined in Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
3. Fugitive emission components shall be monitored and maintained pursuant to Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 0.07 lbs/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Gas compressor seals and pump seals shall have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Gas compressor seals and pump seals shall have no leak of VOC in excess of 3 drops per minute. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
7. Fugitive piping components shall be have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Fugitive components shall have no leak of VOC in excess of 3 drops per minute. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
8. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
9. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
11. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
12. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
13. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
14. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
15. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
16. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
17. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
18. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
19. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
20. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
22. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
23. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
27. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
28. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
29. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
30. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
31. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
32. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

33. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
35. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
36. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
37. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
38. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
40. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

41. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
42. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
43. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
45. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
46. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

47. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
48. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
50. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
51. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
52. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
53. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
54. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
55. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-71-28-2

EXPIRATION DATE: 08/31/2022

**EQUIPMENT DESCRIPTION:**

108,047 GALLON NATURAL GASOLINE/LPG STORAGE TANK

## PERMIT UNIT REQUIREMENTS

---

1. Tank shall be maintained under working pressure sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere (required to be considered exempt from Rule 4623). [District Rule 4623] Federally Enforceable Through Title V Permit
2. Equipment shall be maintained gas and liquid leak free as defined in Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
3. Fugitive emission components shall be monitored and maintained pursuant to Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
4. Volatile organic compound (VOC) emission rate shall not exceed 0.07 lbs/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Gas compressor seals and pump seals shall have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Gas compressor seals and pump seals shall have no leak of VOC in excess of 3 drops per minute. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
7. Fugitive piping components shall have no vapor leaks in excess of 10,000 ppmv above background when measured with a portable hydrocarbon detection instrument calibrated with methane in accordance with EPA Method 21. Fugitive components shall have no leak of VOC in excess of 3 drops per minute. [District Rules 2201 and 4455] Federally Enforceable Through Title V Permit
8. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
9. For valves, threaded connections, and flanges subject to the requirements of Rule 4455, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-28-2 Jan 30 2018 11:18AM - AHMADS

10. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 100 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4455] Federally Enforceable Through Title V Permit
11. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
12. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4455 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit
13. Leaking components at this facility detected during annual operator inspections, as required by Rule 4455 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
14. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455] Federally Enforceable Through Title V Permit
15. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
16. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
17. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4455] Federally Enforceable Through Title V Permit
18. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
19. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
20. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
22. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
23. When pipes are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4455] Federally Enforceable Through Title V Permit
24. All accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4455] Federally Enforceable Through Title V Permit
25. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
26. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4455] Federally Enforceable Through Title V Permit
27. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4455] Federally Enforceable Through Title V Permit
28. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
29. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4455] Federally Enforceable Through Title V Permit
30. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4455] Federally Enforceable Through Title V Permit
31. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4455] Federally Enforceable Through Title V Permit
32. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4455. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



33. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4455] Federally Enforceable Through Title V Permit
34. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4455] Federally Enforceable Through Title V Permit
35. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4455] Federally Enforceable Through Title V Permit
36. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4455] Federally Enforceable Through Title V Permit
37. District inspections shall not be counted as an operator inspection required by District Rule 4455. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
38. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4455] Federally Enforceable Through Title V Permit
39. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4455] Federally Enforceable Through Title V Permit
40. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

41. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4455] Federally Enforceable Through Title V Permit
42. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4455 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4455] Federally Enforceable Through Title V Permit
43. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4455] Federally Enforceable Through Title V Permit
44. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455] Federally Enforceable Through Title V Permit
45. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
46. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4455] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

47. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4455] Federally Enforceable Through Title V Permit
48. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
49. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4455] Federally Enforceable Through Title V Permit
50. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4455] Federally Enforceable Through Title V Permit
51. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4455] Federally Enforceable Through Title V Permit
52. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4455] Federally Enforceable Through Title V Permit
53. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4455] Federally Enforceable Through Title V Permit
54. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4455] Federally Enforceable Through Title V Permit
55. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-29-2

**EXPIRATION DATE:** 08/31/2022

**EQUIPMENT DESCRIPTION:**

DISTILLATION OPERATION INCLUDING MIXED USE DEISOBUTANIZER/DEBUTANIZER COLUMN, UNFIRED REBOILER, AND VARIOUS EXCHANGERS, PUMPS, AND APPURTENANCES

## PERMIT UNIT REQUIREMENTS

---

1. All VOC sampling connections, open-ended valves, and lines shall be equipped with two closed valves or be sealed with blind flanges, caps, or threaded plugs except during actual use. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Process heat shall only be supplied by hot oil heating systems listed on S-71-4, '5 or '14. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Only heat transfer fluid manufactured and marketed for such use shall be used in a closed loop as heat transfer medium. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fugitive VOC emission rate shall not exceed 9.4 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain permit accurate fugitive component counts and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-2c: CAPCOA Oil and Gas Production Screening Value Range Emission Factors. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall keep a copy of the APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4455] Federally Enforceable Through Title V Permit
7. In accordance with the approved OMP, the operator shall meet all applicable operating, inspection and re-inspection, maintenance, process pressure relief device (PRD), component identification, recordkeeping and notification requirements of Rule 4455 for all components containing or contacting VOC at the this gas liquids processing facility, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455] Federally Enforceable Through Title V Permit
8. Except for those components specified in the below condition, a component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of the rule exist at the facility. [District Rule 4455] Federally Enforceable Through Title V Permit
9. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required by this permit shall be retained for a period of at least 5 years and shall be made available to the District, ARB, and USEPA upon request. [District Rules 1070, 2201, and 4455] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-30-2

**EXPIRATION DATE:** 08/31/2022

**EQUIPMENT DESCRIPTION:**

21,000 GPM MECHANICAL DRAFT COOLING TOWER WITH HIGH EFFICIENCY CELLULAR TYPE DRIFT ELIMINATOR, FOUR (4) 450 HP CIRCULATION PUMPS, AND TDS CONTROL SYSTEM

## PERMIT UNIT REQUIREMENTS

---

1. No hexavalent chromium containing compounds shall be added to cooling tower circulating water. [District Rule 4102 and 40 CFR 63 Q] Federally Enforceable Through Title V Permit
2. Cooling tower drift shall not exceed 0.001%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Control system shall maintain total dissolved solids (TDS) in cooling tower water less than 5.0 g/l. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Recirculating water flow rate shall not exceed 21,000 gallons per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance with recirculating water rate limit shall be demonstrated by engineering calculations using manufacturer's pump data, cooling water system pressure, and pump discharge pressure as applicable. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Compliance with the TDS limit will be demonstrated by cooling water sample analysis by independent laboratory within 60 days of initial operation, and by monthly analysis by cooling tower chemical vendor or internal laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
7. Records of cooling tower water TDS and manufacturer's pump data, cooling water system pressure, pump discharge pressure, etc. and resulting engineering calculations of cooling tower water flow rate shall be kept at the facility and made readily available for District inspection upon request for 5 years. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-31-1

**EXPIRATION DATE:** 08/31/2022

**EQUIPMENT DESCRIPTION:**

NATURAL GASOLINE/LPG RAILCAR LOADING/UNLOADING OPERATION WITH SEVEN NATURAL GASOLINE/LPG LOADING/UNLOADING STATIONS INCLUDING: ELEVATED RACK SYSTEM UTILIZING HARD PIPING AND SWIVEL JOINTS; AND NITROGEN PURGE SYSTEM SERVING LIQUID LINES

## PERMIT UNIT REQUIREMENTS

---

1. The organic liquid loading operation shall be bottom loaded. [District Rule 4624, 5.1] Federally Enforceable Through Title V Permit
2. The VOCs from the organic liquid transfer operation shall be routed to: a vapor collection and control system; or a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a floating roof container that meets the control requirements in Rule 4623; or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623; or a closed VOC emission control system. [District Rule 4624, 5.1] Federally Enforceable Through Title V Permit
3. When utilizing a closed VOC emission control system or utilizing a container that meets the control requirements of Rule 4623 (Storage of Organic Liquids) to meet the emission control requirements of this permit, the transfer operation shall demonstrate compliance by complying with the leak inspection requirements of Rule 4624. [District Rule 4624, 5.3] Federally Enforceable Through Title V Permit
4. The vapor collection and control system, except when transferring liquefied petroleum gas, shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum [District Rule 4624, 5.4] Federally Enforceable Through Title V Permit
5. For this Class 1 organic liquid transfer operation, the emission of VOC from the transfer operation shall not exceed 0.08 pounds per 1,000 gallons of organic liquid transferred. [District Rule 4624, 5.1] Federally Enforceable Through Title V Permit
6. Fugitive VOC emissions from component leaks shall not exceed 4.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Maximum VOC emissions from railcar loading/unloading liquid hose connects/disconnects shall not exceed 0.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The maximum number of natural gasoline liquid hose disconnects performed by the natural gasoline railcar loading/unloading operation shall not exceed 48 disconnects/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum number of natural gasoline vapor hose disconnects performed by the natural gasoline railcar loading/unloading operation shall not exceed 24 disconnects/day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The maximum liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
11. After completion of railcar loading/unloading, liquid lines shall be purged with nitrogen prior to disconnection. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Nitrogen purge system shall be a closed loop system and shall not vent to the atmosphere during operation of the system. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Transfer rack shall be maintained and operated in accordance with the manufacturer's specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined in Rule 4624. [District Rule 4624, 5.6] Federally Enforceable Through Title V Permit
14. Except for components subject to Rule 4455, a leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute; or for organic liquids other than gasoline, the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv above a background as methane when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from equipment into a container is not considered a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4624] Federally Enforceable Through Title V Permit
15. Except for components subject to Rule 4455, permittee shall inspect the loading rack for leaks during transfer at least once every calendar quarter using a portable hydrocarbon detection instrument in accordance with EPA Method 21 or alternative method approved in writing by the APCO and EPA. [District Rule 4624, 5.9.1] Federally Enforceable Through Title V Permit
16. Except for components subject to Rule 4455, all equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replaced equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9.3] Federally Enforceable Through Title V Permit
17. Except for components subject to Rule 4455, an operator may apply for a written approval from the APCO to change the inspection frequency required by Rule 4624 from quarterly to annually provided no leaks were found during inspections required under provisions of Sections 5.9.1 and 5.9.2 of Rule 4624 during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection the frequency shall revert back to quarterly and the operator shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9.4] Federally Enforceable Through Title V Permit
18. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455, 5.0] Federally Enforceable Through Title V Permit
19. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within Rule 4455. [District Rule 4455, 5.1.1] Federally Enforceable Through Title V Permit
21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455, 5.1.2] Federally Enforceable Through Title V Permit
22. A component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of Rule 4455 exist at the facility. [District Rule 4455, 5.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be reinspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of Rule 4455. [District Rule 4455, 5.2.1 and 5.2.2] Federally Enforceable Through Title V Permit
24. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455, 5.2.3, 5.2.4, 5.2.5, 5.2.6 and 5.2.7] Federally Enforceable Through Title V Permit
25. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of Rule 4455. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs which shall continue to be inspected on a quarterly basis. [District Rule 4455, 5.2.8] Federally Enforceable Through Title V Permit
26. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of Rule 4455 exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five (5) calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
27. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455, 5.2.11] Federally Enforceable Through Title V Permit
28. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455, 5.2.12] Federally Enforceable Through Title V Permit
29. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this rule. [District Rule 4455, 5.3.1 and 5.3.2] Federally Enforceable Through Title V Permit
30. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455, 5.3.3] Federally Enforceable Through Title V Permit
31. All component leaks shall be immediately minimized to the extent possible, but not later than one (1) hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of Rule 4455, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of Rule 4455 shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



32. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455, 5.3.6] Federally Enforceable Through Title V Permit
33. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of Rule 4455, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of Rule 4455, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two (2) years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455, 5.3.7] Federally Enforceable Through Title V Permit
34. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of Rule 4455. [District Rule 4455, 6.4] Federally Enforceable Through Title V Permit
35. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455, 5.4.1] Federally Enforceable Through Title V Permit
36. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of Rule 4455. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455, 5.4.3 and 5.4.4] Federally Enforceable Through Title V Permit
37. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455, 5.5] Federally Enforceable Through Title V Permit
38. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty (30) calendar days of following notification of process PRD release subject to 6.3.1 of Rule 4455. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of Rule 4455. [District Rule 4455, 6.3] Federally Enforceable Through Title V Permit
39. The operator shall keep a copy of the operator management plan at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved Operator Management Plan. [District Rule 4455, 6.1.2] Federally Enforceable Through Title V Permit
40. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of Rule 4455. [District Rule 4455, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

41. Permittee shall maintain accurate fugitive component counts and resulting emissions calculated using the correlation equations, zero default and 10,000 ppmv pegged factors set forth in the CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-3a: CAPCOA-Revised 1995 EPA Correlation Equations and Factors for Refineries and Marketing Terminals. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
42. Permittee shall keep records of daily unloading rack throughput and the results of any required leak inspections [District Rule 4624, 6.1.3] Federally Enforceable Through Title V Permit
43. Permittee shall keep records of daily number of railcar loading/unloading liquid and vapor disconnects. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
44. Records shall be retained for a minimum of five years and shall be made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-71-32-1

**EXPIRATION DATE:** 08/31/2022

**EQUIPMENT DESCRIPTION:**

300,700 GALLON NATURAL GASOLINE/LPG STORAGE TANK

## PERMIT UNIT REQUIREMENTS

---

1. Fugitive VOC emissions from component leaks shall not exceed 4.4 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The operator shall meet operating, inspection and re-inspection, maintenance, process pressure relief device (PRD) and component identification requirements of District Rule 4455 (4/20/05) for all components containing or contacting VOC, except for those components specifically exempted in Sections 4.1 and 4.2. [District Rule 4455, 5.0] Federally Enforceable Through Title V Permit
3. For valves and connectors, a leak shall be defined as a reading of methane in excess of 100 ppmv above background when measured per EPA Method 21 and Maintenance Program pursuant to District Rule 4455. For pump and compressor seals, a leak shall be defined as a reading of methane in excess of 500 ppmv above background when measure per EPA Method 21 and an Inspection and Maintenance Program pursuant to District Rule 4455. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The operator shall not use any component that leaks in excess of the allowable leak standards, except as follows. A component identified as leaking in excess of an allowable leak standard may be used provided it has been identified with a tag for repair, has been repaired, or is awaiting re-inspection after repair, within the applicable time period specified within Rule 4455. [District Rule 4455, 5.1.1] Federally Enforceable Through Title V Permit
5. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4455, 5.1.2] Federally Enforceable Through Title V Permit
6. A component shall be considered leaking if one of more of the conditions specified in Sections 5.1.4.1 through 5.1.4.4 of Rule 4455 exist at the facility. [District Rule 4455, 5.1.4] Federally Enforceable Through Title V Permit
7. The operator shall audio-visually inspect for leaks all accessible operating pumps, compressors and PRD in service at least once every 24 hours, except when operators do not report to the facility for that given 24 hours. Any identified leak that cannot be immediately repaired shall be reinspected within 24 hours using EPA Method 21. If a leak is found, it shall be repaired as soon as practical but not later than the time frame specified in Table 3 of Rule 4455. [District Rule 4455, 5.2.1 and 5.2.2] Federally Enforceable Through Title V Permit
8. The operator shall inspect all components at least once every calendar quarter. New, replaced, or repaired fittings, flanges and threaded connections shall be inspected immediately after being placed into service. Inaccessible components, unsafe-to-monitor components and pipes shall be inspected in accordance with the requirements set forth in Sections 5.2.5 through 5.2.7. Components shall be inspected using EPA Method 21. [District Rule 4455, 5.2.3, 5.2.4, 5.2.5, 5.2.6 and 5.2.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: PLAINS LPG SERVICES LP

Location: 7TH STANDARD RD & BEECH AVE, SHAFTER, CA 93263

S-71-32-1 Jan 30 2018 11 18AM - AHMADS

9. The operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually for a component type, provided the operator meets all the criteria specified in Sections 5.2.8.1 through 5.2.8.3 of Rule 4455. This approval shall apply to accessible component types, specifically designated by the APCO, except pumps, compressors, and PRDs which shall continue to be inspected on a quarterly basis. [District Rule 4455, 5.2.8] Federally Enforceable Through Title V Permit
10. An annual inspection frequency approved by the APCO shall revert to quarterly inspection frequency for a component type if either the operator inspection or District inspection demonstrates that a violation of the provisions of Sections 5.1, 5.2 and 5.3 of Rule 4455 exists for that component type, or the APCO issued a Notice of Violation for violating any of the provisions of this rule during the annual inspection period for that component type. When the inspection frequency changes from annual to quarterly inspections, the operator shall notify the APCO in writing within five (5) calendar days after changing the inspection frequency, giving the reason(s) and date of change to quarterly inspection frequency. [District Rule 4455, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
11. The operator shall initially inspect a process PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the time of the release. To insure that the process PRD is operating properly, and is leak-free, the operator shall re-inspect the process PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the release using EPA Method 21. If the process PRD is found to be leaking at either inspection, the PRD leak shall be treated as if the leak was found during quarterly operator inspections. [District Rule 4455, 5.2.11] Federally Enforceable Through Title V Permit
12. Except for process PRD, a component shall be inspected within 15 calendar days after repairing the leak or replacing the component using EPA Method 21. [District Rule 4455, 5.2.12] Federally Enforceable Through Title V Permit
13. Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag. The tag shall remain affixed to the component until the leaking component has been repaired or replaced; has been re-inspected using EPA Method 21; and is found to be in compliance with the requirements of this rule. [District Rule 4455, 5.3.1 and 5.3.2] Federally Enforceable Through Title V Permit
14. The tag shall include date and time of leak detection, date and time of leak measurement, indicate the leak concentration in ppmv (gas leaks), indicate whether it is a major or a minor leak (liquid leaks) and whether the leaking component is an essential component, unsafe-to-monitor component or critical component. [District Rule 4455, 5.3.3] Federally Enforceable Through Title V Permit
15. All component leaks shall be immediately minimized to the extent possible, but not later than one (1) hour after detection of leaks, in order to stop or reduce leakage to the atmosphere. As soon as practicable but not later than the time period specified in Table 3 of Rule 4455, components that have been identified as leaking and have had emissions minimized to the extent possible but do not meet the applicable leak standards of Rule 4455 shall either be: 1) repaired or replaced, or 2) vented to a closed vent system, or 3) removed from operation. [District Rule 4455, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit
16. For any leaking component that is an essential or critical component, and which cannot be immediately shut down for repairs, the operator shall minimize the leak within one hour after detection of the leak. If the leak has been minimized but still exceeds any of the applicable leak standards of this rule, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4455, 5.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

17. For any component that has incurred five repair actions for major gas leaks or major liquid leaks (any combination) within a continuous 12-month period, the operator shall as soon as practicable but not later than 12 after the date of detection either: 1) replace or retrofit the component with the control technology specified in Table 4 of Rule 4455, or 2) replace the component with Best Available Control Technology (BACT) equipment, as approved by the APCO, or 3) vent the component to an APCO approved closed vent system as defined in Section 3.0 of Rule 4455, or 4) remove the component from operation. Inaccessible components, unsafe-to-monitor components, essential components, or critical components shall satisfy the above-listed requirement as soon as practicable but not later than the next turnaround or not later than two (2) years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes earlier. The APCO shall be notified in writing prior to the replacement or retrofitting of any component. [District Rule 4455, 5.3.7] Federally Enforceable Through Title V Permit
18. Measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument, calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. Operator shall keep a record of each instrument calibration in accordance with requirements as set forth Section 6.2.3 of Rule 4455. [District Rule 4455, 6.4] Federally Enforceable Through Title V Permit
19. The operator shall monitor process PRD by using electronic process control instrumentation that allows for real time continuous parameter monitoring or by using telltale indicators for the process PRD where parameter monitoring is not feasible. [District Rule 4455, 5.4.1] Federally Enforceable Through Title V Permit
20. The operator shall comply with the process PRD release notification and record keeping requirements specified in Section 6.3 of Rule 4455. After a release from process PRD in excess of 500 pounds of VOC in a continuous 24-hour period, the operator shall immediately conduct a failure analysis and implement corrective actions as soon as practicable but not later than 30 days to prevent the reoccurrence of similar release. [District Rule 4455, 5.4.3 and 5.4.4] Federally Enforceable Through Title V Permit
21. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and record keeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other APCO-approved system that enables an operator or District personnel to locate each individual component. The operator shall replace tags or labels that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4455, 5.5] Federally Enforceable Through Title V Permit
22. The operator shall notify the APCO, by telephone or other APCO-approved methods, of any process PRD release in excess of 500 pounds of VOC in a continuous 24-hour period, and any release in excess of the reportable quantity limits as stipulated in 40 CFR, Part 117, Part 302 and Part 355, including any release in excess of 100 pounds of VOC, within one hour of such occurrence or within one hour of the time said person knew or reasonably should have known of its occurrence. The operator shall submit a written report to the APCO within thirty (30) calendar days of following notification of process PRD release subject to 6.3.1 of Rule 4455. The written report shall include all of the information set forth in Sections 6.3.2.1 through 6.3.2.5 of Rule 4455. [District Rule 4455, 6.3] Federally Enforceable Through Title V Permit
23. The operator shall keep a copy of the operator management plan at the facility and make it available to the APCO, ARB and US EPA upon request. By January 30 of each year, the operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved Operator Management Plan. [District Rule 4455, 6.1.2] Federally Enforceable Through Title V Permit
24. Operator shall maintain an inspection log containing the information set forth in Sections 6.2.1.1 through 6.2.1.10 of Rule 4455. [District Rule 4455, 6.2.1] Federally Enforceable Through Title V Permit
25. Permittee shall maintain accurate fugitive component counts and resulting emissions calculated using the correlation equations, zero default and 10,000 ppmv pegged factors set forth in the CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," February 1999, Table IV-3a: CAPCOA-Revised 1995 EPA Correlation Equations and Factors for Refineries and Marketing Terminals. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. Records shall be retained for a minimum of five years and shall be made readily available to the APCO, ARB, or EPA during normal business hours and submitted upon request to the APCO, ARB, or EPA. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.