

AUG 23 2019

Ms. Angel Topoozian
Scelzi Enterprises Inc.
2286 E Date Ave
Fresno, CA 93706

Re: Final ATCs / Certificates of Conformity (Significant Mod)
Facility Number: C-1080
Project Number: C-1182078

Dear Ms. Topoozian:

The Air Pollution Control Officer has issued Authorities to Construct (ATCs) C-1080-1-6, '-2-7, '-4-4, '-7-4, '-9-4, '-11-1, and '-12-1 with Certificates of Conformity to Scelzi Enterprises Inc. at 2772 S. Cherry Avenue, Fresno. This project authorizes the modification of seven motor vehicle and mobile equipment coating operations to convert the existing daily facility-wide VOC emission limit of 149.0 lb/day to an equivalent annual facility-wide VOC emission limit of 54,385 lb/year and to make other minor changes to the permitted PM10 emission limits. Enclosed are the ATCs and a copy of the notice of final action to be published approximately three days from the date of this letter.

Notice of the District's preliminary decision to issue the ATCs was published on July 2, 2019. The District's analysis of the proposal was also sent to CARB and US EPA Region IX on June 25, 2019. No comments were received following the District's preliminary decision on this project.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

Prior to operating with the modifications authorized by the ATCs, you must submit an application to modify the Title V permit as an administrative amendment in accordance with District Rule 2520, Section 11.5. Application forms are found on the District's website at www.valleyair.org/permits/TVforms.

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Ms. Angel Topoozian
Page 2

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-1-6

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION WITH HVLP SPRAY GUN(S), A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS, AN ENCLOSED SPRAY GUN CLEANER, AND A PERMIT EXEMPT NATURAL GAS DRYING BURNER < 20.0 MMBTU/DAY HEAT INPUT: CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, ESTABLISH A PERMIT SPECIFIC VOC DAILY EMISSION LIMIT OF 149 LB/DAY, AND LOWER PM10 EMISSION LIMIT FROM 50.0 LB/DAY TO 19.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-1080-1-6 : Aug 21 2019 8 25AM - BROWND Joint Inspection NOT Required

6. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
7. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
8. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
9. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
10. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
11. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
12. The emissions from this unit shall not exceed either of the following limits: 149.0 lb-VOC/day or 19.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
14. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
15. PM10 emissions from each coating used shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day or gallons/year) x 0.0125. Total PM10 emissions is the sum of PM10 emissions from all coatings used. [District Rule 2201] Federally Enforceable Through Title V Permit
16. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
21. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
22. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-2-7

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION AND TRUCK BED LINER COATING OPERATION WITH HVLP SPRAY GUN(S), PLURAL COMPONENT APPLICATORS, A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS AND A PERMIT EXEMPT NATURAL GAS-FIRED BOOTH HEATER (LESS THAN 20.0 MMBTU/DAY HEAT INPUT); CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, INCREASE THE PERMIT SPECIFIC PM10 EMISSION LIMIT FROM 14.5 LB/DAY TO 19.0 LB/DAY, AND REMOVE PERMIT EXEMPT BOOTH HEATER

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Booth shall be equipped with dry filters achieving a PM10 control efficiency of at least 95% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-1080-2-7 : Aug 21 2019 8 25AM - BROWND : Joint Inspection NOT Required

6. For all coating application, except truck bed liner coating application, only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
7. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
8. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
9. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
10. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
11. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
12. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
13. The emissions from the truck bed liner coating operation shall not exceed either of the following limits: 0.7 lb-VOC/day or 3.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The total emissions from this unit shall not exceed either of the following limits: 50.0 lb-VOC/day or 19.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
17. PM10 emissions from each coating used shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day or gallons/year) x 0.0125. Total PM10 emissions is the sum of PM10 emissions from all coatings used. [District Rule 2201] Federally Enforceable Through Title V Permit
18. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit
22. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
23. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
24. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit



AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-4-4

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION WITH HVLP SPRAY GUNS, A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS, AN ENCLOSED SPRAY GUN CLEANER, A PERMIT EXEMPT NATURAL GAS DRYING BURNER < 20.0 MMBTU/DAY HEAT INPUT, AND AN ATTACHED DRYING ROOM WITH A PERMIT EXEMPT NATURAL GAS DRYING BURNER < 20.0 MMBTU/DAY HEAT INPUT: CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, ESTABLISH A PERMIT SPECIFIC VOC DAILY EMISSION LIMIT OF 149.0 LB/DAY, AND LOWER PM10 EMISSION LIMIT FROM 50.0 LB/DAY TO 19.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-1080-4-4 : Aug 21 2019 8 25AM - BROWND : Job Inspection NOT Required

5. Only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
6. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
7. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
8. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
9. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
10. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
11. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
12. The emissions from this unit shall not exceed either of the following limits: 149.0 lb-VOC/day or 19.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
14. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
15. PM10 emissions from each coating used shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day or gallons/year) x 0.0125(2). Total PM10 emissions is the sum of PM10 emissions from all coatings used and the booth heater. [District Rule 2201] Federally Enforceable Through Title V Permit
16. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
21. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
22. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit



AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-7-4

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION WITH HVLP SPRAY GUN(S), A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS, AN ATTACHED DRYING BOOTH WITH A 1.075 MMBTU/HR NATURAL GAS-FIRED DRYING BURNER AND AN ENCLOSED SPRAY GUN CLEANER: CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR AND LOWER PM10 EMISSION LIMIT FROM 23.3 LB/DAY TO 19.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services
C-1080-7-4 | Aug 21 2019 8:25AM - BROWND | Joint Inspection NOT Required

6. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
7. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
8. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
9. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
10. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
11. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
12. The emissions from this unit shall not exceed either of the following limits: 99.0 lb-VOC/day or 19.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
14. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
15. PM10 emissions from each coating used shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day or gallons/year) x 0.0125(2). Total PM10 emissions is the sum of PM10 emissions from all coatings used. [District Rule 2201] Federally Enforceable Through Title V Permit
16. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
21. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
22. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-9-4

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION (UNDERCOATING OPERATION) WITH AIRLESS SPRAY GUN(S) AND AN ENCLOSED SPRAY GUN CLEANER: REMOVE ANNUAL VOC EMISSION LIMIT OF 10,400 LB/YEAR, CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, AND ESTABLISH A PERMIT SPECIFIC VOC DAILY EMISSION LIMIT OF 149.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
4. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
5. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-1080-9-4 : Aug 21 2019 8:25AM - BROWND : Job Inspection NOT Required

6. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
7. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
8. The emissions from this unit shall not exceed either of the following limits: 149.0 lb-VOC/day or 50.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
11. PM10 emissions from each coating shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day) x 0.55. Total PM10 emissions is the sum of PM10 emissions from all coatings used. [District Rule 2201] Federally Enforceable Through Title V Permit
12. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
14. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit
16. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
17. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
18. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit



AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-11-1

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION WITH A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS AND A 3.0 MMBTU/HR NATURAL GAS-FIRED BOOTH HEATER: CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, ESTABLISH A PERMIT SPECIFIC VOC DAILY EMISSION LIMIT OF 149.0 LB/DAY, AND INCREASE THE PM10 EMISSION LIMIT FROM 5.4 LB/DAY TO 19.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Booth shall be equipped with dry filters achieving a PM10 control efficiency of at least 95% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

C-1080-11-1 : Aug 21 2019 8 25AM - BROWND : Joint Inspection NOT Required

6. Only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
7. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
8. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
9. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
10. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
11. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
12. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
13. The total emissions from this unit shall not exceed either of the following limits: 149.0 lb-VOC/day or 19.0 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The booth heater shall only be fired on PUC quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Emissions from the booth heater shall not exceed any of the following limits: 0.10 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.0076 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
17. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). VOC emissions from the booth heater shall be calculated as follows: VOC emissions = hours of operation (hrs/day or hrs/year) x 0.0165. Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used and from the booth heater. [District Rule 2201] Federally Enforceable Through Title V Permit

18. PM10 emissions from each coating used shall be calculated as follows: $\text{PM10 emissions} = \text{coating density (lb/gallon)} \times \text{coating solids content (\%)} \times \text{usage (gallons/day or gallons/year)} \times 0.0125$. PM10 emissions from the booth heater shall be calculated as follows: $\text{PM10 emissions} = \text{hours of operation (hrs/day or hrs/year)} \times 0.0228$. Total PM10 emissions is the sum of PM10 emissions from all coatings used and the booth heater. [District Rule 2201] Federally Enforceable Through Title V Permit
19. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
24. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
25. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: C-1080-12-1

ISSUANCE DATE: 08/21/2019

LEGAL OWNER OR OPERATOR: SCELZI ENTERPRISES INC

MAILING ADDRESS: 2286 E DATE AVE
FRESNO, CA 93706

LOCATION: 2772 S CHERRY AVE
FRESNO, CA 93706

EQUIPMENT DESCRIPTION:

MODIFICATION OF MOTOR VEHICLE AND MOBILE EQUIPMENT COATING OPERATION WITH A PAINT SPRAY BOOTH WITH DRY EXHAUST FILTERS AND A 3.0 MMBTU/HR NATURAL GAS-FIRED BOOTH HEATER: INCREASE DAILY VOC EMISSION LIMIT OF 40.0 LB/DAY TO 149.0 LB/DAY, REMOVE PERMIT SPECIFIC ANNUAL VOC EMISSION LIMIT, CONVERT EXISTING DAILY FACILITY-WIDE VOC EMISSION LIMIT OF 149.0 LB/DAY TO AN EQUIVALENT ANNUAL FACILITY-WIDE VOC EMISSION LIMIT OF 54,385 LB/YEAR, AND INCREASE THE PM10 EMISSION LIMIT FROM 3.2 LB/DAY TO 19.0 LB/DAY

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. All coating, including application of primer, shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Arnaud Marjollet, Director of Permit Services

C-1080-12-1 - Aug 21 2019 8 25AM -- BROWND - Joint Inspection NOT Required

6. Booth shall be equipped with dry filters achieving a PM10 control efficiency of at least 95% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. For all coating application, except truck bed liner coating application, only high-volume low-pressure (HVLP) spray equipment, electrostatic, brush, dip, or roll coating application equipment, or other application equipment approved by the District in writing, shall be used. All application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
8. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4612] Federally Enforceable Through Title V Permit
9. All fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners shall be stored in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4612] Federally Enforceable Through Title V Permit
10. No coatings, solvents, or additives containing any of the following compounds shall be used: lead compounds, hexavalent chromium, cadmium, and/or nickel compounds. [District Rule 4102]
11. For solvent cleaning operations other than for bug and tar removal, the permittee shall not use solvents that have VOC content greater than 25 g/l (0.21 lb/gal) of cleaning material. [District Rule 4612] Federally Enforceable Through Title V Permit
12. For bug and tar removal, the permittee shall not use any material other than bug and tar remover regulated under the Consumer Products Regulation (California Code of Regulations Section 94507 et seq.). [District Rule 4612] Federally Enforceable Through Title V Permit
13. The VOC Regulatory content of coatings, as applied, shall not exceed any of the following limits: adhesion promoter 540 g/l (4.5 lb/gal), clear coating 250 g/l (2.1 lb/gal), color coating 420 g/l (3.5 lb/gal), multi-color coating 680 g/l (5.7 lb/gal), pretreatment coating 660 g/l (5.5 lb/gal), primer 250 g/l (2.1 lb/gal), primer sealer 250 g/l (2.1 lb/gal), single-stage coating 340 g/l (2.8 lb/gal), temporary protective coating 60 g/l (0.5 lb/gal), truck bed liner coating 310 g/l (2.6 lb/gal), underbody coating 430 g/l (3.6 lb/gal), uniform finish coating 540 g/l (4.5 lb/gal), and any other coating type 250 g/l (2.1 lb/gal). The VOC Regulatory content for coatings shall be defined as the VOC in grams per liter of coating (or pounds per gallon of coating), excluding water and exempt compounds. [District Rules 2201 and 4612] Federally Enforceable Through Title V Permit
14. The emissions from this unit shall not exceed either of the following limits: 149.0 lb-VOC/day or 19.0 lb-PM10/day [District Rule 2201] Federally Enforceable Through Title V Permit
15. Facility-wide emissions, in any rolling 12-month period, shall not exceed either of the following limits: 54,385 lb-VOC/year or 29,199 lb-PM10/year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. VOC emissions from each coating and/or solvent used shall be calculated as follows: VOC emissions = VOC content (lb/gallon) as applied x usage (gallon/day or gallon/year). Total VOC emissions is the sum of VOC emissions from all coatings and/or solvents used. [District Rule 2201] Federally Enforceable Through Title V Permit
17. PM10 emissions from each coating used shall be calculated as follows: PM10 emissions = coating density (lb/gallon) x coating solids content (%) x usage (gallons/day or gallons/year) x 0.0125. Total PM10 emissions is the sum of PM10 emissions from all coatings used. [District Rule 2201] Federally Enforceable Through Title V Permit
18. On a daily basis, the permittee shall calculate and record the following: total daily VOC emissions (lb/day) and total daily PM10 emissions (lb/day). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. On a monthly basis, the permittee shall calculate and record the VOC and PM10 emissions, in pounds, from this unit for the prior calendar month. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. On a monthly basis, the permittee shall calculate and record the facility-wide VOC and PM10 emissions, in pounds, for the rolling 12-month period. The facility-wide VOC and PM10 emissions shall be calculated by summing the VOC and PM10 emissions from the previous 12 months from every permitted unit at this facility. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records of quantity (gallons) and solids content of coatings applied. Permittee shall also maintain daily records of VOC content as applied (lb/gal) of each coating used, quantity (gallons) of each coating used, and calculated daily VOC emissions. [District Rule 1070] Federally Enforceable Through Title V Permit
22. The permittee shall maintain records on a daily basis and have available at all times the following: a current list of all coatings used that includes the material name and manufacturer, application method, coating type and mix ratio specific to the coating, the VOC Actual for Coatings and VOC Regulatory for Coatings as applied, and the quantity of each type of coating used; current manufacturer specification sheets, material safety data sheets (MSDS), technical data sheets, or air quality data sheets, which list the VOC Actual for Coatings and VOC Regulatory for Coatings of each ready-to-spray coating and automotive coating components; and purchase records identifying the coating type, name, and volume of coatings bought. [District Rule 4612] Federally Enforceable Through Title V Permit
23. The permittee shall keep the following records for each solvent used for cleaning activities: the quantity of solvent used; a copy of the manufacturer's product data or material safety data sheet (MSDS); the solvent's name and manufacturer, the VOC content of the solvent in grams/liter or pounds/gallon, and the mix ratio and VOC content of the batch when the solvent is a mixture of different materials blended by the permittee. [District Rule 4612] Federally Enforceable Through Title V Permit
24. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4612] Federally Enforceable Through Title V Permit