



FEB 21 2020

Darin Bylsma
S&S Dairy, Inc
5870 Crows Landing Road
Modesto, CA 95358

Re: Notice of Preliminary Decision - Authority to Construct
Facility Number: N-7321
Project Number: N-1182555

Dear Mr. Bylsma:

Enclosed for your review and comment is the District's analysis of S&S Dairy, Inc's application for an Authority to Construct for the expansion of an existing dairy operation to increase herd capacity from 1,600 combined milk and dry cows to 2,900 combined milk cows; including the construction of new cow housing units, at 348 E. Monte Vista Road, Ceres, CA.

The notice of preliminary decision for this project has been posted on the District's website (www.valleyair.org). After addressing all comments made during the 30-day public notice period, the District intends to issue the Authority to Construct. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Rupl Gill of Permit Services at (209) 557-6458.

Sincerely,



Arnaud Marjollet
Director of Permit Services

AM:rg

Enclosures

cc: Courtney Graham, CARB (w/ enclosure) via email

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

San Joaquin Valley Air Pollution Control District
Authority to Construct Application Review
(Addition of New Cow Housing and Increase Herd Size)

Facility Name: S & S Dairy Inc
Mailing Address: 5870 Crows Landing Road
Modesto, CA 95358

Date: January 28, 2019
Engineer: Rupi Gill
Lead Engineer: James Harader

Contact Person: Darin Bylsma
Telephone: 209-606-4894

E-Mail: MLk4db@yahoo.com

Application #(s): N-7321-1-5, -2-5, -3-4, -4-3 & -6-2

Project #: N-1182555

Deemed Complete: December 13, 2018

I. Proposal

S &S Dairy has requested Authority to Construct (ATC) permits for the following changes at the existing dairy:

- Increase herd size from 1,400 milk cows and 1,600 mature cows (milk and dry) to 2,500 milk cows and 2,900 mature cows (milk and dry). Increase support stock from 1,400 to 1,550
- Replace open corrals 1 & 2 with a freestall barn
- Replace shade barn #5 with a freestall barn
- Replace shade barn #6 with a freestall barn
- Add two additional new freestall barns (#3 & #4)
- The expansion will increase the total number of freestall barns from two to seven

	Milk Cows	Dry Cows	Mature Cows	Support Stock
Current	1,400	200	1,600	1,400
Proposed	2,500	400	2,900	1,550
Change	1,100	200	1,300	150

The draft ATC permits for the proposed project are included in Appendix A. A project site plan showing the proposed facility is included in Appendix C and the current permits are shown in the Appendix B.

II. Applicable Rules

Rule 2201	New and Modified Stationary Source Review Rule (8/15/19)
Rule 2410	Prevention of Significant Deterioration (6/16/11)
Rule 2520	Federally Mandated Operating Permits (8/15/19)
Rule 2550	Federally Mandated Preconstruction Review for Major Sources of Air Toxics (6/18/98)
Rule 4101	Visible Emissions (2/17/05)
Rule 4102	Nuisance (12/17/92)
Rule 4550	Conservation Management Practices (CMP) (8/19/04)
Rule 4570	Confined Animal Facilities (10/21/10)
CH&SC §41700	Health Risk Assessment
CH&SC §42301.6	School Notice
Public Resources Code 21000-21177:	California Environmental Quality Act (CEQA)
California Code of Regulations, Title 14, Division 6, Chapter 3, Sections 15000-15387:	CEQA Guidelines

III. Project Location

The facility is located at 348 E Monte Vista Avenue in Ceres, CA. The equipment is not located within 1,000 feet of the outer boundary of a K-12 school. Therefore, the public notification requirement of California Health and Safety Code 42301.6 is not applicable to this project.

IV. Process Description

The primary function of the proposed facility will be the production of dairy milk, which is used to make various food products, such as fluid milk,¹ butter, cheese, ice cream, and yogurt. Production of milk requires a herd of mature dairy cows that are lactating (milk cows). A cow's lactation cycle starts shortly after calving and lasts for approximately 12 months. Typically, a 10-month lactation period is followed by a 2-month non-lactation (dry cow) period, during which the cow prepares to calve again and begin a new lactation cycle. After the first few lactation cycles, the cow's milk yield is expected to decline steadily with each subsequent cycle.

Female calves are retained in the herd while the male calves are sold off for meat production or other purposes. The calves take approximately 15 to 24 months to reach reproductive maturity, at which point they enter the milk production stream as bred heifers. Thus, in addition to the mature cows (milk and dry), a typical dairy herd also includes a certain proportion of calves and heifers at various stages of development (support stock). Mature cows that are culled from the herd (primarily due to diminishing milk yield, but also due to injury, disease, or other reasons) are replaced by the bred heifers entering the milk production stream. The support stock may also include a certain number of mature bulls for breeding purposes, although this is not common due to the prevalent use of artificial insemination.

¹ Milk that has been processed in various ways (e.g. pasteurization, homogenization, fortification, etc.) and is intended to be consumed primarily as a beverage.

The primary functions involved in the day to day operation of a dairy include housing and feeding the herd, milking, and management of manure. These functions are described in more detail in the following sections:

A. Milking Operation (N-7321-1):

Milking is a dairy's primary income generating activity. The lactating cows are milked two to four times per day. The milk is chilled and temporarily stored in onsite tanks until it is collected by tanker truck for delivery to a creamery. A purpose-built structure known as the milking barn is used for milking and the associated onsite milk handling activities. The milking barn is located in proximity to, but separate from the lactating cow housing areas. It is designed to facilitate efficient in-and-out movement of groups of cows being milked; and also to allow workers access to individual cows during milking. The first part of the milking barn, known as the holding area, is an open-sided roofed space where cows that are ready for milking are temporarily confined as they enter the milking parlor. The milking occurs in the milking parlor within the barn. There are several different parlor designs, including flat, parallel, herringbone, and rotary. S&S Dairy currently has 60 stall parallel milking parlor.

Due to food safety regulations, high standards of hygiene must be observed in the milking parlor. The parlor floors are constructed of concrete, and are properly sloped to ensure effective drainage. Any manure that is deposited on the parlor floors during milking is promptly sprayed down with clean water and flushed into the drainage system, from where it is carried through pipes into the manure lagoons.

B. Cow Housing N-7321-2

Freestall Barns:

Typically majority of milk cows and dry cows are housed in the freestall barns. The standard freestall barn design consists of an elongated, open-frame, roofed metal structure; with concrete-paved flooring and a central drive-through feed alley. Feed bunks are located along both sides of the drive-through alley. Stanchion fences separate the housing areas from the feed alley and also facilitate the cows' orderly access to the feed (i.e. one cow per stanchion). Watering troughs are located along the outer edges of the barn and can be accessed through the barn fencing. The rest of the barn floor is divided into bays of individual resting stalls. The stalls are padded with various bedding materials, such as sand or dried manure, to increase cow comfort and prevent injury. The stall bays are separated by access lanes, which also serve as manure collection/removal lanes (flush lanes). Manure from barn feed lanes is typically removed by flushing with water.

This dairy will house all milking cows, dry cows, and the part of their support stock in the freestall areas.

Shaded Barn:

Support stock is also housed in the shaded barn.

Detailed pre-project and post project housing arrangements are shown in Appendix C and Appendix D (PM10 Mitigation Measures' sheet).

C. Liquid Manure Handling System (N-7321-3):

Milk cows generate anywhere from 130 to 150 pounds of manure per day. The manure is deposited primarily in areas where the cows are housed and fed (cow housing), but a small amount is deposited in the milking barn and other transit areas. The manure is collected and managed in liquid and solid forms. Manure with a total solids content of 20% or higher usually can be handled as a solid, while manure with a total solids content of 10% or less can be handled as a liquid.

The liquid manure handling system for the dairy includes the following components:

- Settling basin(s)
- One 390 ft x 275 ft x 30 ft, 290 ft x 285 ft x 14 ft and 350 ft x 285 ft x 14 ft treatment lagoons/wastewater ponds with a side slope of 2 ft each

Settling Basin:

The liquid manure from the flushed lanes will flow to the existing settling basin for solids separation prior to entering the lagoon/waste water system. Settling basins are structures designed to separate solids from liquid manure by sedimentation. The inflow of manure is restricted to allow some of the solids to settle out. A settling basin may achieve a solids removal rate of 40-70%. The liquids from the settling basins will gradually drain to the treatment lagoon. Solids remaining in settling basins are left to dry and then are removed. Solids separation reduces the land area required when designing a liquid manure treatment system since the volume to be treated is less. The dairy currently includes settling basin(s). The separated solids will either be applied to cropland or stored for use as fertilizer or bedding in the freestalls.

Anaerobic Treatment System:

An anaerobic treatment system is a waste treatment lagoon/liquid waste storage that is designed to facilitate the decomposition of manure by microbes in the absence of oxygen. This process of anaerobic decomposition results in the preferential conversion of organic compounds in the manure into methane, carbon dioxide, and water rather than intermediate metabolites (VOC). The Natural Resources Conservation Service (NRCS) Field Office Technical Guide No. 359, Waste Treatment Lagoon, for California specifies the following criteria for anaerobic treatment lagoons:

- 1) Minimum treatment volume - the minimum design volume must account for all potential sludge, treatment, precipitation, and runoff volumes;
- 2) Minimum hydraulic retention time - the retention time of the material in the lagoon must be adequate to provide environmentally safe utilization of waste;

- 3) Maximum volatile solids (VS) loading rate - the VS loading rate shall be based on maximum daily loading considering all waste sources that will be treated by the lagoon. The suggested loading rate for the San Joaquin Valley is 6.5 - 11 lb-VS/1000 ft³/day depending on the type of system and solids separation; and
- 4) Minimum operating depth is also stated in the NRCS Guide No. 359 - maximizing the depth of the lagoon has the following advantages: i) The surface area in contact with the atmosphere is minimized, which will reduce volatilization of air pollutants; ii) The smaller surface area reduces the effects of the environment on the lagoon, which provides a more stable and favorable environment for anaerobic bacteria; iii) There is better mixing of lagoon due to rising gas bubbles; and iv) A deeper lagoon requires less land for the required treatment volume.

Land Application:

Liquid manure from the lagoon/storage ponds will be applied to cropland as fertilizer/irrigation water. The application will be done through flood and furrow irrigation, at agronomic rates in conformance with a nutrient management plan that has been approved by the Regional Water Quality Control Board.

D. Solid Manure Handling Operation (N-7321-4):

Solid manure will be stored in stockpiles until ready to be applied to cropland as fertilizer, or shipped offsite. Separated solids will be dried and stockpiled for use as bedding material in the freestalls.

E. Feed Storage and Handling Operation (N-7321-6):

The feed storage and handling area will be used for the storage of feed ingredients and for the preparation of daily feed rations (known as 'total mixed rations' or TMR). Silage, the main ingredient in TMR, is typically stored in large elongated piles on concrete slabs. The required amount is extracted from one end of the pile, as needed. Other additive ingredients such as almond hulls, various grains, and cotton seed are stored in covered barns (commodity barns) to prevent damage from exposure to weather elements. Front-end loaders are used to retrieve the required proportions of the silage and additive ingredients and load them into a feed wagon with a built-in mixer. Once the silage and additive ingredients are thoroughly mixed, the feed wagon drives over to the cow housing areas to spread the TMR along the feed lanes.

V. Equipment Listing

Pre-Project Equipment Description:

N-7321-1-4: 1,400 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR

- N-7321-2-4: COW HOUSING - 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK (HEIFERS, CALVES AND BULLS)
- N-7321-3-3: LIQUID MANURE HANDLING SYSTEM CONSISTING OF TWO SETTLING BASINS; ONE LAGOON; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION
- N-7321-4-2: SOLID MANURE HANDLING CONSISTING OF MANURE HAULED OFFSITE
- N-7321-6-1: FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARN(S) AND SILAGE PILE(S)

Proposed Modification²:

- N-7321-1-5: MODIFICATION OF 1,400 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR: INCREASE MILK COWS FROM 1,400 TO 2,500 MILK COWS. POST PROJECT DESCRIPTION WILL BE: 2,500 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR
- N-7321-2-5: MODIFICATION OF COW HOUSING - 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK (HEIFERS, CALVES AND BULLS): CONSTRUCT FIVE NEW FREESTALL BARN(S) WITH FLUSH SYSTEM AND INCREASE HERD SIZE FROM 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK TO 2,500 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 2,900 MATURE COWS (MILK AND DRY); 1,550 SUPPORT STOCK. POST PROJECT DESCRIPTION WILL BE: COW HOUSING - 2,500 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 2,900 MATURE COWS (MILK AND DRY); 1,550 SUPPORT STOCK (HEIFERS, CALVES AND BULLS); 7 FREESTALL BARN(S) WITH FLUSH SYSTEM
- N-7321-3-4: MODIFICATION OF LIQUID MANURE HANDLING SYSTEM CONSISTING OF SETTLING BASIN(S); 390' X 275' X 30', 290' X 285' X 14' AND 350' X 285' X 14' WASTE STORAGE LAGOON/PONDS; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION: INCREASE IN LIQUID MANURE DUE TO INCREASE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5 AND OPERATE LIQUID MANURE STORAGE IN AN ANAEROBIC TREATMENT SYSTEM AS PER ANAEROBIC TREATMENT LAGOON SPECIFICATION. POST PROJECT DESCRIPTION WILL BE: LIQUID MANURE HANDLING SYSTEM CONSISTING OF SETTLING BASIN(S); 390' X 275' X 30', 290' X 285' X 14' AND 350' X 285' X 14'

² As per revised information provided, the following administrative changes are being made. The facility currently has 2 freestall barns and this project will correct the pre project freestall designations. The addition of five new freestalls bring the total to 7 freestall barn areas after modification. Liquid manure permit description is revised and solid manure land application is added.

WASTE STORAGE LAGOON/PONDS; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION

- N-7321-4-3: MODIFICATION OF SOLID MANURE HANDLING CONSISTING OF MANURE STOCK PILES; SOLID MANURE APPLICATION TO LAND AND HAULED OFFSITE: INCREASE IN SOLID MANURE DUE TO CHANGE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5. POST PROJECT DESCRIPTION WILL BE: SOLID MANURE HANDLING CONSISTING OF MANURE STOCK PILES; SOLID MANURE APPLICATION TO LAND AND HAULED OFFSITE
- N-7321-6-2: MODIFICATION OF FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs AND SILAGE PILES: INCREASE IN TOTAL MIXED RATION DUE TO CHANGE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5. POST PROJECT DESCRIPTION WILL BE: FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs AND SILAGE PILES

Post Project Equipment Description:

- N-7321-1-5: 2,500 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR
- N-7321-2-5: COW HOUSING - 2,500 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 2,900 MATURE COWS (MILK AND DRY); 1,550 SUPPORT STOCK (HEIFERS, CALVES AND BULLS); 7 FREESTALL BARNs WITH FLUSH SYSTEM
- N-7321-3-4: LIQUID MANURE HANDLING SYSTEM CONSISTING OF SETTLING BASIN(S); 390' X 275' X 30', 290' X 285' X 14' AND 350' X 285' X 14' WASTE STORAGE LAGOON/PONDS; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION
- N-7321-4-3: SOLID MANURE HANDLING CONSISTING OF MANURE STOCK PILES; SOLID MANURE APPLICATION TO LAND AND HAULED OFFSITE
- N-7321-6-2: FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs AND SILAGE PILES

VI. Emission Control Technology Evaluation

Particulate Matter (PM), Volatile Organic Compounds (VOCs), and Ammonia (NH₃) are the major pollutants of concern from dairy operations. Hydrogen sulfide (H₂S) is also emitted from anaerobic processes on dairies. Gaseous pollutant emissions at a dairy result from the ruminant digestive processes (enteric emissions), the decomposition and fermentation of feed, and also from the decomposition of organic material in dairy manure. Volatile Organic Compounds are formed as intermediate metabolites when organic matter in manure degrades. Ammonia volatilization is the result of the microbial decomposition of nitrogenous compounds in manure. Hydrogen sulfide and other reduced sulfur compounds are produced when sulfur-containing compounds in manure decompose anaerobically. The quantity of enteric emissions depends directly on the number and types of cows. The quantity of emissions from manure decomposition depends on the amount of manure generated, which also depends on the number and types of cows.

Therefore, the total herd size and composition is the critical factor in quantifying emissions from a dairy. Various management practices will be used to control emissions at this dairy. Examples of some of these practices are discussed below:

A. Milking Parlor (N-7321-1):

This dairy uses a flush/spray system to wash out the manure from the milking parlor after each group of cows is milked. Since the milking parlor is constantly flushed, there will be no particulate matter emissions from the milking parlor. Manure, which is a source of VOC emissions, is removed from the milking parlor many times a day by flushing after each milking. Because of ammonia's high affinity for and solubility in water, volatilization of ammonia from the milking parlor will also be reduced by flushing after each milking. Flushing the milking parlor after each milking will also reduce anaerobic decomposition of manure on the milking parlor floor thereby eliminating the potential for H₂S emissions from the milking parlor floor.

B. Cow Housing (N-7321-2)

Majority of the mature cattle (milk cows and dry cows) at this dairy are housed in freestall barns and some support stock are housed in the shaded barn with flushed lanes. Practices that will be utilized to reduce emissions at the dairy include: frequent flushing of lanes, scraping of exercise pens, and feeding animals in accordance with NRC guidelines. These practices are discussed further below.

Freestall Barns:

S&S Dairy will house all milking and dry cows in the freestall areas.

Housing cattle in freestall barns greatly reduces PM emissions because the cows will be on a paved surface rather than on dry dirt. Additionally, flushing of the freestall lanes creates a moist environment, which further decreases particulate matter emissions.

Shaded Barn:

Manure, which is a source of emissions, will be removed from the shaded barn corral surface lanes by flushing and scraping. When a flush system is used, a large proportion of the VOCs emitted from fresh cow manure will dissolve in the flush water and will not be emitted from the cow housing permit unit. Because of ammonia's high affinity for and solubility in water, flushing the lanes and walkways will also reduce volatilization of ammonia from the manure deposited in the corral lanes.

Frequent flushing is also used for the removal of manure from the lanes and walkways in the housing barns. The emissions control mechanisms are the same as described above.

Frequent Flushing of Lanes:

Manure, which is a source of emissions, will be removed from the freestall barn lanes by flushing. When a flush system is used, a large proportion of the VOCs emitted from fresh cow manure will dissolve in the flush water and will not be emitted from the cow housing permit unit. Because of

ammonia's high affinity for and solubility in water, flushing the lanes and walkways will also reduce volatilization of ammonia from the manure deposited in the lanes of freestall barns and open corrals.

C. Liquid Manure Handling System (N-7321-3)

All emissions from the liquid manure handling system are the result of manure decomposition.

Anaerobic Treatment:

As stated above, the liquid manure handling system at S & S Dairy includes an existing lagoon/storage ponds that meets the anaerobic treatment lagoon designed criteria in accordance with the specifications set forth in NRCS practice standard 359. A properly designed and operated anaerobic treatment system will reduce VOC emissions because the organic compounds in the manure will be mostly converted into methane, carbon dioxide, and water rather than a significant amount of VOCs. An anaerobic treatment system also has an air pollution benefit over a system with only a storage pond. Odorous emissions are reduced with an anaerobic treatment storage system since the lagoon has a constant treatment volume, which promotes more efficient anaerobic digestion. The proposed anaerobic treatment lagoon/storage ponds system meets the appropriate design requirements (see anaerobic treatment lagoon design check in Appendix I).

Solids Separation:

The liquid manure handling system at S&S Dairy includes a settling basin for solids separation. Solids separation prevents excessive loading of volatile solids in lagoon/storage ponds treatment systems. Excessive loading of volatile solids in lagoons/storage ponds inhibits the activity of the methanogenic bacteria and leads to increased rates of volatile solids production. When the activity of the methanogenic bacteria is not inhibited, most of the VOCs are metabolized to simpler compounds, and the potential for VOC emissions is reduced.

Liquid Manure Land Application:

Liquid manure from the lagoon/storage pond will be applied through flood and furrow irrigation. The dairy will apply liquid manure to cropland at agronomic rates. Liquid manure will be applied in thin layers and will be blended with irrigation water in compliance with the dairy's comprehensive nutrient management plan and the requirements of the Regional Water Quality Control Board. These practices will reduce odors and result in faster uptake of nutrients, including organic nitrogen, which can emit VOCs and ammonia during decomposition, and ammonium nitrogen, which is readily lost to the atmosphere as gaseous ammonia.

D. Solid Manure Handling (N-7321-4)

Rapid Incorporation of Solid Manure Applied to Land:

Based on the information currently available, emissions from solid manure applied to cropland are small in comparison to other sources. However, to ensure that any possible emissions are minimized, this dairy will be required to incorporate solid manure applied to cropland immediately

(within two hours) after application. Immediate incorporation of the manure into the soil will reduce any volatilization of gaseous pollutants, including VOC and NH₃. Reduction in gaseous emissions is achieved by minimizing the amount of time that the manure is exposed to the atmosphere. Once manure has been incorporated into the soil, VOCs, NH₃, and any H₂S are absorbed onto particles of soil providing the opportunity for microbes in the soil to oxidize these compounds into carbon dioxide, water, nitrates, and sulfates.³

E. Feed Handling and Storage (N-7321-6)

Feeding Animals in Accordance with the NRC Guidelines:

All animals housed at the dairy will be fed in accordance with National Research Council (NRC) guidelines using routine nutritional analysis for rations. Feeding the cows in accordance with NRC guidelines minimizes undigested protein and other undigested nutrients in the manure, which would emit VOCs, NH₃, and H₂S upon decomposition.

Silage Pile Management:

The feed storage system at S & S Dairy includes storage of silage piles covered with plastic tarps to minimize volatilization of pollutants from the pile surfaces.

The proposed emission reduction measures for feed handling and storage include best management practices such as minimizing the surface area of silage exposed to the atmosphere. This can be done by covering the silage pile securely with a tarp and removing feed only from a small area of the pile (face of pile).

In addition, any refused feed will be removed from the feed lanes on a regular basis to minimize gaseous emissions from decomposition. Silage piles will be covered with plastic tarps to minimize volatilization of pollutants from the pile surfaces.

VII. General Calculations

A. Assumptions

- Potential to emit calculations will be based on the permitted limits for the different age categories of cows in the proposed herd.
- Only non-fugitive emissions are considered when determining major source status. For this facility, the lagoon/storage pond and gasoline dispensing are the only sources of non-fugitive emissions.
- All PM₁₀ emissions will be allocated to the cow housing permit unit (N-7321-2).
- All H₂S emissions will be allocated to the liquid manure permit unit - lagoon/storage pond (N-7321-3); and will be assumed to be equivalent to 10% of the NH₃ emissions from the lagoon/storage pond.

³ U.S. EPA's Draft Document Emissions From Animal Feeding Operations
(<http://www.epa.gov/ttn/chief/ap42/ch09/draft/draftanimalfeed.pdf>)

- The PM₁₀ control efficiency for shade structures is from a District document titled “Dairy/Feedlot PM₁₀ Mitigation Practices and their Control Efficiencies.”⁴
- The PM₁₀ emission factors are from a District document titled “Dairy and Feedlot PM₁₀ Emissions Factors,”⁵ which compiled data from studies performed by Texas A&M and ASAE, and a USDA/UC Davis report, quantifying dairy and feedlot emissions.
- The VOC emission factors for milk cows are from a District document titled “Air Pollution Control Officer’s Revision to the Dairy VOC Emission Factors, February 2012.”⁶ Volatile solids excretion ratios were used to derive the proportionate VOC emission factors for dry cows and support stock.
- The NH₃ emission factor for milk cows is based on California Air Resources Board’s dairy cattle ammonia emission factor.⁷ Manure-based VOC emission ratios were used to apportion the NH₃ emission factor to the various emissions units. Further, nitrogen excretion ratios were used to derive the proportionate NH₃ emission factors for dry cows and support stock.
- All the mitigation measures evaluated are expected to result in VOC emission reductions. Where a specific control efficiency has not been determined, a conservative 10% control efficiency will be assumed, unless noted otherwise.
- An anaerobic waste liquid treatment system designed and operated in accordance with NRCS Field Office Technical Guide No. 359 has the potential to significantly reduce VOC emissions by promoting the conversion of volatile solids in the manure into methane and carbon dioxide. Although significant VOC emission reductions are expected, a conservative control efficiency of 40% will be applied to this mitigation measure for both storage and land application of liquid manure.

B. Emission Factors

Detailed emission factors are listed in the emissions calculation spreadsheet in Appendix D (‘Dairy Emission Factors’ sheet).

C. Calculations

1. Pre-Project Potential to Emit (PE1)

Pre-Project Potential to Emit (PE1) for the dairy will be calculated below based on the maximum design capacity for each type of cow and the pre-project emission control practices in use at the dairy.

Emission calculations for this project are included in the dairy emissions calculation spreadsheet in Appendix D. PE1 for each dairy permit unit is shown in the tables below.

⁴ http://www.valleyair.org/busind/pto/dpag/Dairy_PM10_Control_Efficiencies.pdf

⁵ http://www.valleyair.org/busind/pto/dpag/FYI_%20Dairy_Feedlot_PM10_Emission_Factor.pdf

⁶ [http://www.valleyair.org/busind/pto/emission_factors/2012-Final-Dairy-EE-Report/FinalDairyEFReport\(2-23-12\).pdf](http://www.valleyair.org/busind/pto/emission_factors/2012-Final-Dairy-EE-Report/FinalDairyEFReport(2-23-12).pdf)

⁷ <http://www.arb.ca.gov/ei/areasrc/livestockemisfwp.pdf>

Daily Project Potential to Emit (PE1)							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-4	0	0	0	0	1.5	0.5	0
N-7321-2-4	0	0	37.3	0	55.2	105.5	0
N-7321-3-3	0	0	0	0	13.9	38.8	1.0
N-7321-4-2	0	0	0	0	2.7	14.6	0
N-7321-6-1	0	0	0	0	103.7	0	0
Total	0	0	37.3	0.0	177	159.4	1

Annual Project Potential to Emit (PE1)							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-4	0	0	0	0	560	192	0
N-7321-2-4	0	0	13,611	0	20,198	38,546	0
N-7321-3-3	0	0	0	0	5,096	14,152	368
N-7321-4-2	0	0	0	0	990	5,298	0
N-7321-6-1	0	0	0	0	37,856	0	0
Total	0	0	13,611	0	64,700	58,188	368

2. Post Project Potential to Emit (PE2)

The PE2 is based on the maximum permitted capacity for each age category of cows and the controls required and proposed by the applicant. All the emission calculations are included in Appendix D. A summary of the PE2 is shown in the following table:

Daily Project Potential to Emit (PE2)							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-5	0	0	0	0	2.7	0.9	0
N-7321-2-5	0	0	12.9	0	91.7	180.0	0
N-7321-3-4	0	0	0	0	13.5	41.7	1.0
N-7321-4-3	0	0	0	0	3.2	24.2	0
N-7321-6-2	0	0	0	0	119.2	0	0
Total	0	0.0	12.9	0.0	230.3	246.8	1
Annual Project Potential to Emit (PE2)							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-5	0	0	0	0	1,000	342	0
N-7321-2-5	0	0	4,664	0	33,497	65,686	0
N-7321-3-4	0	0	0	0	4,912	15,226	368
N-7321-4-3	0	0	0	0	1,184	8,810	0
N-7321-6-2	0	0	0	0	43,514	0	0
Total	0	0	4,664	0	84,107	90,064	368

3. Pre-Project Stationary Source Potential to Emit (SSPE1)

Pursuant to District Rule 2201, the SSPE1 is the Potential to Emit (PE) from all units with valid Authorities to Construct (ATC) or Permits to Operate (PTO) at the Stationary Source and the quantity of Emission Reduction Credits (ERC) which have been banked since September 19, 1991 for Actual Emissions Reductions (AER) that have occurred at the source, and which have not been used on-site.

SSPE1							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-4 (milking parlor)	0	0	0	0	560	192	0
N-7321-2-4 (cow housing)	0	0	13,611	0	20,198	38,546	0
N-7321-3-3 (liquid manure handling)	0	0	0	0	5,096	14,152	368
N-7321-4-2 (solid manure handling)	0	0	0	0	990	5,298	0
N-7321-5-0 ⁸ (gasoline dispensing)	0	0	0	0	222	0	0
N-7321-6-1 (feed storage/handling)	0	0	0	0	37,856	0	0
Total	0	0	13,611	0	64,922	58,188	368

4. Post Project Stationary Source Potential to Emit (SSPE2)

Pursuant to District Rule 2201, the SSPE2 is the PE from all units with valid ATCs or PTOs at the Stationary Source and the quantity of ERCs which have been banked since September 19, 1991 for AER that have occurred at the source, and which have not been used on-site.

SSPE2							
Permit Unit	NO _x	SO _x	PM ₁₀	CO	VOC	NH ₃	H ₂ S
N-7321-1-5 (milking parlor)	0	0	0	0	1,000	342	0
N-7321-2-5 (cow housing)	0	0	4,664	0	33,497	65,686	0
N-7321-3-4 (liquid manure handling)	0	0	0	0	4,912	15,226	368
N-7321-4-3 (solid manure handling)	0	0	0	0	1,184	8,810	0
N-7321-5-0 (gasoline dispensing)	0	0	0	0	222	0	0
N-7321-6-2 (feed storage/handling)	0	0	0	0	43,514	0	0
Total	0	0	4,664	0	84,329	90,064	368

⁸ Emissions taken from Project N-1110956.

5. Major Source Determination

Rule 2201 Major Source Determination:

Pursuant to District Rule 2201, a major source is a stationary source with an SSPE2 equal to or exceeding one or more of the major source thresholds shown in Table 3-3. For the purposes of determining major source status the following shall not be included:

- Any ERCs associated with the stationary source
- Emissions from non-road engines (i.e. engines at a particular site at the facility for less than 12 months)
- Fugitive emissions, except for the source categories specified in 40 CFR 51.165

Agricultural operations do not belong to any of the source categories specified in 40 CFR 51.165. Since the proposed facility is an agricultural operation, fugitive emissions shall not be included in determining whether it will be a major stationary source.

40 CFR 71.2 defines fugitive emissions as “those emissions which could not reasonably pass through a stack, chimney, vent, or other functionally-equivalent opening.” In 2005, the California Air Pollution Control Officers Association (CAPCOA) issued guidance for estimating VOC emissions from dairy farms. This guidance determined that VOC emissions from the milking centers, cow housing areas, corrals, common manure storage areas, and land application of manure are considered fugitive since they are not physically contained and could not reasonably pass through a stack, chimney, vent, or other functionally-equivalent opening. The guidance also determined that VOC emissions from liquid manure lagoons and storage ponds are not considered fugitive because emission collection technologies for liquid manure systems exist. The District has researched this issue and concurs with the CAPCOA determinations, as discussed in more detail below:

Milking Parlor

The mechanical ventilation system could arguably be utilized to capture emissions from the milking parlor. In order to achieve and maintain the negative pressure required for this purpose, the adjoining holding area would also need to be completely enclosed. However, enclosing the holding area is not practical due to the continuous movement of cows in and out of the barn throughout the day. In addition, the capital outlay required to enclose this large area would be prohibitive. The District therefore determines that emissions from the milking parlor cannot reasonably be captured, and are to be considered fugitive.

Cow Housing

Although there are smaller dairy farms that have enclosed housing barns, such barns are usually not fully enclosed and do not include any systems for the collection of emissions. In addition, the airflow requirements for dairy cows are extremely high, primarily for herd health reasons. Airflow requirements are expected to be even higher in places such as the San Joaquin Valley, where daytime temperatures can exceed 110 degrees Fahrenheit for prolonged periods during the summer months. Given the

high air flow rates that will be involved, collection and control of the exhaust from housing barns is not only impractical but also cost prohibitive. The District therefore determines that emissions from housing barns cannot reasonably be captured, and are to be considered fugitive.

Manure Storage Areas

Solid manure is typically stored in the housing areas, as mounds or piles in individual corrals or pens. Some manure may also be stored in piles outside the housing areas while awaiting land application, shipment offsite, or other uses. Thus, manure storage areas are widely distributed over the dairy site, making it impractical to capture emissions from any significant proportion of the solid manure. The District therefore determines that emissions from manure storage areas cannot reasonably be captured, and are to be considered fugitive.

Land Application

Since manure has to be applied over large expanses of cropland (hundreds or even thousands of acres), there is no practical method that can be used to capture the associated emissions. The District therefore determines that emissions from land application of manure cannot reasonably be captured, and are to be considered fugitive.

Feed Storage and Handling

Silage and total mixed rations (TMR) are the primary sources of emissions from feed storage and handling.

Silage is stored in silage piles. Only two piles will be actively used at any given time and the remainder of the piles will remain covered. One end/face of the silage pile that is actively being used to prepare feed rations must remain open to allow extraction of the silage. A front-end loader is used to extract silage from the open face of the pile throughout the day as the feed rations for the various groups or categories of cows are prepared. A significant proportion of silage pile emissions are associated with this open face, which is exposed to the atmosphere and frequently disturbed during silage extraction. Due to the need to access the pile's open face throughout the day, it is not practical to enclose it or equip it with any kind of device or system that could be used to capture of emissions.

TMR is prepared by mixing silage with various additives such as seeds, grains, and molasses. Because the quality of silage degrades fairly rapidly upon exposure to air, TMR is prepared only when needed and promptly distributed to the feed lanes for consumption. Most of the TMR emissions are thus emitted from the feed lanes, which are located inside the housing barns, where the TMR will remain exposed to the air for at least several hours as the cows feed. As previously discussed, collection and control of emissions from housing barns is not only impractical but also cost prohibitive.

The District therefore determines that emissions from feed handling and storage cannot be reasonably be captured, and are to be considered fugitive.

Therefore, the VOC emissions from these sources are considered fugitive. The District has determined that control technology to capture emissions from lagoons (biogas collection systems, for instance) is in use and these emissions can be reasonably collected and are not fugitive. Therefore, only emissions from the lagoons/storage ponds, and gasoline dispensing will be used to determine if this facility is a major source.

Pre-Project Major Source Determination:

Pre-Project lagoon emissions for this project are included in Appendix D.

Pre-Project Major Source Determination (lb/year)						
	NO _x	SO _x	PM ₁₀	PM _{2.5}	CO	VOC
N-7321-3-3 (liquid manure handling – Lagoon(s)/storage pond(s))	0	0	0	0	0	2,452
N-7321-5-0 (gasoline)	0	0	0	0	0	222
Non-Fugitive SSPE1	0	0	0	0	0	2,674
Major Source Threshold	20,000	140,000	140,000	200,000	200,000	20,000

Note: PM2.5 assumed to be equal to PM10

Post-Project Major Source Determination:

Post-Project lagoon emissions for this project are included in Appendix D.

Post-Project Major Source Determination (lb/year)						
	NO _x	SO _x	PM ₁₀	PM _{2.5}	CO	VOC
N-7321-3-4 (liquid manure handling – Lagoon(s)/storage pond(s))	0	0	0	0	0	2,352
N-7321-5-0 (gasoline)	0	0	0	0	0	222
Non-Fugitive SSPE2	0	0	0	0	0	2,574
Major Source Threshold	20,000	140,000	140,000	200,000	200,000	20,000

Note: PM2.5 assumed to be equal to PM10

As seen in the table above, the facility is not an existing Major Source and is not becoming a Major Source as a result of this project.

Rule 2410 Major Source Determination:

In determining if a stationary source is a PSD major source, the following sources of emissions shall not be included:

- Emissions from non-road engines (i.e. engines at a particular site at the facility for less than 12 months)

- Fugitive emissions, except for the source categories specified in 40 CFR 52.21(b)(1)(iii)

Agricultural operations do not belong to any of the source categories specified in specified in 40 CFR 52.21(b)(1)(i). Since the proposed facility is an agricultural operation, fugitive emissions shall not be included in determining whether it will be a PSD major source; and the PSD major source threshold is 250 tons/yr (tpy) for any regulated NSR pollutant.

The non-fugitive stationary source emissions from the preceding section have been converted into tons. The PSD major source determination is summarized in the following table:

PSD Major Source Determination						
Category	NO₂	VOC	SO₂	CO	PM	PM₁₀
Estimated facility PE before project increase (tpy)	0	1.3	0	0	0	0
PSD major source threshold (tpy)	250	250	250	250	250	250
PSD major source? (Y/N)	N	N	N	N	N	N

As shown above, the facility is not an existing major source for PSD for at least one pollutant. Therefore the facility is not an existing major source for PSD.

6. Baseline Emissions (BE)

The BE calculation (in lb/year) is performed pollutant-by-pollutant for each unit within the project to calculate the QNEC, and if applicable, to determine the amount of offsets required.

Pursuant to District Rule 2201, BE = PE1 for:

- Any unit located at a non-Major Source,
- Any Highly-Utilized Emissions Unit, located at a Major Source,
- Any Fully-Offset Emissions Unit, located at a Major Source, or
- Any Clean Emissions Unit, located at a Major Source.

otherwise,

BE = Historic Actual Emissions (HAE), calculated pursuant to District Rule 2201.

As shown in Section VII.C.5 above, the facility is not a Major Source for any pollutant.

Therefore BE = PE1.

7. SB 288 Major Modification

SB 288 Major Modification is defined in 40 CFR Part 51.165 as "any physical change in or change in the method of operation of a major stationary source that would result in a significant net emissions increase of any pollutant subject to regulation under the Act."

Since this facility is not a major source for any of the pollutants addressed in this project, this project does not constitute an SB 288 major modification.

8. Federal Major Modification

District Rule 2201 states that a Federal Major Modification is the same as a "Major Modification" as defined in 40 CFR 51.165 and part D of Title I of the CAA.

Since this facility is not a Major Source for any pollutants, this project does not constitute a Federal Major Modification.

9. Rule 2410 – Prevention of Significant Deterioration (PSD) Applicability Determination

Rule 2410 applies to any pollutant regulated under the Clean Air Act, except those for which the District has been classified nonattainment. The pollutants which must be addressed in the PSD applicability determination for sources located in the SJV and which are emitted in this project are: (See 52.21 (b) (23) definition of significant)

- PM
- PM₁₀
- Hydrogen sulfide (H₂S)
- Total reduced sulfur (including H₂S)

Project Emissions Increase - New Major Source Determination

The post-project potentials to emit (PE) from all new and modified units are compared to the PSD major source thresholds to determine if the project constitutes a new major source subject to PSD requirements.

Agricultural operations do not belong to any of the source categories specified in specified in 40 CFR 52.21(b)(1)(i). Since the proposed facility is an agricultural operation, fugitive emissions shall not be included in determining whether it will be a PSD major source; and the PSD major source threshold is 250 tons/yr (tpy) for any regulated NSR pollutant.

The non-fugitive stationary source emissions from Section VII.C.5 have been converted into tons. The PSD applicability determination is summarized in the following table:

PSD Applicability Determination - New Major Source				
Category	PM	PM₁₀	H₂S	S
Total PE from new and modified units (tpy)	0	0	0.2	0.2
PSD major source threshold (tpy)	250	250	250	250
New PSD major source? (Y/N)	N	N	N	N

As shown in the table above, the PE for the proposed project, by itself, does not exceed any PSD major source threshold. Rule 2410 is therefore not applicable and no further analysis is required.

10. Quarterly Net Emissions Change (QNEC)

The QNEC is calculated solely to establish emissions that are used to complete the District’s PAS emissions profile screen. Detailed QNEC calculations are included in Appendix J.

VIII. Compliance Determination

Rule 2201 New and Modified Stationary Source Review Rule

A. Best Available Control Technology (BACT)

1. BACT Applicability

Pursuant to District Rule 2201, Section 4.1, BACT requirements are triggered on a pollutant-by-pollutant basis and on an emissions unit-by-emissions unit basis. Unless specifically exempted by Rule 2201, BACT shall be required for the following actions*:

- a. Any new emissions unit with a potential to emit exceeding two pounds per day,
- b. The relocation from one Stationary Source to another of an existing emissions unit with a potential to emit exceeding two pounds per day,
- c. Modifications to an existing emissions unit with a valid Permit to Operate resulting in an Adjusted Increase in Permitted Emissions (AIPE) exceeding two pounds per day, and/or
- d. Any new or modified emissions unit, in a stationary source project, which results in an SB 288 Major Modification or a Federal Major Modification, as defined by the rule.

*Except for CO emissions from a new or modified emissions unit at a Stationary Source with an SSPE2 of less than 200,000 pounds per year of CO.

a. New emissions units – PE > 2 lb/day

The applicant is proposing to expand the herd size and adding new cow housing. As shown in Appendix E, BACT calculations the following new emissions units will have increases of more than 2.0 lb/day for each respective pollutant and triggers Best Available Control Technology (BACT) requirements.

Cow Housing:

VOC: New Freestall Barn Area # 3 & 4
NH3: New Freestall Barn Area # 3 & 4

b. Relocation of emissions units – PE > 2 lb/day

As discussed in Section I above, there are no emissions units being relocated from one stationary source to another; therefore BACT is not triggered.

c. Modification of emissions units – AIPE > 2 lb/day

$$\text{AIPE} = \text{PE2} - \text{HAPE}$$

Where,

AIPE = Adjusted Increase in Permitted Emissions, (lb/day)

PE2 = Post-Project Potential to Emit, (lb/day)

HAPE = Historically Adjusted Potential to Emit, (lb/day)

$$\text{HAPE} = \text{PE1} \times (\text{EF2}/\text{EF1})$$

Where,

PE1 = The emissions unit's PE prior to modification or relocation, (lb/day)

EF2 = The emissions unit's permitted emission factor for the pollutant after modification or relocation. If EF2 is greater than EF1 then EF2/EF1 shall be set to 1

EF1 = The emissions unit's permitted emission factor for the pollutant before the modification or relocation

$$\text{AIPE} = \text{PE2} - (\text{PE1} * (\text{EF2} / \text{EF1}))$$

The applicant is proposing to expand the herd size and adding new cow housing. As shown in Appendix E, BACT for the following modified emissions units will have increases of more than 2.0 lb/day for each respective pollutant and triggers Best Available Control Technology (BACT) requirements.

N-7321-2-5: Cow Housing:

VOC: Freestall Barn Area # 5 & 6
NH3: Freestall Barn Area # 1, 5 & 6

N-7321-3-4: Liquid Manure Handling

Lagoon/Storage Ponds – VOC & NH3
Liquid Manure Land Application – VOC & NH3

N-7321-4-3: Solid Manure Handling

Solid Manure Storage – NH3

Solid Manure Land Application – NH3

N-7321-6-2: Feed Storage and Handling

Dairy Feed Storage and Handling System & Total Mix Ration (TMR) - VOC

d. SB 288/Federal Major Modification

As discussed in Sections VII.C.7 and VII.C.8 above, this project does not constitute an SB 288 and/or Federal Major Modification for any pollutant. Therefore BACT is not triggered for any pollutant.

2. BACT Guideline

The following BACT Guidelines applies to various dairy emission units stated above:

- BACT Guideline 5.8.2, applies to the cow housing – freestalls
- BACT Guideline 5.8.6, applies to the liquid manure handling – lagoon/storage ponds
- BACT Guideline 5.8.7 applies to the liquid manure handling – land application
- BACT Guideline 5.8.8 applies to the solid manure handling – storage
- BACT Guideline 5.8.9 applies to the solid manure handling – land application
- BACT Guideline 5.8.11 applies to the feed storage and handling – total mixed ration (TMR)

The above-mentioned BACT Guidelines are included in the **Appendix F**.

3. Top-Down BACT Analysis

Per Permit Services policies and procedures for BACT, a top-down BACT analysis shall be performed as a part of the application review for each application subject to the BACT requirements pursuant to the District's NSR rule.

Pursuant to the attached top-down BACT analysis (Appendix G), BACT has been satisfied with the following:

N-7321-2-5: Cow Housing

VOC: New Freestall Barns #3 & 4 and Existing Freestall Barns # 5 & 6

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;

- Properly sloping exercise pens/corrals (minimum of 3% slope where the available space for each animal is 400 square feet or less and minimum of 1.5% where the available space for each animal is more than 400 square feet per animal) or managing exercise pens/corrals to ensure proper drainage;
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions; and
- Rule 4570 measures.

NH₃: New Freestall Barns #3 & 4 and Existing Freestall Barns #1, 5 & 6

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum of 3% slope where the available space for each animal is 400 square feet or less and minimum of 1.5% where the available space for each animal is more than 400 square feet per animal) or managing exercise pens/corrals to ensure proper drainage; and
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions.

ATC Conditions:

Following conditions on the ATC enforces BACT requirements stated above:

- *Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201, 4102 & 4570] N*
- *Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201, 4102, & 4570] N*
- *Permittee shall pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. [District Rules 2201, 4102, & 4570] N*
- *For the Freestall Barns #1, #3, #4, #5 and #6 the feedlanes and walkways shall be*

constructed of concrete. [District Rules 2201, 4102 & 4570] N

- For the Freestall Barns #1, #3, #4, #5 and #6 permittee shall flush the feed lanes and walkways for the mature cows (milk and dry cows) at least four times per day and flushing lanes and walkways for the remaining animals once per day. [District Rule 2201, 4102 & 4570] N
- For the Freestall Barns #1, #3, #4, #5 and #6 permittee shall maintain records sufficient to demonstrate that lanes are flushed at least four times per day for the mature cows and at least once per day for the support stock. [District Rules 2201, 4102, & 4570] N
- Permittee shall implement at least one of the following corral mitigation measures: 1) slope the surface of the corrals at least 3% where the available space for each animal is 400 square feet or less and shall slope the surface of the corrals at least 1.5% where the available space for each animal is more than 400 square feet per animal; 2) maintain corrals to ensure proper drainage preventing water from standing more than forty-eight hours; or 3) harrow, rake, or scrape pens sufficiently to maintain a dry surface except during periods of rainy weather. [District Rules 2201, 4102 & 4570] N
- Permittee shall scrape exercise pen/corral surfaces every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rules 2201 and 4102] N
- Permittee shall maintain sufficient records to demonstrate that exercise pen/corral surfaces are scraped every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rules 2201 and 4102] N

N-7321-3-4: Liquid Manure Handling System

Lagoon/Storage Pond

VOC: 1) Anaerobic treatment lagoon designed according to NRCS guidelines, and solids separation/removal system (mechanical separator(s) or settling basin(s)/weeping wall(s)).

NH₃: 1) All animals fed in accordance with National Research Council (NRC) or other District-approved guidelines utilizing routine nutritional analysis for rations.

Land Application

VOC: 1) Irrigation of crops using liquid/slurry manure from a secondary lagoon/holding/storage pond preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards.

NH₃: 1) All animals fed in accordance with National Research Council (NRC) or other District-approved guidelines utilizing routine nutritional analysis for rations.

ATC Conditions:

Following conditions on the ATC enforces BACT requirements stated above:

- *Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 and 4102] N*
- *All liquid manure shall be treated in an anaerobic treatment lagoon/waste liquid storage system that is designed and operated according to the Natural Resources Conservation Service (NRCS) Field Office Technical Guide No. 359. [District Rules 2201 and 4102] N*
- *Permittee shall maintain design specifications and calculations, including minimum treatment volume (MTV) and hydraulic retention time (HRT) calculations, demonstrating that the anaerobic treatment lagoon system meets the requirements listed in the NRCS Field Office Technical Guide No. 359. [District Rules 2201 and 4102] N*
- *Any liquid manure applied to land shall have been treated in an anaerobic treatment lagoon/waste liquid storage system that is designed and operated according to the NRCS Field Office Technical Guide No. 359. [District Rules 2201 and 4102] N*

N-7321-4-3: Solid Manure Handling Operation

Storage Piles

- NH₃: 1) All animals fed in accordance with National Research Council (NRC) or other District-approved guidelines utilizing routine nutritional analysis for rations.

Land Application

- NH₃: 1) Rapid incorporation of solid manure into the soil after land application, and all animals fed in accordance with NRC or other District-approved guidelines.

ATC Conditions:

Following conditions on the ATC enforces BACT requirements stated above:

- *Solid manure shall be incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]*
- *Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rule 2201 and Rule 4570] N*

N-7321-6-2: Feed Storage and Handling Operation

Silage:

VOC: 1) VOC mitigation measures required by District Rule 4570.

TMR:

VOC: 1) VOC mitigation measures required by District Rule 4570.

See detailed discussion under Rule 4570 compliance section for conditions that will be added to the ATC to enforce BACT. The Rule 2201 reference will be added in the applicable rule section at the end of the each condition to enforce BACT.

B. Offsets

1. Offset Applicability

Pursuant to District Rule 2201, Section 4.5, offset requirements shall be triggered on a pollutant by pollutant basis and shall be required if the SSPE2 equals or exceeds the offset threshold levels in Table 4-1 of Rule 2201.

The SSPE2 is compared to the offset thresholds in the following table.

Offset Determination (lb/year)					
	NO_x	SO_x	PM₁₀	CO	VOC
SSPE2	0	0	4,664	0	84,329
Offset Thresholds	20,000	54,750	29,200	200,000	20,000
Offsets triggered?	No	No	No	No	Yes

2. Quantity of Offsets Required

The SSPE for VOC emissions exceeds the VOC offset threshold level. However, per Section 4.6.9 of Rule 2201, offsets are not required for agricultural sources unless they are a major source. As determined in Section VII.C.5 of this evaluation, the proposed facility will not be a major source for any pollutants. Offsets are therefore not required.

C. Public Notification

1. Applicability

Pursuant to District Rule 2201, Section 5.4, public noticing is required for:

- a. New Major Sources, Federal Major Modifications, and SB 288 Major Modifications,

- b. Any new emissions unit with a Potential to Emit greater than 100 pounds during any one day for any one pollutant,
- c. Any project which results in the offset thresholds being surpassed,
- d. Any project with an SSIFE of greater than 20,000 lb/year for any pollutant, and/or
- e. Any project which results in a Title V significant permit modification

a. New Major Sources, Federal Major Modifications, and SB 288 Major Modifications

New Major Sources are new facilities, which are also Major Sources. Since this is not a new facility, public noticing is not required for this project for New Major Source purposes.

As demonstrated in Sections VII.C.7 and VII.C.8, this project does not constitute an SB 288 or Federal Major Modification; therefore, public noticing for SB 288 or Federal Major Modification purposes is not required.

b. PE > 100 lb/day

Applications which include a new emissions unit with a PE greater than 100 pounds during any one day for any pollutant will trigger public noticing requirements. There are no new emissions units associated with this project. Therefore public noticing is not required for this project for PE > 100 lb/day.

c. Offset Threshold

Pursuant to District Rule 2201, Section 4.5.3, offset requirements shall be triggered on a pollutant-by-pollutant basis, unless exempted pursuant to Section 4.6, offsets shall be required if the post-project Stationary Source Potential to Emit (SSPE2) equals or exceeds specific threshold levels.

The SSPE1 and SSPE2 are compared to the offset thresholds in the following table.

Offset Thresholds				
Pollutant	SSPE1 (lb/year)	SSPE2 (lb/year)	Offset Threshold	Public Notice Required?
NO _x	0	0	20,000 lb/year	No
SO _x	0	0	54,750 lb/year	No
PM ₁₀	13,611	4,664	29,200 lb/year	No
CO	0	0	200,000 lb/year	No
VOC	64,922	84,329	20,000 lb/year	No

As detailed above, there were no thresholds surpassed with this project; therefore public noticing is not required for offset purposes.

d. SSIPE > 20,000 lb/year

Public notification is required for any permitting action that results in a SSIPE of more than 20,000 lb/year of any affected pollutant. According to District policy, the SSIPE = SSPE2 – SSPE1. The SSIPE is compared to the SSIPE Public Notice thresholds in the following table.

SSIPE Public Notice Thresholds					
Pollutant	SSPE2 (lb/year)	SSPE1 (lb/year)	SSIPE (lb/year)	SSIPE Public Notice Threshold	Public Notice Required?
NO _x	0	0	0	20,000 lb/year	No
SO _x	0	0	0	20,000 lb/year	No
PM ₁₀	4,664	13,611	-8,947	20,000 lb/year	No
CO	0	0	0	20,000 lb/year	No
VOC	84,329	64,922	19,407	20,000 lb/year	No
NH ₃	90,064	58,188	31,876	20,000 lb/year	Yes
H ₂ S	368	368	0	20,000 lb/year	No

As demonstrated above, the SSIPEs for NH₃ is greater than 20,000 lb/year; therefore public noticing for SSIPE purposes is required.

e. Title V Significant Permit Modification

Since this facility does not have a Title V operating permit, this change is not a Title V significant Modification, and therefore public noticing is not required.

2. Public Notice Action

As discussed above, public notice is required for this project. Public notice documents will be submitted to the California Air Resources Board (CARB) and a public notice will be published in a local newspaper of general circulation in Madera County prior to the issuance of the ATC permits.

D. Daily Emission Limits (DELs)

DELs and other enforceable conditions are required by Rule 2201 to restrict a unit's maximum daily emissions, to a level at or below the emissions associated with the maximum design capacity. The DEL must be contained in the latest ATC and contained in or enforced by the latest PTO and enforceable, in a practicable manner, on a daily basis. DELs are also required to enforce the applicability of BACT.

For dairies, the DEL is based on the numbers and age categories of the cows in the permitted herd, as well as conditions enforcing BACT requirements. The following DEL conditions also enforce project design specifications proposed by the applicant for compliance with the ambient air quality standard for PM₁₀.

Proposed Rule 2201 (DEL) Conditions:

N-7321-1-5: Milking Operation

- *{modified 4484} Permittee shall flush or hose down the milking parlor immediately prior to, immediately after, or during each milking. [District Rules 2201 and 4570]*

N-7321-2-5: Cow Housing

- *Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201, 4102 and 4570] N*
- *For Freestall Barns #1, #3, #4, #5 and #6 the feedlanes and walkways shall be constructed of concrete. [District Rules 2201, 4102 and 4570] N*
- *For Freestall Barns #1, #3, #4, #5 and #6 permittee shall flush the feed lanes and walkways for the mature cows (milk and dry cows) at least four times per day and flushing lanes and walkways for the remaining animals once per day . [District Rules 2201, 4102 and 4570] N*
- *Permittee shall scrape exercise pen and corral surfaces every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rules 2201 and 4102] N*
- *Permittee shall pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. [District Rules 2201 4102 and 4570] N*
- *Permittee shall remove manure that is not dry from individual cow freestall beds or shall rake, harrow, scrape, or grade freestall bedding at least once every seven (7) days. [District Rules 2201 and 4570] N*
- *Permittee shall inspect water pipes and troughs and repair leaks at least once every seven (7) days. [District Rules 2201 and 4570] N*
- *Permittee shall clean manure from corrals at least four (4) times per year with at least sixty (60) days between each cleaning, or permittee shall clean corrals at least once between April and July and at least once between September and December. [District Rules 2201 and 4570] N*
- *Permittee shall implement at least one of the following corral mitigation measures: 1) slope the surface of the corrals at least 3% where the available space for each animal is 400 square feet or less and shall slope the surface of the corrals at least 1.5% where the available space for each animal is more than 400 square feet per animal; 2) maintain corrals to ensure proper drainage preventing water from standing more than forty-eight hours; or 3) harrow, rake, or scrape pens sufficiently to maintain a dry surface except during periods of rainy weather. [District Rules 2201, 4102 and 4570] N*

- *Permittee shall scrape, vacuum or flush concrete lanes in corrals at least once every day for mature cows and every seven (7) days for support stock. [District Rules 2201 and 4570] N*
- *Permittee shall manage corrals such that the manure depth in the corral does not exceed twelve (12) inches at any time or point, except for in-corral mounding. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. However, permittee must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible. [District Rules 2201 and 4570] N*

N-7321-3-4: Liquid Manure Handling

- *{modified 4454} Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rule 2201]*
- *All liquid manure shall be treated in an anaerobic treatment lagoon system that is designed and operated according to the Natural Resources Conservation Service (NRCS) Field Office Technical Guide No. 359. [District Rule 2201 and 4102]*
- *{modified 4538} Permittee shall remove solids with a solids separation system prior to the manure entering the lagoon. [District Rules 2201 and 4570]*
- *Any liquid manure applied to land shall have been treated in an anaerobic treatment lagoon system that is designed and operated according to the NRCS Field Office Technical Guide No. 359. [District Rule 2201]*
- *{modified 4550} Permittee shall not allow liquid manure to stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]*

N-7321-4-3: Solid Manure Handling

- *{modified 4454} Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rule 2201]*
- *{modified 4526} Within seventy-two (72) hours of removal of solid manure from housing, permittee shall either 1) remove dry manure from the facility, or 2) cover dry manure outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed twenty-four (24) hours per event. [District Rule 4570]*
- *{modified 4541} Solid manure shall be incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]*

N-7321-6-2: Feed Storage and Handling

- *{modified 4454} Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 and 4570]*
- *{modified 4456} Permittee shall push feed so that it is within three feet of the feed lane*

fences within two hours of putting out the feed, or use feed troughs or other feeding structures designed to maintain feed within reach of the animals. [District Rules 2201 and 4570]

- *{modified 4458} Permittee shall begin feeding total mixed rations within two hours of grinding and mixing rations. [District Rules 2201 and 4570]*
- *{modified 4460} Permittee shall store grain in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 and 4570]*
- *{modified 4462} Permittee shall feed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. [District Rules 2201 and 4570]*
- *{modified 4468} For bagged silage/feedstuff, permittee shall utilize a sealed feed storage system (e.g., ag bag). [District Rules 2201 and 4570]*
- *{modified 4469} Permittee shall cover all silage piles, except for the area where feed is being removed from the pile, with a plastic tarp that is at least five (5) mils (0.005 inches) thick, multiple plastic tarps with a cumulative thickness of at least 5 mils (0.005 inches), or an oxygen barrier film covered with a UV resistant material. Silage piles shall be covered within seventy-two (72) hours of last delivery of material to the pile. Sheets of material used to cover silage shall overlap so that silage is not exposed where the sheets meet. [District Rules 2201 and 4570]*
- *{modified 4471} Permittee shall select and implement one of the following mitigation measures for building each silage pile at the facility: Option 1) build the silage pile such that the average bulk density is at least 44 lb/cu ft for corn silage and 40 lb/cu ft for other silage types, as measured in accordance with Section 7.11 of District Rule 4570; Option 2) Adjust filling parameters when creating the silage pile to achieve an average bulk density of at least 44 lb/cu ft for corn silage and at least 40 lb/cu ft for other silage types as determined using a District-approved spreadsheet; or Option 3) build silage piles using crops harvested with the applicable minimum moisture content, maximum Theoretical Length of Chop (TLC), and roller opening identified in District Rule 4570, Table 4.1, 1.d and manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. Records of the option chosen as a mitigation measure for building each silage pile shall be maintained. [District Rules 2201 and 4570]*
- *{modified 4474} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall harvest corn used for the pile at an average moisture content of at least 65% and harvest other silage crops for the pile at an average moisture content of at least 60%. [District Rules 2201 and 4570]*
- *{modified 4476} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall adjust setting of equipment used to harvest crops for the pile to incorporate the following*

parameters for Theoretical Length of Chop (TLC) and roller opening, as applicable: 1) Corn with no processing: TLC not exceeding 1/2 inch, 2) Processed Corn: TLC not exceeding 3/4 inch and roller opening of 1-4 mm, 3) Alfalfa/Grass: TLC not exceeding 1.0 inch, 4) Other silage crops: TLC not exceeding 1/2 inch. [District Rules 2201 and 4570]

- *{modified 4478} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rules 2201 and 4570]*
- *{modified 4480} Permittee shall select and implement at least two of the following mitigation measures for management of silage piles at the facility: Option 1) manage silage piles such that only one silage pile has an uncovered face and the total exposed surface area is less than 2,150 square feet, or manage multiple uncovered silage piles such that the total exposed surface area of all uncovered silage piles is less than 4,300 square feet; Option 2) use a shaver/facer to remove silage from the silage pile, or shall use another method to maintain a smooth vertical surface on the working face of the silage pile; or Option 3) inoculate silage with homolactic lactic acid bacteria in accordance with manufacturer recommendations to achieve a concentration of at least 100,000 colony forming units per gram of wet forage, apply propionic acid, benzoic acid, sorbic acid, sodium benzoate, or potassium sorbate at the rate specified by the manufacturer to reduce yeast counts when forming silage piles, or apply other additives at rates that have been demonstrated to reduce alcohol concentrations in silage and/or VOC emissions from silage and have been approved by the District and EPA. Records of the options chosen for managing each silage pile shall be maintained. [District Rules 2201 and 4570]*

E. Compliance Assurance

1. Source Testing

Pursuant to District Policy APR 1705, source testing is not required to demonstrate compliance with Rule 2201.

2. Monitoring

No monitoring is required to demonstrate compliance with Rule 2201.

3. Recordkeeping

Recordkeeping is required to demonstrate compliance with the public notification and daily emission limit requirements of Rule 2201. In general, recordkeeping for the Milking Parlor (N-7321-1), the Liquid Manure Handling System (N-7321-3), and the Solid Manure Handling System (N-7321-4) and the Feed Storage and Handling System (N-7321-6) is satisfied with the records that must be kept to demonstrate compliance with the numbers and types of cows listed in the permit equipment description for the Cow Housing (N-7321-2). Conditions that will be placed on the ATC permits are listed below.

Additional recordkeeping conditions are included under the Rule 4570 compliance section.

Milking Parlor (N-7321-1)

The following conditions will be placed on the ATC:

- {modified 4485} Permittee shall provide verification that milk parlor is flushed or hosed down immediately prior to, immediately after, or during each milking. [District Rules 2201 and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201 and 4570]

Cow Housing (N-7321-2)

The following conditions will appear on the ATC for the Cow Housing Permit:

- Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201, 4102, and 4570]
- Permittee shall maintain records sufficient to demonstrate that freestall lanes are flushed, scraped or vacuumed immediately prior to, immediately after or during each milking. [District Rules 2201 & 4570] N
- {modified 4488} For Freestall Barns #1, #3, #4, #5 and #6 permittee shall maintain records sufficient to demonstrate that lanes are flushed at least four times per day or scraped four times per day. [District Rules 2201, 4102, and 4570]
- {modified 4500} Permittee shall maintain records demonstrating that water pipes and troughs are inspected and leaks are repaired at least once every seven (7) days. [District Rules 2201 and 4570]
- Permittee shall measure and document the depth of manure on the concrete lanes at least once every ninety (90) days. [District Rule 2201 & 4570] N
- {modified 4502} Permittee shall demonstrate that manure from corrals are cleaned at least four (4) times per year with at least sixty (60) days between each cleaning or demonstrate that corrals are cleaned at least once between April and July and at least once between September and December. [District Rules 2201 and 4570]
- {modified 4555} Permittee shall either 1) maintain sufficient records to demonstrate that exercise pens/corrals are maintained to ensure proper drainage preventing water from standing for more than forty-eight hours; or 2) maintain records of dates when exercise

pens/corrals are groomed (i.e., harrowed, raked, or scraped, etc.). [District Rules 2201, 4102, and 4570]

- Permittee shall maintain sufficient records to demonstrate that exercise pen and corral surfaces are scraped every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rule 2201] N
- {modified 4449} Permittee shall maintain a record of the number of animals of each species and production group at the facility and shall maintain quarterly records of any changes to this information. [District Rules 2201, 4102, and 4570]
- {modified 4519} Permittee shall measure and document the depth of manure in the corrals at least once every ninety (90) days. [District Rules 2201, 4102, and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

Liquid Manure Handling System (N-7321-3)

To ensure that the lagoon system is designed and operating properly, the following conditions will be placed on the ATC for the Liquid Manure Handling System:

- Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4102]
- Permittee shall maintain design specifications and calculations, including minimum treatment volume (MTV) and hydraulic retention time (HRT) calculations, demonstrating that the anaerobic treatment lagoon system meets the requirements listed in the NRCS Field Office Technical Guide No. 359. [District Rules 2201 and 4102]
- Permittee shall maintain records to demonstrate that liquid manure applied to land has been treated in an anaerobic treatment lagoon system that is designed and operated according to the NRCS Field Office Technical Guide No. 359. [District Rule 2201]
- {modified 4551} Permittee shall maintain records to demonstrate liquid manure did not stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

Solid Manure Handling System (N-7321-4)

The following conditions will be placed on the ATC:

- Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rule 2201]
- {modified 4527} Permittee shall keep records of dates when manure is removed from the dairy or permittee shall maintain records to demonstrate that dry manure piles outside the pens are covered with a weatherproof covering from October through May. [District Rules 2201 and 4570]
- {modified 4528} If weatherproof coverings are used, permittee shall maintain records, such as manufacturer warranties or other documentation, demonstrating that the weatherproof covering over dry manure are installed, used, and maintained in accordance with manufacturer recommendations and applicable standards listed in NRCS Field Office Technical Guide Code 313 or 367, or any other applicable standard approved by the APCO, ARB, and EPA. [District Rules 2201 and 4570]
- {modified 4542} Permittee shall maintain records to demonstrate that solid manure has been incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201 and 4570]

Feed Storage and Handling System (N-7321-6)

The following conditions will be placed on the ATC:

- {modified 4455} Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4570]
- {modified 4457} Permittee shall maintain an operating plan/record that requires feed to be pushed within three feet of feedlane fence within two hours of putting out the feed, or use of a feed trough or other structure designed to maintain feed within reach of the animals. [District Rules 2201 and 4570]
- {modified 4459} Permittee shall maintain an operating plan/record of when feeding of total mixed rations began within two hours of grinding and mixing rations. [District Rules 2201 and 4570]

- {modified 4461} Permittee shall maintain records demonstrating grain is/was stored in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 and 4570]
- {modified 4463} Permittee shall maintain records to demonstrate animals are fed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4570]
- {modified 4470} Permittee shall maintain records of the thickness and type of cover used to cover each silage pile. Permittee shall also maintain records of the date of the last delivery of material to each silage pile and the date each pile is covered. [District Rule 2201 & 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201 and 4570]

The permit units are also subject to the recordkeeping requirements of District Rule 4570, *Confined Animal Facilities*, which will be discussed under the Rule 4570 section below.

4. Reporting

No reporting is required to demonstrate compliance with Rule 2201.

F. Ambient Air Quality Analysis (AAQA)

Section 4.14 of District Rule 2201 requires that an AAQA be conducted for the purpose of determining whether a new or modified Stationary Source will cause or make worse a violation of an air quality standard. The District's Technical Services Division conducted the required analysis. Refer to **Appendix H** of this document for the AAQA summary sheet.

The proposed location is in an attainment area for NO_x, CO, and SO_x. As shown by the AAQA summary sheet the proposed equipment will not cause a violation of an air quality standard for NO_x, CO, or SO_x.

The proposed location is in a non-attainment area for the state's PM₁₀ as well as federal and state PM_{2.5} thresholds. As shown by the AAQA summary sheet the proposed equipment will not cause a violation of an air quality standard for PM₁₀ and PM_{2.5}.

Rule 2410 Prevention of Significant Deterioration

As shown in Section VII.C.9 above, this project does not result in a new PSD major source or PSD major modification. No further discussion is required.

Rule 2520 Federally Mandated Operating Permits

Since this facility's potential emissions do not exceed any major source thresholds of Rule 2201, this facility is not a major source, and Rule 2520 does not apply.

Rule 2550 Federally Mandated Preconstruction Review for Major Sources of Air Toxics

The provisions of this rule only apply to applications to construct or reconstruct a major air toxics source with Authority to Construct issued on or after June 28, 1998.

Newly constructed facilities or reconstructed units or sources at existing facilities are subject to preconstruction review requirements if they have the potential to emit hazardous air pollutants (air toxics) in "major" amounts (10 tons or more of an individual pollutant or 25 tons or more of a combination of pollutants) and the new units are not already subject to a standard promulgated under Section 112(d), 112(j), or 112(h) of the Clean Air Act." Facilities or sources subject to Rule 2550 would be subject to stringent air pollution control requirements, referred to as Maximum Achievable Control Technology (MACT).

The federal Clean Air Act (Section 112(b)(1)) lists 189 substances as potential hazardous air pollutants (HAPs). The following table outlines the HAPs expected to be emitted from dairies, and their estimated emission rates, based on the best data currently available:

Hazardous Air Pollutant Emissions from Dairies		
HAP	Emission Rate lb/milk cow-yr	Source
Methanol	1.35	UC Davis - <i>VOC Emission from Dairy Cows and their Excreta</i> , 2005
Carbon disulfide	0.027	Dr. Schmidt - <i>Dairy Emissions using Flux Chambers (Phase I & II)</i> , 2005
Ethylbenzene	0.003	
o-Xylene	0.005	
1,2-Dibromo-3chloropropane	0.011	
1,2,4-Trichlorobenzene	0.025	
Naphthalene	0.012	
Hexachlorobutadiene	0.012	
Formaldehyde	0.005	
Acetaldehyde	0.029	
Chloroform	0.017	California State University Fresno (CSUF) - <i>Monitoring and Modeling of ROG at California Dairies</i> , 2005
Styrene	0.01	Dr. Schmidt - <i>Dairy Emissions using Flux Chambers (Phase I & II)</i> & California State University Fresno (CSUF) - <i>Monitoring and Modeling of ROG at California Dairies</i> , 2005
Vinyl acetate ⁹	0.08	
Toluene ¹⁰	0.162	
Cadmium	0.009	

⁹ 0.01 + 0.07 = 0.08 lbs/hd-yr.

¹⁰ 0.012 + 0.15 = 0.162 lbs/hd-yr.

Hexavalent Chromium	0.004	Air Resources Board's Profile No. 423, Livestock Operations Dust
Nickel	0.026	
Arsenic	0.005	
Cobalt	0.003	
Lead	0.033	
Total	1.828	

Since the proposed dairy is subject to Best Available Control Technology (BACT) emissions control requirements and Rule 4570 mitigation measures, many of the pollutants listed above are expected to be controlled significantly. However, in order to ensure that this evaluation is based on the worst-case scenario, no controls will be factored into the HAPs emissions estimates. Please note that a conclusion that MACT requirements are triggered would necessarily involve consideration of controlled emissions levels. Based on the total emission rate shown in the preceding table, the HAPs emissions calculations for the proposed dairy are summarized in the table below:

HAPs Emissions Calculations						
Category	Number of cows	Emission Rate			Emissions	
			lb/cow-yr ¹¹	=	lb/yr	tons/yr
Milking Cows	2,500	x	1.828	=	4,570	2.29
Dry Cows	400	x	1.123	=	449	0.2
Support Stock	1,550	x	0.786	=	1,218	0.6
Calves (0 - 3 mon)	0	x	0.584	=	0	0
Gasoline Dispensing					222	0.1
Total =					6,459	3.1

As shown above total HAPs emissions are expected to be less than 10 tons per year. The proposed facility will therefore not be a major air toxics source and the provisions of Rule 2550 are not applicable.

Rule 4101 Visible Emissions

Pursuant to Section 4.12, the requirements of this rule do not apply to emissions subject to or specifically exempt from Regulation VIII (Fugitive PM10 Prohibitions).

Pursuant to Rule 8011, Section 4.4, on-field agricultural sources are exempt from the requirements of Regulation VIII.

The proposed project involves only on-field agricultural sources and is therefore exempt from the requirements of Rule 4101.

Rule 4102 Nuisance

Rule 4102 prohibits discharge of air contaminants which could cause injury, detriment, nuisance or annoyance to the public. Public nuisance conditions are not expected as a result of these

¹¹ The emission rate total has been adjusted for each cow category using ratios based on manure production rates.

operations, provided the equipment is well maintained. Therefore, compliance with this rule is expected.

California Health & Safety Code 41700 (Health Risk Assessment)

District Policy APR 1905 – *Risk Management Policy for Permitting New and Modified Sources* specifies that for an increase in emissions associated with a proposed new source or modification, the District perform an analysis to determine the possible impact to the nearest resident or worksite.

An HRA is not required for a project with a total facility prioritization score of less than one. According to the Technical Services Memo for this project (**Appendix H**), the total facility prioritization score including this project was greater than one. Therefore, an HRA was required to determine the short-term acute and long-term chronic exposure from this project.

The cancer risk for this project is shown below:

Units	Prioritization Score	Acute Hazard Index	Chronic Hazard Index	Maximum Individual Cancer Risk	T-BACT Required	Special Permit Requirements
1-5	0.99	0.00	0.00	1.34E-07	No	Yes
2-5	31.55	0.27	0.10	6.46E-06	Yes	Yes
3-4	0.00	0.00	0.00	0.00E+00	No	No
4-3	0.00	0.01	0.00	0.00E+00	No	Yes
Project Totals	32.54	0.28	0.10	6.60E-06		
Facility Totals	32.54	0.28	0.10	6.60E-06		

Notes: No increase in Lagoon emissions

Discussion of T-BACT

BACT for toxic emission control (T-BACT) is required if the cancer risk exceeds one in one million. As demonstrated above, T-BACT is required for emissions units listed below because the HRA indicates that the risk is above the District’s thresholds for triggering T-BACT requirements.

- Cow Housing – New and expanding Freestall barns

For this project T-BACT is triggered for VOC. T-BACT is satisfied with BACT for VOC (see Appendix G); therefore, compliance with the District’s Risk Management Policy is expected.

Rule 4550 Conservation Management Practices (CMP)

This rule applies to agricultural operation sites located within the San Joaquin Valley air basin. The purpose of the rule is to limit fugitive dust emissions from agricultural operation sites. Pursuant to Section 5.1, effective on and after July 1, 2004, an owner/operator shall implement the applicable CMPs selected pursuant to Section 6.2 for each agricultural operation site.

Pursuant to Section 5.2, an owner/operator shall prepare and submit a CMP application for each

agricultural operation site to the APCO for approval.

This facility received District approval for its current CMP plan in 2006. The proposed project does not involve any changes or modifications to the previously approved CMP plan. Continued compliance with the requirements of this rule is therefore expected.

Rule 4570 Confined Animal Facilities (CAF)

This rule applies to Confined Animal Facilities (CAF) located within the San Joaquin Valley Air Basin. The purpose of this rule is to limit emissions of Volatile Organic Compounds (VOC) through the implementation of various mitigation measures for each emissions unit.

The facility was issued ATC permits to implement the requirements of this rule under project N-1110956. All previously selected mitigation measures will be carried over in the Authority to Construct permits issued under this project.

General Condition on all ATCs

- {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the permittee shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

A. Milking Parlor (N-7321-1)

Flush or hose down the milking parlor immediately prior to, immediately after, or during each milking.

- {modified 4484} Permittee shall flush or hose down the milking parlor immediately prior to, immediately after, or during each milking. [District Rules 2201 and 4570]
- {modified 4485} Permittee shall provide verification that the milking parlor is flushed or hosed down immediately prior to, immediately after, or during each milking. [District Rules 2201 and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

B. Cow Housing (N-7321-2)

The following general condition will be included on the cow housing permit.

- {modified 4449} Permittee shall maintain a record of the number of animals of each species and production group at the facility and shall maintain quarterly records of any changes to this information. [District Rules 2201 & 4570]

Freestall Barn Mitigation Measures:

- {modified 4486} Permittee shall pave feedlanes for a width of at least 8 feet along the housing side of the feedlane fence for mature cows and at least 6 feet along the housing side of the feedlane fence for heifers. [District Rules 2201, 4102, and 4570]
- {modified 4489} Permittee shall flush or scrape freestall flush lanes at least three (3) times per day. [District Rules 2201 and 4570] N
- {modified} Permittee shall keep records or maintain an operating plan that requires freestall flush lanes to be flushed or scraped at least three times per day. [Districts Rules 2201 and 4570] N.
-
- {modified 4492} Permittee shall remove manure that is not dry from individual cow freestall beds or rake, harrow, scrape, or grade freestall bedding at least once every seven (7) days. [District Rules 2201, 4102, and 4570]
- {modified 4493} Permittee shall record either of the following: 1) the dates when manure that is not dry is removed from individual cow freestall beds or 2) the dates when the freestall bedding is raked, harrowed, scraped, or graded. [District Rules 2201, 4102, and 4570]

Corral Mitigation Measures

- {modified 4486} Permittee shall pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. [District Rule 2201, 4102 and 4570]
- {modified 4499} Permittee shall inspect water pipes and troughs and repair leaks at least once every seven (7) days. [District Rules 2201 and 4570]
- {modified 4500} Permittee shall maintain records demonstrating that water pipes and troughs are inspected and leaks are repaired at least once every seven (7) days. [District Rules 2201 and 4570]
- {modified 4501} Permittee shall clean manure from corrals at least four (4) times per year with at least sixty (60) days between each cleaning, or permittee shall clean corrals at least once between April and July and at least once between September and December. [District Rules 2201 and 4570]

- {modified 4502} Permittee shall demonstrate that manure from corrals are cleaned at least four (4) times per year with at least sixty (60) days between each cleaning or demonstrate that corrals are cleaned at least once between April and July and at least once between September and December. [District Rules 2201 and 4570]
- Permittee shall implement at least one of the following mitigation measures: 1) slope the surfaces of exercise pens/corrals at least 3% where the available space for each animal is 400 square feet or less and at least 1.5% where the available space for each animal is more than 400 square feet per animal; 2) maintain exercise pens/corrals to ensure proper drainage preventing water from standing more than forty-eight hours; or 3) harrow, rake, or scrape exercise pens/corrals sufficiently to maintain a dry surface except during periods of rainy weather.
- {modified 4511} Shade structures shall be installed in any of the following ways: 1) constructed with a light permeable roofing material; 2) uphill of any slope in the corral; 3) installed so that the structure has a North/South orientation. OR Permittee shall clean manure from under corral shades at least once every fourteen (14) days, when weather permits access into the corral. [District Rules 2201 and 4570] N
- {modified 4555} Permittee shall either 1) maintain sufficient records to demonstrate that exercise pens/corrals are maintained to ensure proper drainage preventing water from standing for more than forty-eight hours; or 2) maintain records of dates when exercise pens/corrals are groomed (i.e., harrowed, raked, or scraped, etc.). [District Rules 2201, 4102, and 4570]
- {modified 4508} Permittee shall scrape, vacuum or flush concrete lanes in corrals at least once every day for mature cows and every seven (7) days for support stock. [District Rules 2201 and 4570]
- {modified 4556} Permittee shall maintain records demonstrating that concrete lanes in corrals are scraped, vacuumed, or flushed at least once every day for mature cows and at least once every seven (7) days for support stock. [District Rules 2201 and 4570]
- Permittee shall manage corrals such that the manure depth in the corral does not exceed twelve (12) inches at any time or point, except for in-corral mounding. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. However, permittee must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible. [District Rules 2201, 4102, and 4570]
- Permittee shall measure and document the depth of manure in the corrals at least once every ninety (90) days. [District Rules 2201, 4102, and 4570]
- {modified 4449} Permittee shall maintain a record of the number of animals of each species and production group at the facility and shall maintain quarterly records of any changes to this information. [District Rules 2201, 4102, and 4570]

- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

C. Liquid Manure Handling System (N-7321-3)

- {modified 4538} Permittee shall remove solids with a solid separator system, prior to the manure entering the lagoon. [District Rules 2201, 4102, and 4570]
- {modified 4550} Permittee shall not allow liquid manure to stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]
- {modified 4551} Permittee shall maintain records to demonstrate liquid manure did not stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]
- {modified 4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

D. Solid Manure Handling System (N-7321-4)

- {modified 4526} Within seventy two (72) hours of removal of solid manure from housing, permittee shall either 1) remove dry manure from the dairy, or 2) cover dry manure outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed twenty-four (24) hours per event. [District Rules 2201 and 4570]
- {modified 4527} Permittee shall keep records of dates when manure is removed from the dairy or permittee shall maintain records to demonstrate that dry manure piles outside the pens are covered with a weatherproof covering from October through May. [District Rules 2201 and 4570]
- {modified 4528} If weatherproof coverings are used, permittee shall maintain records, such as manufacturer warranties or other documentation, demonstrating that the weatherproof covering over dry manure are installed, used, and maintained in accordance with manufacturer recommendations and applicable standards listed in NRCS Field Office Technical Guide Code 313 or 367, or any other applicable standard approved by the APCO, ARB, and EPA. [District Rules 2201 and 4570]
- {modified 4541} Solid manure shall be incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]

- {modified 4542} Permittee shall maintain records to demonstrate that solid manure has been incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]

E. Feed Storage and Handling System (N-7321-6)

- {modified 4454} Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 & 4570]
- {modified 4455} Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 & 4570]
- {modified 4456} Permittee shall push feed so that it is within three feet of feedlane fence within two hours of putting out the feed or use a feed trough or other feeding structure designed to maintain feed within reach of the animals. [District Rules 2201 & 4570]
- {modified 4457} Permittee shall maintain an operating plan or record that requires feed to be pushed within three feet of feedlane fence within two hours of putting out the feed, or use of a feed trough or other structure designed to maintain feed within reach of the animals. [District Rules 2201 & 4570]
- {modified 4458} Permittee shall begin feeding total mixed rations within two hours of grinding and mixing rations. [District Rules 2201 & 4570]
- {modified 4459} Permittee shall maintain an operating plan or record of when feeding of total mixed rations began within two hours of grinding and mixing rations. [District Rules 2201 & 4570]
- {modified 4460} Permittee shall store grain in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 & 4570]
- {modified 4461} Permittee shall maintain records demonstrating grain is/was stored in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 & 4570]
- {modified 4462} Permittee shall feed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. [District Rules 2201 and 4570]
- {modified 4463} Permittee shall maintain records to demonstrate animals are fed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4570]

Silage

- {modified 4469} Permittee shall cover all silage piles, except for the area where feed is being removed from the pile, with a plastic tarp that is at least five (5) mils (0.005 inches) thick, multiple plastic tarps with a cumulative thickness of at least 5 mils (0.005 inches), or an oxygen barrier film covered with a UV resistant material. Silage piles shall be covered within seventy-two (72) hours of last delivery of material to the pile. Sheets of material used to cover silage shall overlap so that silage is not exposed where the sheets meet. [District Rules 2201 & 4570]
- {modified 4470} Permittee shall maintain records of the thickness and type of cover used to cover each silage pile. Permittee shall also maintain records of the date of the last delivery of material to each silage pile and the date each pile is covered. [District Rules 2201 & 4570]
- {modified 4471} Permittee shall select and implement one of the following mitigation measures for building each silage pile at the facility: Option 1) build the silage pile such that the average bulk density is at least 44 lb/cu ft for corn silage and 40 lb/cu ft for other silage types, as measured in accordance with Section 7.11 of District Rule 4570; Option 2) Adjust filling parameters when creating the silage pile to achieve an average bulk density of at least 44 lb/cu ft for corn silage and at least 40 lb/cu ft for other silage types as determined using a District-approved spreadsheet; or Option 3) build silage piles using crops harvested with the applicable minimum moisture content, maximum Theoretical Length of Chop (TLC), and roller opening identified in District Rule 4570, Table 4.1, 1.d and manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. Records of the option chosen as a mitigation measure for building each silage pile shall be maintained. [District Rules 2201 & 4570]
- {modified 4472} For each silage pile that Option 1 (Measured Bulk Density) is chosen as a mitigation measure for building the pile, records of the measured bulk density shall be maintained. [District Rules 2201 & 4570]
- {modified 4473} For each silage pile that Option 2 (Bulk Density Determined by Spreadsheet) is chosen as a mitigation measure for building the pile, records of the filling parameters entered into the District-approved spreadsheet to determine the bulk density shall be maintained. [District Rules 2201 & 4570]
- {modified 4474} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall harvest corn used for the pile at an average moisture content of at least 65% and harvest other silage crops for the pile at an average moisture content of at least 60%. [District Rules 2201 & 4570]
- {modified 4475} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records of the average percent moisture of crops harvested for silage shall be maintained. [District Rules 2201 & 4570]
- {modified 4476} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall adjust

setting of equipment used to harvest crops for the pile to incorporate the following parameters for Theoretical Length of Chop (TLC) and roller opening, as applicable: 1) Corn with no processing: TLC not exceeding 1/2 inch, 2) Processed Corn: TLC not exceeding 3/4 inch and roller opening of 1-4 mm, 3) Alfalfa/Grass: TLC not exceeding 1.0 inch, 4) Other silage crops: TLC not exceeding 1/2 inch. [District Rules 2201 & 4570]

- {modified 4477} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records that equipment used to harvest crops for the pile was set to the required TLC and roller opening for the type of crop harvested shall be maintained. [District Rules 2201 & 4570]
- {modified 4478} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rules 2201 & 4570]
- {modified 4479} For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall maintain a plan or record that requires that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rules 2201 & 4570]
- {modified 4480} Permittee shall select and implement at least two of the following mitigation measures for management of silage piles at the facility: Option 1) manage silage piles such that only one silage pile has an uncovered face and the total exposed surface area is less than 2,150 square feet, or manage multiple uncovered silage piles such that the total exposed surface area of all uncovered silage piles is less than 4,300 square feet; Option 2) use a shaver/facer to remove silage from the silage pile, or shall use another method to maintain a smooth vertical surface on the working face of the silage pile; or Option 3) inoculate silage with homolactic lactic acid bacteria in accordance with manufacturer recommendations to achieve a concentration of at least 100,000 colony forming units per gram of wet forage, apply propionic acid, benzoic acid, sorbic acid, sodium benzoate, or potassium sorbate at the rate specified by the manufacturer to reduce yeast counts when forming silage piles, or apply other additives at rates that have been demonstrated to reduce alcohol concentrations in silage and/or VOC emissions from silage and have been approved by the District and EPA. Records of the options chosen for managing each silage pile shall be maintained. [District Rules 2201 & 4570]
- {modified 4481} If Option 1 (Limiting Exposed Area of Silage) is chosen as a mitigation measure for managing silage piles, the permittee shall calculate and record the maximum (largest part of pile) total exposed area of each silage pile. Records of the maximum calculated area shall be maintained. [District Rules 2201 & 4570]
- {modified 4482} For each silage pile that Option 2 (Shaver/Facer or Smooth Face) is chosen as a mitigation measure for building the pile, the permittee shall maintain records that a shaver/facer was used to remove silage from the pile or shall visually inspect the pile at least daily to verify that the working face was smooth and maintain records of the visual inspections. [District Rules 2201 & 4570]

- {modified 4483} For each silage pile that Option 3 (Silage Additives) is chosen as a mitigation measure for building the pile, records shall be maintained of the type additive (e.g. inoculants, preservative, other District & EPA-approved additive), the quantity of the additive applied to the pile, and a copy of the manufacturer's instructions for application of the additive. [District Rules 2201 & 4570]

According to the District's inspection records, this facility has been operating in compliance with Rule 4570 requirements. Since the proposed modifications do not fundamentally alter the nature of the facility's operations, continued compliance with the requirements of this rule is expected.

California Health & Safety Code 42301.6 (School Notice)

The District has verified that this site is not located within 1,000 feet of a school. Therefore, pursuant to California Health and Safety Code 42301.6, a school notice is not required.

California Environmental Quality Act (CEQA)

The County of Stanislaus (County) is the public agency having principal responsibility for approving the project. As such, the County served as the Lead Agency (CCR §15367). In approving the project, the Lead Agency prepared and adopted a Mitigated Negative Declaration. The Lead agency filed a Notice of Determination, stating that the environmental document was adopted pursuant to the provisions of CEQA and concluding that the project would not have a significant effect on the environment.

The District is a Responsible Agency for the project because of its discretionary approval power over the project via its Permits Rule (Rule 2010) and New Source Review Rule (Rule 2201), (CCR §15381). As a Responsible Agency the District complies with CEQA by considering the environmental document prepared by the Lead Agency, and by reaching its own conclusion on whether and how to approve the project (CCR §15096).

The District has considered the Lead Agency's environmental document. Furthermore, the District has conducted an engineering evaluation of the project, this document, which demonstrates that Stationary Source emissions from the project would be below the District's thresholds of significance for criteria pollutants. Thus, the District finds that through a combination of project design elements, compliance with applicable District rules and regulations, and compliance with District air permit conditions, project specific stationary source emissions will have a less than significant impact on air quality. The District does not have authority over any of the other project impacts and has, therefore, determined that no additional findings are required (CEQA Guidelines §15096(h)).

Indemnification Agreement/Letter of Credit Determination

According to District Policy APR 2010 (CEQA Implementation Policy), when the District is the Lead or Responsible Agency for CEQA purposes, an indemnification agreement and/or a letter of credit may be required. The decision to require an indemnity agreement and/or a letter of credit is based on a case-by-case analysis of a particular project's potential for litigation risk, which in turn may be based on a project's potential to generate public concern, its potential for

significant impacts, and the project proponent's ability to pay for the costs of litigation without a letter of credit, among other factors.

Although the project is located at a potential facility of public concern (Dairy), the criteria pollutant emissions and toxic air contaminant emissions associated with the proposed project are not significant. Therefore, an Indemnification Agreement and/or a Letter of Credit will not be required for this project in the absence of expressed public concern.

IX. Recommendation

Compliance with all applicable rules and regulations is expected. Pending a successful NSR Public Noticing period, issue ATCs N-7321-1-5, -2-5, -3-4, -4-3 & -6-2 subject to the permit conditions on the attached draft ATCs in **Appendix A**.

X. Billing Information

Annual Permit Fees			
Permit Number	Fee Schedule	Fee Description	Annual Fee
N-7321-1-5	3020-06	Milking Operation	\$128
N-7321-2-5	3020-06	Cow Housing	\$128
N-7321-3-4	3020-06	Liquid Manure Handling System	\$128
N-7321-4-3	3020-06	Solid Manure Handling Operation	\$128
N-7321-6-2	3020-06	Feed Storage and Handling Operation	\$128

Appendixes

- A: Draft ATC Permits
- B: Current Permits to Operate N-7321-1-4, -2-4, -3-3, -4-2 & -6-1
- C: Project Site Plan
- D: Emissions Calculations
- E: BACT Calculations
- F: BACT Guidelines
- G: BACT Analysis
- H: RMR and AAQA Summary
- I: Anaerobic Lagoon Design Check Spreadsheets
- J: QNEC

Appendix A

Draft Authority to Construct Permits

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT
ISSUANCE DATE: DRAFT

PERMIT NO: N-7321-1-5

LEGAL OWNER OR OPERATOR: S & S DAIRY INC.
MAILING ADDRESS: 5870 CROWS LANDING RD
MODESTO, CA 95358

LOCATION: 348 E MONTE VISTA AVE
CERES, CA 95366

EQUIPMENT DESCRIPTION:
MODIFICATION OF 1,400 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR: INCREASE MILK COWS FROM 1,400 TO 2,500 MILK COWS. POST PROJECT DESCRIPTION WILL BE: 2,500 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented concurrently with ATC N-7321-2-5. [District Rule 2201]
2. {3215} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
3. {3216} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
4. {3658} This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

DRAFT

Arnaud Marjolle, Director of Permit Services

N-7321-1-5: Feb 3 2020 3:07PM -- GILLR : Joint Inspection NOT Required

5. {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
6. Permittee shall flush or hose milk parlor immediately prior to, immediately after, or during each milking. [District Rules 2201 & 4570]
7. Permittee shall provide verification that milk parlors are flushed or hosed prior to, immediately after, or during each milking. [District Rules 2201 & 4570]
8. {4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: N-7321-2-5

LEGAL OWNER OR OPERATOR: S & S DAIRY INC.
MAILING ADDRESS: 5870 CROWS LANDING RD
MODESTO, CA 95358

LOCATION: 348 E MONTE VISTA AVE
CERES, CA 95366

EQUIPMENT DESCRIPTION:

MODIFICATION OF COW HOUSING - 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK (HEIFERS, CALVES AND BULLS); CONSTRUCT FIVE NEW FREESTALL BARN WITH FLUSH SYSTEM AND INCREASE HERD SIZE FROM 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK TO 2,500 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 2,900 MATURE COWS (MILK AND DRY); 1,550 SUPPORT STOCK. POST PROJECT DESCRIPTION WILL BE: COW HOUSING - 2,500 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 2,900 MATURE COWS (MILK AND DRY); 1,550 SUPPORT STOCK (HEIFERS, CALVES AND BULLS); 7 FREESTALL BARN WITH FLUSH SYSTEM

CONDITIONS

1. {3215} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. {3216} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. {3658} This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

N-7321-2-5 : Feb 3 2020 3:08PM - GILLR : Joint Inspection NOT Required

4. {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201, 4102 and 4570]
6. Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201, 4102 and 4570]
7. For Freestall Barns #1, #3, #4, #5 and #6 the feedlanes and walkways shall be constructed of concrete. [District Rules 2201, 4102 and 4570]
8. For Freestall Barns #1, #3, #4, #5 and #6 permittee shall flush the feed lanes and walkways for the mature cows (milk and dry cows) at least four times per day and flushing lanes and walkways for the remaining animals once per day . [District Rules 2201, 4102 and 4570]
9. For Freestall Barns #1, #3, #4, #5 and #6 shall maintain records sufficient to demonstrate that lanes are flushed at least four times per day for the mature cows and at least once per day for the support stock. [District Rules 2201, 4102 and 4570]
10. Permittee shall scrape exercise pen and corral surfaces every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rules 2201 and 4102]
11. Permittee shall maintain sufficient records to demonstrate that exercise pen and corral surfaces are scraped every two weeks using a pull-type scraper during morning hours, except when prevented by wet conditions. [District Rules 2201 and 4102]
12. Permittee shall pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. [District Rules 2201 4102 and 4570]
13. Permittee shall flush or scrape freestall flush lanes at least three (3) times per day. [District Rules 2201 and 4570]
14. Permittee shall keep records or maintain an operating plan that requires freestall flush lanes to be flushed or scraped at least three times per day. [District Rules 2201 and 4570]
15. Permittee shall remove manure that is not dry from individual cow freestall beds or shall rake, harrow, scrape, or grade freestall bedding at least once every seven (7) days. [District Rules 2201 and 4570]
16. Permittee shall record either of the following: 1) the dates when manure that is not dry is removed from individual cow freestall beds or 2) the dates when the freestall bedding is raked, harrowed, scraped, or graded. [District Rules 2201 and 4570]
17. Permittee shall inspect water pipes and troughs and repair leaks at least once every seven (7) days. [District Rules 2201 and 4570]
18. Permittee shall maintain records demonstrating that water pipes and troughs are inspected and leaks are repaired at least once every seven (7) days. [District Rules 2201 and 4570]
19. Permittee shall clean manure from corrals at least four (4) times per year with at least sixty (60) days between each cleaning, or permittee shall clean corrals at least once between April and July and at least once between September and December. [District Rules 2201 and 4570]
20. Permittee shall demonstrate that manure from corrals are cleaned at least four (4) times per year with at least sixty (60) days between each cleaning or demonstrate that corrals are cleaned at least once between April and July and at least once between September and December. [District Rules 2201 and 4570]

DRAFT
CONDITIONS CONTINUE ON NEXT PAGE

21. Permittee shall implement at least one of the following corral mitigation measures: 1) slope the surface of the corrals at least 3% where the available space for each animal is 400 square feet or less and shall slope the surface of the corrals at least 1.5% where the available space for each animal is more than 400 square feet per animal; 2) maintain corrals to ensure proper drainage preventing water from standing more than forty-eight hours; or 3) harrow, rake, or scrape pens sufficiently to maintain a dry surface except during periods of rainy weather. [District Rules 2201, 4102 and 4570]
22. Permittee shall either 1) maintain sufficient records to demonstrate that corrals are maintained to ensure proper drainage preventing water from standing for more than forty-eight hours or 2) maintain records of dates pens are groomed (i.e., harrowed, raked, or scraped, etc.). [District Rules 2201 and 4570]
23. Permittee shall scrape, vacuum or flush concrete lanes in corrals at least once every day for mature cows and every seven (7) days for support stock. [District Rules 2201 and 4570]
24. Permittee shall maintain records demonstrating that concrete lanes in corrals are scraped, vacuumed, or flushed at least once every day for mature cows and at least once every seven (7) days for support stock. [District Rules 2201 and 4570]
25. Shade structures shall be installed in any of the following ways: 1) constructed with a light permeable roofing material; 2) uphill of any slope in the corral; 3) installed so that the structure has a North/South orientation. OR Permittee shall clean manure from under corral shades at least once every fourteen (14) days, when weather permits access into the corral. [District Rules 2201 and 4570]
26. If permittee has selected to comply using shades constructed with a light permeable roofing material, then permittee shall maintain records, such as design specifications, demonstrating that the shade structures are equipped with such roofing material or if permittee has selected to comply by cleaning the manure from under the corral shades, then permittee shall maintain records demonstrating that manure is cleaned from under the shades at least once every fourteen (14) days, as long as weather permits access to corrals. [District Rules 2201 and 4570]
27. Permittee shall manage corrals such that the manure depth in the corral does not exceed twelve (12) inches at any time or point, except for in-corral mounding. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. However, permittee must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible. [District Rules 2201 and 4570]
28. Permittee shall measure and document the depth of manure in the corrals at least once every ninety (90) days. [District Rules 2201 and 4570]
29. Permittee shall maintain a record of the number of animals of each species and production group at the facility and shall maintain quarterly records of any changes to this information. [District Rules 2201 and 4570]
30. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: N-7321-3-4

LEGAL OWNER OR OPERATOR: S & S DAIRY INC.
MAILING ADDRESS: 5870 CROWS LANDING RD
MODESTO, CA 95358

LOCATION: 348 E MONTE VISTA AVE
CERES, CA 95366

EQUIPMENT DESCRIPTION:

MODIFICATION OF LIQUID MANURE HANDLING SYSTEM CONSISTING OF SETTLING BASIN(S); 390' X 275' X 30', 290' X 285' X 14' AND 350' X 285' X 14' WASTE STORAGE LAGOON/PONDS; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION; INCREASE IN LIQUID MANURE DUE TO INCREASE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5 AND OPERATE LIQUID MANURE STORAGE IN AN ANAEROBIC TREATMENT SYSTEM AS PER ANAEROBIC TREATMENT LAGOON SPECIFICATION. POST PROJECT DESCRIPTION WILL BE: LIQUID MANURE HANDLING SYSTEM CONSISTING OF SETTLING BASIN(S); 390' X 275' X 30', 290' X 285' X 14' AND 350' X 285' X 14' WASTE STORAGE LAGOON/PONDS; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented concurrently with ATC N-7321-2-5. [District Rule 2201]
2. {3215} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
3. {3216} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
4. {3658} This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

N-7321-3-4 Feb 3 2020 3:08PM - GILLR : Joint Inspection NOT Required

5. {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
6. Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 and 4102]
7. Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4102]
8. All liquid manure shall be treated in an anaerobic treatment lagoon/waste liquid storage system that is designed and operated according to the Natural Resources Conservation Service (NRCS) Field Office Technical Guide No. 359. [District Rules 2201 and 4102]
9. Permittee shall maintain design specifications and calculations, including minimum treatment volume (MTV) and hydraulic retention time (HRT) calculations, demonstrating that the anaerobic treatment lagoon system meets the requirements listed in the NRCS Field Office Technical Guide No. 359. [District Rules 2201 and 4102]
10. Permittee shall remove solids with a solid separator system, prior to the manure entering the lagoon/storage ponds. [District Rules 2201 and 4570]
11. Any liquid manure applied to land shall have been treated in an anaerobic treatment lagoon/waste liquid storage system that is designed and operated according to the NRCS Field Office Technical Guide No. 359. [District Rules 2201 and 4102]
12. Permittee shall maintain records to demonstrate that liquid manure applied to land has been treated in an anaerobic treatment system that is designed and operated according to the NRCS Field Office Technical Guide No. 359. [District Rule 2201]
13. Permittee shall not allow liquid manure to stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]
14. Permittee shall maintain records to demonstrate liquid manure did not stand in the fields for more than twenty-four (24) hours after irrigation. [District Rules 2201 and 4570]
15. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201, 4102, and 4570]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: N-7321-4-3

LEGAL OWNER OR OPERATOR: S & S DAIRY INC.
MAILING ADDRESS: 5870 CROWS LANDING RD
MODESTO, CA 95358

LOCATION: 348 E MONTE VISTA AVE
CERES, CA 95366

EQUIPMENT DESCRIPTION:

MODIFICATION OF SOLID MANURE HANDLING CONSISTING OF MANURE STOCK PILES; SOLID MANURE APPLICATION TO LAND AND HAULED OFFSITE; INCREASE IN SOLID MANURE DUE TO CHANGE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5. POST PROJECT DESCRIPTION WILL BE: SOLID MANURE HANDLING CONSISTING OF MANURE STOCK PILES; SOLID MANURE APPLICATION TO LAND AND HAULED OFFSITE

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented concurrently with ATC N-7321-2-5. [District Rule 2201]
2. {3215} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
3. {3216} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
4. {3658} This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

Arnaud Marjolle, Director of Permit Services

N-7321-4-3 Feb 3 2020 3:06PM - GILLR - Joint Inspection NOT Required

5. {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
6. Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 and 4102]
7. Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4102]
8. Solid manure shall be incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]
9. Permittee shall maintain records to demonstrate that solid manure has been incorporated into the soil within two hours of land application. [District Rules 2201 and 4570]
10. Within seventy two (72) hours of removal of solid manure from housing, permittee shall either 1) remove dry manure from the facility, or 2) cover dry manure outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed twenty-four (24) hours per event. [District Rules 2201 & 4570]
11. {4527} Permittee shall keep records of dates when manure is removed from the facility or permittee shall maintain records to demonstrate that dry manure piles outside the pens are covered with a weatherproof covering from October through May. [District Rule 4570]
12. Permittee shall maintain records, such as manufacturer warranties or other documentation, demonstrating that the weatherproof covering over separated solids are installed, used, and maintained in accordance with manufacturer recommendations and applicable standards listed in NRCS Field Office Technical Guide Code 313 or 367, or any other applicable standard approved by the APCO, ARB, and EPA. [District Rules 2201 & 4570]
13. Permittee shall incorporate all solid manure within seventy-two (72) hours of land application. [District Rules 2201 & 4570]
14. Permittee shall maintain records to demonstrate that all solid manure has been incorporated within seventy-two (72) hours of land application. [District Rules 2201 & 4570]
15. {4453} Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: N-7321-6-2

LEGAL OWNER OR OPERATOR: S & S DAIRY INC.
MAILING ADDRESS: 5870 CROWS LANDING RD
MODESTO, CA 95358

LOCATION: 348 E MONTE VISTA AVE
CERES, CA 95366

EQUIPMENT DESCRIPTION:

MODIFICATION OF FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs AND SILAGE PILES:
INCREASE IN TOTAL MIXED RATION DUE TO CHANGE IN HERD PROFILE AS AUTHORIZED BY ATC N-7321-2-5.
POST PROJECT DESCRIPTION WILL BE: FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs
AND SILAGE PILES

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented concurrently with ATC N-7321-2-5. [District Rule 2201]
2. {3215} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
3. {3216} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
4. {3658} This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO

Arnaud Marjolle, Director of Permit Services

N-7321-6-2 - Feb 3 2020 3:08PM - GILLR - Joint Inspection NOT Required

5. {4452} If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
6. Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rules 2201 and 4570]
7. Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 and 4570]
8. Permittee shall push feed so that it is within three feet of feedlane fence within two hours of putting out the feed or use a feed trough or other feeding structure designed to maintain feed within reach of the animals. [District Rules 2201 and 4570]
9. Permittee shall maintain an operating plan or record that requires feed to be pushed within three feet of feedlane fence within two hours of putting out the feed, or use of a feed trough or other structure designed to maintain feed within reach of the animals. [District Rules 2201 and 4570]
10. Permittee shall begin feeding total mixed rations within two hours of grinding and mixing rations. [District Rules 2201 and 4570]
11. Permittee shall maintain an operating plan or record of when feeding of total mixed rations began within two hours of grinding and mixing rations. [District Rules 2201 and 4570]
12. Permittee shall store grain in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 and 4570]
13. Permittee shall maintain records demonstrating grain is/was stored in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rules 2201 and 4570]
14. Permittee shall feed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. [District Rules 2201 & 4570]
15. Permittee shall maintain records to demonstrate animals are fed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rules 2201 & 4570]
16. For bagged silage/feedstuff, permittee shall utilize a sealed feed storage system (e.g., ag bag). [District Rules 2201 and 4570]
17. Permittee shall cover all silage piles, except for the area where feed is being removed from the pile, with a plastic tarp that is at least five (5) mils (0.005 inches) thick, multiple plastic tarps with a cumulative thickness of at least 5 mils (0.005 inches), or an oxygen barrier film covered with a UV resistant material. Silage piles shall be covered within seventy-two (72) hours of last delivery of material to the pile. Sheets of material used to cover silage shall overlap so that silage is not exposed where the sheets meet. [District Rules 2201 and 4570]
18. Permittee shall maintain records of the thickness and type of cover used to cover each silage pile. Permittee shall also maintain records of the date of the last delivery of material to each silage pile and the date each pile is covered. [District Rules 2201 and 4570]

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. Permittee shall select and implement one of the following mitigation measures for building each silage pile at the facility: Option 1) build the silage pile such that the average bulk density is at least 44 lb/cu ft for corn silage and 40 lb/cu ft for other silage types, as measured in accordance with Section 7.11 of District Rule 4570; Option 2) Adjust filling parameters when creating the silage pile to achieve an average bulk density of at least 44 lb/cu ft for corn silage and at least 40 lb/cu ft for other silage types as determined using a District-approved spreadsheet; or Option 3) build silage piles using crops harvested with the applicable minimum moisture content, maximum Theoretical Length of Chop (TLC), and roller opening identified in District Rule 4570, Table 4.1, 1.d and manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. Records of the option chosen as a mitigation measure for building each silage pile shall be maintained. [District Rules 2201 and 4570]
20. For each silage pile that Option 1 (Measured Bulk Density) is chosen as a mitigation measure for building the pile, records of the measured bulk density shall be maintained. [District Rules 2201 and 4570]
21. For each silage pile that Option 2 (Bulk Density Determined by Spreadsheet) is chosen as a mitigation measure for building the pile, records of the filling parameters entered into the District-approved spreadsheet to determine the bulk density shall be maintained. [District Rules 2201 and 4570]
22. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall harvest corn used for the pile at an average moisture content of at least 65% and harvest other silage crops for the pile at an average moisture content of at least 60%. [District Rules 2201 and 4570]
23. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records of the average percent moisture of crops harvested for silage shall be maintained. [District Rules 2201 and 4570]
24. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall adjust setting of equipment used to harvest crops for the pile to incorporate the following parameters for Theoretical Length of Chop (TLC) and roller opening, as applicable: 1) Corn with no processing: TLC not exceeding 1/2 inch, 2) Processed Corn: TLC not exceeding 3/4 inch and roller opening of 1-4 mm, 3) Alfalfa/Grass: TLC not exceeding 1.0 inch, 4) Other silage crops: TLC not exceeding 1/2 inch. [District Rules 2201 and 4570]
25. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records that equipment used to harvest crops for the pile was set to the required TLC and roller opening for the type of crop harvested shall be maintained. [District Rules 2201 and 4570]
26. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rules 2201 and 4570]
27. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall maintain a plan that requires that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rules 2201 and 4570]
28. Permittee shall select and implement at least two of the following mitigation measures for management of silage piles at the facility: Option 1) manage silage piles such that only one silage pile has an uncovered face and the total exposed surface area is less than 2,150 square feet, or manage multiple uncovered silage piles such that the total exposed surface area of all uncovered silage piles is less than 4,300 square feet; Option 2) use a shaver/facer to remove silage from the silage pile, or shall use another method to maintain a smooth vertical surface on the working face of the silage pile; or Option 3) inoculate silage with homolactic lactic acid bacteria in accordance with manufacturer recommendations to achieve a concentration of at least 100,000 colony forming units per gram of wet forage, apply propionic acid, benzoic acid, sorbic acid, sodium benzoate, or potassium sorbate at the rate specified by the manufacturer to reduce yeast counts when forming silage piles, or apply other additives at rates that have been demonstrated to reduce alcohol concentrations in silage and/or VOC emissions from silage and have been approved by the District and EPA. Records of the options chosen for managing each silage pile shall be maintained. [District Rules 2201 and 4570]

29. If Option 1 (Limiting Exposed Area of Silage) is chosen as a mitigation measure for managing silage piles, the permittee shall calculate and record the maximum (largest part of pile) total exposed area of each silage pile. Records of the maximum calculated area shall be maintained. [District Rules 2201 and 4570]
30. For each silage pile that Option 2 (Shaver/Facer or Smooth Face) is chosen as a mitigation measure for managing the pile, the permittee shall maintain records that a shaver/facer was used to remove silage from the pile or shall visually inspect the pile at least daily to verify that the working face was smooth and maintain records of the visual inspections. [District Rules 2201 and 4570]
31. For each silage pile that Option 3 (Silage Additives) is chosen as a mitigation measure for managing the pile, records shall be maintained of the type additive (e.g. inoculants, preservative, other District & EPA-approved additive), the quantity of the additive applied to the pile, and a copy of the manufacturers instructions for application of the additive. [District Rules 2201 and 4570]
32. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rules 2201 and 4570]

DRAFT

Appendix B

**Current Permits to Operate
(N-7321-1-5, -2-5, -3-4, -4-3, -6-2)**

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-7321-1-4

EXPIRATION DATE: 01/31/2019

EQUIPMENT DESCRIPTION:

1,400 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR

PERMIT UNIT REQUIREMENTS

1. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]
4. If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Permittee shall flush or hose milk parlor immediately prior to, immediately after, or during each milking. [District Rule 4570]
6. Permittee shall provide verification that milk parlors are flushed or hosed prior to, immediately after, or during each milking. [District Rule 4570]
7. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-7321-2-4

EXPIRATION DATE: 01/31/2019

EQUIPMENT DESCRIPTION:

COW HOUSING - 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK (HEIFERS, CALVES AND BULLS)

PERMIT UNIT REQUIREMENTS

1. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]
4. If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Permittee shall pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. [District Rule 4570]
6. Permittee shall flush or scrape freestall flush lanes at least three (3) times per day. [District Rule 4570]
7. Permittee shall keep records or maintain an operating plan that requires freestall flush lanes to be flushed or scraped at least three times per day. [District Rule 4570]
8. Permittee shall remove manure that is not dry from individual cow freestall beds or shall rake, harrow, scrape, or grade freestall bedding at least once every seven (7) days. [District Rule 4570]
9. Permittee shall record either of the following: 1) the dates when manure that is not dry is removed from individual cow freestall beds or 2) the dates when the freestall bedding is raked, harrowed, scraped, or graded. [District Rule 4570]
10. Permittee shall inspect water pipes and troughs and repair leaks at least once every seven (7) days. [District Rule 4570]
11. Permittee shall maintain records demonstrating that water pipes and troughs are inspected and leaks are repaired at least once every seven (7) days. [District Rule 4570]
12. Permittee shall clean manure from corrals at least four (4) times per year with at least sixty (60) days between each cleaning, or permittee shall clean corrals at least once between April and July and at least once between September and December. [District Rule 4570]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. Permittee shall demonstrate that manure from corrals are cleaned at least four (4) times per year with at least sixty (60) days between each cleaning or demonstrate that corrals are cleaned at least once between April and July and at least once between September and December. [District Rule 4570]
14. Permittee shall implement at least one of the following corral mitigation measures: 1) slope the surface of the corrals at least 3% where the available space for each animal is 400 square feet or less and shall slope the surface of the corrals at least 1.5% where the available space for each animal is more than 400 square feet per animal; 2) maintain corrals to ensure proper drainage preventing water from standing more than forty-eight hours; or 3) harrow, rake, or scrape pens sufficiently to maintain a dry surface except during periods of rainy weather. [District Rule 4570]
15. Permittee shall either 1) maintain sufficient records to demonstrate that corrals are maintained to ensure proper drainage preventing water from standing for more than forty-eight hours or 2) maintain records of dates pens are groomed (i.e., harrowed, raked, or scraped, etc.). [District Rule 4570]
16. Permittee shall scrape, vacuum or flush concrete lanes in corrals at least once every day for mature cows and every seven (7) days for support stock. [District Rule 4570]
17. Permittee shall maintain records demonstrating that concrete lanes in corrals are scraped, vacuumed, or flushed at least once every day for mature cows and at least once every seven (7) days for support stock. [District Rule 4570]
18. Shade structures shall be installed in any of the following ways: 1) constructed with a light permeable roofing material; 2) uphill of any slope in the corral; 3) installed so that the structure has a North/South orientation. OR Permittee shall clean manure from under corral shades at least once every fourteen (14) days, when weather permits access into the corral. [District Rule 4570]
19. If permittee has selected to comply using shades constructed with a light permeable roofing material, then permittee shall maintain records, such as design specifications, demonstrating that the shade structures are equipped with such roofing material or if permittee has selected to comply by cleaning the manure from under the corral shades, then permittee shall maintain records demonstrating that manure is cleaned from under the shades at least once every fourteen (14) days, as long as weather permits access to corrals. [District Rule 4570]
20. Permittee shall manage corrals such that the manure depth in the corral does not exceed twelve (12) inches at any time or point, except for in-corral mounding. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. However, permittee must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible. [District Rule 4570]
21. Permittee shall measure and document the depth of manure in the corrals at least once every ninety (90) days. [District Rule 4570]
22. Permittee shall maintain a record of the number of animals of each species and production group at the facility and shall maintain quarterly records of any changes to this information. [District Rule 4570]
23. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-7321-3-3

EXPIRATION DATE: 01/31/2019

EQUIPMENT DESCRIPTION:

LIQUID MANURE HANDLING SYSTEM CONSISTING OF TWO SETTLING BASINS; ONE LAGOON; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION

PERMIT UNIT REQUIREMENTS

1. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]
4. If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Permittee shall remove solids with a solid separator system, prior to the manure entering the lagoon. [District Rule 4570]
6. Permittee shall not allow liquid manure to stand in the fields for more than twenty-four (24) hours after irrigation. [District Rule 4570]
7. Permittee shall maintain records to demonstrate liquid manure did not stand in the fields for more than twenty-four (24) hours after irrigation. [District Rule 4570]
8. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-7321-4-2

EXPIRATION DATE: 01/31/2019

EQUIPMENT DESCRIPTION:

SOLID MANURE HANDLING CONSISTING OF MANURE HAULED OFFSITE

PERMIT UNIT REQUIREMENTS

1. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]
4. If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Within seventy two (72) hours of removal of solid manure from housing, permittee shall either 1) remove dry manure from the facility, or 2) cover dry manure outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed twenty-four (24) hours per event. [District Rule 4570]
6. Permittee shall keep records of dates when manure is removed from the facility or permittee shall maintain records to demonstrate that dry manure piles outside the pens are covered with a weatherproof covering from October through May. [District Rule 4570]
7. If weatherproof coverings are used, permittee shall maintain records, such as manufacturer warranties or other documentation, demonstrating that the weatherproof covering over dry manure are installed, used, and maintained in accordance with manufacturer recommendations and applicable standards listed in NRCS Field Office Technical Guide Code 313 or 367, or any other applicable standard approved by the APCO, ARB, and EPA. [District Rule 4570]
8. Permittee shall incorporate all solid manure within seventy-two (72) hours of land application. [District Rule 4570]
9. Permittee shall maintain records to demonstrate that all solid manure has been incorporated within seventy-two (72) hours of land application. [District Rule 4570]
10. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-7321-6-1

EXPIRATION DATE: 01/31/2019

EQUIPMENT DESCRIPTION:

FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARN(S) AND SILAGE PILE(S)

PERMIT UNIT REQUIREMENTS

1. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 1070]
2. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 1070]
3. This permit does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [Public Resources Code 21000-21177: California Environmental Quality Act]
4. If a licensed veterinarian or a certified nutritionist determines that any VOC mitigation measure will be required to be suspended as a detriment to animal health or necessary for the animal to molt, the owners/operators must notify the District in writing within forty-eight (48) hours of the determination including the duration and the specific health condition requiring the mitigation measure to be suspended. If the situation is expected to exist longer than a thirty-day (30) period, the owner/operator shall submit a new emission mitigation plan designating a mitigation measure to be implemented in lieu of the suspended mitigation measure. [District Rule 4570]
5. Permittee shall feed all animals according to National Research Council (NRC) guidelines. [District Rule 4570]
6. Permittee shall maintain records of feed content, formulation, and quantity of feed additive utilized, to demonstrate compliance with National Research Council (NRC) guidelines. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rule 4570]
7. Permittee shall push feed so that it is within three feet of feedlane fence within two hours of putting out the feed or use a feed trough or other feeding structure designed to maintain feed within reach of the animals. [District Rule 4570]
8. Permittee shall maintain an operating plan or record that requires feed to be pushed within three feet of feedlane fence within two hours of putting out the feed, or use of a feed trough or other structure designed to maintain feed within reach of the animals. [District Rule 4570]
9. Permittee shall begin feeding total mixed rations within two hours of grinding and mixing rations. [District Rule 4570]
10. Permittee shall maintain an operating plan or record of when feeding of total mixed rations began within two hours of grinding and mixing rations. [District Rule 4570]
11. Permittee shall store grain in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rule 4570]
12. Permittee shall maintain records demonstrating grain is/was stored in a weatherproof storage structure or under a weatherproof covering from October through May. [District Rule 4570]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Permittee shall feed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. [District Rule 4570]
14. Permittee shall maintain records to demonstrate animals are fed steam-flaked, dry rolled, cracked or ground corn or other steam-flaked, dry rolled, cracked or ground cereal grains. Records such as feed company guaranteed analyses (feed tags), ration sheets, or feed purchase records may be used to meet this requirement. [District Rule 4570]
15. For bagged silage/feedstuff, permittee shall utilize a sealed feed storage system (e.g., ag bag). [District Rule 4570]
16. Permittee shall cover all silage piles, except for the area where feed is being removed from the pile, with a plastic tarp that is at least five (5) mils (0.005 inches) thick, multiple plastic tarps with a cumulative thickness of at least 5 mils (0.005 inches), or an oxygen barrier film covered with a UV resistant material. Silage piles shall be covered within seventy-two (72) hours of last delivery of material to the pile. Sheets of material used to cover silage shall overlap so that silage is not exposed where the sheets meet. [District Rule 4570]
17. Permittee shall maintain records of the thickness and type of cover used to cover each silage pile. Permittee shall also maintain records of the date of the last delivery of material to each silage pile and the date each pile is covered. [District Rule 4570]
18. Permittee shall select and implement one of the following mitigation measures for building each silage pile at the facility: Option 1) build the silage pile such that the average bulk density is at least 44 lb/cu ft for corn silage and 40 lb/cu ft for other silage types, as measured in accordance with Section 7.11 of District Rule 4570; Option 2) Adjust filling parameters when creating the silage pile to achieve an average bulk density of at least 44 lb/cu ft for corn silage and at least 40 lb/cu ft for other silage types as determined using a District-approved spreadsheet; or Option 3) build silage piles using crops harvested with the applicable minimum moisture content, maximum Theoretical Length of Chop (TLC), and roller opening identified in District Rule 4570, Table 4.1, 1.d and manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. Records of the option chosen as a mitigation measure for building each silage pile shall be maintained. [District Rule 4570]
19. For each silage pile that Option 1 (Measured Bulk Density) is chosen as a mitigation measure for building the pile, records of the measured bulk density shall be maintained. [District Rule 4570]
20. For each silage pile that Option 2 (Bulk Density Determined by Spreadsheet) is chosen as a mitigation measure for building the pile, records of the filling parameters entered into the District-approved spreadsheet to determine the bulk density shall be maintained. [District Rule 4570]
21. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall harvest corn used for the pile at an average moisture content of at least 65% and harvest other silage crops for the pile at an average moisture content of at least 60%. [District Rule 4570]
22. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records of the average percent moisture of crops harvested for silage shall be maintained. [District Rule 4570]
23. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall adjust setting of equipment used to harvest crops for the pile to incorporate the following parameters for Theoretical Length of Chop (TLC) and roller opening, as applicable: 1) Corn with no processing: TLC not exceeding 1/2 inch, 2) Processed Corn: TLC not exceeding 3/4 inch and roller opening of 1-4 mm, 3) Alfalfa/Grass: TLC not exceeding 1.0 inch, 4) Other silage crops: TLC not exceeding 1/2 inch. [District Rule 4570]
24. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, records that equipment used to harvest crops for the pile was set to the required TLC and roller opening for the type of crop harvested shall be maintained. [District Rule 4570]
25. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall manage silage material delivery such that the thickness of the layer of un-compacted material delivered on top of the pile is no more than six (6) inches. [District Rule 4570]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. For each silage pile that Option 3 (Moisture, TLC, Roller Opening, & Material Delivery) is chosen as a mitigation measure for building the pile, the permittee shall maintain a plan that requires that the thickness of the layer of uncompacted material delivered on top of the pile is no more than six (6) inches. [District Rule 4570]
27. Permittee shall select and implement at least two of the following mitigation measures for management of silage piles at the facility: Option 1) manage silage piles such that only one silage pile has an uncovered face and the total exposed surface area is less than 2,150 square feet, or manage multiple uncovered silage piles such that the total exposed surface area of all uncovered silage piles is less than 4,300 square feet; Option 2) use a shaver/facer to remove silage from the silage pile, or shall use another method to maintain a smooth vertical surface on the working face of the silage pile; or Option 3) inoculate silage with homolactic lactic acid bacteria in accordance with manufacturer recommendations to achieve a concentration of at least 100,000 colony forming units per gram of wet forage, apply propionic acid, benzoic acid, sorbic acid, sodium benzoate, or potassium sorbate at the rate specified by the manufacturer to reduce yeast counts when forming silage piles, or apply other additives at rates that have been demonstrated to reduce alcohol concentrations in silage and/or VOC emissions from silage and have been approved by the District and EPA. Records of the options chosen for managing each silage pile shall be maintained. [District Rule 4570]
28. If Option 1 (Limiting Exposed Area of Silage) is chosen as a mitigation measure for managing silage piles, the permittee shall calculate and record the maximum (largest part of pile) total exposed area of each silage pile. Records of the maximum calculated area shall be maintained. [District Rule 4570]
29. For each silage pile that Option 2 (Shaver/Facer or Smooth Face) is chosen as a mitigation measure for managing the pile, the permittee shall maintain records that a shaver/facer was used to remove silage from the pile or shall visually inspect the pile at least daily to verify that the working face was smooth and maintain records of the visual inspections. [District Rule 4570]
30. For each silage pile that Option 3 (Silage Additives) is chosen as a mitigation measure for managing the pile, records shall be maintained of the type additive (e.g. inoculants, preservative, other District & EPA-approved additive), the quantity of the additive applied to the pile, and a copy of the manufacturers instructions for application of the additive. [District Rule 4570]
31. Permittee shall keep and maintain all records for a minimum of five (5) years and shall make records available to the APCO and EPA upon request. [District Rule 4570]

These terms and conditions are part of the Facility-wide Permit to Operate.

Appendix C
Project Site Plan

Appendix D

Emissions Calculations

Pre-Project Facility Information

- Does this facility house Holstein or Jersey cows?
Most facilities house Holstein cows unless explicitly stated on the PTO or application.
- Does the facility have an anaerobic treatment lagoon?
- Does the facility land apply liquid manure?
Answering "yes" assumes worst case.
- Does the facility land apply solid manure?
Answering "yes" assumes worst case.
- Is any scraped manure sent to a lagoon/storage pond?
Answering "yes" assumes worst case.

Pre-Project Herd Size							
Herd	Flushed Freestalls	Scraped Freestalls	Flushed Corrals	Scraped Corrals	Total # of Animals		
Milk Cows	1,400				1,400		
Dry Cows			200		200		
Support Stock (Heifers, Calves, and Bulls)			1,400		1,400		
Large Heifers					0		
Medium Heifers					0		
Small Heifers					0		
Bulls					0		
	Calf Hutches				Calf Corrals		Total # of Calves
	Aboveground Flushed	Aboveground Scraped	On-Ground Flushed	On-Ground Scraped	Flushed	Scraped	
Calves							0

Total Herd Summary	
Total Milk Cows	1,400
Total Mature Cows	1,600
Support Stock (Heifers, Calves, and Bulls)	1,400
Total Calves	0
Total Dairy Head	3,000

Pre-Project Silage Information			
Feed Type	Max # Open Piles	Max Height (ft)	Max Width (ft)
Corn	1	30	140
Alfalfa	1	26	90
Wheat	1	26	90

Post-Project Facility Information

- Does this facility house Holstein or Jersey cows?
Most facilities house Holstein cows unless explicitly stated on the PTO or application.
- Does the facility have an anaerobic treatment lagoon?
- Does the facility land apply liquid manure?
Answering "yes" assumes worst case.
- Does the facility land apply solid manure?
Answering "yes" assumes worst case.
- Is any scraped manure sent to a lagoon/storage pond?
Answering "yes" assumes worst case.
- Does this project result in any new lagoon/storage pond(s) or an increase in surface area for any existing lagoon/storage pond(s)?

Post-Project Herd Size							
Herd	Flushed Freestalls	Scraped Freestalls	Flushed Corrals	Scraped Corrals	Total # of Animals		
Milk Cows	2,500				2,500		
Dry Cows	400				400		
Support Stock (Heifers, Calves, and Bulls)	1,250		300		1,550		
Large Heifers					0		
Medium Heifers					0		
Small Heifers					0		
Bulls					0		
	Calf Hutches				Calf Corrals		Total # of Calves
	Aboveground Flushed	Aboveground Scraped	On-Ground Flushed	On-Ground Scraped	Flushed	Scraped	
Calves							0

Total Herd Summary	
Total Milk Cows	2,500
Total Mature Cows	2,900
Support Stock (Heifers, Calves, and Bulls)	1,550
Total Calves	0
Total Dairy Head	4,450

Post-Project Silage Information			
Feed Type	Max # Open Piles	Max Height (ft)	Max Width (ft)
Corn	1	20	110
Alfalfa			
Wheat	1	20	90

VOC Mitigation Measures and Control Efficiencies

Milking Parlor				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	VOC Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Enteric Emissions Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	(D) Feed according to NRC guidelines	10%	10%
Total Control Efficiency			10%	10%
Milking Parlor Floor Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	(D) Feed according to NRC guidelines	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	(D) Flush or hose milk parlor immediately prior to, immediately after, or during each milking. Note: If selected for dairies > 999 milk cows, control efficiency is already included in EF.	0%	0%
Total Control Efficiency			10%	10%

Cow Housing				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	VOC Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Enteric Emissions Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
Total Control Efficiency			10%	10%
Corrals/Pens Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Inspect water pipes and troughs and repair leaks at least once every seven days. Note: If selected for dairies > 999 milk cows, CE is already included in EF.	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Dairies: Clean manure from corrals at least four times per year with at least 60 days between cleaning, or clean corrals at least once between April and July and at least once between September and December. Note: If selected for dairies > 999 milk cows, CE is already included in EF. Note: No additional control given for increased cleaning frequency (e.g. BACT requirement). Heifer/Calf Ranches: Scrape corrals twice a year with at least 90 days between cleanings, excluding in-coral mounds. Note: No additional control given for increased cleaning frequency (e.g. BACT requirement).	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Scrape, vacuum, or flush concrete lanes in corrals at least once every day for mature cows and every seven days for support stock, or clean concrete lanes such that the depth of manure does not exceed 12 inches at any point or time. Note: No additional control given for increased cleaning frequency (e.g. BACT requirement).	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Implement one of the following: 1) slope the surface of the corrals at least 3% where the available space for each animal is 400 sq ft or less and slope the surface of the corrals at least 1.5% where the available space for each animal is more than 400 sq ft; 2) maintain corrals to ensure proper drainage preventing water from standing more than 48 hrs; 3) harrow, rake, or scrape pens sufficiently to maintain a dry surface. Note: If selected for dairies > 999 milk cows, CE already included in EF.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Install shade structures such that they are constructed with a light permeable roofing material. Note: If selected for dairies > 999 milk cows, the control efficiency will be 5% since the EF used includes a partial control for this measure.	5%	5%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Install all shade structures uphill of any slope in the corral. Note: If selected for dairies > 999 milk cows, the control efficiency will be 5% since the EF used includes a partial control for this measure.		
<input type="checkbox"/>	<input type="checkbox"/>	Clean manure from under corral shades at least once every 14 days, when weather permits access into corral. Note: If selected for dairies > 999 milk cows, the control efficiency will be 5% since the EF used includes a partial control for this measure.		
<input type="checkbox"/>	<input type="checkbox"/>	Install shade structure so that the structure has a North/South orientation. Note: If selected for dairies > 999 milk cows, the control efficiency will be 5% since the EF used includes a partial control for this measure.		
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Manage corrals such that the manure depth in the corral does not exceed 12 inches at any time or point, except for in-coral mounding. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. The manure facility must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible. Note: If selected for dairies > 999 milk cows, control efficiency is already included in EF.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Knockdown fence line manure build-up prior to it exceeding a height of 12 inches at any time or point. Manure depth may exceed 12 inches when corrals become inaccessible due to rain events. The facility must resume management of the manure depth of 12 inches or lower immediately upon the corral becoming accessible.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Use lime or a similar absorbent material in the corral according to the manufacturer's recommendation to minimize moisture in the corrals.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Apply thymol to the corral soil in accordance with the manufacturer's recommendation.	0%	0%
Total Control Efficiency			23.05%	23.05%
Bedding Mitigations				

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	Use non-manure-based bedding and non-separated solids based bedding for at least 90% of the bedding material, by weight, for freestalls (e.g. rubber mats, almond shells, sand, or waterbeds).	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	For a large dairy (1,000 milk cows or larger) or a heifer/calf ranch - Remove manure that is not dry from individual cow freestall beds or rake, harrow, scrape, or grade freestall bedding at least once every 7 days.	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	(D) For a medium dairy only (500 to 999 milk cows) - Remove manure that is not dry from individual cow freestall beds or rake, harrow, scrape, or grade freestall bedding at least once every 14 days.	0%	0%
Total Control Efficiency			19.00%	19.00%
Lanes Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Pave feedlanes, where present, for a width of at least 8 feet along the corral side of the feedlane fence for milk and dry cows and at least 6 feet along the corral side of the feedlane for heifers. Note: No control efficiency at this time.	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Dairies: Flush, scrape, or vacuum freestall flush lanes immediately prior to or after, or during each milking, or flush or scrape freestall flush lanes at least 3 times per day. Heifer/Calf Ranches: Vacuum, scrape, or flush freestalls at least once every seven days.	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	(D) Have no animals in exercise pens or corrals at any time.	0%	0%
Total Control Efficiency			19.00%	19.00%

Liquid Manure Handling				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	VOC Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Lagoons/Storage Ponds Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	Use phototropic lagoon	0%	0%
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Use an anaerobic treatment lagoon designed according to NRCS Guideline No. 359	0%	40%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Remove solids from the waste system with a solid separator system, prior to the waste entering the lagoon. Note: If selected for dairies > 999 milk cows, control efficiency is already included in EF.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Maintain lagoon pH between 6.5 and 7.5	0%	0%
Total Control Efficiency			10.00%	46.00%
Liquid Manure Land Application Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Only apply liquid manure that has been treated with an anaerobic or aerobic treatment lagoon, aerobic lagoon, or digester system	0%	40%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Allow liquid manure to stand in the fields for no more than 24 hours after irrigation. Note: If selected for dairies > 999 milk cows, control efficiency is already included in EF.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	Apply liquid/slurry manure via injection with drag hose or similar apparatus	0%	0%
Total Control Efficiency			10.00%	46.00%

Solid Manure Handling				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	VOC Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Solid Manure Storage Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	LARGE CAFO ONLY: Within 72 hours of removal from housing, either a) remove dry manure from the facility, or b) cover dry manure outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed 24 hours per event.	10%	10%
Total Control Efficiency			19.00%	19.00%
Separated Solids Piles Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	LARGE CAFO ONLY: Within 72 hours of removal from the drying process, either a) remove separated solids from the facility, or b) cover separated solids outside the housing with a weatherproof covering from October through May, except for times when wind events remove the covering, not to exceed 24 hours per event.	0%	0%
Total Control Efficiency			10.00%	10.00%
Solid Manure Land Application Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Incorporate all solid manure within 72 hours of land application. Note: If selected for dairies > 999 milk cows, control efficiency is already included in EF. Note: No additional control given for rapid manure incorporation (e.g. BACT requirement).	0%	0%
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Only apply solid manure that has been treated with an anaerobic treatment lagoon, aerobic lagoon or digester system.	0%	40%
<input type="checkbox"/>	<input type="checkbox"/>	Apply no solid manure with a moisture content of more than 50%	0%	0%
Total Control Efficiency			10.00%	46.00%

Silage and TMR				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	VOC Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Com/Alfalfa/Wheat Silage Mitigations				

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<p>1. Utilize a sealed feed storage system (e.g. Ag-Bag) for bagged silage, or</p> <p>2. Cover the surface of silage piles, except for the area where feed is being removed from the pile, with a plastic tarp that is at least 5 mils thick (0.005 inches), multiple plastic tarps with a cumulative thickness of at least 5 mils (0.005 inches), or an oxygen barrier film covered with a UV resistant material within 72 hours of last delivery of material to the pile, and implement one of the following:</p> <p>a) build silage piles such that the average bulk density is at least 44 lb/cu-ft for corn silage and 40 lb/cu-ft for other silage types, as measured in accordance with Section 7,10 of Rule 4570,</p> <p>b) when creating a silage pile, adjust filling parameters to assure a calculated average bulk density of at least 44 lb/cu-ft for corn silage and at least 40 lb/cu-ft for other silage types, using a spreadsheet approved by the District,</p> <p>c) harvest silage crop at > or = 65% moisture for corn; and >= 60% moisture for alfalfa/grass and other silage crops; manage silage material delivery such that no more than 6 inches of materials are uncompacted on top of the pile; and incorporate the applicable Theoretical Length of Chop (TLC) and roller opening for the crop being harvested.</p> <p>For dairies - implement <u>two</u> of the following: For heifer/calf ranches - implement <u>one</u> of the following:</p> <p>Manage Exposed Silage. a) manage silage piles such that only one silage pile has an uncovered face and the uncovered face has a total exposed surface area of less than 2,150 sq. ft., or b) manage multiple uncovered silage piles such that the total exposed surface area of all silage piles is less than 4,300 sq ft.</p> <p>Maintain Silage Working Face. a) use a shaver/facer to remove silage from the silage pile, or b) maintain a smooth vertical surface on the working face of the silage pile</p> <p>Silage Additive: a) inoculate silage with homolactic acid bacteria in accordance with manufacturer recommendations to achieve a concentration of at least 100,000 colony forming units per gram of wet forage or apply propionic acid, benzoic acid, sorbic acid, sodium benzoate, or potassium sorbate at a rate specified by the manufacturer to reduce yeast counts when forming silage pile; or b) apply other additives at specified rates that have been demonstrated to reduce alcohol concentrations in silage and/or VOC emissions from silage and have been approved by the District and EPA.</p>	39.0%	39.0%
Total Control Efficiency*			39.00%	39.00%

*Assumes 25% control for density mitigation measures and 10% each for the two optional measures, resulting in an overall control of 39%. The same conservative control efficiency will be applied to the sealed feed storage system (Ag-Bag).

		TMR Mitigations		
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	(D) Push feed so that it is within 3 feet of feedlane fence within 2 hrs of putting out the feed or use a feed trough or other feeding structure designed to maintain feed within reach of the cows.	10%	10%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	(D) Begin feeding total mixed rations within 2 hrs of grinding and mixing rations. Note: If selected for dairies > 999 milk cows, control efficiency already included in EF.	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed steam-flaked, dry rolled, cracked or ground corn or other ground cereal grains.	10%	10%
<input type="checkbox"/>	<input type="checkbox"/>	Remove uneaten wet feed from feed bunks within 24 hrs after the end of a rain event.	0%	0%
<input type="checkbox"/>	<input type="checkbox"/>	(D) For total mixed rations that contain at least 30% by weight of silage, feed animals total mixed rations that contain at least 45% moisture.	0%	0%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines. Note: If selected for dairies, control efficiency already included in EF.	0%	0%
Total Control Efficiency			19.00%	19.00%

Ammonia Mitigation Measures and Control Efficiencies

Milking Parlor				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	NH3 Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Milking Parlor Floor Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
Total Control Efficiency			28%	28%

Cow Housing				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	NH3 Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Corrals/Pens Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Clean manure from corrals at least four times per year with at least 60 days between cleaning, or clean corrals at least once between April and July and at least once between September and December. OR Use lime or a similar absorbent material in the corral according to the manufacturer's recommendation to minimize moisture in the corrals. OR Apply thymol to the corral soil in accordance with the manufacturer's recommendation.	50%	50%
Total Control Efficiency			64%	64%
Bedding Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Use non-manure-based bedding and non-separated solids based bedding for at least 90% of the bedding material, by weight, for freestalls (e.g. rubber mats, almond shells, sand, or waterbeds). OR For a large dairy only (1,000 milk cows or larger) - Remove manure that is not dry from individual cow freestall beds or rake, harrow, scrape, or grade freestall bedding at least once every 7 days. OR For a medium dairy only (500 to 999 milk cows) - Remove manure that is not dry from individual cow freestall beds or rake, harrow, scrape, or grade freestall bedding at least once every 14 days.	47.7%	47.7%
Total Control Efficiency			62.34%	62.34%
Lanes Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
Total Control Efficiency			28%	28%

Liquid Manure Handling				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	NH3 Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Lagoons/Storage Ponds Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Use phototropic lagoon OR Remove solids from the waste system with a solid separator system, prior to the waste entering the lagoon.	80%	80%
Total Control Efficiency			85.6%	85.6%
Liquid Manure Land Application Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Only apply liquid manure that has been treated with an anaerobic treatment lagoon	0%	42%
Total Control Efficiency			28.00%	58.24%

Solid Manure Handling				
Measure Proposed?		Mitigation Measure(s) per Emissions Point	NH3 Control Efficiency (%)	
Pre-Project	Post-Project		Pre-Project	Post-Project
Solid Manure Land Application Mitigations				
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Feed according to NRC guidelines	28%	28%
<input type="checkbox"/>	<input type="checkbox"/>	Incorporate all solid manure within 72 hours of land application. AND Only apply solid manure that has been treated with an anaerobic treatment lagoon, aerobic lagoon or digester system. AND Apply no solid manure with a moisture content of more than 50%	0%	0%
Total Control Efficiency			28.00%	28.00%

Pre-Project PM10 Control Efficiencies and Emission Factors

Housing Name(s) or #s	Type of Housing	Type of cow	Total # of cows in Each Housing Structure(s)	Maximum Design Capacity of Each Structure	Uncontrolled EF (lb/hd-yr)	Shaded Corrals	Downwind Shelterbelts	Upwind Shelterbelts	No exercise pens, non-manure bedding	No exercise pens, manure bedding	Fibrous layer	Bi-weekly scraping Corrals/Pens	Sprinkling Corrals/Pens	Feed Young Stock Near Dusk	Controlled EF (lb/hd-yr)
1	Freestall Barn #5	milk cows	800	800	1.370										1.37
2	Freestall Barn #6	milk cows	600	600	1.370										1.37
3	Corral #1 & #2	support stock	875	875	10.550										10.55
4	Shade Barn #1	support stock	200	200	1.370										1.37
5	Shade Barn #5	dry cows	100	100	5.460	16.7%									4.55
6	Shade Barn #5-A	dry cows	100	100	5.460	16.7%									4.55
7	Shade Barn #6-B	support stock	125	125	10.550	8.3%									9.67
8	Calf Hutches	calves	200	200	0.343										0.34
9															
10															
11															
12															
13															
14															
15															
16															
17															
18															
19															
20															
21															
22															
23															
24															
25															
26															
27															
28															
29															
30															
31															
32															
33															
34															
35															
36															
37															
38															
39															
40															
														Pre-Project Total # of Cows	3,000

Post-Project PM10 Mitigation Measures

Post-Project PM10 Mitigation Measures														
Housing Name(s) or #s	Type of Housing	Type of cow	Total # of cows in Each Housing Structure(s)	Maximum Design Capacity of Each Structure	# of Combined Housing Structures in row	Shaded Corrals	Downwind Shelterbelts	Upwind Shelterbelts	No exercise pens, non-manure bedding	No exercise pens, manure bedding	Fibrous layer	Bi-weekly scraping Corrals/Pens	Sprinkling Corrals/Pens	Feed Young Stock Near Dusk
1	Freestall Barn #5	milk cows	1,100	1,100	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2	Freestall Barn #6	milk cows	800	800	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3	Freestall Barn #7	support stock	950	950	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4	Shade Barn #1	support stock	300	300	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5	Freestall Barn #1	dry cows	200	200	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6	Freestall Barn #2-A	dry cows	100	100	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7	Freestall Barn #2-B	dry cows	100	100	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
11						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
12						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
13						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
14						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
16						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
17						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
18						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
19						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
21						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
22						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
23						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
27						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
28						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
29						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
30						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
31						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
32						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
33						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
34						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
35						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
36						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
37						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
38						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
39						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
40						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Post-Project PM10 Mitigation Measures for New Housing Units at an Expanding Dairy

Housing Name(s) or #s	Type of Housing	Type of cow	Total # of cows in Each Housing Structure(s)	Maximum Design Capacity of Each Structure	# of Combined Housing Structures in row	Shaded Corrals	Downwind Shelterbelts	Upwind Shelterbelts	No exercise pens, non-manure bedding	No exercise pens, manure bedding	Fibrous layer	Bi-weekly scraping Corrals/Pens	Sprinkling Corrals/Pens	Feed Young Stock Near Dusk
1	Freestall Barn #3	support stock	300	300	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2	Freestall Barn #4	milk cows	600	600	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
11						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
12						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
13						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
14						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Post-Project Total # of Cows			4,450			[The post-project total includes 3,550 dairy cows already on-site and 900 new cows from the expansion.]								

Pre-Project Potential to Emit - Cow Housing

Pre-Project Potential to Emit - Cow Housing												
Housing Name(s) or #s	Type of Cow	# of Cows	Controlled VOC EF (lb/hd-yr)	Controlled NH3 EF (lb/hd-yr)	Controlled PM10 EF (lb/hd-yr)	VOC (lb/day)	VOC (lb/yr)	NH3 (lb/day)	NH3 (lb/yr)	PM10 (lb/day)	PM10 (lb/yr)	
1	Freestall Barn #5	milk cows	800	9.86	21.13	1.37	21.6	7,888	46.3	16,903	3.0	1,096
2	Freestall Barn #6	milk cows	600	9.86	21.13	1.37	16.2	5,916	34.7	12,677	2.3	822
3	Corral #1 & #2	support stock	875	4.27	5.54	10.55	10.2	3,736	13.3	4,844	25.3	9,231
4	Shade Barn #1	support stock	200	4.27	5.54	1.37	2.3	854	3.0	1,107	0.8	274
5	Shade Barn #5	dry cows	100	5.57	10.71	4.55	1.5	557	2.9	1,071	1.2	455
6	Shade Barn #6-A	dry cows	100	5.57	10.71	4.55	1.5	557	2.9	1,071	1.2	455
7	Shade Barn #6-B	support stock	125	4.27	5.54	9.67	1.5	534	1.9	692	3.3	1,209
8	Calf Hutches	calves	200	0.78	0.90	0.34	0.4	156	0.5	181	0.2	69
9												
10												
11												
12												
13												
14												
15												
16												
17												
18												
19												
20												
21												
22												
23												
24												
25												
26												
27												
28												
29												
30												
31												
32												
33												
34												
35												
36												
37												
38												
39												
40												
Pre-Project Total # of Cows		3,000					55.2	20,198	105.5	38,546	37.3	13,611

Pre-Project Totals						
Total # of Cows	VOC (lb/day)	VOC (lb/yr)	NH3 (lb/day)	NH3 (lb/yr)	PM10 (lb/day)	PM10 (lb/yr)
3,000	55.2	20,198	105.5	38,546	37.3	13,611

Calculations:
 Annual PE 1 for each pollutant (lb/yr) = Controlled EF (lb/hd-yr) x # of cows (hd)
 Daily PE 1 for each pollutant (lb/day) = [Controlled EF (lb/hd-yr) x # of cows (hd)] ÷ 365 (day/yr)

Post-Project Potential to Emit - Cow Housing

Post-Project Potential to Emit - Cow Housing												
Housing Name(s) or #s	Type of Cow	# of Cows	Controlled VOC EF (lb/hd-yr)	Controlled NH3 EF (lb/hd-yr)	Controlled PM10 EF (lb/hd-yr)	VOC (lb/day)	VOC (lb/yr)	NH3 (lb/day)	NH3 (lb/yr)	PM10 (lb/day)	PM10 (lb/yr)	
1	Freestall Barn #5	milk cows	1,100	9.86	21.13	1.05	29.7	10,846	63.7	23,241	3.2	1,153
2	Freestall Barn #6	milk cows	800	9.86	21.13	1.05	21.6	7,888	46.3	16,903	2.3	838
3	Freestall Barn #7	support stock	950	4.27	5.54	1.05	11.1	4,057	14.4	5,259	2.7	996
4	Shade Barn #1	support stock	300	4.27	5.54	1.05	3.5	1,281	4.6	1,661	0.9	314
5	Freestall Barn #1	dry cows	200	5.57	10.71	1.05	3.1	1,114	5.9	2,142	0.6	210
6	Freestall Barn #2-A	dry cows	100	5.57	10.71	1.05	1.5	557	2.9	1,071	0.3	105
7	Freestall Barn #2-B	dry cows	100	5.57	10.71	1.05	1.5	557	2.9	1,071	0.3	105
8												
9												
10												
11												
12												
13												
14												
15												
16												
17												
18												
19												
20												
21												
22												
23												
24												
25												
26												
27												
28												
29												
30												
31												
32												
33												
34												
35												
36												
37												
38												
39												
40												
Post-Project # of Cows (non-expansion)		3,550					72.0	26,300	140.7	51,348	10.3	3,721

Post-Project Potential to Emit - Cow Housing: New Housing Units at an Expanding Dairy												
Housing Name(s) or #s	Type of Cow	# of Cows	Controlled VOC EF (lb/hd-yr)	Controlled NH3 EF (lb/hd-yr)	Controlled PM10 EF (lb/hd-yr)	VOC (lb/day)	VOC (lb/yr)	NH3 (lb/day)	NH3 (lb/yr)	PM10 (lb/day)	PM10 (lb/yr)	
1	Freestall Barn #3	support stock	300	4.27	5.54	1.05	3.5	1,281	4.6	1,661	0.9	314
2	Freestall Barn #4	milk cows	600	9.86	21.13	1.05	16.2	5,916	34.7	12,677	1.7	629
3												
4												
5												
6												
7												
8												
9												
10												
11												
12												
13												
14												
Total # of Cows From Expansion		900					19.7	7,197	39.3	14,338	2.6	943

Post-Project Totals						
Total # of Cows	VOC (lb/day)	VOC (lb/yr)	NH3 (lb/day)	NH3 (lb/yr)	PM10 (lb/day)	PM10 (lb/yr)
4,450	91.7	33,497	180.0	65,686	12.9	4,664

Calculations:

Annual PE 2 for each pollutant (lb/yr) = Controlled EF (lb/hd-yr) x # of cows (hd)
 Daily PE2 for each pollutant (lb/day) = [Controlled EF (lb/hd-yr) x # of cows (hd)] ÷ 365 (day/yr)

Pre-Project Potential to Emit (PE1)

Pre-Project Herd Size					
Herd	Flushed Freestalls	Scraped Freestalls	Flushed Corrals	Scraped Corrals	Total # of Animals
Milk Cows	1,400	0	0	0	1,400
Dry Cows	0	0	200	0	200
Support Stock (Heifers, Calves and Bulls)	0	0	1,400	0	1,400
Large Heifers	0	0	0	0	0
Medium Heifers	0	0	0	0	0
Small Heifers	0	0	0	0	0
Bulls	0	0	0	0	0
Calf Hutches					
	Aboveground		On-Ground		Total # of Calves
	Flushed	Scraped	Flushed	Scraped	
Calves	0	0	0	0	0

Silage Information				
Feed Type	Maximum # Open Piles	Maximum Height (ft)	Maximum Width (ft)	Open Face Area (ft ²)
Corn	1	30	140	3,212
Alfalfa	1	26	90	1,863
Wheat	1	26	90	1,863

Milking Parlor				
Cow	VOC		NH3	
	lb/day	lb/yr	lb/day	lb/yr
Milk Cows	1.5	560	0.5	192

Cow Housing						
Cow	VOC		NH3		PM10	
	lb/day	lb/yr	lb/day	lb/yr	lb/day	lb/yr
Total	55.2	20,198	105.5	38,546	37.3	13,611

Liquid Manure Handling						
Cow	VOC		NH3		H2S*	
	lb/day	lb/yr	lb/day	lb/yr	lb/day	lb/yr
Milk Cows	9.3	3,402	29.1	10,626	0.8	295
Dry Cows	0.7	266	2.1	768	0.1	24
Support Stock (Heifers, Calves and Bulls)	3.9	1,428	7.6	2,758	0.1	49
Large Heifers	0.0	0	0.0	0	0	0
Medium Heifers	0.0	0	0.0	0	0	0
Small Heifers	0.0	0	0.0	0	0	0
Calves	0.0	0	0.0	0	0	0
Bulls	0.0	0	0.0	0	0	0
Total	13.9	5,096	38.8	14,152	1	368

Solid Manure Handling				
Cow	VOC		NH3	
	lb/day	lb/yr	lb/day	lb/yr
Milk Cows	1.8	658	10.9	3,962
Dry Cows	0.1	52	0.8	286
Support Stock (Heifers, Calves and Bulls)	0.8	280	2.9	1,050
Large Heifers	0.0	0	0.0	0
Medium Heifers	0.0	0	0.0	0
Small Heifers	0.0	0	0.0	0
Calves	0.0	0	0.0	0
Bulls	0.0	0	0.0	0
Total	2.7	990	14.6	5,298

Feed Handling and Storage		
	Daily PE (lb-VOC/day)	Annual PE (lb-VOC/yr)
Corn Emissions	20.0	7,299
Alfalfa Emissions	2.9	1,066
Wheat Emissions	14.7	5,353
TMR	66.1	24,139
Total	103.7	37,856

Total Daily Pre-Project Potential to Emit (lb/day)							
Permit	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0.0	0.0	0.0	0.0	1.5	0.5	0.0
Cow Housing	0.0	0.0	37.3	0.0	55.2	105.5	0.0
Liquid Manure	0.0	0.0	0.0	0.0	13.9	38.8	1.0
Solid Manure	0.0	0.0	0.0	0.0	2.7	14.6	0.0
Feed Handling	0.0	0.0	0.0	0.0	103.7	0.0	0.0
Total	0.0	0.0	37.3	0.0	177.0	159.4	1.0

Total Annual Pre-Project Potential to Emit (lb/yr)							
Permit	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0	0	0	0	560	192	0
Cow Housing	0	0	13,611	0	20,198	38,546	0
Liquid Manure	0	0	0	0	5,096	14,152	368
Solid Manure	0	0	0	0	990	5,298	0
Feed Handling	0	0	0	0	37,856	0	0
Total	0	0	13,611	0	64,700	58,188	368

Calculations for milking parlor:

Annual PE = (# milk cows) x (EF1 lb-pollutant/hd-yr)

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Calculations for cow housing:

See detailed calculations under Cow Housing Calculations worksheet.

Calculations for liquid manure and solid manure handling:

Annual PE = [(# milk cows) x (EF1 lb-pollutant/hd-yr)] + [(# dry cows) x (EF1 lb-pollutant/hd-yr)] + [(# large heifers) x (EF1 lb-pollutant/hd-yr)] + [(# medium heifers) x (EF1 lb-pollutant/hd-yr)] + [(# small heifers) x (EF1 lb-pollutant/hd-yr)] + [(# calves) x (EF1 lb-pollutant/hd-yr)] + [(# bulls) x (EF1 lb-pollutant/hd-yr)]

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

The H2S emission factor is assumed to be 10% of the NH3 lagoon/storage pond(s) emission factor, for each respective herd size.

Calculations for silage emissions:

Annual PE = (EF1) x (area ft²) x (0.0929 m²/ft²) x (8,760 hr/yr) x (60 min/hr) x 2.20E-9 lb/μg

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Calculation for TMR emissions:

Annual PE = (# cows) x (EF1) x (0.658 m²) x (525,600 min/yr) x (2.20E-9 lb/μg)

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Quotas are not included in TMR calculation.

*Since there will be no change to the lagoons/storage ponds surface area, no change in H2S emissions is expected. Therefore, it will be assumed that PE1 for H2S emissions is equal to PE2 for H2S emissions.

Major Source Emissions (lb/yr)					
Permit	NOx	SOx	PM10	CO	VOC
Milk Parlor	0	0	0	0	0
Cow Housing	0	0	0	0	0
Liquid Manure	0	0	0	0	2,452
Solid Manure	0	0	0	0	0
Feed Handling	0	0	0	0	0
Total	0	0	0	0	2,452

Post-Project Potential to Emit (PE2)

Post-Project Herd Size							
Herd	Flushed Freestalls	Scraped Freestalls	Flushed Corrals	Scraped Corrals	Total # of Animals		
Milk Cows	2,500	0	0	0	2,500		
Dry Cows	400	0	0	0	400		
Support Stock (Heifers, Calves, and Bulls)	1,250	0	300	0	1,550		
Large Heifers	0	0	0	0	0		
Medium Heifers	0	0	0	0	0		
Small Heifers	0	0	0	0	0		
Bulls	0	0	0	0	0		
Calf Hutches							
Calf Corrals							
	Aboveground Flushed	Aboveground Scraped	On-Ground Flushed	On-Ground Scraped	Flushed	Scraped	Total # of Calves
Calves	0	0	0	0	0	0	0

Silage Information				
Feed Type	Maximum # Open Piles	Maximum Height (ft)	Maximum Width (ft)	Open Face Area (ft ²)
Corn	1	20	110	1,642
Alfalfa	0	0	0	
Wheat	1	20	90	1,384

Milking Parlor				
Cow	VOC		NH3	
	lb/day	lb/yr	lb/day	lb/yr
Milk Cows				
Total	2.7	1,000	0.9	342

Cow Housing					
	VOC		NH3		PM10
	lb/day	lb/yr	lb/day	lb/yr	lb/day
Total	91.7	33,497	180.0	65,686	12.9

Liquid Manure Handling						
Cow	VOC		NH3		H2S	
	lb/day	lb/yr	lb/day	lb/yr	lb/day	lb/yr
Milk Cows	10.0	3,650	33.6	12,250	0.8	295
Dry Cows	0.9	316	2.7	992	0.1	24
Support Stock (Heifers, Calves, and Bulls)	2.6	946	5.4	1,984	0.1	49
Large Heifers	0.0	0	0.0	0	0	0
Medium Heifers	0.0	0	0.0	0	0	0
Small Heifers	0.0	0	0.0	0	0	0
Calves	0.0	0	0.0	0	0	0
Bulls	0.0	0	0.0	0	0	0
Total	13.5	4,912	41.7	15,226	1	368

Solid Manure Handling				
Cow	VOC		NH3	
	lb/day	lb/yr	lb/day	lb/yr
Milk Cows	2.4	875	19.4	7,075
Dry Cows	0.2	76	1.6	572
Support Stock (Heifers, Calves, and Bulls)	0.6	233	3.2	1,163
Large Heifers	0.0	0	0.0	0
Medium Heifers	0.0	0	0.0	0
Small Heifers	0.0	0	0.0	0
Calves	0.0	0	0.0	0
Bulls	0.0	0	0.0	0
Total	3.2	1,184	24.2	8,810

Feed Handling and Storage		
	Daily PE (lb-VOC/day)	Annual PE (lb-VOC/yr)
Corn Emissions	10.2	3,733
Alfalfa Emissions	0.0	0
Wheat Emissions	10.9	3,975
TMR	98.1	35,806
Total	119.2	43,514

Total Daily Post-Project Potential to Emit (lb/day)							
Permit	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0.0	0.0	0.0	0.0	2.7	0.9	0.0
Cow Housing	0.0	0.0	12.9	0.0	91.7	180.0	0.0
Liquid Manure	0.0	0.0	0.0	0.0	13.5	41.7	1.0
Solid Manure	0.0	0.0	0.0	0.0	3.2	24.2	0.0
Feed Handling	0.0	0.0	0.0	0.0	119.2	0.0	0.0
Total	0.0	0.0	12.9	0.0	230.3	246.8	1.0

Total Annual Post-Project Potential to Emit (lb/yr)							
Permit	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0	0	0	0	1,000	342	0
Cow Housing	0	0	4,664	0	33,497	65,686	0
Liquid Manure	0	0	0	0	4,912	15,226	368
Solid Manure	0	0	0	0	1,184	8,810	0
Feed Handling	0	0	0	0	43,514	0	0
Total	0	0	4,664	0	84,106	90,064	368

Calculations for milking parlor:

Annual PE = (# milk cows) x (EF2 lb-pollutant/hd-yr)

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Calculations for cow housing:

See detailed calculations under Cow Housing Calculations worksheet.

Calculations for liquid manure and solid manure handling:

Annual PE = [(# milk cows) x (EF1 lb-pollutant/hd-yr)] + [(# dry cows) x (EF2 lb-pollutant/hd-yr)] + [(# large heifers) x (EF2 lb-pollutant/hd-yr)] + [(# medium heifers) x (EF2 lb-pollutant/hd-yr)] + [(# small heifers) x (EF2 lb-pollutant/hd-yr)] + [(# calves) x (EF2 lb-pollutant/hd-yr)] + [(# bulls) x (EF2 lb-pollutant/hd-yr)]

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

The H2S emission factor is assumed to be 10% of the NH3 lagoon/storage pond(s) emission factor, for each respective herd size.

Calculations for silage emissions:

Annual PE = (EF2) x (area ft²) x (0.0929 m²/ft²) x (8,760 hr/yr) x (60 min/hr) x (2.20E-9 lb/μg)

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Calculation for TMR emissions:

Annual PE = (# cows) x (EF2) x (0.658 m³) x (525,600 min/yr) x (2.20E-9 lb/μg)

Daily PE = (Annual PE lb/yr) ÷ (365 day/yr)

Calves are not included in TMR calculation.

Major Source Emissions (lb/yr)					
Permit	NOx	SOx	PM10	CO	VOC
Milk Parlor	0	0	0	0	0
Cow Housing	0	0	0	0	0
Liquid Manure	0	0	0	0	2,352
Solid Manure	0	0	0	0	0
Feed Handling	0	0	0	0	0
Total	0	0	0	0	2,352

Increase in Emissions

SSIPE (lb/yr)							
	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0	0	0	0	440	150	0
Cow Housing	0	0	-8,947	0	13,299	27,140	0
Liquid Manure	0	0	0	0	-185	1,074	0
Solid Manure	0	0	0	0	194	3,512	0
Feed Handling	0	0	0	0	5,658	0	0
Total	0	0	-8,947	0	19,406	31,876	0

Total Daily Change in Emissions (lb/day)							
	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0.0	0.0	0.0	0.0	1.2	0.4	0.0
Cow Housing	0.0	0.0	-24.4	0.0	36.5	74.5	0.0
Liquid Manure	0.0	0.0	0.0	0.0	-0.4	2.9	0.0
Solid Manure	0.0	0.0	0.0	0.0	0.5	9.6	0.0
Feed Handling	0.0	0.0	0.0	0.0	15.5	0.0	0.0
Total	0.0	0.0	-24.4	0.0	53.3	87.4	0.0

Total Annual Change in Non-Fugitive Emissions (Major Source Emissions) (lb/yr)							
	NOx	SOx	PM10	CO	VOC	NH3	H2S
Milking Parlor	0	0	0	0	0	0	0
Cow Housing	0	0	0	0	0	0	0
Liquid Manure	0	0	0	0	-101	0	0
Solid Manure	0	0	0	0	0	0	0
Feed Handling	0	0	0	0	0	0	0
Total	0	0	0	0	-101	0	0

Appendix E

BACT Calculations

BACT Applicability

Milking Parlor					
VOC Emissions					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	2.7	1.5	0.40	0.40	1.2
Total					1.2
NH3 Emissions					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	0.9	0.5	0.14	0.14	0.4
Total					0.4

Cow Housing
See detailed cow housing AIPE calculations on following pages.

Liquid Manure Handling					
VOC Emissions - Lagoon/Storage Pond(s)					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	4.8	4.5	0.70	1.17	2.1
Dry Cows	0.4	0.4	0.38	0.64	0.2
Support Stock (Heifers, Calves, and Bulls)	1.2	1.9	0.29	0.49	0.1
Large Heifers	0.0	0.0	0.29	0.49	0.0
Medium Heifers	0.0	0.0	0.20	0.33	0.0
Small Heifers	0.0	0.0	0.11	0.19	0.0
Calves	0.0	0.0	0.05	0.09	0.0
Bulls	0.0	0.0	0.18	0.30	0.0
Total					2.3

VOC Emissions - Land Application					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	5.2	4.8	0.76	1.26	2.3
Dry Cows	0.5	0.4	0.41	0.69	0.3
Support Stock (Heifers, Calves, and Bulls)	1.3	2.0	0.32	0.53	0.1
Large Heifers	0.0	0.0	0.32	0.53	0.0
Medium Heifers	0.0	0.0	0.22	0.36	0.0
Small Heifers	0.0	0.0	0.12	0.20	0.0
Calves	0.0	0.0	0.06	0.10	0.0
Bulls	0.0	0.0	0.19	0.32	0.0
Total					2.7

NH3 Emissions - Lagoon/Storage Pond(s)					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	8.1	4.5	1.18	1.18	3.6
Dry Cows	0.7	0.3	0.60	0.60	0.4
Support Stock (Heifers, Calves, and Bulls)	1.3	1.2	0.32	0.32	0.1
Large Heifers	0.0	0.0	0.32	0.32	0.0
Medium Heifers	0.0	0.0	0.22	0.22	0.0
Small Heifers	0.0	0.0	0.17	0.17	0.0
Calves	0.0	0.0	0.05	0.05	0.0
Bulls	0.0	0.0	0.43	0.43	0.0
Total					4.1

NH3 Emissions - Land Application					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	25.5	24.6	3.72	6.41	11.2
Dry Cows	2.1	1.8	1.88	3.24	1.1
Support Stock (Heifers, Calves, and Bulls)	4.1	6.4	0.96	1.66	0.4
Large Heifers	0.0	0.0	0.96	1.66	0.0
Medium Heifers	0.0	0.0	0.71	1.22	0.0
Small Heifers	0.0	0.0	0.54	0.94	0.0
Calves	0.0	0.0	0.15	0.27	0.0
Bulls	0.0	0.0	1.35	2.33	0.0
Total					12.7

H2S Emissions - Lagoon/Storage Pond(s)					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	0.8	0.8	0.12	0.12	0.0
Dry Cows	0.1	0.1	0.06	0.06	0.0
Support Stock (Heifers, Calves, and Bulls)	0.1	0.1	0.03	0.03	0.0
Large Heifers	0.0	0.0	0.03	0.03	0.0
Medium Heifers	0.0	0.0	0.02	0.02	0.0
Small Heifers	0.0	0.0	0.02	0.02	0.0
Calves	0.0	0.0	0.01	0.01	0.0
Bulls	0.0	0.0	0.04	0.04	0.0
Total					0.0

Solid Manure Handling					
VOC Emissions - Solid Manure Storage/Separated Solids Piles					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	1.2	0.7	0.18	0.18	0.5
Dry Cows	0.1	0.1	0.10	0.10	0.0
Support Stock (Heifers, Calves, and Bulls)	0.3	0.3	0.10	0.07	0.0
Large Heifers	0.0	0.0	0.07	0.07	0.0
Medium Heifers	0.0	0.0	0.05	0.05	0.0
Small Heifers	0.0	0.0	0.03	0.03	0.0
Calves	0.0	0.0	0.01	0.01	0.0
Bulls	0.0	0.0	0.05	0.05	0.0
Total					0.5

VOC Emissions - Land Application					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	1.2	1.1	0.18	0.30	0.5
Dry Cows	0.1	0.1	0.10	0.16	0.0
Support Stock (Heifers, Calves, and Bulls)	0.3	0.5	0.07	0.12	0.0
Large Heifers	0.0	0.0	0.07	0.12	0.0
Medium Heifers	0.0	0.0	0.05	0.08	0.0
Small Heifers	0.0	0.0	0.03	0.05	0.0
Calves	0.0	0.0	0.01	0.02	0.0
Bulls	0.0	0.0	0.04	0.07	0.0
Total					0.6

NH3 Emissions - Solid Manure Storage/Separated Solids Piles					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	9.1	5.1	1.33	1.33	4.0
Dry Cows	0.7	0.4	0.67	0.67	0.3
Support Stock (Heifers, Calves, and Bulls)	1.5	1.3	0.35	0.35	0.2
Large Heifers	0.0	0.0	0.35	0.35	0.0
Medium Heifers	0.0	0.0	0.25	0.25	0.0
Small Heifers	0.0	0.0	0.18	0.18	0.0
Calves	0.0	0.0	0.06	0.06	0.0
Bulls	0.0	0.0	0.49	0.49	0.0
Total					4.5

NH3 Emissions - Land Application					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Milk Cows	10.3	5.8	1.50	1.50	4.5
Dry Cows	0.8	0.4	0.76	0.76	0.4
Support Stock (Heifers, Calves, and Bulls)	1.7	1.5	0.40	0.40	0.2
Large Heifers	0.0	0.0	0.40	0.40	0.0
Medium Heifers	0.0	0.0	0.28	0.28	0.0
Small Heifers	0.0	0.0	0.22	0.22	0.0
Calves	0.0	0.0	0.06	0.06	0.0
Bulls	0.0	0.0	0.55	0.55	0.0
Total					5.1

Feed Storage and Handling					
VOC Emissions - Silage					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
Corn Silage	10.2	20.0	21.155	21.155	-9.8
Alfalfa Silage	0.0	2.9	10.649	10.649	-2.9
Wheat Silage	10.9	14.7	26.745	26.745	-3.8
Total					-16.5
VOC Emissions - TMR					
	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)
TMR	98.1	66.1	10,575	10,575	32.0
Total					32.0

Cow Housing - PM10 Emissions

	Housing Name(s) or #(s)	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	AIPE (lb/day)	BACT Triggered?
1	Freestall Barn #5	3.2	3.0	1.05	1.37	0.9	No
2	Freestall Barn #6	2.3	2.3	1.05	1.37	0.5	No
3	Freestall Barn #7	2.7	25.3	1.05	10.55	0.2	No
4	Shade Barn #1	0.9	0.8	1.05	1.37	0.3	No
5	Freestall Barn #1	0.6	1.2	1.05	4.55	0.3	No
6	Freestall Barn #2-A	0.3	1.2	1.05	4.55	0.0	No
7	Freestall Barn #2-B	0.3	3.3	1.05	9.67	-0.1	No
8	Calf Hutches	0.0	0.2	0.00	0.34	0.0	No
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							
31							
32							
33							
34							
35							
36							
37							
38							
39							
40							

New Units from Expansion

	Housing Name(s) or #(s)	PE2 (lb/day)	PE1 (lb/day)	EF2	EF1	PE2 (lb/day)	BACT Triggered?
1	Freestall Barn #3	0.9	0.0	1.05	0.00	0.9	No
2	Freestall Barn #4	1.7	0.0	1.05	0.00	1.7	No
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							

*Multiple emissions units (freestalls, corrals, calf hutch areas, etc.) are combined in these rows. BACT applicability has been calculated for EACH emissions unit in this row.

Appendix F

BACT Guidelines

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.2*

Last Update: 12/18/2013

Cow Housing - Freestall and Saudi-Style Barns

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	<p>1) Concrete feed lanes and walkways;</p> <p>2) Flushing the lanes and walkways for the mature cows (milk and dry cows) four times per day and flushing lanes and walkways for the remaining animals once per day (or for dairies that cannot use a flush system, Scraping lanes and walkways for mature cows with an automatic scraper (or equivalent) four times per day and cleaning lanes and walkways for support stock (heifers) at least once per day);</p> <p>3) Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;</p> <p>4) Properly sloping exercise pens (minimum of 3% slope where the available space for each animal is 400 square feet or less and minimum of 1.5% where the available space for each animal is more than 400 square feet per animal) or managing corrals to maintain a dry surface;</p> <p>5) Scraping exercise pens every two weeks using pull-type scraper in the morning hours except when prevented by wet conditions; and</p> <p>6) Rule 4570 Measures</p>		
PM10	<p>1) Concrete feed lanes and walkways;</p> <p>2) Scraping exercise pens every two weeks using pull-type scraper in the morning hours except when prevented by wet conditions</p>		

San Joaquin Valley Unified Air Pollution Control District

NH3

- 1) Concrete feed lanes and walkways;
- 2) Flushing the lanes and walkways for the mature cows (milk and dry cows) four times per day and flushing lanes and walkways for the remaining animals once per day (or for dairies that cannot use a flush system, Scraping lanes and walkways for mature cows with an automatic scraper (or equivalent) four times per day and cleaning lanes and walkways for support stock (heifers) at least once per day);
- 3) Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- 4) Properly sloping exercise pens (minimum of 3% slope where the available space for each animal is 400 square feet or less and minimum of 1.5% where the available space for each animal is more than 400 square feet per animal) or managing corrals to maintain a dry surface; and
- 5) Scraping exercise pens every two weeks using pull-type scraper in the morning hours except when prevented by wet conditions;

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.6*

Last Update: 12/18/2013

Liquid Manure Handling - Lagoon/Storage Pond

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Anaerobic treatment lagoon designed according to NRCS Guideline, and solids removal/separation system (mechanical separator(s) or settling basin(s)/weeping wall(s))	1) Aerobic treatment lagoon or mechanically aerated lagoon; 2) Covered lagoon digester vented to a control device with minimum 95% control	
NH3	All animals fed in accordance with NRCS or other District-approved guidelines		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.7*

Last Update: 12/18/2013

Liquid Manure Handling - Liquid/Slurry Land Application

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards	1) Irrigation of crops using liquid manure from an aerobic treatment lagoon or mechanically aerated lagoon (95% VOC control efficiency) 2) Irrigation of crops using liquid manure from a holding/storage pond after being treated in a covered lagoon/digester (80% VOC control efficiency)	
NH3	All animals fed in accordance with NRCS or other District-approved guidelines		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.8*

Last Update: 12/18/2013

Solid Manure Handling - Storage/Separated Solids Piles

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NH3	All animals fed in accordance with NRCS or other District-approved guidelines		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.9*

Last Update: 12/18/2013

Solid Manure Handling - Land Application

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Rapid incorporation of solid manure into the soil after land application	<p>1a) Land Application of Solid Manure Processed by Either an Open or Enclosed Negatively-Aerated Static Pile (ASP) Vented to a biofilter (or equivalent) $\geq 80\%$ destruction efficiency With Rapid Incorporation of the Manure Into the Soil After Land Application;</p> <p>1b) Land Application of Solid Manure Processed by In-Vessel/Enclosed Negatively-Aerated Static Piles vented to biofilter $\geq 80\%$ destruction efficiency;</p> <p>2) Land Application of Solid Manure Processed by Open Negatively-Aerated Static Piles vented to biofilter $\geq 80\%$ destruction efficiency;</p> <p>3) Land Application of Solid Manure Processed by an Open Negatively-Aerated Static Piles (ASP) (With Thick Layer of Bulking Agent or Equivalent) With Rapid Incorporation of the Manure Into the Soil After Land Application</p>	
NH3	Rapid incorporation of solid manure into the soil after land application, and all animals fed in accordance with NRCS or other District-approved guidelines		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.8.11*

Last Update: 12/18/2013

Feed Storage and Handling - Feed/TMR

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	District Rule 4570 Measures for Feed/TMR		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

Appendix G

BACT Analysis

I. Top-Down BACT Analysis for the Cow Housing

VOC: New Freestall Barn Area # 3 & 4 & Existing Freestall Barn Area # 5 & 6
NH3: New Freestall Barn Area # 3 & 4 & Existing Freestall Barn Area # 1, 5 & 6

1. VOC Emissions

a. Step 1 - Identify all control technologies

The following options have been identified as possible controls for VOC emissions from cow housing freestall barns and Saudi-style barns using flush cleaning:

1) Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface;
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions; and
- Rule 4570 measures.

Description of Control Technologies

Concrete feed lanes and walkways

Dairy cows spend a large proportion of time on the feed lanes and walkways. A significant proportion of manure is consequently deposited in these areas. The concrete lanes and walkways are necessary for an effective flush system, which in turn is a key component of management practices used for the control of VOC and ammonia emissions (see below).

Increased flushing of feed lanes and walkways

Many dairy operations use a flush system to remove manure from the feed lanes and walkways. The flush system introduces a large volume of water at the head of the paved area, and the cascading water carries the manure downslope. The required volume of flush water varies with the size and slope of the area to be flushed.

In addition to cleaning the feed lanes and walkways, the flush system also serves as an emissions control method. Many of the VOCs emitted from fresh cow manure, such as alcohols (ethanol and methanol) and many Volatile Fatty Acids (VFAs), are highly soluble in water. Therefore, a large proportion of these compounds will dissolve in the flush water

instead of being emitted directly from the housing areas. The flush water then carries the manure and the dissolved volatile compounds into an anaerobic treatment system where they are digested and converted into less polluting byproducts by microbial activity.

Feed lanes and walkways are typically flushed once or twice per day in the mature cow housing areas; and as infrequently as once a week in the support stock housing areas. Flushing the lanes four times per day for mature cows and once per day for support stock will increase the frequency with which manure is removed from the housing areas, which should result in a higher percentage of soluble volatile compounds being captured in the flush water, and therefore higher control efficiency. Although the control efficiency may actually be much higher, increasing the cleaning frequency of the lanes will be conservatively assumed to have a control efficiency of 10% for VOCs emitted from manure in cow housing areas, until better data becomes available.

Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for VOC emissions can be reduced by reducing the quantity of undigested nutrients in the manure. Many of the VOCs emitted from Confined Animal Facilities, including dairies, originate from the decomposition of undigested protein in animal waste.¹² This undigested protein also produces ammonia emissions. The level of microbial action in the manure corresponds to the level of organic nitrogen content in the manure; the lower the level of nitrogen the lower the level of microbial action and the lower the production of ammonia and VOCs.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea and organic nitrogen content of the manure, which will reduce the production of VOCs and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nutrients into the manure.

Based on very limited data (Klaunser, 1998, *J Prod Agric*), diet manipulation decreased nitrogen excretion by 34% while improving milk production. Up to 70% of excess nitrogen is lost off of the farm through volatilization, denitrification and leaching. Because of limited research, feeding cows in accordance with National Research Council (NRC) or other District-approved guidelines will be conservatively assumed to have a control efficiency of only 5-10% for both enteric¹³ and manure VOC emissions.

Properly sloping exercise pens/corrals

Accumulation of water on exercise pen/corral surfaces, due to rain or on-farm activities, could result in anaerobic conditions and thereby increase emissions. Keeping exercise

¹² "Emissions of Volatile Organic Compounds Originating from UK Livestock Agriculture", Hobbs, P.J. 2004 - Journal of the Science of Food and Agriculture.

¹³ Enteric emissions are those emitted directly from the animal (primarily via belching and flatulence), due to feed digestion processes.

pen/corral surfaces dry and properly aerated, on the other hand, promotes the aerobic conditions that reduce emissions. Proper slope design is therefore required to ensure that drainage of any water deposited on the exercise pen surfaces will be as rapid as possible.

Scraping of exercise pens/corrals with a pull-type scraper

Frequent scraping of the corrals will reduce the amount of manure on the pen/corral surfaces, which will reduce VOC and ammonia emissions resulting from decomposition of this manure. This practice will also provide a uniform surface that promotes aerobic conditions on the pen/corral surface, which will reduce gaseous pollutants from this area.

b. Step 2 - Eliminate technologically infeasible options

All the options identified in step 1 are technologically feasible.

c. Step 3 - Rank remaining options by control effectiveness

All the options identified in step 1 are assumed to each have the same control effectiveness:

1) Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface;
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions; and
- Rule 4570 measures.

d. Step 4 - Cost Effectiveness Analysis

Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;

- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface;
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions; and
- Rule 4570 measures.

The applicant has proposed these options. In addition, these options are achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed the following feed and manure management practices:

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface;
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions; and
- Rule 4570 measures.

The proposal satisfies BACT for this category.

2. Ammonia (NH₃) Emissions

a. Step 1 - Identify all control technologies

The following options have been identified as possible controls for ammonia emissions from cow housing freestall barns using flush cleaning and open corrals:

1) Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;

- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface; and
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions.

Description of Control Technologies

Concrete feed lanes and walkways

Dairy cows spend a large proportion of time on the feed lanes and walkways. A significant proportion of manure is consequently deposited in these areas. The concrete lanes and walkways are necessary for an effective flush system, which in turn is a key component of management practices used for the control of VOC and ammonia emissions (see below).

Increased Flushing for feed lanes and walkways

Many dairy operations use a flush system to remove manure from the feed lanes and walkways. The flush system introduces a large volume of water at the head of the paved area, and the cascading water carries the manure downslope. The required volume of flush water varies with the size and slope of the area to be flushed.

In addition to cleaning the feed lanes and walkways, the flush system also serves as an emissions control method. Ammonia is highly soluble in water. Therefore, a large proportion of ammonia in manure will dissolve in the flush water instead of being emitted directly from the housing areas. The flush water then carries the manure and the dissolved ammonia into the liquid manure storage system, where ammonia can be sequestered until it is applied to cropland as a nitrogen fertilizer.

Feed lanes and walkways are typically flushed once or twice per day in the mature cow housing areas; and as infrequently as once a week in the support stock housing areas. Flushing the lanes four times per day for mature cows and once per day for support stock will increase the frequency with which manure is removed from the housing areas, which should result in a higher percentage of ammonia being captured in the flush water, and therefore higher control efficiency.

Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for ammonia emissions can be reduced by reducing the amount of undigested nitrogen compounds in the manure. The level of microbial action in the manure corresponds to the level of organic nitrogen present, hence the lower the level of nitrogen the lower the level of microbial action and the lower the production of ammonia.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea

and organic nitrogen content of the manure, which will reduce the production of VOC and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nitrogen into the manure.

Properly sloping exercise pens/corrals

Accumulation of water on exercise pen/corral surfaces, due to rain or on-farm activities, could result in anaerobic conditions and thereby increase emissions. Keeping exercise pen/corral surfaces dry and properly aerated, on the other hand, promotes the aerobic conditions that reduce emissions. Proper slope design is therefore required to ensure that drainage of any water deposited on the exercise pen surfaces will be as rapid as possible.

b. Step 2 - Eliminate technologically infeasible options

All the options identified in step 1 are technologically feasible.

c. Step 3 - Rank remaining options by control effectiveness

All the options identified in step 1 are assumed to have the same control effectiveness:

1) Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface; and
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions.

d. Step 4 - Cost Effectiveness Analysis

Feed and Manure Management Practices

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;

- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface; and
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions.

The applicant has proposed these options. In addition, these options are achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed the following feed and manure management practices:

- Concrete feed lanes and walkways;
- Flushing feed lanes and walkways for mature cows (milk and dry cows) at least four times per day and flushing feed lanes and walkways for support stock at least once per day;
- Feeding all animals in accordance with National Research Council (NRC) or other District-approved guidelines;
- Properly sloping exercise pens/corrals (minimum slope of 3% where the available space for each animal is 400 square feet or less and 1.5% where the available space for each animal is more than 400 square feet) or managing exercise pens/corrals to maintain a dry surface; and
- Scraping exercise pens/corrals every two weeks using a pull-type scraper in the morning hours except when prevented by wet conditions.

The proposal satisfies BACT for this category.

II. Top-Down BACT Analysis for the Liquid Manure Handling System - Lagoon & Storage Pond

1. VOC Emissions

a. Step 1 - Identify all control technologies

The following options were identified as possible controls for VOC emissions from the lagoon & storage pond:

- 1) Aerobic treatment lagoon or mechanically aerated lagoon
- 2) Covered lagoon digester vented to a control device with minimum 95% control
- 3) Anaerobic treatment lagoon designed according to NRCS guidelines, and solids removal/separation system (mechanical separator(s) or settling basin(s)/weeping wall(s))

Description of Control Technologies

1) Aerobic Treatment Lagoon or Mechanically Aerated Lagoon

An aerobic lagoon is a waste treatment lagoon that is designed to facilitate the decomposition of wastewater by microbes in the presence of oxygen (O_2). The process of aerobic decomposition results in the conversion of organic compounds in the wastewater into carbon dioxide (CO_2), and (H_2O), nitrates, sulfates, and inert biomass (sludge). This process is sometimes referred to as nitrification (especially when discussing NH_3 transformation). Complete aerobic decomposition (100% aeration) removes nearly all malodors and also virtually eliminates VOC, H_2S , and NH_3 emissions.

In completely aerated lagoons, sufficient oxygen must be provided to sustain the aerobic microorganisms. NRCS Practice Standard Code 359 specifies that naturally aerobic lagoons have a minimum surface area determined by regional climate and daily Biological Oxygen Demand (BOD_5) and requires naturally aerobic lagoons to have a maximum depth no greater than five feet. For mechanically aerated lagoons, NRCS Practice Standard Code 359 specifies that the aeration equipment shall provide a minimum of 1 pound of oxygen for each pound of daily BOD_5 loading. The mechanical aerators that provide the required oxygen may float on the lagoon surface or be submerged in the lagoon. Aeration can also be performed by injection of tiny air bubbles into the lagoon water, mixing of the lagoon water, or spraying of the water into the air. According to Dr. Ruihong Zhang, a researcher at the University of California, Davis, at least 95% VOC control can be achieved if the dissolved oxygen (DO) concentration of the liquid manure is 2.0 mg/L or more. However, the DO concentrations achieved in mechanically aerated lagoons treating manure are typically much less than this and the control efficiencies will therefore be lower.

2) Covered Lagoon Digester

Covered treatment lagoons are one type of anaerobic digester. An anaerobic digester is an enclosed basin or tank that is designed to facilitate the decomposition of wastewater by microbes in the absence of oxygen. The process of anaerobic decomposition results in the preferential conversion of organic compounds in the wastewater into methane (CH_4), carbon dioxide (CO_2), and water rather than intermediate metabolites (VOC). The gas generated by this process is known as biogas, waste gas or digester gas. In addition to methane and carbon dioxide, biogas also contains small amounts of Nitrogen (N_2), Oxygen (O_2), Hydrogen Sulfide (H_2S), and Ammonia (NH_3). Biogas will also include trace amounts of various Volatile Organic Compounds (VOCs) that remain from incomplete digestion of the volatile solids in the incoming wastewater. The small amounts of undigested solids that remain after digestion are removed from the digester as sludge. Because biogas is mostly composed of methane, the main component of natural gas, the gas produced in the digester can be cleaned to remove H_2S and other impurities and used as fuel. The captured biogas can be combusted in a flare or may be sent to a boiler or internal combustion engine, where the gas can be used to generate useful heat or electrical energy.

As stated above, the gas generated in the covered lagoon anaerobic digester can be captured and then sent to a suitable combustion device. During combustion, gaseous

hydrocarbons are oxidized to form CO₂ and water. The VOC emitted from the liquid manure in the covered lagoon can be reduced by 95% with the use of an appropriate combustion device. Therefore, installation of the digester will lower the total VOC emitted from the liquid manure handling system. Although the control efficiency of the gas captured from the primary lagoon is expected to be 95% or more, the overall control efficiency is expected to be less, since some VOC will also be emitted from the storage pond and as fugitive emissions. For this analysis, the overall control efficiency is assumed to be 80% of the emissions that would have been emitted from the lagoon system.

3) Anaerobic Treatment Lagoon and Solids Removal/Separation System

An anaerobic treatment lagoon is a waste treatment lagoon that is designed to facilitate the decomposition of manure by microbes in the absence of oxygen. The process of anaerobic decomposition results in the preferential conversion of organic compounds in the wastewater into methane (CH₄), carbon dioxide (CO₂), and water rather than intermediate metabolites (VOC). The Natural Resources Conservation Service (NRCS) Field Office Technical Guide No. 359, Waste Treatment Lagoon, for California specifies the following criteria for the design of anaerobic treatment lagoons:

- Required volume - the minimum design volume should account for all potential sludge, treatment, precipitation, and runoff volumes.
- Treatment period - retention time of the material in the lagoon shall be the time required to provide environmentally safe utilization of waste. The minimum hydraulic retention time for a covered lagoon in the San Joaquin Valley is about 38 days.
- Waste loading shall be based on the maximum daily loading considering all waste sources that will be treated by the lagoon. The loading rate is typically based on volatile solids (VS) loading per unit of volume. The suggested loading rate for the San Joaquin Valley is 6.5-11 lb-VS/1000 ft³/day depending on separation and type of system.
- The operating depth of the lagoon as per Guide No. 359, Waste Treatment Lagoon. Maximizing the depth of the lagoon minimizes the surface area, which in turn minimizes the cover size and cost. Increasing the lagoon depth has the following advantages:
 - Minimizes surface area in contact with the atmosphere, thus reducing surface available to convection, evaporation
 - Smaller surface areas provide a more favorable and stable environment for methane bacteria
 - Better mixing of lagoon due to rising gas bubbles
 - Requires less land
 - More efficient for mechanical mixing

The lagoon design shall also consider location, soils and foundation, erosion, and depth to groundwater as required by the regional water control board.

The NRCS guideline suggests that this system consist of two cells, a treatment lagoon (primary lagoon) and a storage pond (secondary lagoon). The first stage of the lagoon system is the biological treatment stage and is designed with a constant liquid level to stabilize the anaerobic digestion. The effluent from the first stage overflows into a second lagoon designed for liquid storage capacity. Effluent from the second lagoon/storage pond is used in the flush lanes and for the irrigation of cropland. The secondary (overflow) lagoon acts as the storage pond, which can be emptied when necessary. However, a single lagoon can also be considered an anaerobic lagoon as long as all the criteria are met and that the liquid manure is not drawn less than 6 feet at any time.

A properly designed anaerobic treatment lagoon will reduce the volatile solids (VS) by at least 50%. This will reduce the biological oxygen demand (BOD) and increase the efficiency at which organic compounds are converted into methane and carbon dioxide rather than VOC. Although the VS reduction is expected to be at least 50%, a conservative control efficiency of 40% will be assumed, until better data becomes available.

Solids Removal/Separation

The liquid manure handling system at S&S Dairy includes settling basin for solids separation. Solids separation prevents excessive loading of volatile solids in lagoon treatment systems. Excessive loading of volatile solids in lagoons inhibits the activity of the methanogenic bacteria and leads to increased rates of volatile solids production. When the activity of the methanogenic bacteria is not inhibited, most of the VOCs are metabolized to simpler compounds, and the potential for VOC emissions is reduced.

b. Step 2 - Eliminate technologically infeasible options

There are no technologically infeasible options to eliminate from step 1.

c. Step 3 - Rank remaining options by control effectiveness

The remaining options are ranked below according to their control effectiveness:

- 1) Aerobic treatment lagoon or mechanically aerated lagoon (95% control efficiency)
- 2) Covered lagoon digester vented to a control device (80% control efficiency)
- 3) Anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards (40% control efficiency)
- 4) Solids Removal/Separation

d. Step 4 - Cost Effectiveness Analysis

Aerobic Treatment Lagoon or Mechanically Aerated Lagoon

Aerobic Treatment Lagoon

NRCS Practice Standard Code 359 requires that naturally aerobic lagoons be designed to have a minimum treatment surface area as determined on the basis of daily BOD₅ loading per unit of lagoon surface. The standard specifies that the maximum loading rate of naturally aerobic lagoons shall not exceed the loading rate indicated by the NRCS Agricultural Waste Management Field Handbook (AWMFH) or the maximum loading rate according to state regulatory requirements, whichever is more stringent. According to Figure 10-30 (August 2009) of the latest version of the AWMFH, the maximum aerobic lagoon loading rate for the San Joaquin Valley is 45 - 55 lb-BOD₅/acre-day. According to Table 4-5 (March 2008) of the NRCS AWMFH, the total daily manure produced by a milk cow will have 2.9 lb-BOD₅/day. Assuming that at least 80% of the manure will be flushed to the lagoon system, the minimum lagoon surface area required for a naturally aerobic lagoon treating manure from 2,500 milk cows in the San Joaquin Valley can be calculated as follows:

$$\begin{aligned} \text{BOD}_5 \text{ loading (lb/day)} &= 2,500 \text{ milk cows} \times 2.9 \text{ lb-BOD}_5/\text{cow-day} \times 0.80 \\ &= 5,800 \text{ lb-BOD}_5/\text{day} \end{aligned}$$

$$\begin{aligned} \text{Minimum Surface Area (acres)} &= 5,800 \text{ lb-BOD}_5/\text{day} \div 55 \text{ lb-BOD}_5/\text{acre-day} \\ &= 105.5 \text{ acres} \end{aligned}$$

As shown above, the minimum surface area required for a naturally aerobic lagoon to treat manure from the proposed number of milk cows is 105.5 acres. This does not include the additional surface area that would be required to treat manure from support stock. Based on the space requirements alone it is clear that this option cannot reasonably be required and no further analysis is needed.

Mechanically Aerated Lagoon

As discussed above, the very large space requirements for naturally aerobic lagoons cause this option to be infeasible for most confined animal facilities. Mechanically aerating a lagoon can achieve some of the benefits of a naturally aerobic lagoon without the large space requirements. However, the costs of energy for complete aeration have also caused this option to be infeasible. The amount of energy required for aeration is based on the amount of volatile solids that must be treated; thus, this cost will be directly proportional to the number of cows. The following analysis will determine the cost of emission reductions that can be achieved from a mechanically aerated lagoon treating manure from the proposed milk cow herd.

Biological Oxygen Demand (BOD₅)

In order to effectively calculate the cost of this control option, the energy requirement for complete aeration must be determined. It should be noted that approximately 1.5 to 2.5 pounds of oxygen is required to digest 1 pound of Biological Oxygen Demand (BOD₅) with additional oxygen required for conversion of ammonia to nitrate (nitrification). It is generally accepted that at least twice the BOD should be provided for complete aeration. According to Dr. Ruihong Zhang of the University of California, Davis, 2.4 lb (1.1 kg) of oxygen per cow must be provided each day for removal of BOD and an additional 3 lb (1.4 kg) per cow for oxidation of 70% of the nitrogen.

The proposed rule specifies that an aerobic lagoon be designed and operated in accordance with NRCS Practice Standard Code 359. NRCS Practice Standard Code 359 requires that mechanically aerated lagoons use aeration equipment that provides a minimum of one pound of oxygen for each pound of daily BOD₅ loading. As discussed above, the total daily manure produced by a milk cow will have a BOD₅ of 2.9 lb/day and a lagoon handling flushed manure from 2,500 milk cows will have a loading rate of approximately 5,800 lb-BOD₅/day (2,631 kg-BOD₅/day).

Energy Requirement

Based on the data gathered in a UC Davis study on aerator performance for wastewater lagoons, aeration efficiencies for mechanical aerators ranged from 0.10 to 0.68 kg of oxygen provided per kW-hr of energy utilized. The most efficient aerator tested that had been installed in dairy lagoons had an aeration efficiency of 0.49 kg-O₂/kW-hr. These efficiency tests were performed in clean water and lower aeration efficiencies are expected in liquid manure because of the significant amount of solids that it contains. The yearly energy requirement for a mechanically aerated lagoon system treating flushed manure from 4,000 milk cows is calculated as follows:

$$2,631 \text{ kg-BOD}_5/\text{day} \div (0.68 \text{ kg-O}_2/\text{kW-hr}) \times (365 \text{ day/year}) = 1,412,228 \text{ kW-hr/year}$$

Cost of Electricity

The cost of electricity will be based upon the average price for industrial electricity in California as of April 2018, as taken from the Energy Information Administration (EIA) website:¹⁴

$$\text{Average cost of electricity} = \$0.1144/\text{kW-hr}$$

The electricity cost for complete aeration is calculated as follows:

$$1,412,228 \text{ kW-hr/year} \times \$0.1144/\text{kW-hr} = \$ 161,559/\text{year}$$

VOC Emissions Reductions

It will be conservatively assumed that a mechanically aerated lagoon providing 1 lb of oxygen for every 1 lb of BOD₅ loading will control 90% of the VOC emissions from the lagoon/storage pond. However, as noted above, it is generally accepted that the oxygen provided should be twice the BOD₅ loading rate for complete aeration. Thus, the actual control from providing 1 lb of oxygen for every 1 lb of BOD₅ loading is probably in the 50% range.

The annual VOC emissions reductions are calculated as:

$$\begin{aligned} & [\text{Number of cows}] \times [\text{Lagoon/Storage Pond VOC EF (lb/cow-year)}] \times [\text{Complete} \\ & \text{Aeration Control Efficiency for Lagoon/Storage Pond}] \\ & = 2,500 \text{ cows} \times 1.3 \text{ lb-VOC/cow-yr} \times 90\% \text{ control} \\ & = 2,925 \text{ lb-VOC/yr} \end{aligned}$$

¹⁴ http://www.eia.gov/electricity/monthly/epm_table_grapher.cfm?t=epmt_5_06_b

Cost of Reductions

$$\begin{aligned} \text{Cost of reductions} &= (\$161,559/\text{year})/[(2,925 \text{ lb-VOC}/\text{year})(1 \text{ ton}/2000 \text{ lb})] \\ &= \$110,468/\text{ton} \end{aligned}$$

As shown above, based on the cost of electricity alone, the cost of the VOC reductions for this control option is greater than the \$17,500/ton cost effectiveness threshold specified by the District's BACT policy. This control option is therefore not cost effective and will not be required.

Covered Lagoon Digester

Capital Cost for Installation

The capital cost estimates for installation of a covered lagoon digester are based on information from the United States EPA AgSTAR publication "Anaerobic Digestion Capital Costs for Dairy Farms" (May 2010)¹⁵ and the California Energy Commission (CEC) Public Interest Energy Research (PIER) Program Dairy Methane Digester System Program Evaluation Report (Feb 2009).¹⁶ The formula in the AgSTAR publication results in a capital cost of \$1,032 per cow. This estimate excludes costs of solids separation after digestion, hydrogen sulfide removal, and utility charges including line upgrades and interconnection costs and fees. Based on information from installations in California, the CEC PIER Dairy Methane Digester Program Evaluation Report gives an average cost of \$585 per cow for installation of covered lagoon anaerobic digesters (see Table 9 - Total Project Costs and Cost per Cow and per kW).

For the purposes of this analysis, the more conservative capital cost of \$585/cow will be used. Thus, the installation capital cost for the proposed herd of 2,500 milk cows is at least \$ 1,462,500 (\$585/cow x 2,500 cows).

Pursuant to the District's BACT policy, the equivalent annual cost will be calculated using the capital recovery equation, as shown below:

$$A = P \frac{i(1+i)^n}{(1+i)^n - 1}$$

Where:

A = Equivalent annual capital cost of the control equipment

P = Present value of the control equipment, including installation cost

i = Interest rate (assumed to be 10%)

¹⁵ "Anaerobic Digestion Capital Costs for Dairy Farms" (May 2010), EPA AgSTAR http://www.epa.gov/agstar/pdf/digester_cost_fs.pdf

¹⁶ "Dairy Power Production Program – Dairy Methane System Program Evaluation Report" (February 2009). Western United Resource Development, Inc. prepared for the California Energy Commission (CEC) Public Interest Energy Research Program. (CEC-500-2009-009) <http://www.energy.ca.gov/2009publications/CEC-500-2009-009/CEC-500-2009-009.PDF>

$n =$ Equipment life (assumed to be 10 years)

$$A = [\$ 1,462,500 \times 0.1(1.1)^{10}] / [(1.1)^{10} - 1]$$

$$= \$ 237,656/\text{year}$$

Potential Production of Electricity

It may be possible to offset some of the installation costs of a covered lagoon anaerobic digester with revenue from generation of electricity. Based on the information given in the CEC PIER Dairy Methane Digester Program Evaluation Report, Table 7 – Actual Generation per Cow Comparisons, California dairies that used a covered lagoon digester to produce electricity generated between 429.1 and 1,031.8 kW-hr/yr per lactating cow with an overall per facility average generation rate of 670.3 kW-hr/yr per lactating cow. This average annual generation rate is actually higher than all the facilities included in the average except one that had a very high generation rate. In addition, this average may overestimate the per-cow generation potential because the contributions of support stock to the digesters were not accounted for. However, for more conservative calculations, this average will be used to calculate the potential annual savings in electricity costs.

The potential quantity of electricity produced is calculated as follows:

$$\text{Electrical Produced} = 670.3 \text{ kW-hr}/(\text{milk cow-yr}) \times 2,500 \text{ milk cows}$$

$$= 1,675,750 \text{ kW-hr/yr}$$

Potential Cost Savings from Production of Electricity

The value of electricity generated will be calculated using the previously cited EIA rate of \$0.1144/kW-hr.

$$\text{Potential Cost Savings} = 1,675,750 \text{ kW-hr/yr} \times \$0.1144/\text{kW-hr}$$

$$= \$ 191,706/\text{yr}$$

The annualized capital cost less the potential savings from electricity produced is:

$$= \$ 237,656 - \$ 191,706$$

$$= \$ 45,950$$

VOC Emissions Reductions

The annual VOC emissions reductions are calculated as:

$$= [\text{Number of cows}] \times [\text{Lagoon/Storage Pond VOC EF (lb/cow-year)}] \times [\text{Covered Lagoon Digester Efficiency for Lagoon/Storage Pond}]$$

$$= 2,500 \text{ cows} \times 1.3 \text{ lb-VOC/cow-yr} \times 80\% \text{ control}$$

$$= 2,925 \text{ lb-VOC/yr}$$

Cost of Reductions

$$\begin{aligned}\text{Cost of reductions} &= (\$ 45,950/\text{year})/[(2,925 \text{ lb-VOC}/\text{year})(1 \text{ ton}/2000 \text{ lb})] \\ &= \$ 31,419/\text{ton}\end{aligned}$$

As shown above, based the on the installation cost alone, after offsetting this cost by potential savings from electricity produced, the cost of the VOC reductions for this control option is greater than the \$17,500/ton cost effectiveness threshold specified by the District's BACT policy. This control option is therefore not cost effective and will not be required.

Anaerobic Treatment Lagoon and Solids Removal/Separation System

The applicant has proposed these options. In addition, these options are achieved in practice. Cost effectiveness analyses are therefore not required.

e. Step 5 - Select BACT

The applicant has proposed an anaerobic treatment system designed according to NRCS guidelines, and a solids removal/separation system (mechanical separator(s)). The proposal satisfies BACT for this category.

2. NH₃ Emissions

a. Step 1 - Identify all control technologies

The following option was identified as a possible control for NH₃ emissions from the lagoons & storage ponds:

- 1) All animals fed in accordance with NRC or other District-approved guidelines

Description of Control Technology

- 1) All animals fed in accordance with NRC or other District-approved guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for ammonia emissions can be reduced by reducing the amount of undigested nitrogen compounds in the manure. The level of microbial action in the manure corresponds to the level of organic nitrogen content in the manure; the lower the level of nitrogen the lower the level of microbial action and the lower the production of ammonia and VOCs.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea and organic nitrogen content of the manure, which will reduce the production of VOCs and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nitrogen into the manure, which will reduce ammonia emissions from the liquid manure in the lagoon and storage pond.

b. Step 2 - Eliminate technologically infeasible options

The option listed in Step 1 above is technologically feasible.

c. Step 3 - Rank remaining options by control effectiveness

The remaining option is listed below:

- 1) All animals fed in accordance with NRC or other District-approved guidelines

d. Step 4 - Cost Effectiveness Analysis

The applicant has proposed this option. In addition, this option is achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed to feed all animals in accordance with NRC or other District-approved guidelines. The proposal satisfies BACT for this category.

IV. Top-Down BACT Analysis for the Liquid Manure Handling System – Liquid Manure Land Application

1. VOC Emissions

a. Step 1 - Identify all control technologies

The following options were identified as possible controls for VOC emissions from land application of manure:

- 1) Irrigation of crops using liquid manure from an aerobic treatment lagoon or mechanically aerated lagoon
- 2) Irrigation of crops using liquid manure from a holding/storage pond after being treated in a covered lagoon/digester
- 3) Irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards

Description of Control Technologies

- 1) Irrigation of crops using liquid/slurry manure from an aerobic treatment lagoon or mechanically aerated lagoon

An aerobic lagoon is a waste treatment lagoon that is designed to facilitate the decomposition of wastewater by microbes in the presence of oxygen (O₂). The process of aerobic decomposition results in the conversion of organic compounds in the wastewater into carbon dioxide (CO₂), and (H₂O), nitrates, sulfates, and inert biomass

(sludge). This process is sometimes referred to as nitrification (especially when discussing NH_3 transformation). Complete aerobic decomposition (100% aeration) removes nearly all malodors and also virtually eliminates VOC, H_2S , and NH_3 emissions.

In completely aerated lagoons, sufficient oxygen must be provided to sustain the aerobic microorganisms. NRCS Practice Standard Code 359 specifies that naturally aerobic lagoons have a minimum surface area determined by regional climate and daily Biological Oxygen Demand (BOD_5) and requires naturally aerobic lagoons to have a maximum depth no greater than five feet. For mechanically aerated lagoons, NRCS Practice Standard Code 359 specifies that the aeration equipment shall provide a minimum of 1 pound of oxygen for each pound of daily BOD_5 loading. The mechanical aerators that provide the required oxygen may float on the lagoon surface or be submerged in the lagoon. Aeration can also be performed by injection of tiny air bubbles into the lagoon water, mixing of the lagoon water, or spraying of the water into the air. According to Dr. Ruihong Zhang, a researcher at the University of California, Davis, at least 95% VOC control can be achieved if the dissolved oxygen (DO) concentration of the liquid manure is 2.0 mg/L or more. However, the DO concentrations achieved in mechanically aerated lagoons treating manure are typically much less than this and the control efficiencies will therefore be lower.

2) Irrigation of crops using liquid/slurry manure from a holding/storage pond after being treated in a covered lagoon/digester

This practice would only allow the irrigation of liquid manure to cropland from the secondary lagoon after proper treatment has taken place in a covered lagoon/anaerobic digester. Covered treatment lagoons are one type of anaerobic digester. An anaerobic digester is an enclosed basin or tank that is designed to facilitate the decomposition of wastewater by microbes in the absence of oxygen. The process of anaerobic decomposition results in the preferential conversion of organic compounds in the wastewater into methane (CH_4), carbon dioxide (CO_2), and water rather than intermediate metabolites (VOC). The gas generated by this process is known as biogas, waste gas or digester gas. In addition to methane and carbon dioxide, biogas also contains small amounts of Nitrogen (N_2), Oxygen (O_2), Hydrogen Sulfide (H_2S), and Ammonia (NH_3). Biogas will also include trace amounts of various VOC that remain from incomplete digestion of the volatile solids in the incoming wastewater. The small amounts of undigested solids are removed from the digester as sludge.

Assumptions:

- 80% of the Volatile Solids (VS) can be removed from the covered anaerobic digestion process.
- 20% of the remaining VS will be assumed to be in the manure during land application. This will be considered worst-case because further digestion of the VS is likely to occur in the secondary lagoon.
- As a worst-case scenario, it will be assumed that all remaining VS will be emitted as VOC during land application.

Since 80% of the VS is removed or digested in the covered lagoon and the remaining VS have been assumed to be emitted as VOC, a control efficiency of 80% can be used for land application of liquid manure from a holding/storage pond after treatment in a covered lagoon.

3) Irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond where preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards

This practice would only allow the irrigation of liquid manure to cropland from the secondary lagoon after going through a treatment phase in an anaerobic treatment lagoon, or the primary lagoon.

An anaerobic treatment lagoon is a waste treatment lagoon that is designed to facilitate the decomposition of manure by microbes in the absence of oxygen. The process of anaerobic decomposition results in the preferential conversion of organic compounds in the wastewater into methane (CH₄), carbon dioxide (CO₂), and water rather than intermediate metabolites (VOC).

The NRCS Field Office Technical Guide No. 359, Waste Treatment Lagoon, for California specifies the following criteria for anaerobic treatment lagoons:

- Required volume - the minimum design volume should account for all potential sludge, treatment, precipitation, and runoff volumes.
- Treatment period - retention time of the material in the lagoon shall be the time required to provide environmentally safe utilization of waste. The minimum hydraulic retention time for a covered lagoon in the San Joaquin Valley is about 38 days.
- Waste loading shall be based on the maximum daily loading considering all waste sources that will be treated by the lagoon. The loading rate is typically based on volatile solids (VS) loading per unit of volume. The suggested loading rate for the San Joaquin Valley is 6.5-11 lb-VS/1000 ft³/day depending on separation and type of system.
- The operating depth of the lagoon as per Guide No. 359, Waste Treatment Lagoon. Maximizing the depth of the lagoon minimizes the surface area, which in turn minimizes the cover size and cost. Increasing the lagoon depth has the following advantages:
 - Minimizes surface area in contact with the atmosphere, thus reducing surface available to convection, evaporation
 - Smaller surface areas provide a more favorable and stable environment for methane bacteria
 - Better mixing of lagoon due to rising gas bubbles

- Requires less land
- More efficient for mechanical mixing

The lagoon design shall also consider location, soils and foundation, erosion, and depth to groundwater as required by the regional water control board.

The NRCS guideline suggests that this system consist of two cells, a treatment lagoon (primary lagoon) and a storage pond (secondary lagoon). The first stage of the lagoon system is the biological treatment stage and is designed with a constant liquid level to stabilize the anaerobic digestion. The effluent from the first stage overflows into a second lagoon designed for liquid storage capacity. Effluent from the second lagoon/storage pond is used in the flush lanes and for the irrigation of cropland. The secondary (overflow) lagoon acts as the storage pond, which can be emptied when necessary.

A properly designed anaerobic treatment lagoon will reduce the volatile solids (VS) by at least 50%. This will reduce the biological oxygen demand (BOD) and increase the efficiency at which organic compounds are converted into methane and carbon dioxide rather than VOC. Since 50% of the VS in the liquid manure will have been removed or digested in the lagoon, there will be less VS remaining in the effluent to decompose into VOC. Although, the VS reduction will be at least 50%, a conservative control efficiency of 40% will be applied to irrigation from a storage pond after an anaerobic treatment lagoon.

b. Step 2 - Eliminate technologically infeasible options

There are no technologically infeasible options to eliminate from step 1.

c. Step 3 - Rank remaining options by control effectiveness

The remaining options are ranked below according to their control effectiveness:

- 1) Irrigation of crops using liquid/slurry manure from an aerobic treatment lagoon or mechanically aerated lagoon (95% control efficiency)
- 2) Irrigation of crops using liquid/slurry manure from a holding/storage pond after being treated in a covered lagoon/digester (80% control efficiency)
- 3) Irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond where preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards (40% control efficiency)

d. Step 4 - Cost Effectiveness Analysis

Irrigation of crops using liquid/slurry manure from an aerobic treatment lagoon or mechanically aerated lagoon

The cost effectiveness analysis performed in the previous section (BACT analysis for VOC emissions from the lagoons/storage ponds) demonstrated that, based on the space

requirements alone, aerobic treatment cannot reasonably be required for this project. The previous analysis also demonstrated that mechanically aerated lagoons are not cost effective. Since the emission rate from land application of manure (1.4 lb/cow-yr) is not significantly different from the emission rate from lagoons/storage ponds (1.3 lb/cow-yr), no significant change from the previous cost effectiveness determination can be expected.

Irrigation of crops using liquid/slurry manure from a holding/storage pond after being treated in a covered lagoon digester

The cost effectiveness analysis performed in the previous section (BACT analysis for VOC emissions from the lagoons/storage ponds) demonstrated that a covered lagoon digester is not cost effective. Since the emission rate from land application of manure (1.4 lb/cow-yr) is not significantly different from the emission rate from lagoons/storage ponds (1.3 lb/cow-yr), no significant change from the previous cost effectiveness determination can be expected.

Irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond where preceded by an uncovered anaerobic treatment lagoon designed to meet Natural Resources Conservation Service (NRCS) standards

The applicant has proposed this option. In addition, this option is achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed irrigation of crops using liquid/slurry manure from the secondary lagoon/holding/storage pond preceded by an uncovered anaerobic treatment system designed to meet Natural Resources Conservation Service (NRCS) standards. The proposal satisfies BACT for this category.

2. NH₃ Emissions

a. Step 1 - Identify all control technologies

The following option has been identified as a possible control option for NH₃ emissions from land application of liquid manure:

- 1) All animals fed in accordance with NRC or other District-approved guidelines

Description of Control Technology

- 1) All animals fed in accordance with NRC or other District-approved guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for ammonia emissions can be reduced by reducing the amount of undigested nitrogen compounds in the manure. The level of microbial action in the manure corresponds to the level of organic nitrogen content in the manure; the lower the

level of nitrogen the lower the level of microbial action and the lower the production of ammonia and VOCs.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea and organic nitrogen content of the manure, which will reduce the production of VOCs and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nitrogen into the manure, which will reduce ammonia emissions from liquid manure applied to cropland.

b. Step 2 - Eliminate technologically infeasible options

The option listed in Step 1 above is technologically feasible.

c. Step 3 - Rank remaining options by control effectiveness

The remaining option is listed below:

- 1) All animals fed in accordance with NRC or other District-approved guidelines

d. Step 4 - Cost Effectiveness Analysis

The applicant has proposed this option. In addition, this option is achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed to feed all animals in accordance with NRC or other District-approved guidelines. The proposal satisfies BACT for this category.

V. Top-Down BACT Analysis for the Solid Manure Handling Operation – Storage

1. NH₃ Emissions

a. Step 1 - Identify all control technologies

The following options were identified as possible controls for NH₃ emissions from solid manure storage:

- 1) All Animals Fed in Accordance With National Research Council (NRC) or other District-Approved Guidelines

Description of Control Technologies

1) All Animals fed in accordance with National Research Council (NRC) or other District-approved Guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for ammonia emissions can be reduced by reducing the amount of undigested nitrogen compounds in the manure. The level of microbial action in the manure corresponds to the level of organic nitrogen content in the manure; the lower the level of nitrogen the lower the level of microbial action and the lower the production of ammonia and VOCs.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea and organic nitrogen content of the manure, which will reduce the production of VOCs and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nitrogen into the manure, which will reduce ammonia emissions from solid manure.

b. Step 2 - Eliminate technologically infeasible options

There are no technologically infeasible options to eliminate from step 1.

c. Step 3 - Rank remaining options by control effectiveness

After eliminating the technologically infeasible options, the remaining options are ranked according to their control efficiency.

- 1) All animals Fed in Accordance With National Research Council (NRC) or Other District-Approved Guidelines.

d. Step 4 - Cost Effectiveness Analysis

The applicant has proposed the only option listed; therefore a cost effectiveness analysis is not required.

e. Step 5 - Select BACT

The applicant has proposed to feed all animals in accordance with NRC or other District-approved guidelines. The proposal satisfies BACT for this category.

VI. Top-Down BACT Analysis for the Solid Manure Handling Operation – Land Application

1. NH₃ Emissions

a. Step 1 - Identify all control technologies

The following options were identified as possible controls for NH₃ emissions from solid manure land application:

- 1) Rapid incorporation of solid manure into the soil after land application, and All Animals Fed in Accordance With National Research Council (NRC) or Other District-Approved Guidelines

Description of Control Technologies

- 1) Rapid Incorporation of Solid Manure into the Soil After Land Application

Various types of spreading techniques, such as box spreaders, flail type spreaders, side discharge spreaders, and spinner spreaders, are used to apply solid manure to cropland. Regardless of which technique is used, this practice requires the immediate incorporation of the manure into the soil, reducing emissions and surface run-off while minimizing the loss of nitrogen into the atmosphere. Based on a study by a local Valley dairy, there is a great potential of reducing emissions by incorporating slurry manure rapidly into the soil. A similar reduction may be obtained by the rapid incorporation of solid manure. This technology is expected to yield a NH₃ control efficiency ranging from 49% to upwards of 98%.¹⁷

- 2) All Animals fed in accordance with National Research Council (NRC) or other District-approved Guidelines

Nutritional management of dairy feed is routinely practiced to improve milk production and herd health. The potential for ammonia emissions can be reduced by reducing the amount of undigested nitrogen compounds in the manure. The level of microbial action in the manure corresponds to the level of organic nitrogen content in the manure; the lower the level of nitrogen the lower the level of microbial action and the lower the production of ammonia and VOCs.

A diet that is formulated to feed proper amounts of ruminantly degradable protein will result in improved nitrogen utilization by the animal and corresponding reduction in urea and organic nitrogen content of the manure, which will reduce the production of VOCs and ammonia. The latest National Research Council (NRC) guidelines for the selection of an optimal bovine diet should be followed to the maximum extent possible. The diet recommendations made in this publication seek to achieve the maximum uptake of protein by the animal and the minimum carryover of nitrogen into the manure, which will reduce ammonia emissions from solid manure.

b. Step 2 - Eliminate technologically infeasible options

There are no technologically infeasible options to eliminate from step 1.

¹⁷ Page 81 of "Recommendations to the San Joaquin Valley Air Pollution Control Officer Regarding Best Available Control Technology for Dairies in the San Joaquin Valley" January 31, 2006 (http://www.valleyair.org/busind/pto/dpag/dpag_idx.htm).

c. Step 3 - Rank remaining options by control effectiveness

- 1) Rapid Incorporation of Solid Manure into the Soil After Land Application; and All animals Fed in Accordance With National Research Council (NRC) or Other District-Approved Guidelines.

d. Step 4 - Cost Effectiveness Analysis

Rapid Incorporation of Solid Manure into the Soil After Land Application; and All animals Fed in Accordance With National Research Council (NRC) or Other District-Approved Guidelines.

These technologies/practices are currently used at multiple dairies located throughout the valley, therefore a cost effective analysis is not required.

e. Step 5 - Select BACT

The Achieved in Practice option is determined to be BACT. Therefore, BACT for this category is rapid incorporation of solid manure into the soil after land application; and all animals fed in accordance with National Research Council (NRC) or other District-approved guidelines.

VII. Top-Down BACT Analysis for Feed Storage and Handling – Total Mixed Ration (TMR) Feeding

VOC Emissions

a. Step 1 - Identify all control technologies

The following option has been identified as a possible control for VOC emissions from TMR feeding:

- 1) District Rule 4570 measures

Description of Control Technology

District Rule 4570 measures

District Rule 4570 requires the implementation of various management practices to reduce VOC emissions from TMR. These practices include pushing feed so that it is within three feet of feedlane fence within two hours of putting out the feed or use a feed trough or other feeding structure designed to maintain feed within reach of the animals, so the area of the feed is minimized and the feed can be consumed by the cows in a shorter time period instead of continuing to emit VOCs; beginning feeding total mixed rations within two hours of grinding and mixing rations, reducing the time that fresh feed emits VOCs; storing grain in a weatherproof storage structure or under a weatherproof covering from October through May; feeding stream-flaked, dry rolled, cracked or ground corn or other ground cereal grains; removal of uneaten wet feed from feeding areas; and preparing TMR with a

minimum moisture content, which reduces VOC since most of the compounds emitted are highly soluble in water.

b. Step 2 - Eliminate technologically infeasible options

The option identified in step 1 is technologically feasible.

c. Step 3 - Rank remaining options by control effectiveness

Only one option was previously identified in step 1:

- 1) District Rule 4570 measures

d. Step 4 - Cost Effectiveness Analysis

District Rule 4570 Measures

The applicant has proposed this option. In addition, this option is achieved in practice. A cost effectiveness analysis is therefore not required.

e. Step 5 - Select BACT

The applicant has proposed to implement District Rule 4570 measures. The proposal satisfies BACT for this category.

Appendix H
RMR and AAQA Summary

San Joaquin Valley Air Pollution Control District Risk Management Review

To: Rupí Gill – Permit Services
 From: Adrian Ortiz – Technical Services
 Date: December 19, 2018
 Facility Name: S & S DAIRY INC.
 Location: 348 E MONTE VISTA AVE, CERES
 Application #(s): N-7321-1-5, -2-5, -3-4, -4-3, -6-2
 Project #: N-1182555

1. Summary

1.1 RMR

Units	Prioritization Score	Acute Hazard Index	Chronic Hazard Index	Maximum Individual Cancer Risk	T-BACT Required	Special Permit Requirements
1-5	0.99	0.00	0.00	1.34E-07	No	Yes
2-5	31.55	0.27	0.10	6.46E-06	Yes	Yes
3-4	0.00	0.00	0.00	0.00E+00	No	No
4-3	0.00	0.01	0.00	0.00E+00	No	Yes
Project Totals	32.54	0.28	0.10	6.60E-06		
Facility Totals	32.54	0.28	0.10	6.60E-06		

Notes: No increase in Lagoon emissions

1.2 AAQA

Pollutant	Air Quality Standard (State/Federal)				
	1 Hour	3 Hours	8 Hours	24 Hours	Annual
CO	NA		NA		
NO _x	NA				NA
SO _x	NA	NA		NA	NA
PM10				Pass	Pass
PM2.5				NA	NA

Notes:

- Results were taken from the attached AAQA Report.
- The criteria pollutants are below EPA's level of significance as found in 40 CFR Part 51.165 (b)(2) unless otherwise noted below.
- The court has vacated EPA's PM2.5 SILs. Until such time as new SIL values are approved, the District will use the corresponding PM10 SILs for both PM10 and PM2.5 analyses.

T-BACT is required for this unit because of emissions of 1,2-Dibromo-3-chloropropane (DBCP) which is a VOC.

2. Project Description

Technical Services received a request on December 13, 2018 to perform a Risk Management Review (RMR) for the following:

- Unit -1-5: MODIFICATION OF 1,400 COW MILKING OPERATION WITH ONE DOUBLE 30 PARALLEL (60 STALLS) MILKING PARLOR: INCREASE HERD SIZE
- Unit -2-5: MODIFICATION OF COW HOUSING - 1,400 MILK COWS NOT TO EXCEED A COMBINED TOTAL OF 1,600 MATURE COWS (MILK AND DRY); 1,400 SUPPORT STOCK (HEIFERS, CALVES AND BULLS): INCREASE HERD SIZE AND ADD NEW COW HOUSING
- Unit -3-4: MODIFICATION OF LIQUID MANURE HANDLING SYSTEM CONSISTING OF TWO SETTLING BASINS; ONE LAGOON; MANURE IS LAND APPLIED THROUGH FLOOD IRRIGATION: INCREASE HERD SIZE
- Unit -4-3: MODIFICATION OF SOLID MANURE HANDLING CONSISTING OF MANURE HAULED OFFSITE: INCREASE HERD SIZE
- Unit -6-2: MODIFICATION OF FEED STORAGE AND HANDLING CONSISTING OF COMMODITY BARNs AND SILAGE PILES: INCREASE HERD SIZE

3. RMR Report

3.1 Analysis

The District performed an analysis pursuant to the District's Risk Management Policy for Permitting New and Modified Sources (APR 1905, May 28, 2015) to determine the possible cancer and non-cancer health impact to the nearest resident or worksite. This policy requires that an assessment be performed on a unit by unit basis, project basis, and on a facility-wide basis. If a preliminary prioritization analysis demonstrates that:

- A unit's prioritization score is less than the District's significance threshold and;
- The project's prioritization score is less than the District's significance threshold and;
- The facility's total prioritization score is less than the District's significance threshold

Then, generally no further analysis is required.

The District's significant prioritization score threshold is defined as being equal to or greater than 1.0. If a preliminary analysis demonstrates that either the unit(s) or the project's or the facility's total prioritization score is greater than the District threshold, a screening or a refined assessment is required

If a refined assessment is greater than one in a million but less than 20 in one million for carcinogenic impacts (Cancer Risk) and less than 1.0 for the Acute and Chronic hazard indices (Non-Carcinogenic) on a unit by unit basis, project basis and on a facility-wide basis the proposed application is considered less than significant. For unit's that exceed a cancer risk of 1 in one million, Toxic Best Available Control Technology (TBACT) must be implemented.

Toxic emissions for this project were calculated using the following methods:

- Toxic emissions for the Cow Housing, Lagoon(s), and Milk Parlor(s) were calculated using emission factors derived from the District's evaluation of dairy research studies conducted by California colleges and universities. PM based toxic emissions for the Cow

Housing were calculated using emission factors generated from using the worst case composite of the 1997 EPA speciation of Kern County feedlot soil.

These emissions were input into the San Joaquin Valley APCD's Hazard Assessment and Reporting Program (SHARP). In accordance with the District's Risk Management Policy, risks from the proposed unit's toxic emissions were prioritized using the procedure in the 2016 CAPCOA Facility Prioritization Guidelines. The prioritization score for this proposed facility was greater than 1.0 (see RMR Summary Table). Therefore, a refined health risk assessment was required.

The AERMOD model was used, with the parameters outlined below and meteorological data for 2013-2017 from Modesto (rural dispersion coefficient selected) to determine the dispersion factors (i.e., the predicted concentration or X divided by the normalized source strength or Q) for a receptor grid. These dispersion factors were input into the SHARP Program, which then used the Air Dispersion Modeling and Risk Tool (ADMRT) of the Hot Spots Analysis and Reporting Program Version 2 (HARP 2) to calculate the chronic and acute hazard indices and the carcinogenic risk for the project.

The following parameters were used for the review:

Source Process Rate							
	PM10 lb/hr	PM10 lb/yr	VOC lb/hr	VOC lb/yr	NH3 lb/hr	NH3 lb/yr	H2S lb/yr
Milking Parlor (Unit 1-5)							
Milking Parlor	-	-	0.05	440	0.02	150	-
Cow Housing (Unit 2-5)							
FSB 4 (Milk Cows)	0.07	629	0.68	5,916	1.45	12,677	-
FSB 3 (Support Stock)	0.04	314	0.15	1,281	0.20	1,661	-
FSB 2 (Dry Cows)	0.00	0	0.00	23	0.04	379	-
FSB 1 (Dry cows)	0.03	0	0.07	557	0.13	1,071	-
SB 1 (Support Stock)	0.00	40	0.05	427	0.07	554	-
FSB 7 (Support Stock)	0.00	0	0.04	321	0.05	415	-
FSB 6 (Milk Cows)	0.00	16	0.23	1,972	0.48	4,226	-
FSB 5 (Milk Cows)	0.01	57	0.34	2,958	0.73	6,338	-
Liquid Manure Handling (Unit 3-4)							
Lagoon/Storage Pond	-	-	0.00	0	0.17	1,497	0
Land Application (Liquid)	-	-	0.00	0	0.00	0	-
Solid Manure Handling (Unit 4-3)							
Solid Manure Storage	-	-	0.00	183	0.19	1,643	-
Land Application (Solid)	-	-	0.00	0	0.213	1,862	-

Polygon Area Source Parameters				
Unit ID	Unit Description	Release Height (m)	No. Vertices	Area (m ²)
1	Milk Parlor 1	1.00	8	1760
2	Freestall Barn #4	1.00	4	3302
2	Freestall Barn #3	1.00	4	2955
2	Freestall Barn #2-B	1.00	4	2918
2	Freestall Barn #1	1.00	4	2536
2	Shade Barn #1	1.00	4	2467
2	Freestall Barn #7	1.00	4	7208
2	Freestall Barn #6	1.00	4	5252
2	Freestall Barn #5	1.00	8	10765
4	Land App Solid	0.00	5	150053
4	Solid Pile Storage	0.00	4	260

4. Conclusion

4.1 RMR

The cumulative acute and chronic indices for this facility, including this project, are below 1.0; and the cumulative cancer risk for this facility, including this project, is less than 20 in a million. However, the cancer risk for one or more units in this project is greater than 1.0 in a million. **In accordance with the District's Risk Management Policy, the project is approved with Toxic Best Available Control Technology (T-BACT).**

To ensure that human health risks will not exceed District allowable levels; the permit requirements listed on page 1 of this report must be included for this proposed unit.

These conclusions are based on the data provided by the applicant and the project engineer. Therefore, this analysis is valid only as long as the proposed data and parameters do not change.

4.2 AAQA

The ambient air quality impacts from PM₁₀ emissions at the proposed dairy (modification) (does not) exceed the District's 24-hour or Annual interim threshold for fugitive dust sources.

5. Attachments

- A. Modeling request from the project engineer
- B. Additional information from the applicant/project engineer
- C. Prioritization score w/ toxic emissions summary
- D. Facility Summary

Appendix I

Anaerobic Treatment Lagoon Design Check

LAGOON DESIGN FOR ONE LAGOON WW1

Lagoon Design Check in Accordance with NRCS Guideline #359

Proposed Lagoon Volume

$$\text{Volume of treatment lagoon} = (L \times W \times D) - (S \times D^2) \times (W + L) + (4 \times S^2 \times D^3 \div 3)$$

Primary Treatment Lagoon Dimensions

Length	390	ft
Width	275	ft
Depth	28	ft
Slope	2	ft

(Subtract 2 feet from the actual lagoon depth for run-off or miscellaneous water.)

Primary Lagoon Volume **2,077,357 ft³**

INSTRUCTIONS

* only input yellow fields

- Step 1 Enter primary lagoon dimensions on this sheet
- Step 2 Go to "Net Volatile Solids Loading" sheet and enter number of animals flushing manure to lagoon
- Step 3 Adjust % in flush and separation as necessary (see notes on sheet)
- Step 4 Go to "Minimum Treatment Volume"
- Step 5 Minimum treatment volume should be less than lagoon volume to be considered anaerobic treatment lagoon
- Step 6 Go to "Hydraulic Retention Time"
- Step 7 Adjust fresh water as applicable
- Step 8 Hydraulic retention time should be greater than 34 days to be considered anaerobic treatment lagoon.

Lagoon Design Check in Accordance with NRCS Guideline #359

Net Volatile Solids loading Calculation

Net Volatile Solids (VS) Loading of Treatment Lagoons							
Breed: Holstein Type of Cow	Number of Animals	VS Excreted ^[1] (lb/day)	% Manure in Flush ^[2]	x	(1 - % VS Removed in Separation) ^[3]	=	Net VS Loading (lb/day)
Milk Cows	2,500	17	71%	x	50%	=	15,088
Dry Cow	400	9.2	71%	x	50%	=	1,306
Heifer (15 to 24 months)	850	7.1	48%	x	50%	=	1,448
Heifer (7 to 14 months)	400	4.9	48%	x	50%	=	470
Heifer (3 to 6 months)	300	2.7	48%	x	50%	=	194
Calf (under 3 months)	0	1.0	100%	x	50%	=	0
Bulls	0	9.2	48%	x	50%	=	0
Total for Dairy							18,507

^[1]The Volatile Solids (VS) excretion rates for Holstein cattle are based on Table 1.b – Section 3 of ASAE D384.2 (March 2005). VS excretion rates for milk cows, dry cows, & heifers 15-24 months were taken from directly from the table. The VS excretion rate for heifers 3-6 months was estimated based on total solids excretion. The VS excretion rate for heifers 7-14 months was estimated as the average of heifers 15-24 months and heifers 3-6 months. The table did not give values for total solids or volatile solids excreted by baby calves. The VS excretion rate for baby calves was estimated based on an estimated dry matter intake (DMI) of 1.7% of body weight and the ratio of DMI to VS excretion for 150 kg calves. The VS excretion rate for mature bulls was assumed to be similar to dry cows.

^[2] The % manure was taken from Table 3-1 of the California Regional Water Quality Control Board Document “Managing Dairy Manure in the Central Valley of California”, UC Davis, June 2005. This document estimated that 21-48% of the manure in open corral dairies is handled as a liquid. Therefore, as a worst case assumption, 48% will be used for all cows housed in open corrals with flush lanes. The document also estimates a range of 42-100% manure handled as a liquid in the freestalls. For freestalls without exercise pens, 100% of manure as a liquid in the flush will be used; for freestalls with exercise pens, the average of the range $((100+42)/2 = 71\%)$ will be used. (<http://groundwater.ucdavis.edu/Publications/uc-committee-of-experts-final-report%202006.pdf>) Saudi style/loafing barns are hybrids between freestalls and open corrals, the percentage of manure collected on the concrete feed lanes will be averaged between the values from the cows housed in freestall barns and open corrals. Therefore the % of manure deposited on the concrete lanes is equal to 60% $[(71+48)/2]$.

^[3] Chastain, J.P., Vanotti, M. B., and Wingfield, M. M., Effectiveness of Liquid-Solid Separation For Treatment of Flushed Dairy Manure: A Case Study, Applied Engineering in Agriculture, Vol 17(3): 343-354 - This document outlines a VS removal rate of 50.1% to 70% depending on the type of separation system used, however to be conservative, a 50% VS removal will be used for all systems.

Lagoon Design Check in Accordance with NRCS Guideline #359

Minimum Treatment Volume Calculation

$$MTV = TVS/VSLR$$

Where:

MTV = Minimum Treatment Volume (ft³)

TVS = daily Total Volatile solids Loading (lb/day) = 0.011 lb/ft³-day

VSLR = Volatile Solids Loading Rate (lb/1000 ft³-day)

Minimum Treatment Volume in Primary Lagoon				
Breed: Holstein Type of Cow	Net VS Loading (lb/day)	÷	VSLR (lb/ft ³ -day)[1]	= MTV (ft ³)
Milk Cows	15,088	÷	0.011	= 1,371,591
Dry Cow	1,306	÷	0.011	= 118,764
Heifer (15 to 24 months)	1,448	÷	0.011	= 131,673
Heifer (7 to 14 months)	470	÷	0.011	= 42,764
Heifer (3 to 6 months)	194	÷	0.011	= 17,673
Calf (under 3 months)	0	÷	0.011	= 0
Bulls	0	÷	0.011	= 0
Total for Dairy				1,682,464

[1] VSLR for an anaerobic treatment lagoon in San Joaquin Valley would be 6.5 lb VS/1000 ft³-day to 11 lb VS/1000 ft³-day according to the NRCS and USDA AWTFH. Based on phone conversation with Matt Summers (USDA) on July 14, 2006, he suggested that the 11 lb VS VS/1000 ft³-day

Lagoon Design Check in Accordance with NRCS Guideline #359

Sludge Accumulation Volume

The sludge accumulation volume accounts for the solids contained in the manure that cannot be fully digested by bacteria and that gradually settle to the bottom of the lagoon as sludge.

The sludge accumulation volume for lagoon systems without solids separation can be calculated from the USDA Field Handbook. However, there are no accepted guidelines for calculating the sludge accumulation volume for lagoon systems with solids separation, but many designers of digester expect it to be minimal.

This facility has an efficient solids separation system consisting prior to the anaerobic treatment lagoon system. The separation system will remove a large portion of the fibers, lignin, cellulose, and other fibrous materials from the manure. These are the materials that would otherwise cause sludge accumulation from the lack of digestion in a lagoon or digester. Because fibrous materials and other solids will not enter the lagoon system, the sludge accumulation volume required will be minimized and can be considered negligible.

Nevertheless, the primary lagoon will have sufficient space remaining for sludge accumulation, as shown by the following calculation:

$$SAV = VPL - MTV$$

Where:

SAV = Sludge Accumulation Volume (ft³)

VPL = total Volume of Primary Lagoon (ft³)

MTV = Minimum Treatment Volume (ft³)

$$SAV = VPL - MTV$$

$$SAV = 2,077,357 - 1,682,464 = 394,894 \text{ (ft}^3\text{)}$$

Lagoon Design Check in Accordance with NRCS Guideline #359

Hydraulic Retention Time (HRT) Calculation

The anaerobic treatment lagoon and covered lagoon anaerobic digester must be designed to provide sufficient Hydraulic Retention Time (HRT) to adequately treat the waste entering the lagoon and to allow environmentally safe utilization of this waste. The NRCS Technical Guide Code 365 – Anaerobic Digester – Ambient Temperature specifies a minimum HRT 38 days in the San Joaquin Valley.

The Hydraulic Retention Time (HRT) is calculated as follows:

$$\text{HRT} = \text{MTV}/\text{HFR}$$

where:

HFR = Hydraulic flow rate (1000ft³/day)

HRT = Hydraulic Retention Time (day)

The Hydraulic Flow Rate is Calculated below

Type	# of cows	Amount of Manure*	HFR
Milk Cows	2,500	x 2.40	ft ³ = 6,000
Dry Cows	400	x 1.30	ft ³ = 520
Heifers (15-24 mo)	850	x 0.78	ft ³ = 663
Heifers (7-14 mo)	400	x 0.78	ft ³ = 312
Heifers (3-6 mo)	300	x 0.30	ft ³ = 90
Calves	0	x 0.15	ft ³ = -
Bulls	0	x 1.30	ft ³ = -
Total	4,450		7,585
Fresh water per milk cow used in flush at milk parlor		50	gal/day

*Table 1.b - Section 3 of ASAE D384.2 (March 2005). The calf manure was estimated to be 1/2 of the calf number found in the table, since the average weight of these calves is approx. 1/2 of the calves identified in the table.

Lagoon Design Check in Accordance with NRCS Guideline #359 Cont.

Formula:

Gallon Milk Cow*Day	# Milk Cows	x	ft3 gallon	+	ft3 day
------------------------	----------------	---	---------------	---	------------

Total HFR:

50 gal milk-ew*day	2500 milk-ews	x	7.48 gal ft3	+	7,585 ft3 day	
					=	24,296.2 ft3/day

Formula:

MTV (ft3)	/	(day) HFR (ft3)	=
-----------	---	--------------------	---

HRT:

1,682,464 ft3	/	24,296.2 ft3 day	=	69.2479302 days
---------------	---	---------------------	---	-----------------

Combined Wastewater Volume

For WW1, WW2 & WW3

Waste Pond	Volume (ft³)
WW1	2,077,357
WW2	835,416
WW3	1,023,336
Total	3,936,109

Lagoon Design Check in Accordance with NRCS Guideline #359

Proposed Lagoon Volume

Volume of treatment lagoon = $(L \times W \times D) - (S \times D^2) \times (W + L) + (4 \times S^2 \times D^3 \div 3)$

Primary Treatment Lagoon Dimensions

Length	390	ft
Width	275	ft
Depth	28	ft
Slope	2	ft

(Subtract 2 feet from the actual lagoon depth for run-off or miscellaneous water.)

Primary Lagoon Volume 2,077,357 ft3

INSTRUCTIONS

* only input yellow fields

- Step 1 Enter primary lagoon dimensions on this sheet
- Step 2 Go to "Net Volatile Solids Loading" sheet and enter number of animals flushing manure to lagoon
- Step 3 Adjust % in flush and separation as necessary (see notes on sheet)
- Step 4 Go to "Minimum Treatment Volume"
- Step 5 Minimum treatment volume should be less than lagoon volume to be considered anaerobic treatment lagoon
- Step 6 Go to "Hydraulic Retention Time"
- Step 7 Adjust fresh water as applicable
- Step 8 Hydraulic retention time should be greater than 34 days to be considered anaerobic treatment lagoon.

Lagoon Design Check in Accordance with NRCS Guideline #359

Proposed Lagoon Volume

$$\text{Volume of treatment lagoon} = (L \times W \times D) - (S \times D^2) \times (W + L) + (4 \times S^2 \times D^3 \div 3)$$

Primary Treatment Lagoon Dimensions

Length	290	ft
Width	285	ft
Depth	12	ft
Slope	2	ft

(Subtract 2 feet from the actual lagoon depth for run-off or miscellaneous water.)

Primary Lagoon Volume 835,416 ft³

INSTRUCTIONS

* only input yellow fields

- Step 1 Enter primary lagoon dimensions on this sheet
- Step 2 Go to "Net Volatile Solids Loading" sheet and enter number of animals flushing manure to lagoon
- Step 3 Adjust % in flush and separation as necessary (see notes on sheet)
- Step 4 Go to "Minimum Treatment Volume"
- Step 5 Minimum treatment volume should be less than lagoon volume to be considered anaerobic treatment lagoon
- Step 6 Go to "Hydraulic Retention Time"
- Step 7 Adjust fresh water as applicable
- Step 8 Hydraulic retention time should be greater than 34 days to be considered anaerobic treatment lagoon.

Lagoon Design Check in Accordance with NRCS Guideline #359

Proposed Lagoon Volume

$$\text{Volume of treatment lagoon} = (L \times W \times D) - (S \times D^2) \times (W + L) + (4 \times S^2 \times D^3 \div 3)$$

Primary Treatment Lagoon Dimensions

Length	350	ft
Width	285	ft
Depth	12	ft
Slope	2	ft

(Subtract 2 feet from the actual lagoon depth for run-off or miscellaneous water.)

Primary Lagoon Volume 1,023,336 ft³

INSTRUCTIONS

* only input yellow fields

- Step 1 Enter primary lagoon dimensions on this sheet
- Step 2 Go to "Net Volatile Solids Loading" sheet and enter number of animals flushing manure to lagoon
- Step 3 Adjust % in flush and separation as necessary (see notes on sheet)
- Step 4 Go to "Minimum Treatment Volume"
- Step 5 Minimum treatment volume should be less than lagoon volume to be considered anaerobic treatment lagoon
- Step 6 Go to "Hydraulic Retention Time"
- Step 7 Adjust fresh water as applicable
- Step 8 Hydraulic retention time should be greater than 34 days to be considered anaerobic treatment lagoon.

Lagoon Design Check in Accordance with NRCS Guideline #359

Net Volatile Solids loading Calculation

Net Volatile Solids (VS) Loading of Treatment Lagoons						
Breed: Holstein Type of Cow	Number of Animals	VS Excreted ^[1] (lb/day)	% Manure in Flush ^[2]	(1 - % VS Removed in Separation ^[3])	=	Net VS Loading (lb/day)
Milk Cows	2,500	17	71%	50%	=	15,088
Dry Cow	400	9.2	71%	50%	=	1,306
Heifer (15 to 24 months)	850	7.1	48%	50%	=	1,448
Heifer (7 to 14 months)	400	4.9	48%	50%	=	470
Heifer (3 to 6 months)	300	2.7	48%	50%	=	194
Calf (under 3 months)	0	1.0	100%	50%	=	0
Bulls	0	9.2	48%	50%	=	0
Total for Dairy						18,507

^[1]The Volatile Solids (VS) excretion rates for Holstein cattle are based on Table 1.b – Section 3 of ASAE D384.2 (March 2005). VS excretion rates for milk cows, dry cows, & heifers 15-24 months were taken from directly from the table. The VS excretion rate for heifers 3-6 months was estimated based on total solids excretion. The VS excretion rate for heifers 7-14 months was estimated as the average of heifers 15-24 months and heifers 3-6 months. The table did not give values for total solids or volatile solids excreted by baby calves. The VS excretion rate for baby calves was estimated based on an estimated dry matter intake (DMI) of 1.7% of body weight and the ratio of DMI to VS excretion for 150 kg calves. The VS excretion rate for mature bulls was assumed to be similar to dry cows.

^[2] The % manure was taken from Table 3-1 of the California Regional Water Quality Control Board Document “Managing Dairy Manure in the Central Valley of California”, UC Davis, June 2005. This document estimated that 21-48% of the manure in open corrals with flush lanes. The document also estimates a range of 42-100% manure handled as a liquid in the freestalls. For freestalls without exercise pens, 100% of manure as a liquid in the flush will be used; for freestalls with exercise pens, the average of the range $(100+42)/2 = 71\%$ will be used. (<http://groundwater.ucdavis.edu/Publications/uc-committee-of-experts-final-report%202006.pdf>) Saudi style/loafing barns are hybrids between freestalls and open corrals, the percentage of manure collected on the concrete feed lanes will be averaged between the values from the cows housed in freestall barns and open corrals. Therefore the % of manure deposited on the concrete lanes is equal to 60% $[(71+48)/2]$.

^[3] Chastain, J.P., Vanotti, M. B., and Wingfield, M. M., Effectiveness of Liquid-Solid Separation For Treatment of Flushed Dairy Manure: A Case Study, Applied Engineering in Agriculture, Vol 17(3): 343-354 - This document outlines a VS removal rate of 50.1% to 70% depending on the type of separation system used, however to be conservative, a 50% VS removal will be used for all systems.

Lagoon Design Check in Accordance with NRCS Guideline #359

Minimum Treatment Volume Calculation

$$MTV = TVS/VSLR$$

Where:

MTV = Minimum Treatment Volume (ft³)

TVS = daily Total Volatile solids Loading (lb/day) = 0.011 lb/ft³-day

VSLR = Volatile Solids Loading Rate (lb/1000 ft³-day)

Minimum Treatment Volume in Primary Lagoon				
Breed: Holstein	Net VS Loading (lb/day)	VSLR (lb/ft ³ -day)[1]		MTV (ft ³)
Milk Cows	15,088	÷ 0.011	=	1,371,591
Dry Cow	1,306	÷ 0.011	=	118,764
Heifer (15 to 24 months)	1,448	÷ 0.011	=	131,673
Heifer (7 to 14 months)	470	÷ 0.011	=	42,764
Heifer (3 to 6 months)	194	÷ 0.011	=	17,673
Calf (under 3 months)	0	÷ 0.011	=	0
Bulls	0	÷ 0.011	=	0
Total for Dairy				1,682,464

[1] VSLR for an anaerobic treatment lagoon in San Joaquin Valley would be 6.5 lb VS/1000 ft³-day to 11 lb VS/1000 ft³-day according to the NRCS and USDA AWTFH. Based on phone conversation with Matt Summers (USDA) on July 14, 2006; he suggested that the 11 lb VS/1000 ft³-day

Lagoon Design Check in Accordance with NRCS Guideline #359

Hydraulic Retention Time (HRT) Calculation

The anaerobic treatment lagoon and covered lagoon anaerobic digester must be designed to provide sufficient Hydraulic Retention Time (HRT) to adequately treat the waste entering the lagoon and to allow environmentally safe utilization of this waste. The NRCS Technical Guide Code 365 – Anaerobic Digester – Ambient Temperature specifies a minimum HRT 38 days in the San Joaquin Valley.

The Hydraulic Retention Time (HRT) is calculated as follows:

$$HRT = MTV/HFR$$

where:

HFR = Hydraulic flow rate (1000ft³/day)

HRT = Hydraulic Retention Time (day)

The Hydraulic Flow Rate is Calculated below

Type	# of cows	Amount of Manure*	HFR
Milk Cows	2,500	x 2.40	= 6,000 ft ³ /day
Dry Cows	400	x 1.30	= 520 ft ³ /day
Heifers (15-24 mo)	850	x 0.78	= 663 ft ³ /day
Heifers (7-14 mo)	400	x 0.78	= 312 ft ³ /day
Heifers (3-6 mo)	300	x 0.30	= 90 ft ³ /day
Calves	0	x 0.15	= - ft ³ /day
Bulls	0	x 1.30	= - ft ³ /day
Total	4,450		= 7,585 ft³/day
Fresh water per milk cow used in flush at milk parlor		50	gal/day

*Table 1.b - Section 3 of ASAE D384.2 (March 2005). The calf manure was estimated to be 1/2 of the calf number found in the table, since the average weight of these calves is approx. 1/2 of the calves identified in the table.

Sludge Accumulation Volume

The sludge accumulation volume accounts for the solids contained in the manure that cannot be fully digested by bacteria and that gradually settle to the bottom of the lagoon as sludge. The sludge accumulation volume for lagoon systems without solids separation can be calculated from the USDA Field Handbook. However, there are no accepted guidelines for calculating the sludge accumulation volume for lagoon systems with solids separation, but many designers of digester expect it to be minimal.

This facility has an efficient solids separation system consisting prior to the anaerobic treatment lagoon system. The separation system will remove a large portion of the fibers, lignin, cellulose, and other fibrous materials from the manure. These are the materials that would otherwise cause sludge accumulation from the lack of digestion in a lagoon or digester. Because fibrous materials and other solids will not enter the lagoon system, the sludge accumulation volume required will be minimized and can be considered negligible.

Nevertheless, the primary lagoon will have sufficient space remaining for sludge accumulation, as shown by the following calculation:

$$\text{SAV} = \text{VPL} - \text{MTV}$$

Where:

- SAV = Sludge Accumulation Volume (ft³)
- VPL = total Volume of Primary Lagoon (ft³)
- MTV = Minimum Treatment Volume (ft³)

$$\begin{aligned} \text{SAV} &= \text{VPL} - \text{MTV} \\ \text{SAV} &= 3,936,109 - 1,682,464 = 2,253,645 \text{ (ft}^3\text{)} \end{aligned}$$

Lagoon Design Check in Accordance with NRCS Guideline #359 Cont.

Formula:

Gallon		x		ft ³
Milk Cow*Day	#	Milk Cows		day
			gallon	

Total HFR:

50 gal	2500 milk-cows	x		ft ³	+	7,585	ft ³
milk-cow*-day			7.48	gal			day
					=	24,296.2	ft ³ /day

Formula:

MTV (ft ³)	/	(day)	=
		HFR (ft ³)	

HRT:

1,682,464 ft ³		24,296.2 ft ³	day	=	69.2479302	days
---------------------------	--	--------------------------	-----	---	------------	------

Appendix J

QNEC

Quarterly Net Emissions Change (QNEC)

The Quarterly Net Emissions Change is used to complete the emission profile screen for the District's PAS database. The QNEC shall be calculated as follows:

QNEC = PE2 - PE1, where:

- QNEC = Quarterly Net Emissions Change for each emissions unit, lb/qtr
- PE2 = Post-Project Potential to Emit for each emissions unit, lb/qtr
- PE1 = Pre-Project Potential to Emit for each emissions unit, lb/qtr

The quarterly PE values are calculated as follows: PE (lb/yr) ÷ 4 (qtr/yr)

Using the annual PE2 and PE1 values previously calculated, the QNEC (lb/qtr) for each permit unit is shown below:

Milking Parlor						
	NOx	SOx	PM10	CO	VOC	NH3
Annual PE2 (lb/yr)	0	0	0	0	1,000	342
Daily PE2 (lb/day)	0.0	0.0	0.0	0.0	2.7	0.9
Quarterly Net Emissions Change (lb/qtr)	1:	0.0	0.0	0.0	110.0	37.6
	2:	0.0	0.0	0.0	110.0	37.6
	3:	0.0	0.0	0.0	110.0	37.6
	4:	0.0	0.0	0.0	110.0	37.6

Cow Housing						
	NOx	SOx	PM10	CO	VOC	NH3
Annual PE2 (lb/yr)	0	0	4,664	0	33,497	65,686
Daily PE2 (lb/day)	0.0	0.0	12.9	0.0	91.7	180.0
Quarterly Net Emissions Change (lb/qtr)	1:	0.0	-2,236.8	0.0	3,324.8	6,785.0
	2:	0.0	-2,236.8	0.0	3,324.8	6,785.0
	3:	0.0	-2,236.8	0.0	3,324.8	6,785.0
	4:	0.0	-2,236.8	0.0	3,324.8	6,785.0

Liquid Manure Handling							
	NOx	SOx	PM10	CO	VOC	NH3	H2S
Annual PE2 (lb/yr)	0	0	0	0	4,912	15,226	368
Daily PE2 (lb/day)	0.0	0.0	0.0	0.0	13.5	41.7	1
Quarterly Net Emissions Change (lb/qtr)	1:	0.0	0.0	0.0	-46.1	268.5	0.0
	2:	0.0	0.0	0.0	-46.1	268.5	0.0
	3:	0.0	0.0	0.0	-46.1	268.5	0.0
	4:	0.0	0.0	0.0	-46.1	268.5	0.0

Solid Manure Handling						
	NOx	SOx	PM10	CO	VOC	NH3
Annual PE2 (lb/yr)	0	0	0	0	1,184	8,810
Daily PE2 (lb/day)	0.0	0.0	0.0	0.0	3.2	24.2
Quarterly Net Emissions Change (lb/qtr)	1:	0.0	0.0	0.0	48.4	877.9
	2:	0.0	0.0	0.0	48.4	877.9
	3:	0.0	0.0	0.0	48.4	877.9
	4:	0.0	0.0	0.0	48.4	877.9

Feed Storage and Handling						
	NOx	SOx	PM10	CO	VOC	NH3
Annual PE2 (lb/yr)	0	0	0	0	43,514	0
Daily PE2 (lb/day)	0.0	0.0	0.0	0.0	119.2	0.0
Quarterly Net Emissions Change (lb/qtr)	1:	0.0	0.0	0.0	1,414.4	0.0
	2:	0.0	0.0	0.0	1,414.4	0.0
	3:	0.0	0.0	0.0	1,414.4	0.0
	4:	0.0	0.0	0.0	1,414.4	0.0