



February 25, 2026

Mr. Gary Beltrami
E&J Gallo Winery - Turner Road Vintners
4614 W Turner Rd
Lodi, CA 95242

Re: Notice of Final Action - Title V Permit Renewal
Facility Number: N-4939
Project Number: N-1240895

Dear Mr. Beltrami:

The District has issued the Final Renewed Title V Permit for E&J Gallo Winery - Turner Road Vintners (see enclosure). The preliminary decision for this project was made on January 7, 2026. No comments were received following the District's preliminary decision on this project.

The public notice for issuance of the Final Title V Permit will be posted on the District's website (<https://valleyair.org/>).

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

FOR 
Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: EPA Region 9 Air Permitting Manager (w/enclosure) via EPS

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

San Joaquin Valley Air Pollution Control District

FACILITY: N-4939-0-4

EXPIRATION DATE: 08/31/2029

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; and San Joaquin County Rule 110] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; and San Joaquin County Rule 110] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-0-4 : 2/25/2026 2:12:20 PM -- ANSARIZ

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (04/16/20) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (04/16/20) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (04/16/20). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/21/2023) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: San Joaquin County Rule 401, San Joaquin County Rule 110, and San Joaquin County Rule 202. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (04/16/20); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (9/21/2023); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin November 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
43. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit
44. Operator shall achieve Required Annual Emissions Reductions (RAER) equal to at least 35% of the winery's Baseline Fermentation Emissions (BFE). [District Rule 4694]
45. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
46. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1 [District Rule 4694]
47. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
48. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-1-6

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

244 BHP CUMMINS MODEL 6BTA-5.9 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP (NORTH)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, and 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
6. NOx emissions shall not exceed 6.63 g/hp-hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The PM10 emissions rate shall not exceed 0.25 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District NSR Rule] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 66 hours per calendar year. [District Rule 2201, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-1-6 : 2/25/2026 2:12:25 PM -- ANSARIZ

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR Subpart ZZZZ]
13. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63.6603/66.6640 Table 2d, Row 1.a] Federally Enforceable Through Title V Permit
14. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 1.b] Federally Enforceable Through Title V Permit
15. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 1.c] Federally Enforceable Through Title V Permit
16. The permittee shall keep records of the maintenance conducted on the engine. [40 CFR 63.6655(e)] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-2-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,400 GALLON NOMINAL (14,384 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 24

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-3-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,400 GALLON NOMINAL (14,395 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 25

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-4-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,500 GALLON NOMINAL (14,510 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 19

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-5-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,500 GALLON NOMINAL (14,530 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 20

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-6-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,500 GALLON NOMINAL (14,467 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 22

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-7-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,500 GALLON NOMINAL (14,470 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 23

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-8-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,600 GALLON NOMINAL (14,597 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 18

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-9-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,700 GALLON NOMINAL (14,653 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 21

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-10-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

27,900 GALLON NOMINAL (27,885 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 15

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-11-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

27,900 GALLON NOMINAL (27,862 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 16

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-11-7 : 2/25/2026 2:13:13 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-12-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

28,000 GALLON NOMINAL (28,033 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 17

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-13-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

28,300 GALLON NOMINAL (28,250 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 14

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-13-7 : 2/25/2026 2:13:24 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-14-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 101

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-15-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 102

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-16-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE STORAGE TANK 103

PERMIT UNIT REQUIREMENTS

1. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-17-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 104

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-18-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 105

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-19-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 106

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-19-7 : 2/25/2026 2:13:53 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-20-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 107

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-20-7 : 2/25/2026 2:13:59 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-21-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,300 GALLON NOMINAL (33,253 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 108

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-22-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

33,600 GALLON NOMINAL (33,595 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 128

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-23-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,500 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 109

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-24-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,000 GALLON NOMINAL (35,000 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 126

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-24-7 : 2/25/2026 2:14:17 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-25-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,000 GALLON NOMINAL (35,000 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 129

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-25-7 : 2/25/2026 2:14:22 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-26-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,000 GALLON NOMINAL (35,000 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 131

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-27-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,000 GALLON NOMINAL (35,000 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 132

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-28-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 110

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-29-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 111

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-30-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 112

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-31-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 113

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-32-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 114

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-33-6

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 115

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-34-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 116

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-35-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 117

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-35-7 : 2/25/2026 1:19:02 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-36-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 118

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-37-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 119

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-38-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 120

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-39-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 121

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-40-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 122

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-41-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 123

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-42-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 124

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-43-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 125

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-44-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

34,500 GALLON NOMINAL (34,473 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 127

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-45-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,500 GALLON NOMINAL (35,500 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 130

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-46-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

35,700 GALLON NOMINAL (35,700 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 133

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-46-7 : 2/25/2026 1:19:57 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-47-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,100 GALLON NOMINAL (59,131 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 11

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-48-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,401 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 60

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-49-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,300 GALLON NOMINAL (59,263 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 9

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-49-7 : 2/25/2026 1:20:14 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-50-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,551 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 10

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-51-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,573 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 12

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-52-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,442 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 64

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-53-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,540 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 65

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-54-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,368 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 8

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-55-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,487 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 34

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-56-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,452 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 62

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-57-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,595 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 63

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-58-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,446 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 2

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-59-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,470 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 4

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-59-7 : 2/25/2026 1:21:04 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-60-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,407 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 6

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-61-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,354 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 7

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-62-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,400 GALLON NOMINAL (59,419 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 13

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-63-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,522 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 3

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-64-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,639 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 30

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-65-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,500 GALLON NOMINAL (59,517 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 47

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-66-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,626 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 59

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-67-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,733 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 26

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-68-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 29

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-69-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,800 GALLON NOMINAL (59,842 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 33

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-70-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,600 GALLON NOMINAL (59,606 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 44

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-71-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,688 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 1

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-72-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,900 GALLON NOMINAL (59,930 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 32

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-73-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,000 GALLON NOMINAL (59,960 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 37

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-74-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,717 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 43

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-75-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,679 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 48

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-75-7 : 2/25/2026 1:22:18 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-76-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,800 GALLON NOMINAL (59,820 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 61

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-77-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,800 GALLON NOMINAL (59,750 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 28

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-77-7 : 2/25/2026 1:22:28 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-78-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,000 GALLON NOMINAL (60,024 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 38

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-79-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,800 GALLON NOMINAL (59,779 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 45

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-79-7 : 2/25/2026 1:22:37 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-80-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,000 GALLON NOMINAL (60,034 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 58

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-80-7 : 2/25/2026 1:22:42 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-81-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,900 GALLON NOMINAL (59,856 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 66

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-82-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,800 GALLON NOMINAL (59,810 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 5

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-83-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,000 GALLON NOMINAL (59,997 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 46

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-83-7 : 2/25/2026 1:22:55 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-84-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,000 GALLON NOMINAL (59,964 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 31

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-85-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,100 GALLON NOMINAL (60,089 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 35

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-86-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,200 GALLON NOMINAL (60,230 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 27

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-87-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,400 GALLON NOMINAL (60,409 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 36

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-88-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,500 GALLON NOMINAL (62,454 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 42

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-88-7 : 2/25/2026 1:23:17 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-89-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,770 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 41

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-89-7 : 2/25/2026 1:23:22 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-90-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

63,000 GALLON NOMINAL (62,953 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 40

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-91-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

63,000 GALLON NOMINAL (62,994 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 39

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-92-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

123,000 GALLON NOMINAL (122,983 GALLON GAUGE) NOMINAL CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 68

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-93-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

123,700 GALLON NOMINAL (123,663 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 70

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-94-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,900 GALLON NOMINAL (122,947 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 67

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-94-7 : 2/25/2026 1:23:45 PM -- ANSARIZ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-95-7

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

123,700 GALLON NOMINAL (123,663 GALLON GAUGE) CONCRETE ENCLOSED TOP RED AND WHITE WINE STORAGE TANK 69

PERMIT UNIT REQUIREMENTS

1. The storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds 10% of the maximum allowable working pressure of the tank. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The daily VOC emissions rate for wine storage shall not exceed 0.212 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the 12-month rolling average total fermentation and storage emissions from the facility, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-96-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

355,200 GALLON NOMINAL (355,228 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 92 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-96-5 : 2/25/2026 1:23:55 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-97-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

355,200 GALLON NOMINAL (355,228 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 93 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-97-5 : 2/25/2026 1:23:59 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-98-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

5,900 GALLON NOMINAL (5,890 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-98-5 : 2/25/2026 1:24:04 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-99-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 217 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-99-5 : 2/25/2026 1:24:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-100-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 218 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-100-5 : 2/25/2026 1:24:15 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-101-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 219 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-101-5 : 2/25/2026 1:24:21 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-102-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 220 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-102-5 : 2/25/2026 1:24:26 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-103-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 229 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-103-5 : 2/25/2026 1:24:30 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-104-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 230 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-104-5 : 2/25/2026 1:24:36 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-105-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 231 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-105-5 : 2/25/2026 1:24:41 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-106-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,000 GALLON NOMINAL (6,991 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 232 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-106-5 : 2/25/2026 1:24:46 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-107-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 198 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-107-5 : 2/25/2026 1:24:51 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-108-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 199 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-108-5 : 2/25/2026 1:24:55 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-109-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 200 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-109-5 : 2/25/2026 1:25:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-110-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 233 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-110-5 : 2/25/2026 1:25:04 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-111-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 234 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-111-5 : 2/25/2026 1:25:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-112-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

7,100 GALLON NOMINAL (7,071 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 235 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-112-5 : 2/25/2026 1:25:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-113-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 365 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-113-5 : 2/25/2026 1:25:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-114-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 366 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-114-5 : 2/25/2026 1:25:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-115-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 367 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-115-5 : 2/25/2026 1:25:28 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-116-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 368 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-116-5 : 2/25/2026 1:25:33 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-117-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 369 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-117-5 : 2/25/2026 1:25:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-118-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 370 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-118-5 : 2/25/2026 1:25:43 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-119-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 371 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-119-5 : 2/25/2026 1:25:48 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-120-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,100 GALLON NOMINAL (10,098 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 372 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-120-5 : 2/25/2026 1:25:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-121-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,300 GALLON NOMINAL (10,326 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 207 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-121-5 : 2/25/2026 1:25:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-122-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,300 GALLON NOMINAL (10,326 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 208 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-122-5 : 2/25/2026 1:26:01 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-123-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,300 GALLON NOMINAL (10,326 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 209 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-123-5 : 2/25/2026 1:26:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-124-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

10,300 GALLON NOMINAL (10,326 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 210 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-124-5 : 2/25/2026 1:26:12 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-125-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 236 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-125-5 : 2/25/2026 1:26:16 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-126-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 237 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-126-5 : 2/25/2026 1:26:22 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-127-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 238 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-127-5 : 2/25/2026 1:26:28 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-128-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 239 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-128-5 : 2/25/2026 1:26:33 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-129-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 240 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-129-5 : 2/25/2026 1:26:37 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-130-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 241 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-130-5 : 2/25/2026 1:26:42 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-131-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 242 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-131-5 : 2/25/2026 1:26:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-132-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,000 GALLON NOMINAL (13,982 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 243 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-132-5 : 2/25/2026 1:26:51 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-133-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 221 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-133-5 : 2/25/2026 1:26:58 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-134-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 222 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-134-5 : 2/25/2026 1:27:03 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-135-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 223 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-135-5 : 2/25/2026 1:27:09 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-136-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 224 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-136-5 : 2/25/2026 1:27:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-137-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 225 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-137-5 : 2/25/2026 1:27:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-138-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 226 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-138-5 : 2/25/2026 1:27:25 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-139-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 227 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-139-5 : 2/25/2026 1:27:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-140-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

14,300 GALLON NOMINAL (14,260 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 228 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-140-5 : 2/25/2026 1:27:37 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-141-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 361 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-141-5 : 2/25/2026 1:27:42 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-142-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 362 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-142-5 : 2/25/2026 1:27:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-143-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 363 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-143-5 : 2/25/2026 1:27:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-144-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 364 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-144-5 : 2/25/2026 1:27:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-145-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 373 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-145-5 : 2/25/2026 1:28:01 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-146-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 374 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-146-5 : 2/25/2026 1:28:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-147-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 375 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-147-5 : 2/25/2026 1:28:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-148-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,400 GALLON NOMINAL (20,427 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 376 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-148-5 : 2/25/2026 1:28:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-149-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,500 GALLON NOMINAL (20,496 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 205 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-149-5 : 2/25/2026 1:28:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-150-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,500 GALLON NOMINAL (20,496 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 206 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-150-5 : 2/25/2026 1:28:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-151-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,500 GALLON NOMINAL (20,496 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 211 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-151-5 : 2/25/2026 1:28:29 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-152-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,500 GALLON NOMINAL (20,496 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 212 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-152-5 : 2/25/2026 1:28:33 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-153-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 201 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-153-5 : 2/25/2026 1:28:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-154-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 202 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-154-5 : 2/25/2026 1:28:45 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-155-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 203 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-155-5 : 2/25/2026 1:28:50 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-156-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 204 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-156-5 : 2/25/2026 1:28:54 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-157-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 213 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-157-5 : 2/25/2026 1:29:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-158-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 214 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-158-5 : 2/25/2026 1:29:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-159-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 215 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-159-5 : 2/25/2026 1:29:12 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-160-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,300 GALLON NOMINAL (31,291 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 216 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-160-5 : 2/25/2026 1:29:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-161-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-161-5 : 2/25/2026 1:29:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-162-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 427 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-162-5 : 2/25/2026 1:29:28 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-163-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 428 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-163-5 : 2/25/2026 1:29:34 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-164-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 429 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-164-5 : 2/25/2026 1:29:41 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-165-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 430 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-165-5 : 2/25/2026 1:29:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-166-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 431 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-166-5 : 2/25/2026 1:29:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-167-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 432 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-167-5 : 2/25/2026 1:29:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-168-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 433 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-168-5 : 2/25/2026 1:30:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-169-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 434 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-169-5 : 2/25/2026 1:30:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-170-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

31,000 GALLON NOMINAL (30,382 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 435 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-170-5 : 2/25/2026 1:30:11 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-171-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-171-5 : 2/25/2026 1:30:16 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-172-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 348 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-172-5 : 2/25/2026 1:30:21 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-173-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 349 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-173-5 : 2/25/2026 1:30:25 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-174-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 350 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-174-5 : 2/25/2026 1:30:30 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-175-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 351 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-175-5 : 2/25/2026 1:30:35 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-176-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-176-5 : 2/25/2026 1:30:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-177-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-177-5 : 2/25/2026 1:30:44 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-178-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-178-5 : 2/25/2026 1:30:48 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-179-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-179-5 : 2/25/2026 1:30:53 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-180-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-180-5 : 2/25/2026 1:30:58 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-181-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 357 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-181-5 : 2/25/2026 1:31:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-182-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 358 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-182-5 : 2/25/2026 1:31:09 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-183-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 359 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-183-5 : 2/25/2026 1:31:15 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-184-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 360 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-184-5 : 2/25/2026 1:31:21 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-185-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 377 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-185-5 : 2/25/2026 1:31:26 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-186-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 378 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-186-5 : 2/25/2026 1:31:30 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-187-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 379 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-187-5 : 2/25/2026 1:31:35 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-188-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

41,000 GALLON NOMINAL (41,009 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 380 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-188-5 : 2/25/2026 1:31:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-189-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,200 GALLON NOMINAL (60,155 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-189-5 : 2/25/2026 1:31:44 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-190-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,200 GALLON NOMINAL (60,155 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-190-5 : 2/25/2026 1:31:50 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-191-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,800 GALLON NOMINAL (60,841 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 71 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-191-5 : 2/25/2026 1:31:56 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-192-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,800 GALLON NOMINAL (60,841 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 72 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-192-5 : 2/25/2026 1:32:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-193-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,800 GALLON NOMINAL (60,841 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-193-5 : 2/25/2026 1:32:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-194-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,800 GALLON NOMINAL (60,841 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-194-5 : 2/25/2026 1:32:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-195-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,800 GALLON NOMINAL (60,841 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 75 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-195-5 : 2/25/2026 1:32:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-196-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 436 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-196-5 : 2/25/2026 1:32:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-197-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 437 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-197-5 : 2/25/2026 1:32:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-198-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 438 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-198-5 : 2/25/2026 1:32:29 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-199-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 439 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-199-5 : 2/25/2026 1:32:33 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-200-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 440 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-200-5 : 2/25/2026 1:32:38 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-201-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 441 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-201-5 : 2/25/2026 1:32:42 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-202-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 442 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-202-5 : 2/25/2026 1:32:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-203-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

59,700 GALLON NOMINAL (59,653 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 443 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-203-5 : 2/25/2026 1:32:51 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-204-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 381 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-204-5 : 2/25/2026 1:32:58 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-205-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 382 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-205-5 : 2/25/2026 1:33:03 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-206-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 383 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-206-5 : 2/25/2026 1:33:07 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-207-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 384 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-207-5 : 2/25/2026 1:33:13 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-208-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 385 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-208-5 : 2/25/2026 1:33:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-209-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 386 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-209-5 : 2/25/2026 1:33:22 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-210-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 387 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-210-5 : 2/25/2026 1:33:27 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-211-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 388 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-211-5 : 2/25/2026 1:33:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-212-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 389 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-212-5 : 2/25/2026 1:33:36 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-213-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 390 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-213-5 : 2/25/2026 1:33:41 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-214-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 391 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-214-5 : 2/25/2026 1:33:46 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-215-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 392 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-215-5 : 2/25/2026 1:33:51 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-216-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 393 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-216-5 : 2/25/2026 1:33:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-217-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 394 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-217-5 : 2/25/2026 1:34:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-218-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 395 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-218-5 : 2/25/2026 1:34:07 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-219-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 396 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-219-5 : 2/25/2026 1:34:13 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-220-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 397 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-220-5 : 2/25/2026 1:34:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-221-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 398 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-221-5 : 2/25/2026 1:34:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-222-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 399 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-222-5 : 2/25/2026 1:34:28 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-223-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-223-5 : 2/25/2026 1:34:35 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-224-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-224-5 : 2/25/2026 1:34:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-225-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-225-5 : 2/25/2026 1:34:46 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-226-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-226-5 : 2/25/2026 1:34:50 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-227-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-227-5 : 2/25/2026 1:34:55 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-228-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-228-5 : 2/25/2026 1:35:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-229-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-229-5 : 2/25/2026 1:35:05 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-230-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-230-5 : 2/25/2026 1:35:09 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-231-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-231-5 : 2/25/2026 1:35:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-232-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 410 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-232-5 : 2/25/2026 1:35:20 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-233-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-233-5 : 2/25/2026 1:35:25 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-234-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-234-5 : 2/25/2026 1:35:32 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-235-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

60,600 GALLON NOMINAL (60,603 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-235-5 : 2/25/2026 1:35:36 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-236-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 329 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-236-5 : 2/25/2026 1:35:41 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-237-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 330 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-237-5 : 2/25/2026 1:35:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-238-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-238-5 : 2/25/2026 1:35:53 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-239-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-239-5 : 2/25/2026 1:35:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-240-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-240-5 : 2/25/2026 1:36:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-241-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-241-5 : 2/25/2026 1:36:08 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-242-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-242-5 : 2/25/2026 1:36:12 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-243-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-243-5 : 2/25/2026 1:36:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-244-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-244-5 : 2/25/2026 1:36:23 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-245-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 338 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-245-5 : 2/25/2026 1:36:27 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-246-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 339 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-246-5 : 2/25/2026 1:36:32 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-247-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 340 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-247-5 : 2/25/2026 1:36:38 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-248-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-248-5 : 2/25/2026 1:36:43 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-249-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-249-5 : 2/25/2026 1:36:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-250-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-250-5 : 2/25/2026 1:36:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-251-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-251-5 : 2/25/2026 1:36:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-252-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-252-5 : 2/25/2026 1:37:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-253-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

62,800 GALLON NOMINAL (62,772 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-253-5 : 2/25/2026 1:37:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-254-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

69,700 GALLON NOMINAL (56,718 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-254-5 : 2/25/2026 1:37:13 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-255-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

69,700 GALLON NOMINAL (56,718 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-255-5 : 2/25/2026 1:37:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-256-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

69,700 GALLON NOMINAL (56,718 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-256-5 : 2/25/2026 1:37:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-257-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

69,700 GALLON NOMINAL (56,718 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-257-5 : 2/25/2026 1:37:30 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-258-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

69,700 GALLON NOMINAL (56,718 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-258-5 : 2/25/2026 1:37:37 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-259-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-259-5 : 2/25/2026 1:37:41 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-260-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 444 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-260-5 : 2/25/2026 1:37:46 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-261-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 445 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-261-5 : 2/25/2026 1:37:51 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-262-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 446 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-262-5 : 2/25/2026 1:37:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-263-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 447 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-263-5 : 2/25/2026 1:38:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-264-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 448 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-264-5 : 2/25/2026 1:38:08 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-265-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 449 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-265-5 : 2/25/2026 1:38:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-266-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 450 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-266-5 : 2/25/2026 1:38:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-267-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 451 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-267-5 : 2/25/2026 1:38:25 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-268-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 452 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-268-5 : 2/25/2026 1:38:29 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-269-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 453 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-269-5 : 2/25/2026 1:38:34 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-270-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,200 GALLON NOMINAL (119,549 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 454 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-270-5 : 2/25/2026 1:38:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-271-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-271-5 : 2/25/2026 1:38:45 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-272-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-272-5 : 2/25/2026 1:38:50 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-273-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-273-5 : 2/25/2026 1:38:55 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-274-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 417 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-274-5 : 2/25/2026 1:38:59 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-275-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 418 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-275-5 : 2/25/2026 1:39:04 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-276-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 419 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-276-5 : 2/25/2026 1:39:08 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-277-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 420 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-277-5 : 2/25/2026 1:39:13 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-278-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-278-5 : 2/25/2026 1:39:17 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-279-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-279-5 : 2/25/2026 1:39:22 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-280-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-280-5 : 2/25/2026 1:39:26 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-281-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-281-5 : 2/25/2026 1:39:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-282-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

124,600 GALLON NOMINAL (124,607 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-282-5 : 2/25/2026 1:39:35 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-283-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 315 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-283-5 : 2/25/2026 1:39:40 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-284-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 316 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-284-5 : 2/25/2026 1:39:46 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-285-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 317 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-285-5 : 2/25/2026 1:39:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-286-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 318 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-286-5 : 2/25/2026 1:39:58 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-287-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 319 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-287-5 : 2/25/2026 1:40:03 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-288-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 320 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-288-5 : 2/25/2026 1:40:09 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-289-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-289-5 : 2/25/2026 1:40:13 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-290-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-290-5 : 2/25/2026 1:40:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-291-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-291-5 : 2/25/2026 1:40:23 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-292-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-292-5 : 2/25/2026 1:40:28 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-293-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-293-5 : 2/25/2026 1:40:33 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-294-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-294-5 : 2/25/2026 1:40:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-295-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-295-5 : 2/25/2026 1:40:44 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-296-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

129,400 GALLON NOMINAL (129,357 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 328 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-296-5 : 2/25/2026 1:40:49 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-297-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,008 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 80 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-297-5 : 2/25/2026 1:40:54 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-298-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,008 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 81 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-298-5 : 2/25/2026 1:40:59 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-299-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,048 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 82 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-299-5 : 2/25/2026 1:41:03 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-300-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,008 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 83 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-300-5 : 2/25/2026 1:41:08 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-301-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,008 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 84 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-301-5 : 2/25/2026 1:41:14 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-302-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,000 GALLON NOMINAL (130,048 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 85 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-302-5 : 2/25/2026 1:41:19 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-303-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,300 GALLON NOMINAL (130,288 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 76 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-303-5 : 2/25/2026 1:41:24 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-304-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,300 GALLON NOMINAL (130,288 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 77 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-304-5 : 2/25/2026 1:41:29 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-305-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,300 GALLON NOMINAL (130,288 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 78 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-305-5 : 2/25/2026 1:41:34 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-306-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

130,300 GALLON NOMINAL (130,288 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 79 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-306-5 : 2/25/2026 1:41:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-307-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-307-5 : 2/25/2026 1:41:43 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-308-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-308-5 : 2/25/2026 1:41:48 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-309-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-309-5 : 2/25/2026 1:41:53 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-310-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-310-5 : 2/25/2026 1:41:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-311-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 308 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-311-5 : 2/25/2026 1:42:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-312-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 309 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-312-5 : 2/25/2026 1:42:07 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-313-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 310 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-313-5 : 2/25/2026 1:42:12 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-314-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,800 GALLON NOMINAL (216,776 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 311 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-314-5 : 2/25/2026 1:42:18 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-315-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-315-5 : 2/25/2026 1:42:22 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-316-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-316-5 : 2/25/2026 1:42:27 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-317-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-317-5 : 2/25/2026 1:42:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-318-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 312 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-318-5 : 2/25/2026 1:42:37 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-319-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 313 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-319-5 : 2/25/2026 1:42:43 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-320-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

216,100 GALLON NOMINAL (216,096 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 314 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-320-5 : 2/25/2026 1:42:48 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-321-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 86 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-321-5 : 2/25/2026 1:42:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-322-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 87 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-322-5 : 2/25/2026 1:42:57 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-323-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 88 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-323-5 : 2/25/2026 1:43:02 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-324-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 89 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-324-5 : 2/25/2026 1:43:06 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-325-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 90 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-325-5 : 2/25/2026 1:43:11 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-326-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

220,000 GALLON NOMINAL (215,594 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 91 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-326-5 : 2/25/2026 1:43:16 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-327-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 456 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-327-5 : 2/25/2026 1:43:20 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-328-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 457 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-328-5 : 2/25/2026 1:43:27 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-329-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 458 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-329-5 : 2/25/2026 1:43:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-330-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 459 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-330-5 : 2/25/2026 1:43:37 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-331-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 460 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-331-5 : 2/25/2026 1:43:43 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-332-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 461 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-332-5 : 2/25/2026 1:43:49 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-333-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 462 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-333-5 : 2/25/2026 1:43:54 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-334-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 463 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-334-5 : 2/25/2026 1:43:58 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-335-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 464 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-335-5 : 2/25/2026 1:44:04 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-336-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

248,400 GALLON NOMINAL (248,387 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 465 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-336-5 : 2/25/2026 1:44:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-337-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 466 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-337-5 : 2/25/2026 1:44:15 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-338-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 467 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-338-5 : 2/25/2026 1:44:21 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-339-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 468 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-339-5 : 2/25/2026 1:44:26 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-340-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 469 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-340-5 : 2/25/2026 1:44:32 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-341-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 470 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-341-5 : 2/25/2026 1:44:36 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-342-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 471 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-342-5 : 2/25/2026 1:44:40 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-343-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 472 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-343-5 : 2/25/2026 1:44:45 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-344-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

351,408 GALLON NOMINAL (351,408 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 473 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-344-5 : 2/25/2026 1:44:49 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-346-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,913 GALLON NOMINAL (122,913 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-346-5 : 2/25/2026 1:44:55 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-347-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,913 GALLON NOMINAL (122,913 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-347-5 : 2/25/2026 1:45:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-348-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,913 GALLON NOMINAL (122,913 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-348-5 : 2/25/2026 1:45:05 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-349-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

122,913 GALLON NOMINAL (122,913 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-349-5 : 2/25/2026 1:45:10 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-350-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,758 GALLON NOMINAL (20,758 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-350-5 : 2/25/2026 1:45:15 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-351-5

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

20,758 GALLON NOMINAL (20,758 GALLON GAUGE) STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-351-5 : 2/25/2026 1:45:21 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-352-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

2,000 GALLON NOMINAL (2,050 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 522) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-352-3 : 2/25/2026 1:45:26 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-353-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

2,000 GALLON NOMINAL (1,960 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 523) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-353-3 : 2/25/2026 1:45:31 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-354-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

6,000 GALLON NOMINAL (6,284 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 514) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-354-3 : 2/25/2026 1:45:38 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-355-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

6,000 GALLON NOMINAL (6,284 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 515) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-355-3 : 2/25/2026 1:45:42 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-356-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

8,000 GALLON NOMINAL (8,050 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 516) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-356-3 : 2/25/2026 1:45:47 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-357-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

8,000 GALLON NOMINAL (8,050 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 517) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-357-3 : 2/25/2026 1:45:52 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-358-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

12,000 GALLON NOMINAL (12,049 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 519)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-358-3 : 2/25/2026 1:45:56 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-359-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

12,000 GALLON NOMINAL (12,049 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 518)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-359-3 : 2/25/2026 1:46:00 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-360-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 292)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-360-3 : 2/25/2026 1:46:05 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-361-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 293)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-361-3 : 2/25/2026 1:46:11 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-362-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 294)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-362-3 : 2/25/2026 1:46:17 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-363-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 295)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-363-3 : 2/25/2026 1:46:22 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-364-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 296)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-364-3 : 2/25/2026 1:46:27 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-365-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 297)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-365-3 : 2/25/2026 1:46:34 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-366-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 298)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-366-3 : 2/25/2026 1:46:39 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-367-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

185,000 GALLON NOMINAL (186,690 GALLON GAUGE) WINE FERMENTATION AND STORAGE TANK (TANK # 299)
WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed two times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-367-3 : 2/25/2026 1:46:44 PM -- ANSARIZ

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of the 12-month rolling average total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-368-2

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

700,000 GALLON NOMINAL (733,567 GALLON GAUGE) WINE STORAGE TANK (TANK # 474) WITH
PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-368-2 : 2/25/2026 1:46:48 PM -- ANSARIZ

11. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling average total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-369-2

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

700,000 GALLON NOMINAL (729,985 GALLON GAUGE) WINE STORAGE TANK (TANK # 475) WITH
PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-369-2 : 2/25/2026 1:46:53 PM -- ANSARIZ

11. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling average total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-370-2

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

700,000 GALLON NOMINAL (731,794 GALLON GAUGE) WINE STORAGE TANK (TANK # 476) WITH
PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-370-2 : 2/25/2026 1:46:58 PM -- ANSARIZ

11. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling average total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-371-2

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

700,000 GALLON NOMINAL (730,633 GALLON GAUGE) WINE STORAGE TANK (TANK # 477) WITH
PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-371-2 : 2/25/2026 1:47:03 PM -- ANSARIZ

11. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling average total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-372-2

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

700,000 GALLON NOMINAL (730,469 GALLON GAUGE) WINE STORAGE TANK (TANK # 478) WITH
PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month average basis, shall not exceed 259,738 lbs. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-372-2 : 2/25/2026 1:47:10 PM -- ANSARIZ

11. The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %, $a = -0.38194E-4$, $b = 0.97917E-2$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling average total storage emissions, including calculation methods and parameters used, shall be maintained and updated monthly. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-373-3

EXPIRATION DATE: 08/31/2029

EQUIPMENT DESCRIPTION:

175 BHP [INTERMITTENT] JOHN DEERE MODEL 6068HFC28 TIER 3 CERTIFIED DIESEL FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP (SOUTH)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801; 17 CCR 93115; and 40 CFR 60.4207(b)] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 40 CFR 60.4209(a)] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems". Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60.4211(f)] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall not be operated for maintenance and testing purposes between 7:30 a.m. and 3:30 p.m. on days when school is in session. [17 CCR 93115]
8. Emissions from this IC engine shall not exceed any of the following limits: 2.77 g-NOx/bhp-hr, 0.90 g-CO/bhp-hr, or 0.14 g-VOC/bhp-hr. [District Rule 2201; 13 CCR 2423 and 17 CCR 93115; and 40 CFR 60.4205(c) and 60.4211(c)] Federally Enforceable Through Title V Permit
9. Emissions from this IC engine shall not exceed 0.09 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102; 13 CCR 2423 and 17 CCR 93115; and 40 CFR 60.4205(c) and 60.4211(c)] Federally Enforceable Through Title V Permit
10. This engine and control device(s) must be operated and maintained according to the manufacturer's emission-related written instructions, and must achieve the specified emission standards over its entire life. [40 CFR 60.4206 and 60.4211] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-373-3 : 2/25/2026 2:15:08 PM -- ANSARIZ

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 60.4214(b)] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E&J GALLO WINERY - TURNER ROAD VINTNERS

Location: 4614 W TURNER RD, LODI, CA 95242

N-4939-373-3 : 2/25/2026 2:15:08 PM -- ANSARIZ