

May 12, 2026

William Holmes  
Darling Ingredients, Inc.  
PO Box 1608  
Turlock, CA 95381

**Re: Notice of Preliminary Decision – Title V Permit Renewal**  
**Facility Number: N-2107**  
**Project Number: N-1261178**


Dear Mr. Holmes:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Darling Ingredients, Inc. at 11946 Carpenter Rd, in Crows Landing.

The notice of preliminary decision for this project has been posted on the District's website ([www.valleyair.org](http://www.valleyair.org)). After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Nick Peirce, Permit Services Manager, at (209) 557-6400.

Sincerely,



Brian Clements  
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email  
cc: EPA Region 9 Air Permitting Manager (w/enclosure) via EPS

**Samir Sheikh**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: (661) 392-5500 FAX: (661) 392-5585

**SAN JOAQUIN VALLEY  
AIR POLLUTION CONTROL DISTRICT**

**Proposed Title V Permit Renewal Evaluation  
Darling Ingredients, Inc.  
N-2107**

**TABLE OF CONTENTS**

---

I.	PROPOSAL.....	1
II.	FACILITY LOCATION.....	1
III.	EQUIPMENT LISTING.....	2
IV.	GENERAL PERMIT TEMPLATE USAGE.....	2
V.	SCOPE OF EPA AND PUBLIC REVIEW.....	2
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS.....	2
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE.....	5
VIII.	PERMIT REQUIREMENTS.....	6
IX.	PERMIT SHIELD.....	177
X.	CALIFORNIA ENVIRONMENTAL QUALITY ACT.....	17
XI.	PERMIT CONDITIONS.....	18
XII.	ATTACHMENTS.....	18

# TITLE V PERMIT RENEWAL EVALUATION

## Animal Rendering Plant

**Engineer:** Jagmeet Kahlon  
**Date:** May 11, 2026

**Facility Number:** N-2107  
**Facility Name:** Darling Ingredients, Inc.  
**Mailing Address:** PO Box 1608  
Turlock, CA 95381

**Contact Name:** William Holmes  
**Title:** Director of Environmental Affairs  
**Phone:** (214) 790-4500

**Responsible Official:** William Holmes  
**Title:** Director of Environmental Affairs

**Project # :** N-1261178  
**Deemed Complete:** March 26, 2026

---

### I. PROPOSAL

Darling Ingredients, Inc. submitted a permit application on February 27, 2026 to renew their Title V permit. This application was submitted in a timely manner, that is, within 6 to 18 months prior to the permit expiration date, as required by Section 5.2 of District Rule 2520; therefore, all terms and conditions of the Title V permit shall remain in effect until the renewal permit will be issued pursuant to Section 8.3 of District Rule 2520. During this permit renewal project, the existing permits will be revised to include any updated or new requirements from applicable District, State and Federal rules that were adopted or amended since the issuance of the previous Title V permit renewal project that was finalized on June 2, 2022.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. This document also identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

### II. FACILITY LOCATION

The facility is located at 11946 Carpenter Rd, in Crows Landing, California.

### **III. EQUIPMENT LISTING**

A detailed facility printout listing all permitted equipment at the facility is included as **Attachment C**.

### **IV. GENERAL PERMIT TEMPLATE USAGE**

The applicant has requested to use the following model general permit templates:

#### **A. Template SJV-UM-03 Facility-wide Umbrella**

The applicant has requested to utilize template SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

### **V. SCOPE OF EPA AND PUBLIC REVIEW**

Certain segments of the proposed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

Conditions 3 through 22 and 26 through 40 in facility-wide permit requirement permit N-2107-0-6, including their underlying applicable requirements, originate from template SJV-UM-0-3 and are not subject to further EPA or public review.

### **VI. FEDERALLY ENFORCEABLE REQUIREMENTS**

#### **A. Rules Updated**

The following rules have been modified since the date the previous Title V renewal project was finalized on June 2, 2022:

- District Rule 2201, District New and Modified Stationary Source Review Rule (Amended April 20, 2023)

- District Rule 2520, Federally Mandated Operating Permits  
(Amended June 20, 2024)
- District Rule 4101, Visible Emissions  
(Amended April 16, 2026)
- District Rule 4601, Architectural Coatings  
(Amended April 16, 2020, EPA approval into SIP on December 22, 2022)
- District Rule 8051, Open Areas  
(Amended August 21, 2023)
- 40 CFR 63 Subpart DDDDD, National Emission Standards for Hazardous Air pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters  
(Last updated October 6, 2022)
- 40 CFR Part 82, Subpart F, Recycling and Emissions Reduction  
(Last updated June 13, 2024)

## **B. Rules Removed**

There are no applicable rules that were removed since the previous Title V renewal.

## **C. Rules Added**

None

## **D. Rules Not Updated**

- District Rule 1070, Inspections  
(Amended December 17, 1992)
- District Rule 1081, Source Sampling  
(Amended December 16, 1993)
- District Rule 1160, Emission Statements  
(Adopted November 18, 1992)
- District Rule 2010, Permits Required  
(Amended December 17, 1992)

- District Rule 2020, Exemptions  
(Amended December 18, 2014)
- District Rule 2031, Transfer of Permits  
(Amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications  
(Amended December 17, 1992)
- District Rule 2080, Conditional Approval  
(Amended December 17, 1992)
- District Rule 2410, Prevention of Significant Deterioration  
(Amended June 16, 2011)
- District Rule 4301, Fuel Burning Equipment  
(Amended December 17, 1992)
- District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2  
(Amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators, and Process Heaters – Phase 3 (Amended December 17, 2020)
- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr  
(Amended December 17, 2020)
- District Rule 4801, Sulfur Compounds  
(Amended December 17, 1992)
- District Rule 8011, General Requirements  
(Amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction and Other Earthmoving Activities  
(Amended August 19, 2004)

- District Rule 8031, Bulk Materials  
(Amended August 19, 2004)
- District Rule 8041, Carryout and Trackout  
(Amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads  
(Amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas  
(Amended September 16, 2004)
- 40 CFR 60 Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units  
(Amended February 16, 2012)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos  
(Amended July 20, 2004)
- 40 CFR 63 Subpart JJJJJJ, National Emission Standards for Hazardous Air pollutants for Industrial, Commercial, and Institutional Boilers Area Sources  
(Amended September 14, 2016)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners  
(Last updated March 24, 2021)

## **VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE**

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

### **A. Rules Added**

None

## **B. Rules Not Updated**

- District Rule 1100, Equipment Breakdown  
(Amended December 17, 1992)
- District Rule 2040, Applications  
(Amended December 17, 1992)
- District Rule 4102, Nuisance  
(Amended December 17, 1992)

## **VIII. PERMIT REQUIREMENTS**

The purpose of this evaluation is to review changes to federally enforceable requirements and to ensure the renewed operating permit contains conditions enforcing the requirements of all applicable federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the previous Title V permit.

### **District Rule 2201, New and Modified Stationary Source Review Rule**

District Rule 2201 has been amended since this facility's previous Title V permit was issued. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any new source review (NSR) permit actions have already been incorporated into the current Title V permit.

### **District Rule 4101, Visible Emissions**

The recent amendments to District Rule 4101 allow for alternative methods of becoming certified to accurately read visible emissions using EPA Method 9. The changes to the Rule do not affect any of the conditions on the Title V permits at this facility; therefore, no changes to the TV permit were required to address the amendments to District Rule 4101.

### **District Rule 2520, Federally Mandated Operating Permits**

This rule has been amended since this facility's previous Title V permit was issued. The June 2024 amendments removed Emergency Provisions from the rule to align the rule with US EPA Title V regulation and revised definitions for consistency with the Clean Air Act, federal regulations and District Rule 2201<sup>1</sup>.

---

<sup>1</sup> <https://ww2.valleyair.org/media/f1rl31kv/draft-2520-staff-report.pdf>

These rule amendments did not require any changes to existing permit conditions. Thus, continued compliance is expected.

#### Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

#### **District Rule 4601 - Architectural Coatings**

District Rule 4601 was last amended on April 16, 2020. EPA approved the amended rule for its inclusion in the State Implementation Plan (SIP) in December 2022.

The purpose of this rule is to limit VOC emissions from architectural coatings. This rule specifies architectural coatings storage, cleanup, and labeling requirements. This rule is applicable to any person who supplies, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating. This rule is applicable to any person who supplies, markets, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the San Joaquin Valley Air Pollution Control District.

As required by a September 2016 decision by the U.S. Court of Appeals for the Ninth Circuit in *Bahr v. U.S. Environmental Protection Agency*,<sup>2</sup> the April 16, 2020 amendments to District Rule 4601 added a contingency measure for the District's 2016 Ozone Plan that would remove the exemption for specific categories of coatings sold in small containers with a volume of one liter or less if EPA issues a finding that the San Joaquin Valley Air Basin has failed to attain, or to make reasonable further progress towards attainment of, the 2008 National Ambient Air Quality Standard (NAAQS) for ozone. The April 16, 2020 amendments to District Rule 4601 implemented provisions of the 2019 California Air Resources Board (ARB) Suggested Control Measure for Architectural Coatings,<sup>3</sup> including lowering VOC limits for several categories of architectural coatings, setting VOC limits for three new categories of architectural coatings, and adding new requirements for colorants.

---

<sup>2</sup>United States Court of Appeals for the Ninth Circuit (September 12, 2016) *Bahr v. U.S. Environmental Protection Agency*. <https://cdn.ca9.uscourts.gov/datastore/opinions/2016/09/12/14-72327.pdf>

<sup>3</sup>California Air Resources Board (May 2019) California Air Resources Board (CARB) Suggested Control Measure for Architectural Coatings. [https://ww2.arb.ca.gov/sites/default/files/2020-05/10602\\_scm\\_final.pdf](https://ww2.arb.ca.gov/sites/default/files/2020-05/10602_scm_final.pdf)

The primary effect of the April 16, 2020 amendments to District Rule 4601 was reducing VOC content limits required for specific categories of coatings and adding VOC content limits for specific categories of colorants. The previous VOC content limits of District Rule 4601 and the VOC content limits of coatings and colorants that became effective on and after January 1, 2022 are summarized below.

Section 5.1 - VOC Content Limits:

Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2, after the specified effective date in Table 1 or Table 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.

<b>Rule 4601, Table 1 - VOC Content Limits for Coatings<sup>1</sup></b>		
<b>COATING CATEGORY</b>	<b>Previous VOC Limit (g/l)</b>	<b>VOC Limit (g/l) Effective on and after 1/1/2022</b>
Flat Coatings	50	50
Nonflat Coatings	100	50
<b>Specialty Coatings</b>	-	-
Aluminum Roof Coatings	400	100
Basement Specialty Coatings	400	400
Bituminous Roof Coatings	50	50
Bituminous Roof Primers	350	350
Bond Breakers	350	350
Building Envelope Coatings	-	50
Concrete Curing Compounds	350	350
Concrete/Masonry Sealers	100	100
Driveway Sealers	50	50
Dry Fog Coatings	150	50
Faux Finishing Coatings	350	350
Fire Resistive Coatings	350	150
Floor Coatings	100	50
Form-Release Compounds	250	100
Graphic Arts Coatings (Sign Paints)	500	500
High Temperature Coatings	420	420
Industrial Maintenance Coatings	250	250
Low Solids Coatings <sup>2</sup>	120	120
Magnesite Cement Coatings	450	450
Mastic Texture Coatings	100	100
Metallic Pigmented Coatings	500	500

<b>Rule 4601, Table 1 - VOC Content Limits for Coatings<sup>1</sup></b>		
<b>COATING CATEGORY</b>	<b>Previous VOC Limit (g/l)</b>	<b>VOC Limit (g/l) Effective on and after 1/1/2022</b>
Multi-Color Coatings	250	250
Pre-Treatment Wash Primers	420	420
Primers, Sealers, and Undercoaters	100	100
Reactive Penetrating Sealers	350	350
Recycled Coatings	250	250
Roof Coatings	50	50
Rust Preventative Coatings	250	250
Shellacs:		
Clear	730	730
Opaque	550	550
Specialty Primers, Sealers, and Undercoaters	100	100
Stains	250	100
Interior Stains		250
Stone Consolidants	450	450
Swimming Pool Coatings	340	340
Tile and Stone Sealers		100
Traffic Marking Coatings	100	100
Tub and Tile Refinish Coatings	420	420
Waterproofing Membranes	250	100
Wood Coatings	275	275
Wood Preservatives	350	350
Zinc-Rich Primers	340	340

1. Limits are expressed as VOC Regulatory (except where noted otherwise), thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.
2. Units are grams of VOC per liter of coating, including water and exempt compounds, in accordance with Section 3.72.

<b>Rule 4601, Table 2 VOC Content Limits for Colorants<sup>1</sup></b>	
<b>Colorants Added To</b>	<b>VOC Limit (g/l) Effective on and after 1/1/2022</b>
Architectural Coatings, excluding Industrial Maintenance Coatings	50
Solvent Based Industrial Maintenance Coatings	600
Waterborne Industrial Maintenance Coatings	50
Wood Coatings	600

1. Limits are expressed as VOC Regulatory.

The following table lists draft renewed permit and condition numbers that ensure on-going compliance with this section:

Permit #	Condition #
N-2107-0-6	*23 through 25

\*The following conditions (23 through 25) in the facility-wide permit enforces on-going compliance with the requirements of this rule:

- No person shall manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2 of District Rule 4601 (4/16/20), after the specified effective dates in Table 1 or Table 2 of District Rule 4601. [District Rule 4601, 5.1]
- All architectural coating containers and containers of any VOC-containing materials subject to Rule 4601 (4/16/20) shall be closed when not in use. [District Rule 4601, 5.4]
- The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601, sections 6.1 and 6.3 (4/16/20). [District Rule 4601, 6.1 and 6.3]

### **District Rule 8051 – Open Areas**

The purpose of this rule is to limit fugitive dust emissions from open areas. Except as provided in section 7.0 of this rule, this rule applies to any open area having 0.5 acres or more within urban areas, or 3.0 acres or more within rural areas; and contain at least 1,000 square feet of disturbed surface area.

Whenever an open areas is a disturbed surface area or vehicles are used in an open area, an owner/operator shall implement one or a combination of control measures indicated in Table 8051-1 to comply with the conditions of a stabilized surface at all times and to limit VDE to no more than 20% opacity. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

TABLE 8051-1 SOURCE TYPE AND CONTROL MEASURES FOR OPEN AREAS
<p>A. OPEN AREAS:            Implement, apply, maintain, and reapply if necessary, at least one or a combination of the following control measures to comply at all times with the conditions for a stabilized surface and limit VDE to 20% opacity as defined in Rule 8011:            A1 Apply and maintain water or dust suppressant(s) to all unvegetated areas; or            A2 Establish vegetation on all previously disturbed surface areas; or            A3 Pave, apply and maintain gravel, or apply and maintain chemical/organic</p>

stabilizers/suppressants.
<b>B. VEHICLE USE IN OPEN AREAS:</b> Upon evidence of trespass, prevent unauthorized vehicle access by: Posting “No Trespassing” signs or installing physical barriers such as fences, gates, posts, and/or other appropriate barriers to effectively prevent access to the area.

The following condition in N-2107-0-6 ensure on-going compliance with this section:

- Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/21/2023) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051]

**40 CFR 63 Subpart DDDDD, National Emission Standards for Hazardous Air pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters**

This subpart is applicable to new, reconstructed, and existing industrial, commercial, institutional boilers, or process heaters located at a Major Source of HAP emissions. A Major Source of HAP emissions is any facility with a potential to emit, considering controls, in the aggregate, 10 tons per year or more of any hazardous air pollutant or 25 tons per year or more of any combination of hazardous air pollutants.

Per HAP calculation in Attachment C, the facility is an area source of HAP emissions. Therefore, the boilers are not subject to the requirements of this subpart.

**40 CFR Part 64, Compliance Assurance Monitoring (CAM)**

40 CFR Part 64 requires CAM for units that meet all of the following three criteria:

1. Unit must have an emission limit for the pollutant;
2. Unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), SCR system, baghouses, and thermal/catalytic oxidizers; and
3. Unit must have a pre-control potential to emit of greater than the major source thresholds given below:

NOx: 20,000 lb/yr  
SOx: 140,000 lb/yr  
PM<sub>10</sub>: 140,000 lb/yr  
CO: 200,000 lb/yr  
VOC: 20,000 lb/yr

N-2107-5: A Raw Material Receiving Operation Equipped With Outdoor Raw Material Receiving Concrete Slabs, Grinding System, And Primary And Secondary Wastewater Treatment System With DAF Unit And An Outdoor Wastewater Lagoon System (Permit Exempt Low Emitting Unit)

This permit does not have emission limit(s) for any pollutant. Therefore, CAM is not required for this permit unit.

N-2107-9: Food Processing Byproduct Recycling Operation Including Three Dupps Pre-Heat Cookers, A Haarslev 2564 Cooker And Air Cooled Condenser Served By A Shared 3.0 MMBtu/hr Natural Gas-Fired Gulf Coast Environmental Regenerative Thermal Oxidizer (RTO) With A Venturi Scrubber Prior To The RTO (Controls Shared With N-2107-14)

NOx, SOx and CO:

The permit contains emission limits for NOx, SOx, and CO but the units do not have add-on control device(s) to reduce these pollutants. Therefore, these units are not subject to CAM for NOx, SOx and CO emissions.

VOC and PM10:

This permit contains emission limits for VOC and PM10 emissions. The cookers are vented through an air cooled condenser, scrubber(s), and the RTO to reduce VOC and PM10 emissions. Overall control efficiency for the add-on controls is conservatively assumed to be 95% for VOC emissions and 50% for PM10 emissions. The pre-control potential VOC and PM10 emissions from the unit are estimated to be 180,675<sup>4</sup> pounds per year and 58,418<sup>5</sup> pounds per year, respectively.

Since unit's pre-control VOC emissions exceed the major source threshold of 20,000 pounds per year, the unit is subject to CAM requirements.

The facility is required to maintain the RTO chamber temperature at or above 1400°F. The chamber temperature is required to be continuously monitored and recorded at all times. Use of the continuous monitoring and recording device satisfies the CAM requirements for VOC emissions.

---

<sup>4</sup> VOC (pre-control) = 0.03 lb-VOC/ton of material x 301,125 tons/yr x 1/(1-0.95) = 180,675 lb-VOC/yr;

<sup>5</sup> PM10 (pre-control) = 0.097 lb-PM10/ton of material x 301,125 tons/yr x 1/(1-0.50) = 58,418 lb-PM10/yr

Note that the pre-control PM10 emissions are not greater than the Major Source threshold of 140,000 pounds per year; therefore, CAM is not required for PM10 emissions.

N-2107-12: Protein Meal Finishing And Loadout Operation With One Drag Line Conveyor, One 104 Ton Storage/Loadout Bin, Three 84 Ton Storage/Loadout Bins, One 450 Ton Storage/Loadout Bin, Crax Receiving, Three Hammermills, Three Screens, And A Loadout Building With Vertilok Storage/Loadout Bins; Another Enclosed Mechanical Conveyance Line Conveyor With A Curing Bin, A Hammermill And Screen System Served By An Aspirator Connected To A Cyclone Discharge Routed Through A Bag Filter Inside The Building, Bucket Elevator, A 400-Ton Storage/Loadout Bin With Bin Vent Filtration System, And A Loadout Building.

This permit contains an emission limit for PM10.

The hammermill and screen system is served by an aspirator connected to a cyclone, which is discharged through a dust collector. Further, the 400-ton storage/loadout bin is equipped with bin vent filtration system. These units may be subject to CAM requirements for PM10 only if the pre-control potential emissions are greater than the major source threshold of 140,000 lb-PM10/year.

*Hammermill:*

Using emission factors noted under project N1201629 and conservatively assuming filter efficiency of 99%, the pre-control emissions are estimated to be:

$$\begin{aligned} \text{EF2} &= 0.0048 \text{ lb-PM10/ton of material processed} \times 1/(1-0.99) \\ &= 0.48 \text{ lb-PM10/ton of material processed} \end{aligned}$$

Hammermill process capacity is 5 tons/hr; using 8,760 hr/yr worst-case operation, the total process rate could be up to 43,800 tons/yr.

$$\begin{aligned} \text{PE2 (pre-control)} &= 0.48 \text{ lb-PM10/ton of material processed} \times 43,800 \text{ tons/yr} \\ &= 21,024 \text{ lb-PM10/yr} \end{aligned}$$

The pre-control PM10 emissions are below the Major Source threshold of 140,000 lb/yr. Thus, CAM is not required for PM10 emissions from this unit.

*Screen:*

Using emission factors noted under project N1201629 and conservatively assuming filter efficiency of 99%, the pre-control emissions are estimated to be:

$$\begin{aligned} \text{EF2} &= 0.00002 \text{ lb-PM10/ton of material processed} \times 1/(1-0.99) \\ &= 0.002 \text{ lb-PM10/ton of material processed} \end{aligned}$$

Screen process capacity is 5 tons/hr; using 8,760 hr/yr worst-case operation, the total process rate could be up to 43,800 tons/yr.

$$\begin{aligned} \text{PE2 (pre-control)} &= 0.002 \text{ lb-PM10/ton of material processed} \times 43,800 \text{ tons/yr} \\ &= 88 \text{ lb-PM10/yr} \end{aligned}$$

The pre-control PM10 emissions are below the Major Source threshold of 140,000 lb/yr. Thus, CAM is not required for PM10 emissions from this unit.

*Storage silo:*

Using emission factors noted under project N1201629 and conservatively assuming filter efficiency of 99%, the pre-control emissions are estimated to be:

$$\begin{aligned} \text{EF2} &= 0.000025 \text{ lb-PM10/ton of material processed} \times 1/(1-0.99) \\ &= 0.0025 \text{ lb-PM10/ton of material processed} \end{aligned}$$

$$\begin{aligned} \text{PE2 (pre-control)} &= 0.0025 \text{ lb-PM10/ton of material processed} \times 43,800 \\ &\quad \text{tons/yr} \\ &= 110 \text{ lb-PM10/yr} \end{aligned}$$

The pre-control PM10 emissions are below the Major Source threshold of 140,000 lb/yr. Thus, CAM is not required for PM10 emissions from this unit.

N-2107-13: 76.93 MMBtu/hr Nebraska Model Ns-E-57 Water-Tube Natural Gas-Fired Boiler Equipped With A Flue Gas Recirculation (FGR) System And Ammonia Selective Catalytic Reduction (SCR) System

This permit contains emission limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO and VOC. However, the unit is equipped with a selective catalytic reduction (SCR) system to reduce NO<sub>x</sub> emissions only. Therefore, this unit may be subject to CAM requirements for NO<sub>x</sub> only if the pre-control potential emissions are greater than the major source threshold of 20,000 lb-NO<sub>x</sub>/year.

SCR system is expected to provide 95% control of NOx emissions. The pre-control potential to emit for this unit will be calculated based on the heat input rating of the boiler, 76.93 MMBtu/hr, the NOx emission factor of 0.008 lb/MMBtu, and the worst-case operating schedule of 8,760 hr/yr as follows:

$$\begin{aligned} \text{PE (pre-control)} &= 76.93 \text{ MMBtu/hr} \times 0.008 \text{ lb-NOx/MMBtu} \times 8,760 \text{ hr/yr} \times 1/(1 - 0.95) \\ &= 107,825 \text{ lb-NOx/yr} \end{aligned}$$

Since the pre-control NOx emissions are greater than the major source threshold of 20,000 lb-NOx/year, this unit is subject to CAM requirements.

As noted previously, this boiler is served by an SCR system to reduce NOx emissions. To ensure that the SCR is operated at its optimum level and reduces the maximum amount of NOx emissions, the owner or operator is required to establish ammonia flow rate range during source tests, and monitor and record the ammonia flow rate at least once during each day. In addition, monthly monitoring of NH3 slip is required at the time when NOx and CO readings are taken. Condition #18 through 22, 25 and 27 in the draft Title V permit satisfies the CAM requirement for NOx emissions.

N-2104-14: Feather Recycling Operation Consisting Of An Indoor Feather Receiving Hopper, A Steam-Fired Continuous Feather Hydrolyzer, A Feather Press, A Steam-Fired Feather Dryer, A Blood Staging Tank, Blood Centrifuge, Spray Chamber And Air Cooled Condenser Served By A Shared 3.0 MMBtu/hr Natural Gas-Fired Gulf Coast Environmental Regenerative Thermal Oxidizer (RTO) With A Venturi Scrubber Prior To The RTO (Controls Shared With N-2107-9)

NOx, SOx and CO:

The permit contains emission limits for NOx, SOx, and CO but the emission units do not have add-on control equipment to reduce these pollutants. Therefore, the units are not subject to CAM for NOx, SOx and CO emissions.

VOC and PM10:

This permit contains emission limit for VOC and PM10 emissions. The units are vented through an air cooled condenser, scrubber(s), and the RTO to reduce VOC and PM10 emissions. Overall control efficiency for the add-on controls is conservatively assumed to be 95% for VOC emissions and 50% for PM10 emissions. The pre-control potential VOC and PM10 emissions from the unit are estimated to be 180,675<sup>6</sup> pounds per year and 58,418<sup>7</sup> pounds per year, respectively.

---

<sup>6</sup> VOC (pre-control) = 0.03 lb-VOC/ton of material x 301,125 tons/yr x 1/(1-0.95) = 180,675 lb-VOC/yr;

<sup>7</sup> PM10 (pre-control) = 0.097 lb-PM10/ton of material x 301,125 tons/yr x 1/(1-0.50) = 58,418 lb-PM10/yr

Since unit's pre-control VOC emissions exceed the major source threshold of 20,000 pounds per year, the unit is subject to CAM requirements.

The facility is required to maintain the RTO chamber temperature at or above 1400°F. The chamber temperature is required to be continuously monitored and recorded at all times. Use of the continuous monitoring and recording device satisfies the CAM requirements for VOC emissions.

Note that the pre-control PM10 emissions are not greater than the Major Source threshold of 140,000 pounds per year; therefore, CAM is not required for PM10 emissions.

N-2107-15-1: 48 MMBtu/hr Babcock & Wilcox Model Fmo-40 Water-Tube Natural Gas-Fired Boiler With A Todd Model V4851go Low-NOx Burner, A Flue Gas Recirculation System (FGR), And A Selective Catalytic Reduction (SCR) System

This permit contains emission limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO and VOC. However, the unit is equipped with a selective catalytic reduction (SCR) system to reduce NO<sub>x</sub> emissions only. Therefore, this unit may be subject to CAM requirements for NO<sub>x</sub> only if the pre-control potential emissions are greater than the major source threshold of 20,000 lb-NO<sub>x</sub>/year.

SCR system is expected to provide 95% control of NO<sub>x</sub> emissions. The pre-control potential to emit for this unit will be calculated based on the heat input rating of the boiler, 48 MMBtu/hr, the permitted NO<sub>x</sub> emission factor of 0.0073 lb/MMBtu on natural gas fuel, and the worst-case operating schedule of 8,760 hr/yr as follows:

$$\begin{aligned} \text{PE (pre-control)} &= (48 \text{ MMBtu/hr} \times 0.0073 \text{ lb-NO}_x\text{/MMBtu} \times 8,760 \text{ hr/yr}) \times 1/(1 - 0.95) \\ &= 61,390 \text{ lb-NO}_x\text{/yr} \end{aligned}$$

Since the pre-control NO<sub>x</sub> emissions are greater than the major source threshold of 20,000 lb-NO<sub>x</sub>/year, this unit is subject to CAM requirements.

This boiler is served by an SCR system to reduce NO<sub>x</sub> emissions. To ensure that the SCR is operated at its optimum level and reduces the maximum amount of NO<sub>x</sub> emissions, the owner or operator is required to establish ammonia flow rate range during source tests, and monitor and record the ammonia flow rate at least once during each day. The periodic monthly monitoring of NO<sub>x</sub>, CO and NH<sub>3</sub> emissions will continually be required. Condition #19 through 23 and 27 (similar to conditions in permit N-2107-13) are established to ensure on-going compliance with CAM requirements.

#### **40 CFR Part 82, Subpart F, Recycling and Emissions Reduction**

The purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

These regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

Condition 27 in the draft renewed permit N-2107-0-6 ensures ongoing compliance with the requirements of this subpart.

### **IX. PERMIT SHIELD**

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

#### **A. Requirements Addressed by Model General Permit Templates**

By using the model general permit template(s) listed in Section IV of this evaluation, the applicant has requested that a permit shield be issued for requirements addressed in the template(s). The basis for each permit shield is discussed in the Permit Shield section of each template.

#### **B. Requirements not Addressed by Model General Permit Templates**

The applicant has not requested any new permit shields. Therefore, no further discussion is necessary.

## **X. CALIFORNIA ENVIRONMENTAL QUALITY ACT**

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

## **XI. PERMIT CONDITIONS**

See Attachment A - Draft Renewed Title V Operating Permit.

## **XII. ATTACHMENTS**

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. HAP Calculations
- D. Detailed Facility List

---

# ATTACHMENT A

Draft Renewed Title V Operating Permit

---

*San Joaquin Valley*  
*Air Pollution Control District*

FACILITY: N-2107-0-6

EXPIRATION DATE: 08/31/2026

## FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Merced County Rule 109] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Merced County Rule 109] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: DARLING INGREDIENTS INC  
Location: 11946 CARPENTER RD, CROWS LANDING, CA 95313  
N-2107-0-6 : 5/13/2026 8:29:19 AM - KAHOLONJ

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

DRAFT  
FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. No person shall manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2 of District Rule 4601 (4/16/20), after the specified effective dates in Table 1 or Table 2 of District Rule 4601. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All architectural coating containers and containers of any VOC-containing materials subject to Rule 4601 (4/16/20) shall be closed when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601, sections 6.1 and 6.3 (4/16/20). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/21/2003) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Merced), Rule 109 (Merced), and Rule 202 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On November 30, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin December 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {118} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. Facility-wide PM10 emissions shall not exceed 29,200 lb/year. Permittee shall maintain annual fuel-use records for all combustion devices and applicable records for other PM10 emitting devices to show compliance with this emissions limit. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-5-11

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

A RAW MATERIAL RECEIVING OPERATION EQUIPPED WITH OUTDOOR RAW MATERIAL RECEIVING CONCRETE SLABS, GRINDING SYSTEM, AND PRIMARY AND SECONDARY WASTEWATER TREATMENT SYSTEM WITH DAF UNIT AND AN OUTDOOR WASTEWATER LAGOON SYSTEM (PERMIT EXEMPT LOW EMITTING UNIT)

### **PERMIT UNIT REQUIREMENTS**

---

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The Air Pollution Control District shall be immediately notified of any breakdown or malfunction that reduces or disrupts the normal processing of odors required by this permit. [District Rules 1100 and 4102] Federally Enforceable Through Title V Permit
3. The District shall have authority to investigate possible odors alleged to originate from the facility and to make a determination of whether or not a nuisance exists, either in response to a complaint or on its own initiative. [District Rules 1070 and 4102] Federally Enforceable Through Title V Permit
4. The APCO or any authorized representative shall have access to inspect any equipment, operation, records, method required in this permit, to sample emissions from the source or require samples to be taken, or perform any other actions to assure compliance with the requirements of this permit and all District rules and regulations. [District Rule 1070] Federally Enforceable Through Title V Permit
5. The premises of the plant except for raw material receiving and storage areas and their associated pits and bins shall be kept clean and free from spillage of raw or finished materials, refuse, and standing pools of water which may present a nuisance condition. All raw material spills shall be cleaned up immediately. [District Rule 4102]
6. The delivery truck holding time shall not exceed 48 hours and the animal mortality holding time shall not exceed 96 hours from the time the raw materials enter the property. [District Rule 4102]
7. No storage of raw materials outside of the pits, bins, or open slab areas is permitted. [District NSR Rule and Rule 4102] Federally Enforceable Through Title V Permit
8. Raw material receiving areas (pits/bins and open slabs) not currently holding raw material for processing shall be cleaned daily. [District Rule 4102]
9. Trucks waiting their turn to unload within the 48 or 96 hour unload time limitation are not considered storage outside of the pit/slab area. [District Rule 4102]
10. All trucks and truck tires delivering raw material shall be washed clean of raw material and raw material residue prior to exiting the facility premises in order to minimize trackout of raw material and raw material residue. [District Rule 4102]
11. All raw material trucks shall be maintained in condition to prevent leakage of any solid or liquid material. [District Rule 4102]
12. The rendering plant shall not be operated unless the odor control system is operating and in full use. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
14. Except during periods of equipment breakdown as determined by the District under Rule 1100, all raw material received shall be processed within 24 hours of entering the receiving pits and in compliance with other conditions in this permit. Raw material shall be monitored to ensure that processing is performed within this time limit using plant processing records. [District Rules 1100 and 4102]
15. If raw material cannot be processed within the time constraints of this permit, raw material shall be diverted to other facilities. No further deliveries shall be received until a 48 (or 96) hour turnaround for raw material is achievable. [District Rule 4102]
16. The owner and/or operator shall comply with all the provisions of District Rule 4102, Nuisance. [District Rule 4102]
17. Permittee shall keep daily and annual records of the amount of raw material received. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-2107-9-23

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

FOOD PROCESSING BYPRODUCT RECYCLING OPERATION INCLUDING THREE DUPPS PRE-HEAT COOKERS, A HAARSLEV 2564 COOKER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-14)

## PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. [District Rules 2520, 9.3.2, 4801 and Stanislaus County Rule 407] Federally Enforceable Through Title V Permit
3. Tallow and yellow grease storage tanks shall be kept in good operating condition. These tanks shall not contribute to a nuisance condition. [District Rule 4102]
4. The shared RTO shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year from the combined units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined emissions from the process lines (N-2107-9 and N-2107-14) served by the RTO shall not exceed any of the following: 0.98 lb-NO<sub>x</sub>/MMBtu, 0.15 lb-SO<sub>x</sub>/ton of raw material processed, 0.097 lb-PM<sub>10</sub>/ton of raw material processed, 1.12 lb-CO/MMBtu, and 0.03 lb-VOC/ton of raw material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Source testing to measure the VOC emissions from the shared RTO exhaust shall be conducted at least once every 24 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Source testing shall be performed while processing raw material under normal operating conditions or another load previously approved by the District in writing. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Source testing to measure the VOC emissions shall be conducted using EPA Methods 18, 25, 25A, or 25B or CARB Method 100. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The shared RTO shall be operated with a combustion chamber temperature of no less than 1400 degrees F and the retention time shall be no less than one second. A continuous temperature monitoring and recording device shall be used and kept in good working order. [District Rules 2201 and 4104, and 40 CFR Part 64] Federally Enforceable Through Title V Permit
13. The shared RTO shall be heated to proper operating temperature prior to any contaminated process air entering the oxidizer. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
14. The shared RTO shall continue to operate after the shut-down of the rendering processes until all contaminated process air is incinerated. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
15. Permittee shall keep a record of the shared RTO combustion chamber temperature readings. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
16. Permittee shall keep a daily record of the combined quantity of raw material processed by units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Facility-wide PM10 emissions shall not exceed 29,200 lbs per year. Operator shall maintain copies of all natural gas fuel invoices, and records of hours of operation of the shared RTO in order to show compliance with this emissions limit. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. All records shall be retained for a minimum of five years, and shall be made readily available for District inspection upon request. [District Rules 1070, 2201, and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley Air Pollution Control District*

**PERMIT UNIT:** N-2107-12-9

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

PROTEIN MEAL FINISHING AND LOADOUT OPERATION WITH ONE DRAG LINE CONVEYOR, ONE 104 TON STORAGE/LOADOUT BIN, THREE 84 TON STORAGE/LOADOUT BINS, ONE 450 TON STORAGE/LOADOUT BIN, CRAX RECEIVING, THREE HAMMERMILLS, THREE SCREENS, AND A LOADOUT BUILDING WITH VERTILOK STORAGE/LOADOUT BINS; ANOTHER ENCLOSED MECHANICAL CONVEYANCE LINE CONVEYOR WITH A CURING BIN, A HAMMERMILL AND SCREEN SYSTEM SERVED BY AN ASPIRATOR CONNECTED TO A CYCLONE DISCHARGE ROUTED THROUGH A BAG FILTER INSIDE THE BUILDING, BUCKET ELEVATOR, A 400-TON STORAGE/LOADOUT BIN WITH BIN VENT FILTRATION SYSTEM, AND A LOADOUT BUILDING.

## **PERMIT UNIT REQUIREMENTS**

---

1. All loadout material trucks shall be maintained in condition to prevent leakage of solid or liquid material. [District Rule 4102]
2. Equipment shall be operated in such a manner as to not constitute a nuisance or annoyance to a considerable number of people. [District Rule 4102]
3. The District shall have authority to investigate possible odors alleged to originate from the facility and to make a determination of whether or not a nuisance exists, either in response to a complaint or on its own initiative. [District Rule 4102]
4. The District shall have access to the facility at any time to inspect operations, review records or perform other actions to assure compliance. [District Rule 1070] Federally Enforceable Through Title V Permit
5. The combined total quantity of protein meal loaded into trucks/containers for shipping through both the old (existing) and new loadout areas shall not exceed 1,200 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. PM10 emissions from the protein meal finishing and loadout operation shall not exceed 0.00333 pounds per ton of protein meal loaded out. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall keep a daily record of the combined quantity of protein meal loaded out. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-2107-13-11

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

76.93 MMBTU/HR NEBRASKA MODEL NS-E-57 WATER-TUBE NATURAL GAS-FIRED BOILER EQUIPPED WITH A FLUE GAS RECIRCULATION (FGR) SYSTEM AND AMMONIA SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM

## PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rules 2201 and 4320, and 40 CFR 60.48c(d)] Federally Enforceable Through Title V Permit
4. The boiler shall be equipped with a non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit. [40 CFR 60.48c(g)] Federally Enforceable Through Title V Permit
5. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.008 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 100 ppmvd CO @ 3% O<sub>2</sub> or 0.073 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. The ammonia emission rate shall not exceed 10.0 ppmvd @ 3% O<sub>2</sub> over a 15 minute averaging period. [District Rule 4102]
7. Source testing to measure natural gas combustion NO<sub>x</sub>, CO, and NH<sub>3</sub> emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
11. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rule 4320] Federally Enforceable Through Title V Permit
16. Fuel sulfur content shall be determined using EPA Method 11 or EPA Method 15 or District, CARB and EPA approved alternative methods. [District Rule 4320] Federally Enforceable Through Title V Permit
17. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> at least once during each month in which source testing is not performed. NO<sub>x</sub>, CO and O<sub>2</sub> monitoring shall be conducted utilizing a portable analyzer that meets District specifications. NH<sub>3</sub> monitoring shall be conducted utilizing gas detection tubes (Draeger brand or District approved equivalent). Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
19. The ammonia (NH<sub>3</sub>) flow rate range shall be established during required source tests. [40 CFR Part 64] Federally Enforceable Through Title V Permit
20. The permittee shall monitor and record the ammonia (NH<sub>3</sub>) flow rate at least once during each day. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit. [40 CFR Part 64] Federally Enforceable Through Title V Permit
21. If either the NO<sub>x</sub>, CO or NH<sub>3</sub> concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
22. All NO<sub>x</sub>, CO, O<sub>2</sub> and NH<sub>3</sub> emission readings and NH<sub>3</sub> flow rate readings shall be taken with the unit operating at conditions representative of normal operation or under the conditions specified in the Permit to Operate. The NO<sub>x</sub>, CO and O<sub>2</sub> analyzer as well as the NH<sub>3</sub> emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. Ammonia emission readings shall be conducted at the time the NO<sub>x</sub>, CO and O<sub>2</sub> readings are taken. The readings shall be converted to ppmvd @ 3% O<sub>2</sub>. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub>, CO and NH<sub>3</sub> concentrations corrected to 3% O<sub>2</sub>, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH<sub>3</sub> emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
26. The permittee shall record and maintain records of the amount of fuel combusted during each calendar month. The record shall be updated on at least a monthly basis. [40 CFR 60.48c(g)(2)] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, 40 CFR Part 64, and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit
28. {5026} Pursuant to Rule 4320, beginning January 1, 2025 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in the December 17, 2020 version of Rule 4320. [District Rule 4320]

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-2107-14-6

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

FEATHER RECYCLING OPERATION CONSISTING OF AN INDOOR FEATHER RECEIVING HOPPER, A STEAM-FIRED CONTINUOUS FEATHER HYDROLYZER, A FEATHER PRESS, A STEAM-FIRED FEATHER DRYER, A BLOOD STAGING TANK, BLOOD CENTRIFUGE, SPRAY CHAMBER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-9)

## PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. [District Rules 2520, 9.3.2, 4801 and Stanislaus County Rule 407] Federally Enforceable Through Title V Permit
3. The shared RTO shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year from the combined units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Combined emissions from the process lines (N-2107-9 and N-2107-14) served by the RTO shall not exceed any of the following: 0.98 lb-NO<sub>x</sub>/MMBtu, 0.15 lb-SO<sub>x</sub>/ton of raw material processed, 0.097 lb-PM<sub>10</sub>/ton of raw material processed, 1.12 lb-CO/MMBtu, and 0.03 lb-VOC/ton of raw material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Source testing to measure the VOC emissions from the shared RTO shall be conducted at least once every 24 months. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Source testing shall be performed while processing raw material under normal operating conditions or another load previously approved by the District in writing. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Source testing to measure the VOC emissions shall be conducted using EPA Methods 18, 25, 25A, or 25B or CARB Method 100. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
10. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The shared RTO shall be operated with a combustion chamber temperature of no less than 1400 degrees F and the retention time shall be no less than one second. A continuous temperature monitoring and recording device shall be used and kept in good working order. [District Rules 2201 and 4104, and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The shared RTO shall be heated to proper operating temperature prior to any contaminated process air entering the oxidizer. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
13. The shared RTO shall continue to operate after the shut-down of the rendering processes until all contaminated process air is incinerated. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
14. Permittee shall keep a record of the shared RTO combustion chamber temperature readings. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
15. Permittee shall keep a daily record of the combined quantity of material processed by units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Facility-wide PM10 emissions shall not exceed 29,200 lbs per year. Operator shall maintain copies of all natural gas fuel invoices, and records of hours of operation of the shared regenerative thermal oxidizer in order to show compliance with this emissions limit. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. All records shall be retained for a minimum of five years, and shall be made readily available for District inspection upon request. [District Rules 1070, 2201, and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-2107-15-5

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

48 MMBTU/HR BABCOCK & WILCOX MODEL FMO-40 WATER-TUBE NATURAL GAS-FIRED BOILER WITH A TODD MODEL V4851GO LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM (FGR), AND A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM

## PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201 and 4320; and 40 CFR 60.42c(d)] Federally Enforceable Through Title V Permit
3. The boiler shall be equipped with a non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit. [District Rule 2201 and 40 CFR 60.48c(g)] Federally Enforceable Through Title V Permit
4. Except during start-up and shutdown, emissions from natural gas combustion shall not exceed any of the following limits: 6 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.0073 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 50 ppmvd CO @ 3% O<sub>2</sub> or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from natural gas combustion shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.036 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 50 ppmvd CO @ 3% O<sub>2</sub> or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. The total duration of startup and shutdown time shall not exceed any of the following limits: 2.0 hours startup per day, 2.0 hours shutdown per day, or 730 hours total startup and shutdown time per year. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The ammonia (NH<sub>3</sub>) emission rate shall not exceed 10.0 ppmvd @ 3% O<sub>2</sub> over a 15 minute averaging period. [District Rule 4102]
8. Source testing to measure natural gas combustion NO<sub>x</sub>, CO, and NH<sub>3</sub> emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
12. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 1081] Federally Enforceable Through Title V Permit
16. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rule 4320] Federally Enforceable Through Title V Permit
17. Fuel sulfur content shall be determined using EPA Method 11 or EPA Method 15 or District, CARB and EPA approved alternative methods. [District Rule 4320] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The permittee shall monitor and record the stack concentration of NOx, CO, NH3 and O2 at least once during each month in which source testing is not performed. NOx, CO and O2 monitoring shall be conducted utilizing a portable analyzer that meets District specifications. NH3 monitoring shall be conducted utilizing gas detection tubes (Dräger brand or District approved equivalent). Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
20. The ammonia (NH3) flow rate range shall be established during required source tests. [40 CFR Part 64] Federally Enforceable Through Title V Permit
21. The permittee shall monitor and record the ammonia (NH3) flow rate at least once during each day. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit. [40 CFR Part 64] Federally Enforceable Through Title V Permit
22. If either the NOx, CO or NH3 concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
23. All NOx, CO, O2 and NH3 emission readings shall be taken with the unit operating at conditions representative of normal operation or under the conditions specified in the Permit to Operate. The NOx, CO and O2 analyzer as well as the NH3 emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. Ammonia emissions readings shall be conducted at the time the NO<sub>x</sub>, CO and O<sub>2</sub> readings are taken. The readings shall be converted to ppmvd @ 3% O<sub>2</sub>. [District Rule 4102]
26. Daily and annual records of start-up and shutdown durations and number of occurrences of each shall be kept. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
27. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub>, CO and NH<sub>3</sub> concentrations corrected to 3% O<sub>2</sub>, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH<sub>3</sub> emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
28. The permittee shall record and maintain records of the amount of fuel combusted during each calendar month. The record shall be updated on at least a monthly basis. [40 CFR 60.48c(g)(2)] Federally Enforceable Through Title V Permit
29. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320; and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit
30. {5026} Pursuant to Rule 4320, beginning January 1, 2025 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in the December 17, 2020 version of Rule 4320. [District Rule 4320]

These terms and conditions are part of the Facility-wide Permit to Operate.

---

# ATTACHMENT B

Previous Title V Operating Permit

---

# Permit to Operate

**FACILITY:** N-2107

**EXPIRATION DATE:** 08/31/2026

**LEGAL OWNER OR OPERATOR:** DARLING INGREDIENTS INC  
**MAILING ADDRESS:** P O BOX 1608  
TURLOCK, CA 95381

**FACILITY LOCATION:** 11946 CARPENTER RD  
CROWS LANDING, CA 95313

**FACILITY DESCRIPTION:** RENDERING

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

**Samir Sheikh**  
Executive Director / APCO

**Brian Clements**  
Director of Permit Services

# *San Joaquin Valley*

## *Air Pollution Control District*

**FACILITY:** N-2107-0-5

**EXPIRATION DATE:** 08/31/2026

### **FACILITY-WIDE REQUIREMENTS**

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1]
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0]
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: DARLING INGREDIENTS INC  
Location: 11946 CARPENTER RD, CROWS LANDING, CA 95313  
N-2107-0-5 : 5/13/2026 8:33:22 AM - KAHLOJ

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On November 30, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin December 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. Facility-wide PM10 emissions shall not exceed 29,200 lb/year. Permittee shall maintain annual fuel-use records for all combustion devices and applicable records for other PM10 emitting devices to show compliance with this emissions limit. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-5-10

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

A RAW MATERIAL RECEIVING OPERATION EQUIPPED WITH OUTDOOR RAW MATERIAL RECEIVING CONCRETE SLABS, GRINDING SYSTEM, AND PRIMARY AND SECONDARY WASTEWATER TREATMENT SYSTEM WITH DAF UNIT AND AN OUTDOOR WASTEWATER LAGOON SYSTEM (PERMIT EXEMPT LOW EMITTING UNIT)

### **PERMIT UNIT REQUIREMENTS**

---

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The Air Pollution Control District shall be immediately notified of any breakdown or malfunction that reduces or disrupts the normal processing of odors required by this permit. [District Rules 1100 and 4102] Federally Enforceable Through Title V Permit
3. The District shall have authority to investigate possible odors alleged to originate from the facility and to make a determination of whether or not a nuisance exists, either in response to a complaint or on its own initiative. [District Rules 1070 and 4102] Federally Enforceable Through Title V Permit
4. The APCO or any authorized representative shall have access to inspect any equipment, operation, records, method required in this permit, to sample emissions from the source or require samples to be taken, or perform any other actions to assure compliance with the requirements of this permit and all District rules and regulations. [District Rule 1070] Federally Enforceable Through Title V Permit
5. The premises of the plant except for raw material receiving and storage areas and their associated pits and bins shall be kept clean and free from spillage of raw or finished materials, refuse, and standing pools of water which may present a nuisance condition. All raw material spills shall be cleaned up immediately. [District Rule 4102]
6. The delivery truck holding time shall not exceed 48 hours and the animal mortality holding time shall not exceed 96 hours from the time the raw materials enter the property. [District Rule 4102]
7. No storage of raw materials outside of the pits, bins, or open slab areas is permitted. [District NSR Rule and Rule 4102] Federally Enforceable Through Title V Permit
8. Raw material receiving areas (pits/bins and open slabs) not currently holding raw material for processing shall be cleaned daily. [District Rule 4102]
9. Trucks waiting their turn to unload within the 48 or 96 hour unload time limitation are not considered storage outside of the pit/slab area. [District Rule 4102]
10. All trucks and truck tires delivering raw material shall be washed clean of raw material and raw material residue prior to exiting the facility premises in order to minimize trackout of raw material and raw material residue. [District Rule 4102]
11. All raw material trucks shall be maintained in condition to prevent leakage of any solid or liquid material. [District Rule 4102]
12. The rendering plant shall not be operated unless the odor control system is operating and in full use. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
14. Except during periods of equipment breakdown as determined by the District under Rule 1100, all raw material received shall be processed within 24 hours of entering the receiving pits and in compliance with other conditions in this permit. Raw material shall be monitored to ensure that processing is performed within this time limit using plant processing records. [District Rules 1100 and 4102]
15. If raw material cannot be processed within the time constraints of this permit, raw material shall be diverted to other facilities. No further deliveries shall be received until a 48 (or 96) hour turnaround for raw material is achievable. [District Rule 4102]
16. The owner and/or operator shall comply with all the provisions of District Rule 4102, Nuisance. [District Rule 4102]
17. Permittee shall keep daily and annual records of the amount of raw material received. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-2107-9-20

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

FOOD PROCESSING BYPRODUCT RECYCLING OPERATION INCLUDING THREE DUPPS PRE-HEAT COOKERS, A HAARSLEV 2564 COOKER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-14)

## **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. [District Rules 2520, 9.3.2, 4801 and Stanislaus County Rule 407] Federally Enforceable Through Title V Permit
3. Tallow and yellow grease storage tanks shall be kept in good operating condition. These tanks shall not contribute to a nuisance condition. [District Rule 4102]
4. The shared RTO shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year from the combined units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined emissions from the process lines (N-2107-9 and N-2107-14) served by the RTO shall not exceed any of the following: 0.98 lb-NO<sub>x</sub>/MMBtu, 0.15 lb-SO<sub>x</sub>/ton of raw material processed, 0.097 lb-PM10/ton of raw material processed, 1.12 lb-CO/MMBtu, and 0.03 lb-VOC/ton of raw material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Source testing to measure the VOC emissions from the shared RTO exhaust shall be conducted at least once every 24 months. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Source testing shall be performed while processing raw material under normal operating conditions or another load previously approved by the District in writing. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Source testing to measure the VOC emissions shall be conducted using EPA Methods 18, 25, 25A, or 25B or CARB Method 100. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The shared RTO shall be operated with a combustion chamber temperature of no less than 1400 degrees F and the retention time shall be no less than one second. A continuous temperature monitoring and recording device shall be used and kept in good working order. [District Rules 2201 and 4104, and 40 CFR Part 64] Federally Enforceable Through Title V Permit
13. The shared RTO shall be heated to proper operating temperature prior to any contaminated process air entering the oxidizer. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
14. The shared RTO shall continue to operate after the shut-down of the rendering processes until all contaminated process air is incinerated. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
15. Permittee shall keep a record of the shared RTO combustion chamber temperature readings. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
16. Permittee shall keep a daily record of the combined quantity of raw material processed by units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Facility-wide PM10 emissions shall not exceed 29,200 lbs per year. Operator shall maintain copies of all natural gas fuel invoices, and records of hours of operation of the shared RTO in order to show compliance with this emissions limit. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. All records shall be retained for a minimum of five years, and shall be made readily available for District inspection upon request. [District Rules 1070, 2201, and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-12-6

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

PROTEIN MEAL FINISHING AND LOADOUT OPERATION WITH ONE DRAG LINE CONVEYOR, ONE 104 TON STORAGE/LOADOUT BIN, THREE 84 TON STORAGE/LOADOUT BINS, ONE 450 TON STORAGE/LOADOUT BIN, CRAX RECEIVING, THREE HAMMERMILLS, THREE SCREENS, AND A LOADOUT BUILDING WITH VERTILOK STORAGE/LOADOUT BINS; ANOTHER ENCLOSED MECHANICAL CONVEYANCE LINE CONVEYOR WITH A CURING BIN, A HAMMERMILL AND SCREEN SYSTEM SERVED BY AN ASPIRATOR CONNECTED TO A CYCLONE DISCHARGE ROUTED THROUGH A BAG FILTER INSIDE THE BUILDING, BUCKET ELEVATOR, A 400-TON STORAGE/LOADOUT BIN WITH BIN VENT FILTRATION SYSTEM, AND A LOADOUT BUILDING.

### **PERMIT UNIT REQUIREMENTS**

---

1. All loadout material trucks shall be maintained in condition to prevent leakage of solid or liquid material. [District Rule 4102]
2. Equipment shall be operated in such a manner as to not constitute a nuisance or annoyance to a considerable number of people. [District Rule 4102]
3. The District shall have authority to investigate possible odors alleged to originate from the facility and to make a determination of whether or not a nuisance exists, either in response to a complaint or on its own initiative. [District Rule 4102]
4. The District shall have access to the facility at any time to inspect operations, review records or perform other actions to assure compliance. [District Rule 1070] Federally Enforceable Through Title V Permit
5. The combined total quantity of protein meal loaded into trucks/containers for shipping through both the old (existing) and new loadout areas shall not exceed 1,200 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. PM10 emissions from the protein meal finishing and loadout operation shall not exceed 0.00333 pounds per ton of protein meal loaded out. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall keep a daily record of the combined quantity of protein meal loaded out. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-13-8

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

76.93 MMBTU/HR NEBRASKA MODEL NS-E-57 WATER-TUBE NATURAL GAS-FIRED BOILER EQUIPPED WITH A FLUE GAS RECIRCULATION (FGR) SYSTEM AND AMMONIA SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM

### **PERMIT UNIT REQUIREMENTS**

---

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rules 2201 and 4320, and 40 CFR 60.48c(d)] Federally Enforceable Through Title V Permit
4. The boiler shall be equipped with a non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit. [40 CFR 60.48c(g)] Federally Enforceable Through Title V Permit
5. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.008 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 100 ppmvd CO @ 3% O<sub>2</sub> or 0.073 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. The ammonia emission rate shall not exceed 10.0 ppmvd @ 3% O<sub>2</sub> over a 15 minute averaging period. [District Rule 4102]
7. Source testing to measure natural gas combustion NO<sub>x</sub>, CO, and NH<sub>3</sub> emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
11. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rule 4320] Federally Enforceable Through Title V Permit
16. Fuel sulfur content shall be determined using EPA Method 11 or EPA Method 15 or District, CARB and EPA approved alternative methods. [District Rule 4320] Federally Enforceable Through Title V Permit
17. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> at least once during each month in which source testing is not performed. NO<sub>x</sub>, CO and O<sub>2</sub> monitoring shall be conducted utilizing a portable analyzer that meets District specifications. NH<sub>3</sub> monitoring shall be conducted utilizing gas detection tubes (Dräger brand or District approved equivalent). Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
19. The ammonia (NH<sub>3</sub>) flow rate range shall be established during required source tests. [40 CFR Part 64] Federally Enforceable Through Title V Permit
20. The permittee shall monitor and record the ammonia (NH<sub>3</sub>) flow rate at least once during each day. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit. [40 CFR Part 64] Federally Enforceable Through Title V Permit
21. If either the NO<sub>x</sub>, CO or NH<sub>3</sub> concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
22. All NO<sub>x</sub>, CO, O<sub>2</sub> and NH<sub>3</sub> emission readings and NH<sub>3</sub> flow rate readings shall be taken with the unit operating at conditions representative of normal operation or under the conditions specified in the Permit to Operate. The NO<sub>x</sub>, CO and O<sub>2</sub> analyzer as well as the NH<sub>3</sub> emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. Ammonia emission readings shall be conducted at the time the NO<sub>x</sub>, CO and O<sub>2</sub> readings are taken. The readings shall be converted to ppmvd @ 3% O<sub>2</sub>. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub>, CO and NH<sub>3</sub> concentrations corrected to 3% O<sub>2</sub>, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH<sub>3</sub> emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
26. The permittee shall record and maintain records of the amount of fuel combusted during each calendar month. The record shall be updated on at least a monthly basis. [40 CFR 60.48c(g)(2)] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, 40 CFR Part 64, and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit
28. Pursuant to Rule 4320, beginning January 1, 2025 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in the December 17, 2020 version of Rule 4320. [District Rule 4320]

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-14-3

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

FEATHER RECYCLING OPERATION CONSISTING OF AN INDOOR FEATHER RECEIVING HOPPER, A STEAM-FIRED CONTINUOUS FEATHER HYDROLYZER, A FEATHER PRESS, A STEAM-FIRED FEATHER DRYER, A BLOOD STAGING TANK, BLOOD CENTRIFUGE, SPRAY CHAMBER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-9)

### **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. [District Rules 2520, 9.3.2, 4801 and Stanislaus County Rule 407] Federally Enforceable Through Title V Permit
3. The shared RTO shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The total facility raw material process rate shall not exceed 1,650,000 pounds (825 tons) per day or 602,250,000 pounds (301,125 tons) per year from the combined units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Combined emissions from the process lines (N-2107-9 and N-2107-14) served by the RTO shall not exceed any of the following: 0.98 lb-NO<sub>x</sub>/MMBtu, 0.15 lb-SO<sub>x</sub>/ton of raw material processed, 0.097 lb-PM<sub>10</sub>/ton of raw material processed, 1.12 lb-CO/MMBtu, and 0.03 lb-VOC/ton of raw material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Source testing to measure the VOC emissions from the shared RTO shall be conducted at least once every 24 months. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Source testing shall be performed while processing raw material under normal operating conditions or another load previously approved by the District in writing. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Source testing to measure the VOC emissions shall be conducted using EPA Methods 18, 25, 25A, or 25B or CARB Method 100. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
10. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The shared RTO shall be operated with a combustion chamber temperature of no less than 1400 degrees F and the retention time shall be no less than one second. A continuous temperature monitoring and recording device shall be used and kept in good working order. [District Rules 2201 and 4104, and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The shared RTO shall be heated to proper operating temperature prior to any contaminated process air entering the oxidizer. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
13. The shared RTO shall continue to operate after the shut-down of the rendering processes until all contaminated process air is incinerated. [District Rules 2201 and 4104] Federally Enforceable Through Title V Permit
14. Permittee shall keep a record of the shared RTO combustion chamber temperature readings. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
15. Permittee shall keep a daily record of the combined quantity of material processed by units N-2107-9 and N-2107-14. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Facility-wide PM10 emissions shall not exceed 29,200 lbs per year. Operator shall maintain copies of all natural gas fuel invoices, and records of hours of operation of the shared regenerative thermal oxidizer in order to show compliance with this emissions limit. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. All records shall be retained for a minimum of five years, and shall be made readily available for District inspection upon request. [District Rules 1070, 2201, and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-2107-15-2

**EXPIRATION DATE:** 08/31/2026

**EQUIPMENT DESCRIPTION:**

48 MMBTU/HR BABCOCK & WILCOX MODEL FMO-40 WATER-TUBE NATURAL GAS-FIRED BOILER WITH A TODD MODEL V4851GO LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM (FGR), AND A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM

### **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201 and 4320; and 40 CFR 60.42c(d)] Federally Enforceable Through Title V Permit
3. The boiler shall be equipped with a non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit. [District Rule 2201 and 40 CFR 60.48c(g)] Federally Enforceable Through Title V Permit
4. Except during start-up and shutdown, emissions from natural gas combustion shall not exceed any of the following limits: 6 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.0073 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 50 ppmvd CO @ 3% O<sub>2</sub> or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. During start-up and shutdown periods, emissions from natural gas combustion shall not exceed any of the following limits: 30 ppmvd NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.036 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.003 lb-PM<sub>10</sub>/MMBtu, 50 ppmvd CO @ 3% O<sub>2</sub> or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. The total duration of startup and shutdown time shall not exceed any of the following limits: 2.0 hours startup per day, 2.0 hours shutdown per day, or 730 hours total startup and shutdown time per year. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The ammonia (NH<sub>3</sub>) emission rate shall not exceed 10.0 ppmvd @ 3% O<sub>2</sub> over a 15 minute averaging period. [District Rule 4102]
8. Source testing to measure natural gas combustion NO<sub>x</sub>, CO, and NH<sub>3</sub> emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
12. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 1081] Federally Enforceable Through Title V Permit
16. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rule 4320] Federally Enforceable Through Title V Permit
17. Fuel sulfur content shall be determined using EPA Method 11 or EPA Method 15 or District, CARB and EPA approved alternative methods. [District Rule 4320] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The permittee shall monitor and record the stack concentration of NOx, CO, NH3 and O2 at least once during each month in which source testing is not performed. NOx, CO and O2 monitoring shall be conducted utilizing a portable analyzer that meets District specifications. NH3 monitoring shall be conducted utilizing gas detection tubes (Dräger brand or District approved equivalent). Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. If either the NOx, CO or NH3 concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. All NOx, CO, O2 and ammonia emission readings shall be taken with the unit operating at conditions representative of normal operation or under the conditions specified in the Permit to Operate. The NOx, CO and O2 analyzer as well as the NH3 emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Ammonia emissions readings shall be conducted at the time the NO<sub>x</sub>, CO and O<sub>2</sub> readings are taken. The readings shall be converted to ppmvd @ 3% O<sub>2</sub>. [District Rule 4102]
24. Daily and annual records of start-up and shutdown durations and number of occurrences of each shall be kept. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, NH<sub>3</sub> and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub>, CO and NH<sub>3</sub> concentrations corrected to 3% O<sub>2</sub>, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH<sub>3</sub> emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. The permittee shall record and maintain records of the amount of fuel combusted during each calendar month. The record shall be updated on at least a monthly basis. [40 CFR 60.48c(g)(2)] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320; and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit
28. Pursuant to Rule 4320, beginning January 1, 2025 the operator shall pay an annual emission fee to the District for NO<sub>x</sub> emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO<sub>x</sub> emission limit listed in the December 17, 2020 version of Rule 4320. [District Rule 4320]

These terms and conditions are part of the Facility-wide Permit to Operate.

---

# ATTACHMENT C

HAP Calculations

---

**Summary of Hazardous Air Pollutants  
Darling Ingredients, Inc.  
(N-2107)**

Substances	CAS #	N-2107-5-11 (Material Receiving)	N-2107-9 & 14 (Processing Operations)	N-2107-9 & 14 (RTO, NG Fuel)	N-2107-12 (Material Loadout)	N-2107-13 (Boiler, NG Fuel)	N-2107-15 (Boiler, NG Fuel)	Total, all permit units (lb/yr)	HAP?	HAP, Total of all permit units (lb/yr)	
Acetaldehyde	75070	--	--	0.1	--	2.1	1.3	3.5	Y	3.5	
Acrolein	107028	--	--	0.1	--	1.8	1.1	3	Y	3	
Benzene	71432	--	--	0.2	--	3.9	2.4	6.5	Y	6.5	
Cadmium	7440439	--	--	--	0	--	--	0	Y	0	
Carbon disulfide	75150	--	70.1	--	--	--	--	70.1	Y	70.1	
Chromium	7440473	--	--	--	0	--	--	0	Y	0	
Copper	7440508	--	--	--	0	--	--	0			
Ethyl Benzene	100414	--	--	0.2	--	4.6	2.9	7.7	Y	7.7	
Formaldehyde	50000	--	--	0.3	--	8.3	5.2	13.8	Y	13.8	
Hexane	110543	--	228.7	0.1	--	3.1	1.9	233.8	Y	233.8	
Hexavalent Chromium**	18540299	--	--	--	0	--	--	0	Y	0	
Lead	7439921	--	--	--	0	--	--	0	Y	0	
Manganese	7439965	--	--	--	0.1	--	--	0.1	Y	0.1	
Methanol	67561	--	2191.5	--	--	--	--	2191.5	Y	2191.5	
Methyl Chloride	74873	--	457.4	--	--	--	--	457.4	Y	457.4	
Methyl Ethyl Ketone	78933	--	2058.4	--	--	--	--	2058.4			
Naphthalene	91203	--	--	0	--	0.2	0.1	0.3	Y	0.3	
Nickel	7440020	--	--	--	0	--	--	0	Y	0	
PAHs	1151	--	--	0	--	0.1	0	0.1	Y	0.1	
Propylene	115071	--	228.7	13.9	--	357.2	222.9	822.7			
Toluene	108883	--	228.7	0.7	--	17.9	11.1	258.4	Y	258.4	
Xylene	1330207	--	--	0.5	--	13.3	8.3	22.1	Y	22.1	
Zinc	7440666	--	--	--	0.1	--	--	0.1			
									<b>Total:</b>	<b>3268.3</b>	<b>lb/yr</b>
										<b>1.6</b>	<b>tons/yr</b>

## **N-2107-5(Material Receiving)**

HAP data is not available for this operation at this time.

**N-2107-9&-14(Process Oper)**

<b>Substances</b>	<b>CAS#</b>	<b>EF (lb/lb-VOC)*</b>	<b>**Emissions PE (lb/yr)</b>
Carbon disulfide	75150	7.76E-03	7.01E+01
Hexane	110543	2.53E-02	2.29E+02
Methanol	67561	2.43E-01	2.19E+03
Methyl Chloride	74873	5.06E-02	4.57E+02
Methyl Ethyl Ketone	78933	2.28E-01	2.06E+03
Propylene	115071	2.53E-02	2.29E+02
Toluene	108883	2.53E-02	2.29E+02
<b>References:</b>			
*Emission factors taken from toxics worksheet used under project N1201629. EFs are derived from a 2017 source test of Sacramento Rendering Company by Best Environmental. Worst case of scrubber runs used.			
**Emissions (lb/yr) = EF (lb/lb-VOC) x 9,034 lb-VOC/yr; Permit limits VOC emissions to 0.03 lb-VOC/ton of raw material processed and processing rate to 301,125 tons/yr. Using these values VOC emissions would be: 0.03 lb-VOC/ton of raw material processed x 301,125 tons/yr = 9,034 lb-VOC/yr			

### N-2107-9&-14 (RTO, NG fuel)

Substances	CAS#	EF (lb/MMscf)*	**Emissions PE (lb/yr)
Acetaldehyde	75070	3.10E-03	0.1
Acrolein	107028	2.70E-03	0.1
Benzene	71432	5.80E-03	0.2
Ethyl Benzene	100414	6.90E-03	0.2
Formaldehyde	50000	1.23E-02	0.3
Hexane	110543	4.60E-03	0.1
Naphthalene	91203	3.00E-04	0.0
PAHs	1151	1.00E-04	0.0
Propylene	115071	5.30E-01	13.9
Toluene	108883	2.65E-02	0.7
Xylene	1330207	1.97E-02	0.5
<b>References:</b>			
*The emission factors are from the table, "Natural Gas Fired External Combustion Equipment" in the May 2001 update of VCAPCD AB 2588 Combustion Emission Factors. PAHs emission factor adjusted from table values to subtract Naphthalene portion.			
**Emissions PE (lb/yr) = EF (lb/MMscf) x 3 MMBtu/hr x scf/1,000 Btu x 8,760 hr/yr; higher heating value of natural gas is assumed to be 1,000 Btu/scf (District practice)			

### N-2107-12(Material loadout)

Substances	CAS#	EF (lb/ton of PM dust)*	***Emissions PE (lb/yr)
Cadmium	7440439	2.57E-04	0.0
Chromium	7440473	2.42E-03	0.0
Copper	7440508	2.59E-02	0.0
Hexavalent Chromium**	18540299	1.21E-04	0.0
Lead	7439921	1.63E-03	0.0
Manganese	7439965	8.79E-02	0.1
Nickel	7440020	1.28E-02	0.0
Zinc	7440666	9.55E-02	0.1
<b>References:</b>			
* Emission factors are from a 1990 ARB approved California Grain & Feed Association pooled source tests.			
*Feed values are an average of the Dairy and Poultry results ** 5% of Chromium is considered Hexavalent Chromium according to District policy			
***Emissions PE (lb/yr) = EF (lb/ton of PM dust) x 1,459 lb-PM10/yr x PM/0.5 lb-PM10 x ton/2,000 lb			

### N-2107-13 (Boiler, NG fuel)

Substances	CAS#	EF (lb/MMscf)*	**Emissions PE (lb/yr)
Acetaldehyde	75070	3.10E-03	2.1
Acrolein	107028	2.70E-03	1.8
Benzene	71432	5.80E-03	3.9
Ethyl Benzene	100414	6.90E-03	4.6
Formaldehyde	50000	1.23E-02	8.3
Hexane	110543	4.60E-03	3.1
Naphthalene	91203	3.00E-04	0.2
PAHs	1151	1.00E-04	0.1
Propylene	115071	5.30E-01	357.2
Toluene	108883	2.65E-02	17.9
Xylene	1330207	1.97E-02	13.3
<b>References:</b>			
<p>*The emission factors are from the table, "Natural Gas Fired External Combustion Equipment" in the May 2001 update of VCAPCD AB 2588 Combustion Emission Factors. PAHs emission factor adjusted from table values to subtract Naphthalene portion.</p>			
<p>**Emissions PE (lb/yr) = EF (lb/MMscf) x 76.93 MMBtu/hr x scf/1,000 Btu x 8,760 hr/yr; higher heating value of natural gas is assumed to be 1,000 Btu/scf (District practice).</p>			

### N-2107-15(Boiler, NG fuel)

Substances	CAS#	EF (lb/MMscf)*	**Emissions PE (lb/yr)
Acetaldehyde	75070	3.10E-03	1.3
Acrolein	107028	2.70E-03	1.1
Benzene	71432	5.80E-03	2.4
Ethyl Benzene	100414	6.90E-03	2.9
Formaldehyde	50000	1.23E-02	5.2
Hexane	110543	4.60E-03	1.9
Naphthalene	91203	3.00E-04	0.1
PAHs	1151	1.00E-04	0.0
Propylene	115071	5.30E-01	222.9
Toluene	108883	2.65E-02	11.1
Xylene	1330207	1.97E-02	8.3
<b>References:</b>			
<p>*The emission factors are from the table, "Natural Gas Fired External Combustion Equipment" in the May 2001 update of VCAPCD AB 2588 Combustion Emission Factors. PAHs emission factor adjusted from table values to subtract Naphthalene portion.</p>			
<p>**Emissions PE (lb/yr) = EF (lb/MMscf) x 48 MMBtu/hr x scf/1,000 Btu x 8,760 hr/yr; higher heating value of natural gas is assumed to be 1,000 Btu/scf (District practice)</p>			

---

# ATTACHMENT D

Detailed Facility List

---

### Detailed Facility Report

For Facility=2107 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

DARLING INGREDIENTS INC 11946 CARPENTER RD CROWS LANDING, CA 95313	<b>Fac #:</b> N-2107 <b>Status:</b> A <b>Phone:</b> 9722814409	<b>Type:</b> TitleV <b>Toxic ID:</b> 10302	<b>Expiration:</b> 8/31/2026 <b>Area:</b> 2 / <b>Insp. Date:</b> 12/26
--	--	---	--

Permit #	Fee Description	Fee Rule	Fee Amount	Permit Status	Equipment Description
0-5				A	
5-10	125 HP	3020-01 D	410.00	A	A RAW MATERIAL RECEIVING OPERATION EQUIPPED WITH OUTDOOR RAW MATERIAL RECEIVING CONCRETE SLABS, GRINDING SYSTEM, AND PRIMARY AND SECONDARY WASTEWATER TREATMENT SYSTEM WITH DAF UNIT AND AN OUTDOOR WASTEWATER LAGOON SYSTEM (PERMIT EXEMPT LOW EMITTING UNIT)
9-20	1.5 MMBtu/hr	3020-02 E	535.00	A	FOOD PROCESSING BYPRODUCT RECYCLING OPERATION INCLUDING THREE DUPPS PRE-HEAT COOKERS, A HAARSLEV 2564 COOKER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-14)
12-6	359,718 gallons	3020-05 E	320.00	A	PROTEIN MEAL FINISHING AND LOADOUT OPERATION WITH ONE DRAG LINE CONVEYOR, ONE 104 TON STORAGE/LOADOUT BIN, THREE 84 TON STORAGE/LOADOUT BINS, ONE 450 TON STORAGE/LOADOUT BIN, CRAX RECEIVING, THREE HAMMERMILLS, THREE SCREENS, AND A LOADOUT BUILDING WITH VERTILOK STORAGE/LOADOUT BINS; ANOTHER ENCLOSED MECHANICAL CONVEYANCE LINE CONVEYOR WITH A CURING BIN, A HAMMERMILL AND SCREEN SYSTEM SERVED BY AN ASPIRATOR CONNECTED TO A CYCLONE DISCHARGE ROUTED THROUGH A BAG FILTER INSIDE THE BUILDING, BUCKET ELEVATOR, A 400-TON STORAGE/LOADOUT BIN WITH BIN VENT FILTRATION SYSTEM, AND A LOADOUT BUILDING.
13-8	76.93 MMBtu/hr Boiler	3020-02 H	1,338.00	A	76.93 MMBTU/HR NEBRASKA MODEL NS-E-57 WATER-TUBE NATURAL GAS-FIRED BOILER EQUIPPED WITH A FLUE GAS RECIRCULATION (FGR) SYSTEM AND AMMONIA SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM
14-3	1.5 MMBtu/hr	3020-02 E	535.00	A	FEATHER RECYCLING OPERATION CONSISTING OF AN INDOOR FEATHER RECEIVING HOPPER, A STEAM-FIRED CONTINUOUS FEATHER HYDROLYZER, A FEATHER PRESS, A STEAM-FIRED FEATHER DRYER, A BLOOD STAGING TANK, BLOOD CENTRIFUGE, SPRAY CHAMBER AND AIR COOLED CONDENSER SERVED BY A SHARED 3.0 MMBTU/HR NATURAL GAS-FIRED GULF COAST ENVIRONMENTAL REGENERATIVE THERMAL OXIDIZER (RTO) WITH A VENTURI SCRUBBER PRIOR TO THE RTO (CONTROLS SHARED WITH N-2107-9)
15-2	48 MMBtu/hr boiler	3020-02 H	1,338.00	A	48 MMBTU/HR BABCOCK & WILCOX MODEL FMO-40 WATER-TUBE NATURAL GAS-FIRED BOILER WITH A TODD MODEL V4851GO LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM (FGR), AND A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM

Number of Facilities Reported: 1