

August 9, 2022

Ms. Janis Mein
Fink Road Landfill
PO Box 86
Crows Landing, CA 95313

Re: Notice of Final Action - Title V Permit Renewal
Facility Number: N-3969
Project Number: N-1204550

Dear Ms. Mein:

The District has issued the Final Renewed Title V Permit for Fink Road Landfill (see enclosure). The preliminary decision for this project was made on June 10, 2022.

The public notice for issuance of the Final Title V Permit will be posted on the District's website (www.valleyair.org).

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Nick Peirce, Permit Services Manager, at (209) 557-6400.

Sincerely,



Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Gerardo Rios, EPA (w/enclosure) via EPS

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95358-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1890 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-8000 FAX: (559) 230-8061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

San Joaquin Valley Air Pollution Control District

FACILITY: N-3969-0-3

EXPIRATION DATE: 07/31/2026

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1]
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0]
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: FINK ROAD LANDFILL
Location: 4000 FINK RD, CROWS LANDING, CA 95313
N-3969-0-3 : Aug 9 2022 7:38AM -- YOSHIMUJ

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Stanislaus County Rule 110. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin June 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-3969-1-5

EXPIRATION DATE: 07/31/2026

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT PHASE I VAPOR RECOVERY SYSTEM, AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)

PERMIT UNIT REQUIREMENTS

1. The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
2. For Phase I vapor recovery system compliance, the gasoline throughput for this permit unit shall not exceed 18,000 gallons in any one calendar year. If throughput exceeds stated limits, the permittee shall submit a complete application for an Authority to Construct (ATC) to the District within 30 days of the loss of exemption and install and test a certified Phase I EVR vapor recovery system within six (6) months from the date the ATC is issued. [District Rules 2201 and 4621] Federally Enforceable Through Title V Permit
3. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit
9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
16. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
17. The permittee shall perform and pass a Static Leak Test for Aboveground Tanks using ARB TP-201.3B or TP-206.3 at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
19. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
23. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
26. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-3969-2-11

EXPIRATION DATE: 07/31/2026

SECTION: 30 **TOWNSHIP:** 6S **RANGE:** 7E

EQUIPMENT DESCRIPTION:

MUNICIPAL SOLID WASTE LANDFILL, 11.6 MILLION CUBIC METER CAPACITY (202 ACRES), WITH A LANDFILL GAS COLLECTION SYSTEM SERVED BY A 35 MMBTU/HR ENCLOSED FLARE

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC destruction efficiency for an enclosed flare shall be at least 98% by weight or NMOC emissions shall be less than 20 ppmvd @ 3% O₂. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The methane destruction efficiency for the enclosed flare shall be at least 99% by weight. [17 CCR 95464]
5. This flare shall only be fired on landfill gas (LFG) collected from the well system. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Emissions for the enclosed flare shall not exceed any of the following: 0.05 lb-NO_x/MMBtu; 0.30 lb-CO/MMBtu; 0.03 lb-VOC/MMBtu; or 0.034 lb-PM₁₀/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The sulfur content of landfill gas (LFG) collected shall not exceed 5.8 grains/100 scf (6.2 grains-H₂S/100 scf). [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
8. A minimum operating temperature shall be maintained at or above 1,400 degrees F when the flare is in operation. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The flare shall be equipped with a temperature indicator and recorder which measures and records the operating temperature. The temperature indicator and recorder must operate continuously. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Gas collection system shall be operated in a manner which maximizes the amount of landfill gas extracted while preventing overdraw that can cause fires or damage the gas collection system. [District Rule 2201] Federally Enforceable Through Title V Permit
11. During maintenance of the gas collection system or incineration device, emissions of landfill gas shall be minimized during shutdown. [District Rule 2201 and Rule 2020, 7.3] Federally Enforceable Through Title V Permit
12. Maintenance is defined as work performed on a gas collection system and/or control device in order to ensure continued compliance with District rules, regulations, and/or Permits to Operate, and to prevent its failure or malfunction. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The gas collection system shall be operated such that the concentration of total organic compounds (as CH₄) shall not exceed 500 ppmv at any point along the gas transfer path of the gas collection system. [District Rule 2201 and 17 CCR 95464] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Landfill gas line from collection header shall be equipped with a gas flow rate measurement device. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The entire gas collection system shall be inspected for leaks with a portable analyzer in accordance with EPA Method 21 at least quarterly. After four successful inspections, the frequency shall be annually. If a leak is detected, quarterly inspections shall resume. A leak is defined as a measurement in excess of 500 ppm (measured as methane) above background when measured at a distance of one (1) centimeter from the potential source. Leaks shall be repaired within 10 calendar days after it is detected. [District Rule 2201, 17 CCR 95464 and 17 CCR 95471] Federally Enforceable Through Title V Permit
16. The permittee shall notify the APCO by telephone at least 24 hours before performing any maintenance work that requires the system to be shutdown. The notification shall include a description of work, the date work will be performed and the amount of time needed to complete the maintenance work. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of system inspections including: date, time and inspection results. [District Rule 1070, 4.0] Federally Enforceable Through Title V Permit
18. Permittee shall maintain daily records of landfill gas flow rate to any control device. [District Rule 1070, 4.0] Federally Enforceable Through Title V Permit
19. Landfill gas flow rate to the flare shall not exceed 1,728,000 scf/day. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Permittee shall maintain records of maintenance related or other collection system and control device downtime, including individual well shutdown [District Rule 1070, 4.0] Federally Enforceable Through Title V Permit
21. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
22. Source testing to demonstrate compliance with NOx, CO, and VOC emission limits shall be conducted annually. [District Rule 1081] Federally Enforceable Through Title V Permit
23. Source testing to demonstrate compliance with CH4 destruction efficiency shall be conducted annually. If the destruction efficiency is shown in compliance after three source tests the facility may conduct source test every 3 years. If a subsequent source test shows the destruction efficiency is out of compliance annual testing will resume. [17 CCR 95464]
24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
25. Source testing for NOx and CO shall be conducted utilizing EPA method 7E and EPA method 10 respectively, or CARB method 100. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Source testing for VOC emission concentration shall be conducted utilizing EPA method 25 referenced as methane. [District Rule 2201] Federally Enforceable Through Title V Permit
27. Source testing for methane destruction efficiency shall be conducted utilizing EPA Method 18, EPA Method 25, EPA Method 25A, or EPA Method 25C. Alternative methods may be utilized provided they are previously approved in writing by the District. [17 CCR 95471]
28. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

29. The NMOC emission rate shall be calculated using the equation in 40 CFR 62.16718(a)(1)(i)(A), if the actual year-to-year solid waste acceptance rate is known or the equation in 40 CFR 62.16718(ii)(A)), if the actual year-to-year solid waste acceptance rate is unknown. The values for k, Lo, and CNMOC for both equations shall be taken from 40 CFR 62.16718(a)(1), as appropriate. Both equations may be used if the actual year-to-year acceptance rate is known for a part of the landfill life, but unknown for another part of the landfill life. The mass of nondegradable solid waste may be subtracted from the average annual acceptance rate when calculating R, if documentation of the nature and amount of such wastes is maintained. (Tier 1 specifications). [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
30. If the calculated NMOC emission rate is equal to or greater than 34 megagrams/year, then the landfill owner or operator shall either comply with the requirements of this permit to submit a collection and control design plan and install the system, or determine a site-specific NMOC concentration and recalculate the NMOC emission rate using Tier 2 specifications. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
31. Tier 2 specifications to determine the site-specific NMOC concentration shall include the following: 1) For sampling, at least 2 sample probes shall be installed per hectare of landfill surface that has retained waste for at least 2 years, up to a maximum of 50 required probes. One sample of landfill gas shall be collected from each probe to determine the NMOC concentration, using EPA Method 25, 25C, another method approved by the EPA, or 18, in accordance with 40 CFR 62 Subpart OOO. If EPA Method 18 is used, the minimum list of compounds to be tested shall be those published in the most recent Compilation of AP-42. If composite sampling is used, equal sample volumes are required. All samples taken shall be used in the analysis. The NMOC concentration from Method 25 or 25C shall be divided by 6 to convert from C-NMOC, as carbon to as hexane. 2) For landfills equipped with active collection systems, samples may be collected from the common header pipe before gas moving or condensate removal equipment; a minimum of 3 samples must be collected. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
32. Tier 2 specifications to determine the site-specific NMOC concentration shall include the following: 1)The NMOC mass emission rate shall be recalculated using the average site-specific concentration, instead of the default value, 2) If the resulting calculated mass emission rate is equal to or greater than 34 megagrams/year, the landfill owner or operator shall either 1) submit a gas collection and control system design plan within 1 year as specified in § 62.16724(c), 2) Determine a site-specific methane generation rate constant and recalculate the NMOC rate using the site-specific methane generation rate using the Tier 3 procedures; or 3) conduct a surface emission monitoring demonstration using the Tier 4 procedures. . [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
33. If the resulting NMOC mass emission rate is less than 34 megagrams per year, then the owner or operator shall submit a periodic estimate of NMOC emissions in an NMOC emission rate report according to § 62.16724(c) and must recalculate the NMOC mass emission rate annually as required under § 62.16714(e). The site-specific NMOC concentration must be retested every 5 years using the methods specified in this section. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
34. Tier 3 specifications to determine the site-specific methane generation rate constant shall include the following: 1) EPA Method 2E or another method approved by the EPA shall be used, 2) The NMOC mass emission rate shall be recalculated using the average site-specific NMOC concentration and the site-specific methane generation rate constant k, instead of the default values in 40 CFR 62 Subpart OOO, and 3) If the resulting calculated NMOC mass emission rate is equal to or greater than 34 megagrams/year, the landfill owner or operator must either 1) submit a gas collection and control system design plan within 1 year as specified in § 62.16724(d) and install and operate a gas collection and control system within 30 months according to § 62.16724(b) and § 62.16724(c); or 2) conduct a surface emission monitoring demonstrating using Tier 4 procedures. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. If the NMOC mass emission rate calculated using Tier 3 specifications is less than 34 megagrams per year, then the owner or operator must recalculate the NMOC mass emission rate annually using Equation 1 or Equation 2 in paragraph (a)(1) of this 40 CFR 62 Subpart OOO and using the site-specific Tier 2 NMOC concentration and Tier 3 methane generation rate constant and submit a periodic NMOC emission rate report as provided in § 62.16724(c). The calculation of the methane generation rate constant is performed only once, and the value obtained from this test must be used in all subsequent annual NMOC emission rate calculations. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
36. Tier 4 specifications may be used to demonstrate that surface methane emissions are below 500 parts per million. Surface emission monitoring must be conducted on a quarterly basis using the following procedures. Tier 4 is allowed only if the landfill owner or operator can demonstrate that NMOC emissions are greater than or equal to 34 megagrams per year but less than 50 megagrams per year using Tier 1 or Tier 2. If both Tier 1 and Tier 2 indicate NMOC emissions are megagrams per year or greater, then Tier 4 cannot be used. In addition, the landfill must meet the following criteria: 1) Measure surface concentrations of methane along the entire perimeter of the landfill and along a pattern that traverses the landfill at no more than 30-meter intervals using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in § 62.16720(d), 2) The background concentration must be determined by moving the probe inlet upwind and downwind at least 30 meters from the waste mass boundary of the landfill, 3) Surface emission monitoring must be performed in accordance with section 8.3.1 of EPA Method 21 of appendix A-7 of 40 CFR part 60, except that the probe inlet must be placed no more than 5 centimeters above the landfill surface; the constant measurement of distance above the surface should be based on a mechanical device such as with a wheel on a pole, 4) Each owner or operator seeking to comply with the Tier 4 provisions in paragraph (a)(6) of 40 CFR 62.16718 must maintain records of surface emission monitoring as provided in § 62.16726(g) and submit a Tier 4 surface emissions report as provided in § 62.16724(d)(4)(iii), 5) If there is any measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must submit a gas collection and control system design plan within 1 year of the first measured concentration of methane of 500 parts per million or greater from the surface of the landfill according to § 62.16724(d) and install and operate a gas collection and control system according to § 62.16714(b) and (c) within 30 months of the most recent NMOC emission rate report in which the NMOC emission rate equals or exceeds 34 megagrams per year based on Tier 2, 6) If after four consecutive quarterly monitoring periods at a landfill, other than a closed landfill, there is no measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must continue quarterly surface emission monitoring using the methods specified in this section, 7) If after four consecutive quarterly monitoring periods at a closed landfill there is no measured concentration of methane of 500 parts per million or greater from the surface of the landfill, the owner or operator must conduct annual surface emission monitoring using the methods specified in this section. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
37. For PSD purposes, the NMOC emission rate shall be estimated and compared to the PSD major source and significance levels in 40 CFR 51.166 or 52.21, using AP-42 or EPA-approved procedures. [40 CFR 62.16718(c)] Federally Enforceable Through Title V Permit
38. The NMOC emission rate shall be recalculated and reported to the APCO annually, except as otherwise provided in this permit, until such time as the calculated NMOC emission rate is equal to or greater than 34 megagrams/year and a collection and control system is installed or until the landfill is closed. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
39. If the NMOC emission rate, as reported in the annual report is less than 34 megagrams/year in each of the next 5 consecutive years, the owner or operator may elect to submit an estimate of the NMOC emission rate for the next 5-year period in lieu of the annual reports for those 5 years. This estimate shall include the current amount of solid waste-in-place and the estimated waste acceptance rate for each year of the 5 years. All data and calculations upon which this estimate is based shall be provided to the APCO. This estimate shall be revised at least once every 5 years. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
40. If the actual waste acceptance rate exceeds the estimated rate used in any year reported in a 5-year estimate of the NMOC emission rate, then a revised 5-year estimate shall be submitted to the APCO. The revised estimate shall cover the 5-year period beginning with the year in which the actual waste acceptance rate exceeded the estimated acceptance rate. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

41. The NMOC emission rate report shall include all the data, calculations, sample reports and measurements used to estimate the annual or 5-year emissions. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
42. If the owner or operator elects to recalculate the NMOC emission rate using Tier 2 specifications and the resulting NMOC emission rate is less than 34 megagrams/year, annual periodic reporting shall resume. The revised NMOC emission rate report, with the recalculated NMOC emission rate using Tier 2 specifications, shall be submitted within 180 days of the first Tier 1 calculated exceedance of 34 megagrams/year. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
43. If the owner or operator elects to recalculate the NMOC emission rate using Tier 3 specifications and the resulting NMOC emission rate is less than 34 megagrams/year, annual periodic reporting shall resume. The revised NMOC emission rate report, with the recalculated NMOC emission rate using Tier 3 specifications, shall be submitted within 1 year of the first Tier 1 calculated exceedance of 34 megagrams/year. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
44. Each owner or operator shall keep for at least 5 years up-to-date, readily accessible, on-site records of the maximum design capacity, the current amount of solid waste in-place, and the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
45. This operating permit may be cancelled with APCO approval when the landfill is closed, pursuant to the requirements of this permit, if the landfill is not otherwise subject to the requirements of either 40 CFR part 70 or part 71 and if either 1) it was never subject to the requirement to install and operate a gas collection and a control system under 40 CFR 62.16714; or 2) the owner or operator meets the conditions for control system removal specified in 40 CFR 62.16714(f). [40 CFR 62.16711(f)] Federally Enforceable Through Title V Permit
46. If the landfill is permanently closed, a closure notification shall be submitted to the APCO within 30 days of waste disposal cessation. A permanent closure must take place in accordance with 40 CFR 258.60. If a closure report has been submitted, no additional waste may be placed in the landfill without filing a notification of modification to the APCO, pursuant to 40 CFR 60.7(a)(4). [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
47. If the calculated NMOC is equal to or greater than 34 megagrams/year, the owner or operator shall install a collection and control system, that effectively captures the gas generated within the landfill, within 30 months of that determination. This operating permit must be modified accordingly to show compliance with 40 CFR 62 Subpart OOO requirements applicable to a MSWL with a collection and control system. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
48. If a gas collection and control system is installed for NSPS compliance purposes, it shall comply with the operational standards of 40 CFR 62.16716, the compliance provisions of 40 CFR 62.16720, the monitoring provisions of 40 CFR 62.16722 the reporting and record keeping requirements of 40 CFR 62.16724 and 40 CFR 62.16726, and the requirements of 40 CFR 62.16728 (for active collection systems). [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
49. Permittee shall comply with the Increments of Progress as defined in Table 1 of 40 CFR 62 Subpart OOO, unless a site specific schedule is approved by EPA, which includes notification of EPA no later than 10 business days after completing each increment of progress. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
50. Permittee shall submit the Final Control Plan (as defined in 40 CFR 62.16730) one year after the first annual emission rate report showing NMOC emissions > 34 megagrams/year, unless a site-specific schedule is approved by EPA. (Increment 1) [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
51. Permittee shall Award Contract(s) (as defined in 40 CFR 62.16730) 20 months after the first annual emission rate report showing NMOC emissions > 34 megagrams/year, unless a site-specific schedule is approved by EPA. (Increment 2) [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
52. Permittee shall Initiate On-Site Construction (as defined in 40 CFR 62.16730) 24 months after the first annual emission rate report showing NMOC emissions > 34 megagrams/year, unless a site-specific schedule is approved by EPA. (Increment 3) [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

53. Permittee shall Complete On-Site Construction (as defined in 40 CFR 62.16730) 30 months after the first annual emission rate report showing NMOC emissions > 34 megagrams/year, unless a site-specific schedule is approved by EPA. (Increment 4) [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
54. Permittee shall Achieve Final Compliance (as defined in 40 CFR 62.16730) 30 months after the first annual emission rate report showing NMOC emissions > 34 megagrams/year, unless a site-specific schedule is approved by EPA. (Increment 5) [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
55. Permittee must conduct initial performance tests of the landfill gas collection system and air pollution control equipment within 180 days after the date the facility is required to achieve final compliance with the emission standards specified in 40 CFR 62.14353(b) of this subpart, unless a site-specific schedule is approved by EPA. [40 CFR 62 Subpart OOO] Federally Enforceable Through Title V Permit
56. Permittee may use actual landfill gas generation values in future expansion designs of the gas collection and control system (GCCS). All records and recovery data shall be submitted with GCCS plans. [17 CCR 95468]
57. Landfill gas collection and control system must be operated such that methane emission from the landfill do not exceed instantaneous and integrated limit requirements. [17 CCR 95464]
58. Landfill gas collection system wellheads must be operated under vacuum. Monthly monitoring of wellheads is required. Landfill gas collection system wellheads may be operated under neutral or positive pressure when there is a fire or during other times as allowed in sections 95464(c), 95464(d), and 95464(e) [17 CCR 95464 and 17 CCR 95468]
59. Landfill gas collection system components downstream of blower have a leak limit of 500 ppmv as methane. Components must be checked quarterly. If compliance with the methane limit has been demonstrated for 4 consecutive quarters, then the component checking frequency shall be annually. If an annual test fails to show compliance, quarterly testing shall resume. [17 CCR 95464]
60. The flare must have automatic dampers, an automatic shutdown device, a flame arrester, and continuous recording temperature sensors. [17 CCR 95464]
61. The flare must operate within the parameter ranges established during the initial or most recent source test. [17 CCR 95464]
62. Landfill collection and control system must be operated such that landfill surface methane emissions shall not exceed instantaneous surface emission limit of 500 ppmv as methane and integrated surface emission limit of 25 ppmv as methane. [17 CCR 95464 and 17 CCR 95465]
63. Instantaneous and integrated landfill surface emissions measurements shall be done quarterly. The landfill may monitor annually provided they comply with requirements of 17 CCR 95469(a)(1) and 17 CCR 95469(a)(2). [17 CCR 95469]
64. Permittee shall keep records of all gas collection system downtime exceeding five days, including individual well shutdown and disconnection times and the reason for downtime. [17 CCR 95470]
65. Permittee shall keep records of all gas control system downtime in excess of one hour, the reason for the downtime and the length of time the gas control system was shutdown. [17 CCR 95470]
66. Permittee shall keep records of the expected gas generation flow rate calculated pursuant to section 95471(e). [17 CCR 95470]
67. Permittee shall keep records of all instantaneous surface readings of 200 ppmv or greater; all exceedances of the limits in sections 95464(b)(1)(B) or 95465, including the location of the leak (or affected grid), leak concentration in ppmv, date and time of measurement, the action taken to repair the leak, date of repair, any required re-monitoring and the re-monitored concentration in ppmv, and wind speed during surface sampling; and the installation date and location of each well installed as part of a gas collection system expansion. [17 CCR 95470]
68. Permittee shall keep records of any positive wellhead gauge pressure measurements, the date of the measurements, the well identification number, and the corrective action taken. [17 CCR 95470]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

69. Permittee shall conduct surface emission monitoring using either the procedures specified in section 95471 or the Los Angeles County Sanitation District monitoring procedure. Permittee shall keep records of which procedure was used. [17 CCR 95468 and 17 CCR 95469]
70. Permittee shall keep records of delays encountered during repair of leaks or repair of positive wellhead readings. Documentation of delays shall be submitted with the annual report. [17 CCR 95468]
71. Permittee shall keep records of alternate landfill gas collection system modifications being implemented to correct an exceedance in the landfill gas surface emissions or wellhead pressure. Any alternative to installing a new well shall be documented and submitted with the annual report. [17 CCR 95468]
72. Permittee shall identify areas which are dangerous and unable to be inspected. Areas shall be clearly identified on a map of the facility. A copy of the map shall be kept onsite as well as submitted with the annual report. [17 CCR 95468]
73. Permittee shall conduct monitoring of the landfill surface within 3 inches of the surface. The facility may monitor surface emissions with the probe tip at the height of the vegetation if there is vegetation and it is impractical to monitor at 3 inches from the landfill surface. [17 CCR 95468]
74. Permittee shall terminate surface emission testing when the measured average wind speed is over 10 mph or the instantaneous wind speed is over 20 mph. [17 CCR 95468 and 17 CCR 95471]
75. Permittee shall only conduct surface emission testing when precipitation has met the following requirements. It has been 24 hours since measured precipitation of 0.01 to 0.15 inches. It has been 48 hours since measured precipitation of 0.16 to 0.24 inches. It has been 72 hours since measured precipitation of 0.25 or more inches. [17 CCR 95468]
76. Permittee shall keep records of the annual solid waste acceptance rate and the current amount of waste-in-place. [17 CCR 95470]
77. Permittee shall keep records of the nature, location, amount, and date of deposition of non-degradable waste for any landfill areas excluded from the collection system. [17 CCR 95470]
78. Permittee shall keep records of any source tests conducted pursuant to section 95464(b)(4). [17 CCR 95470]
79. Permittee shall keep records describing the mitigation measures taken to prevent the release of methane or other emissions into the atmosphere during the following activities: 1. When solid waste was brought to the surface during the installation or preparation of wells, piping, or other equipment; 2. During repairs or the temporary shutdown of gas collection system components; or, 3. When solid waste was excavated and moved. [17 CCR 95470]
80. Permittee shall keep records of any construction activities pursuant to section 95466. The records must contain the following information: 1. A description of the actions being taken, the areas of the MSW landfill that will be affected by these actions, the reason the actions are required, and any landfill gas collection system components that will be affected by these actions. 2. Construction start and finish dates, projected equipment installation dates, and projected shut down times for individual gas collection system components. 3. A description of the mitigation measures taken to minimize methane emissions and other potential air quality impacts. [17 CCR 95470]
81. Permittee shall keep records of the equipment operating parameters specified to be monitored under section 95469(b)(1) as well as records for periods of operation during which the parameter boundaries established during the most recent source test are exceeded. The records must include the following information: 1. For enclosed flares, all 3-hour periods of operation during which the average temperature difference was more than 28 degrees Celsius (or 50 degrees Fahrenheit) below the average combustion temperature during the most recent source test at which compliance with sections 95464(b)(2) was determined and a gas flow rate device which must record the flow to the control device at least every 15 minutes. [17 CCR 95470]
82. Permittee shall submit the following reports as required in section 95470(b): Closure notification, Equipment removal report, and Annual report. All reports must be accompanied by a certification of truth, accuracy, and completeness signed by a responsible official. [17 CCR 95470]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

83. Permittee may comply with the CARB regulation for landfill methane control measures by using approved alternative compliance options. The permittee shall obtain written District approval for the use of any alternative compliance options not approved by this permit. Changes to the approved alternate compliance options must be made and approved in writing. Documentation of approved alternative compliance options shall be available for inspection upon request. [17 CCR 95468]
84. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.